




PRODUCT NUMBER: 4612-0-31-01-30-02-04-0

www.mill-max.com
DATA SHEET




4612-0-31-01-30-02-04-0 SPECIFICATIONS

General Info		Materials	Technical Specs
Description¹:	Receptacle With a Press-Fit Tail	Shell Material⁴: Brass Alloy	Mechanical life 1,000 Cycles Minimum (Durability) ⁷ :
Mounting Feature²:	Press-Fit into a Plated Through Hole (PTH)	Shell Plating⁵: 200 - 300 μ " Tin/Lead over Nickel	Operating Temperature Range⁸: -55/+125° C
Mounting Hole:	.040" (1,016mm)	Contact Plating⁶: 100 - 200 μ " Tin/Lead over Nickel	Current Rating⁹: 3A @ 10°C Temperature Rise
Pin Diameter Range:	.015"-.025" (0,381-0,635mm)		Contact Resistance¹⁰: 10 m Ω Max
Packaging:	Packaged in Bulk		Shock¹¹: No Elect. Discontinuity > 1 μ s @ 50g
RoHS:	No		Vibration¹²: No Elect. Discontinuity > 1 μ s @ 10-2000HZ, 20 G
Product Lifecycle³:	Active		

NOTES:

1. Standard Tolerances:
Lengths +/- .005" (0,13)
Diameters: +/- .002" (0,051)
Angles: +/- 2°
2. The suggested mounting hole represents the plated through-hole size. Press-fit pins designed for plated through-holes require the bare board drill size to be .001" (.0254 mm) larger than the diameter of the press-fit feature. This is a general guideline; your application may require different specifications
3. Part is Active and in Production, No Scheduled Obsolescence
4. Brass Alloy 360 per ASTM B 16, or 385 per ASTM B455
5. TIN/LEAD (93/7) per ASTM B 545 (Appendix X6.3.2.5 to eliminate whisker growth) Bright finish; NICKEL per ASTM B 689, Type 2 (Bright)
6. TIN/LEAD (93/7) per ASTM B 545 (Appendix X6.3.2.5 to eliminate whisker growth) Bright finish, NICKEL per ASTM B 689, Type 2 (Bright)
7. Receptacles are capable of 1,000 Minimum insertion/extraction cycles for a broad range of applications. Mating pin size, shape and finish, along with application specific variables, will affect the life of a receptacle contact.
8. Per IEC 60512-11-(4,-9,-10,-12)
9. Per IEC 60512-5-1, Current Carrying Capacity (evaluated at 10° C Temp. Rise)
10. Per EIA-364-23C, Low Level Contact Resistance
11. Per IEC 60512-6-3: Test 6c: Shock
12. Per IEC 60512-6-4: Test 6d: Vibration (sinusoidal)

CONTACT:



The insertion / extraction force characteristics above were derived using a 30 microinch gold-plated contact and polished steel gauge pins having a bullet-shaped tip. The curves represent typical average values; they are best used to compare the differences between similar size contacts and to guide you in selecting one that is suitable for your application. Your results may vary, so for your specification, we encourage you to obtain complimentary samples for your evaluation.

Material	Beryllium Copper	Fingers	4
Length	.080" (2,032mm)	Maximum Current	12A @ 30° C Temp. Rise
Maximum Operating Temp @ Max Current	120.00° C	20% De-rated Maximum Current	9.60A
Contact Resistance	10.00mΩ Max	Contact Group	C

ADDITIONAL NOTES AND SPECIFICATIONS

In the interest of improved design, quality and performance , Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. The tolerance on dimensions of critical to function features is typically held tighter than the stated standard tolerances, such as press-fits, holes and lengths affecting the coplanarity of SMT products. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.

RELATED LINKS AND DOCUMENTS

Engineering Notebook: (<https://www.mill-max.com/engineering-notebooks/introduction-to-mill-max-press-fit-technology>)

Environmental Compliance: (<https://www.mill-max.com/rohs>)