





IDEAS GENERATED DRAWING, DON'T CHANGE BY HAND.

REV.	ECN. NO.	APPD.
A	BC-08-7081973	Herry Yang
B	BC-09-7108234	Herry Yang
C	BC-11-0024706	Herry Yang

- NOTES:
- 1.ELECTRICAL CHARACTERISTICS :
 - 1.1 VOLTAGE RATING 50V DC PER CONTACT.
 - 1.2 INSULATION RESISTANCE : 250MEGAOHMS. MIN. AT 500V DC.
 - 2 MECHANICAL CHARACTERISTICS :
 - 2.1 DURABILITY : 30 MATING CYCLES.
 - 3.OPERATION TEMPERATURE : -40°C TO + 85°C
 - 4.THE NVIDIA'S MOBILE PCI EXPRESS MODULE ELECTROMECHANICAL SPECIFICATION CONTROLS MXM GRAPHICS MODULE PCB AND CONNECTOR MOTHERBOARD FOOTPRINT DIMENSIONS.IT IS SHOWN FOR REFERENCE ONLY,AND IS SUBJECT TO CHANGE.
 - 5.INTERPRET DRAWING PER ASME Y14.5M-1994.
 - 6.PLEASE CONTACT FOXCONN SALES REPRESENTATIVE TO VERIFY PRODUCT DETAILS & AVAILABILITY.



PART NO. DESCRIPTION: A S O B8 2 * - S 43 * - * H


MEMORY MODULE SOCKET
HORIZONTAL TYPE
SINGLE ROW
NO. OF POS.
B8= 314 POS.
SMT
CONTACT AREA PLATING


1=GOLD FLASH
6=10u" GOLD PLATING

H=HALOGEN/LEAD FREE
7=TAPE & REEL
4=SOFT TRAY
B=BLACK COLOR
N=IVORY COLOR
43=4.3mm HEIGHT
STANDARD






③	METAL EAR	2	COPPER ALLOY	50u" NICKLE UNDER PLATING OVER ALL 30u" PURE TIN PLATING OVER ALL
②	CONTACT	314	COPPER ALLOY	50u" NICKLE UNDER PLATING GOLD FLASH AT TAIL 10u" OR 30u" GOLD PLATING OR GOLD FLASH AT CONTACT AREA
①	HOUSING	1	THERMOPLASTIC	UL94V-0,HALOGEN FREE
ITEM	DESCRIPTION	Q'TY	MATERIAL	TREATMENT
X. ± 0.30	X° ± 2.0°	UNITS	mm	NAME (INTENDED USE)
.X ± 0.20	.X° ± 1.0°	MAT'L		MXM 3.0 CONNECTOR
.XX ± 0.15	.XX°			PART NO. (INTENDED USE)
.XXX±	.XXX°±	FINISH		ASOB82*-S43*-*H
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON HAI PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON HAI PRECISION IND. CO., LTD.				APPD: Herry Yang
				CHKD: Alex Wong
				DR: FL LIU 3/08'11
				TITLE:
				CUSTOMER DRAWING
				DWG NO.:
				317-0000-1659
				SCALE SHEET REV.
				N/A 1/4 C

REV.	ECN. NO.	APPD.



X. ±	X°. ±	UNITS mm	NAME(INTENDED USE)	FOXCONN HON HAI PRECISION IND. CO.,LTD. TAIPEI, TAIWAN, R.O.C.			
.X ± 0.10	.X° ±	MAT'L	MXM 3.0 CONNECTOR	TITLE: CUSTOMER DRAWING			
.XX ± 0.05	.XX°		PART NO.(INTENDED USE) ASOB82*-S43*-*H				
.XXX±	.XXX°±	FINISH	APPD: Herry Yang	DWG NO.: 317-0000-1659			
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON HAI PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON HAI PRECISION IND. CO., LTD.		Q'TY	CHKD: Alex Wong		SCALE	SHEET	REV.
			DR: FL LIU 3/08'11		N/A	2/4	C

REV.	ECN. NO.	APPD.





630 PCS	21 PCS	ASOB82*-S43*-4H
QTY/BOX	QTY/TRAY	CONNECTOR P/N

X. ±	X°. ±	UNITS mm	NAME (INTENDED USE)	FOXCONN HON HAI PRECISION IND. CO., LTD. TAIPEI, TAIWAN, R.O.C.		
.X ± 1.0	.X° ±	MAT'L	MXM 3.0 CONNECTOR			
.XX ± 0.50	.XX°	FINISH	PART NO. (INTENDED USE)	TITLE:		
.XXX±	.XXX°±		AS0B82*-S43*-*H	CUSTOMER DRAWING		
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON HAI PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON HAI PRECISION IND. CO., LTD.			Q'TY	APPD:	DWG NO.: 317-0000-1659	
		Herry Yang				
		CHKD:				
Alex Wong	SCALE	SHEET	REV.			
DR: FL LIU 3/08'11				N/A	3/4	C


IDEAS GENERATED DRAWING, DO NOT CHANGE BY HAND

REV.	ECN.	NO.	APPD.





NOTES:


1. 10 POCKETS HOLE PITCH CUMULATIVE TOLERANCE $\pm 0.20\text{mm}$.
2. COVER TAPE PEELING STRENGTH : 0.01kgf MIN., 0.15 kgf MAX. AT 300mm/min.



3. PACKING CAPACITY : 600 PCS/REEL, 3 REELS/BOX, TOTAL 1800 PCS/BOX.



③	REEL	POLYSTYRENE
②	COVER TAPE	POLYSTER
①	CARRIER TAPE	POLYSTYRENE
ITEM	DESCRIPTION	MATERIAL

X.± 1.0	X°.±	UNITS mm	NAME (INTENDED USE) MXM3.0 CONNECTOR	FOXCONN HON HAI PRECISION IND. CO.,LTD. TAIPEI, TAIWAN, R.O.C.			
.X± 0.50	.X°.±						
.XX± 0.20	.XX°.±	FINISH	PART NO. (INTENDED USE) ASOB82*-S43*-H	TITLE: CUSTOMER DRAWING			
.XXX±	.XXX°.±		Q'TY	APPD: Herry Yang	DWG NO.: 317-0000-1659		
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON HAI PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED. COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON HAI PRECISION IND. CO., LTD.		CHKD: Alex Wong					
		DR: FL LIU 3/08'11					
				N/A	4/4	C	

CONNECTOR P/N ASOB82*-S43*-7H