


64 X 8 Serial Real Time Clock--DS1307Z-TD

FEATURES:

- Real time clock counts seconds, minutes, hours, date of the month, month, day of the week, and year with leap year compensation valid up to 2100
- 56 byte nonvolatile RAM for data storage
- 2-wire serial interface
 - Programmable squarewave output signal
- Automatic power-fail detect and switch Circuitry
- Consumes less than 1uA in battery backup mode with oscillator running
- Optional industrial temperature range -40°C to +85°C
- Recognized by Underwriters Laboratory DS1307Z-TDCompatible



PIN DESCRIPTION:

VCC: Primary Power Supply
 X1, X2: 32.768 kHz Crystal Connection
 VBAT: +3V Battery Input
 GND: Ground
 SDA: Serial Data
 SCL : Serial Clock
 SQW/OUT: Square wave/Output Driver

DESCRIPTION


The DS1307Z-TD Serial Real Time Clock is a low power, full BCD clock/calendar plus 56 bytes of nonvolatile SRAM. Address and data are transferred serially via a 2-wire bi-directional bus. The clock/calendar provides seconds, minutes, hours, day, date, month, and year information. Corrections for leap year is automatically adjusted for in months with less than 31 days including AM/PM indicator. The DS1307Z-TD power sense circuit which detects power failures and automatically switches to the battery supply.

OPERATION

The DS1307Z-TD operates as a slave device on the serial bus. Access is obtained by implementing a START condition and providing a device identification code followed by a register address. Subsequent registers can be accessed sequentially until a STOP condition is received. When V_{CC} falls below V_{BAT} the device enters a low current battery backup mode. Upon power up, the device switches from battery to V_{CC} when V_{CC} is greater than V_{BAT} +0.2V and recognizes inputs when V_{CC} is greater than 1.15 x V_{BAT}. The block diagram in Figure 1 shows the main elements of the Serial Real Time Clock.

DS1307Z-TD BLOCK DIAGRAM

:



SIGNAL DESCRIPTIONS

V_{CC}, GND - DC power is provided to the device on these pins. V_{CC} is the +5 volt input. When 5 volts is applied within normal limits, the device is fully accessible and data can be written and read. When a 3-volt battery is connected to the device and V_{CC} is below 1.15 x V_{BAT}, reads and writes are inhibited. However, the Timekeeping function continues unaffected by the lower input voltage. As V_{CC} falls below V_{BAT} the RAM and timekeeper are switched over to the external power supply (nominal 3.0V DC) at V_{BAT}.

V_{BAT} - Battery input for any standard 3-volt lithium cell or other energy source. Battery voltage must be held between 2.0 and 3.5 volts for proper operation. The nominal write protect trip point voltage at which access to the real time clock and user RAM is denied is set by the internal circuitry as 1.15 x V_{BAT} nominal. A lithium battery with 100 mAh or greater will back up the DS1307Z-TD for more than 10 years in the absence of power at 25 degrees C.

SCL (Serial Clock Input) - SCL is used to synchronize data movement on the serial interface.

SDA (Serial Data Input/Output) - SDA is the input/output pin for the 2-wire serial interface. The SDA pin is open drain which requires an external pullup resistor.

SQW/OUT (Square Wave/ Output Driver) - When enabled, the SQWE bit set to 1, the SQW/OUT pin outputs one of four square wave frequencies (1 Hz, 4 kHz, 8 kHz, 32 kHz). The SQW/OUT pin is open drain which requires an external pullup resistor. SQW/OUT will operate with either V_{CC} or V_{BAT} applied.

X1, X2 - Connections for a standard 32.768 kHz quartz crystal. The internal oscillator circuitry is designed for operation with a crystal having a specified load capacitance (CL) of 12.5 pF.

RTC AND RAM ADDRESS MAP

The address map for the RTC and RAM registers of the DS1307Z-TD is shown in Figure 2.

The clock registers are located in address locations 00h to 07h. The RAM registers are located in address locations 08h to 3Fh. During a multi-byte access, when the address pointer reaches 3Fh, the end of RAM space, it wraps around to location 00h, the beginning of the clock space.

DS1307Z-TDADDRESS MAP Figure 2

SECONDS	00H
MINUTES	
HOURS	
DAY	
DATE	
MONTH	
YEAR	
CONTROL	07H
RAM	08H
56 x 8	3FH

CLOCK AND CALENDAR

The time and calendar information is obtained by reading the appropriate register bytes. The real time clock registers are illustrated in Figure 3. The time and calendar are set or initialized by writing the appropriate register bytes. The contents of the time and calendar registers are in the Binary-Coded Decimal (BCD) format. Bit 7 of Register 0 is the Clock Halt (CH) bit. When this bit is set to a 1, the oscillator is disabled. When cleared to a 0, the oscillator is enabled.

Please note that the initial power on state of all registers is not defined. Therefore it is important to

enable the oscillator (CH bit=0) during initial configuration.

The DS1307Z-TD can be run in either 12-hour or 24-hour mode.

Bit 6 of the hours register is defined

~~as the bit 5 in 24-hour mode is with 10. When high in the PM-hour mode this 24-bit mode, the 52 is the second 10 hour bit (20- 23 hours).~~

On a 2-wire START, the current time is transferred to a second set of registers. The time information is read from these secondary registers, while the clock may continue to run. This

	BIT7							BIT0			
00H	CH	10 SECONDS			SECONDS						
	X	10 MINUTES			MINUTES						
	X	12 24	10 HR A/P	10 HR	HOURS						
	X	X	X	X	X	DAY					
	X	X	10 DATE		DATE						
	X	X	X	10 MONTH	MONTH						
	10 YEAR				YEAR						
07H	OUT	X	X	SQWE	X	X	RS1	RS0			

00-59
00-59
01-12
00-23
1-7
01-28/29
01-30
01-31
01-12
00-99

eliminates the need to re-read the registers in case of an update of the main registers during a read.

DS1307Z-TD TIMEKEEPER REGISTERS Figure 3

CONTROL REGISTER

The DS1307Z-TD Control Register is used to control the operation of the SQW/OUT pin.

OUT pin.	BIT 6	BIT 5	BIT 4	BIT 3	BIT 2	BIT 1	BIT 0
OUT	X	X	SQWE	X	X	RS1	RS0

OUT (Output control): This bit controls the output level of the SQW/OUT pin when the square wave output is disabled. If SQWE=0, the logic level on the SQW/OUT pin is 1 if OUT=1 and is 0 if OUT=0.

SQWE (Square Wave Enable): This bit, when set to a logic 1, will enable the oscillator output. The frequency of the square wave output depends upon the value of the RS0 and RS1 bits.

RS (Rate Select):

These bits control the frequency of the square wave output when the square wave output has been enabled. Table 1 lists the square wave frequencies that can be selected with the RS bits.

SQUAREWAVE OUTPUT FREQUENCY Table 1

RS1	RS0	SQW OUTPUT FREQUENCY
0	0	1 Hz
0	1	4.096 kHz
1	0	8.192 kHz
1	1	32.768 kHz


2-WIRE SERIAL DATA BUS

The DS1307Z-TD supports a bi-directional 2-wire bus and data transmission protocol.

A device that

sends data onto the bus is defined as a transmitter and a device receiving data as a receiver. The device that controls the message is called a master. The devices that are controlled by the master are referred to as slaves. The bus must be controlled by a master device which generates the serial clock (SCL), controls the bus access, and generates the START and STOP conditions. The DS1307Z-TD operates as a slave on the 2-wire bus. A typical bus configuration using this 2-wire

pr



TYPICAL 2-WIRE BUS CONFIGURATION Figure 4

Figures 5, 6, and 7 detail how data is transferred on the 2-wire bus.

- Data transfer may be initiated only when the bus is not busy.
- During data transfer, the data line must remain stable whenever the clock line is HIGH. Changes in the data line while the clock line is high will be interpreted as control signals.

Accordingly, the following bus conditions have been defined:

Bus not busy: Both data and clock lines remain HIGH.

Start data transfer: A change in the state of the data line, from HIGH to LOW, while the clock is HIGH, defines a START condition.

Stop data transfer: A change in the state of the data line, from LOW to HIGH, while the clock line is HIGH, defines the STOP condition.


Data valid: The state of the data line represents valid data when, after a START condition, the data line is stable for the duration of the HIGH period of the clock signal. The data on the line must be changed during the LOW period of the clock signal. There is one clock pulse per bit of data.

Each data transfer is initiated with a START condition and terminated with a STOP condition. The number of data bytes transferred between START and STOP conditions is not limited, and is determined by the master device. The information is transferred byte-wise and each receiver acknowledges with a ninth bit. Within the 2-wire bus specifications a regular mode (100 kHz clock rate) and a fast mode (400 kHz clock rate) are defined. The DS1307Z-TD operates in the regular mode (100 kHz) only.

Acknowledge: Each receiving device, when addressed, is obliged to generate an acknowledge after the reception of each byte. The master device must generate an extra clock pulse which is associated with this acknowledge bit.

A device that acknowledges must pull down the SDA line during the acknowledge clock pulse in such a way that the SDA line is stable LOW during the HIGH period of the acknowledge related clock pulse. Of course, setup and hold times must be taken into account. A master must signal an end of data to the slave by not generating an acknowledge bit on the last byte that has been clocked out of the slave. In this case, the slave must leave the data line HIGH to enable the master to generate the STOP condition.

DATA TRANSFER ON 2-WIRE SERIAL BUS Figure 5



Depending upon the state of the R/W bit, two types of data transfer are possible:

1. **Data transfer from a master transmitter to a slave receiver.** The first byte transmitted by the

master is the slave address. Next follows a number of data bytes. The slave returns an acknowledge

bit after each received byte. Data is transferred with the most significant bit (MSB) first.

2. **Data transfer from a slave transmitter to a master receiver.** The first byte (the slave address) is

transmitted by the master. The slave then returns an acknowledge bit. This is followed by the slave

transmitting a number of data bytes. The master returns an acknowledge bit after all received bytes

other than the last byte. At the end of the last received byte, a 'not acknowledge' is returned.

The master device generates all of the serial clock pulses and the START and STOP conditions. A transfer is ended with a STOP condition or with a repeated START condition. Since a repeated START condition is also the beginning of the next serial transfer, the bus will not be released. Data is transferred with the most significant bit (MSB) first.

The DS1307Z-TD may operate in the following two modes:

1. Slave receiver mode (DS1307Z-TD write mode):

Serial data and clock are received through SDA and

SCL. After each byte is received an acknowledge bit is transmitted. START and STOP conditions

are recognized as the beginning and end of a serial transfer. Address recognition is

performed by

hardware after reception of the slave address and *direction bit (See Figure 6). The address byte is

the first byte received after the start condition is generated by the master. The address byte contains

the 7 bit DS1307Z-TDaddress, which is 1101000, followed by the *direction bit (R/W) which, for a write,

is a 0. After receiving and decoding the address byte the device outputs an acknowledge on the SDA


line. After the DS1307Z-TDacknowledges the slave address + write bit, the master transmits a register

address to the DS1307Z-TD. This will set the register pointer on the DS1307Z-TD. The master will then begin

transmitting each byte of data with the DS1307Z-TDacknowledging each byte received. The master will

generate a stop condition to terminate the data write.

DATA WRITE - SLAVE RECEIVER MODE Figure 6



2. Slave transmitter mode(DS1307Z-TDread mode):

The first byte is received and handled as in the slave

receiver mode. However, in this mode, the *direction bit will indicate that the transfer direction is

reversed. Serial data is transmitted on SDA by the DS1307Z-TD while the serial clock is input on SCL.

START and STOP conditions are recognized as the beginning and end of a serial transfer (See

Figure 7). The address byte is the first byte received after the start condition is generated by the

master. The address byte contains the 7-bit DS1307Z-TDaddress, which is 1101000, followed by the

*direction bit (R/W) which, for a read, is a 1. After receiving and decoding the address byte the

device inputs an acknowledge on the SDA line. The DS1307Z-TD then begins to transmit data starting


with the register address pointed to by the register pointer. If the register pointer is not written to

before the initiation of a read mode the first address that is read is the last one stored in the

register

pointer. The DS1307Z-TD must receive a Not Acknowledge to end a read.

DATA READ - SLAVE TRANSMITTER MODE Figure 7



ABSOLUTE MAXIMUM RATINGS*

Voltage on Any Pin Relative to Ground	-0.5V to +7.0V
Operating Temperature (industrial)	0° C to 70° C (-40° C to 85° C for
Storage Temperature	-55° C to +125° C
Soldering Temperature	260° C for 10 seconds DIP See JPC/JEDEC Standard J-STD-020A for Surface Mount Devices

* This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operation sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods of time may affect reliability.

RECOMMENDED DC OPERATING CONDITIONS

(0° C to 70° C or -40° C to +85° C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	NOTES
Supply Voltage	V _{CC}	4.5	5.0	5.5	V	1
Logic 1	V _{IH}	2.2		V _{CC} +0.3	V	1
Logic 0	V _{IL}	-0.3		+0.8	V	1
VBAT Battery Voltage	V _{BAT}	2.0		3.5	V	1

DC ELECTRICAL CHARACTERISTICS

(0° C to 70° C or -40° C to +85° C; V_{CC} = 4.5V to 5.5V)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	NOTES
Input Leakage	I _{LI}			1	uA	10
I/O Leakage	I _{LO}			1	uA	11
Logic 0 Output	V _{OL}			0.4	V	2


Active Supply Current	I _{CCA}			1	mA	9
Standby Current	I _{CCS}			500	uA	3
Battery Current (OSC ON); SQW/OUT OFF	I _{BAT1}		1	2	uA	4
Battery Current (OSC ON); SQW/OUT ON (32 kHz)	I _{BAT2}		1.2	2	uA	4

AC ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	NOTES
SCL Clock Frequency	f _{SCL}	0		100	kHz	
Bus Free Time Between a STOP and START Condition	t _{BUF}	4.7		1	us	
Hold Time (Repeated) START Condition	t _{HD:STA}	4.0			us	5
LOW Period of SCL Clock	t _{LOW}	4.7			us	
HIGH Period of SCL Clock	t _{HIGH}	4.0			us	
Set-up Time for a Repeated START Condition	t _{SU:STA}	4.7			us	
Data Hold Time	t _{HD:DAT}	0			us	6,7
Data Set-up Time	t _{SU:DAT}	250			ns	
Rise Time of Both SDA and SCL Signals	t _R			1000	ns	
Fall Time of Both SDA and SCL Signals	t _F			300	ns	
Set-up Time for STOP Condition	t _{SU:STO}	4.7			us	
Capacitive Load for each Bus Line	C _B			400	pF	8
I/O Capacitance	C _{I/O}		10		pF	
Crystal Specified Load Capacitance			12.5		pF	

NOTES:

1. All voltages are referenced to ground.
2. Logic zero voltages are specified at a sink current of 5 mA at V_{CC}=4.5V, V_{OL}=GND for capacitive loads.
3. I_{CCS} specified with V_{CC}=5.0V and SDA, SCL=5.0V.
4. V_{CC}=0V, V_{BAT}=3V.
5. After this period, the first clock pulse is generated.
6. A device must internally provide a hold time of at least 300 ns for the SDA signal (referred to the VIHMIN of the SCL signal) in order to bridge the undefined region of the falling edge of SCL.
7. The maximum t_{HD:DAT} has only to be met if the device does not stretch the LOW period (t_{LOW}) of the SCL signal.
8. C_B - total capacitance of one bus line in pF.
9. I_{CCA} - SCL clocking at max frequency = 100 kHz.
10. SCL only.
11. SDA and SQW/OUT



TIMING DIAGRAM Figure 8