

Features


- ◆ 80W (8/20 μ s) Peak Pulse Power
- ◆ Ultra-Low Capacitance ESD Protection
- ◆ DFN1006-2 Package
- ◆ RoHS Compliant
- ◆ Matte Tin Lead finish (Pb-Free)
- ◆ Protect One High Speed Data Line
- ◆ Meet IEC61000-4-2 Level 4:

Contact Discharge > 15kV

Air Discharge > 20kV



Circuit Diagram



Package Outline

Applications


- ◆ Serial ATA
- ◆ USB Ports
- ◆ MDDI Ports
- ◆ Display Port
- ◆ PCI Express
- ◆ Digital Visual Interface (DVI)
- ◆ Cellular Handsets and Accessories

Maximum Ratings (Ta = 25°C)

Symbol	Parameter	Value	Unit
PPK	Peak Pulse Power	80	W
IPP	Peak Pulse Current	3.8	A
VESD (Contact)	Contact ESD Voltage per IEC61000-4-2	15	kV
VESD (Air)	Air ESD Voltage per IEC61000-4-2	20	kV
TJ	Junction Temperature	-55 to +125	°C
TSTG	Storage Temperature	-55 to +150	°C

Portion Electronics Parameter


Symbol	Parameter
I_T	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_C




Electrical Characteristics (Ta = 25°C)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
VRWM	Reverse Working Peak Voltage				5	V
VBR	Reverse Breakdown Voltage	$I_T = 1\text{mA}$	6			V
IR	Reverse Leakage Current	$VRWM = 5\text{V}$			0.1	μA
VC	Clamping Voltage	$IPP = 1\text{A} (8/20\mu\text{s})$			12	V
VC	Clamping Voltage	$IPP = 3.8\text{A} (8/20\mu\text{s})$			23	V
CJ	Capacitance	$VR = 0\text{V}, f = 1\text{MHz}$		0.35	0.5	pF


Typical Performance Curves




Junction Capacitance vs. Reverse Voltage




Clamping Voltage vs. Peak Pulse Current




Peak Pulse Power vs. Pulse Time



IEC61000-4-2 Pulse Waveform




Power Derating Curve




8 X 20us Pulse Waveform

DFN1006-2(0402)Package Outline Drawing



SYM	DIMENSIONS					
	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.45	0.50	0.55	0.018	0.020	0.022
A1	0.00	0.02	0.05	0.000	0.001	0.002
b	0.45	0.50	0.55	0.018	0.020	0.022
c	0.12	0.15	0.18	0.005	0.006	0.007
D	0.95	1.00	1.05	0.037	0.039	0.041
e	0.65 BSC			0.026 BSC		
E	0.55	0.60	0.65	0.022	0.024	0.026
L	0.20	0.25	0.30	0.008	0.010	0.012
h	0.07	0.12	0.17	0.003	0.005	0.007

Suggested Land Pattern



SYM	DIMENSIONS	
	MILLIMETERS	INCHES
X	0.60	0.024
Y1	0.50	0.020
Y2	0.30	0.012
Y3	0.80	0.032
Z	1.30	0.052