版 本	变 更 内 容	工程确认	日 期



NOTE
1. Material
   Plunger: Brass C6801
   Barrel: Brass C6801
   Spring: SUS 304
2. Plating
   Plunger: 1 micro-inch minimum Au over 50~100 micro-inch nickel
   Barrel: 1 micro-inch minimum Au over 50~100 micro-inch nickel
3. Electrical
   Rated current & voltage: DC 12V; 1.0A Max.
   Contact resistance: 50 mohm maximum at normal working height(quiescence)
4. Mechanic
   Spring force: 60g±20% at normal working height
   Durability: 10,000 cycles(minimum)
5. To ensure the best usage,please operate it based on the working height
   Based on the engineering drawings,shall not exceed the maximum allowed compression
6. To avoid arcing issue, The adaptor start to power supply after connector mated fully.
7. RoHS compliant product.

深圳市怡远科技有限公司 SHENZHEN YIYUAN TECHNOLOGY CO.,LTD		页码 (SHEET)	1/1
		版本 (REV)	A1
		日期 (DATE)	2021.10.12
品名 (ITEM NO)	M2x10.5导电铜针	设计 (DESIGN)	LUO
料号 (PART NO)	YTC1P-8025-01	审核 (CHECKED)	ROGER LI
图号 (DWG NO)		核准 (APPROVED)	ROC ZHAO

单位(UNIT): MM
比例(SCALE)
未注公差 TOLERANCE UNSPECIFIED
X.X ±0.15
X.XX ±0.10
X.XXX
ANG. ±2°

These drawings and specifications are Shenzhen Yiyuan Technology Co Ltd.The property should not be copied. Without Shenzhen Yiyuan Technology Co. Ltd.Prior written consent to copy or use in any way. Email at info@yiyuanswitches.com