

281/282 Series Panel Mount Holders for MICRO™/TR3® Fuses



Dimensions units in inch (mm)

0281 0001

Front of Panel Mounting with Push-On / Rear Retaining Nut






Mounting Hole 190" 193" 158" 158" 160"


Rear of Panel Mounting with Threaded Knurled / Front Retaining Nut Sealed/Moisture Resist Knob Note: These products are shipped unassembled and without fuse device Front of Panel Mounting with Threaded Hex / Rear Retaining Nut

Dimensions units in inch (mm)

0282 0002 and 0282 0008 Rear of Panel Mounting with Threaded Knurled / Front Retaining Nut



0282 0001 and 0282 0007 Front of Panel Mounting with Threaded Hex / Rear Retaining Nut



Product Characteristics			
Compatible Fuses	MICRO™/TR3®		
Description	Panel mount holder designed for Littelfuse MICRO™/TR3® type and other fuse series with .025" diameter leads rated to 5 amps		
Electrical Specs	Rated at 5 amperes for any voltage up to 125 volts		
Mounting Specs	Maximum panel thickness is .09".		
Ambient Temp.	-40°C to +125°C.		
Retaining Hardware	"Push-On" retaining nut		
Molded Material	Black Thermoset		
Terminal Material	Beryllium copper with silver plating		

Note: Ensure proper fuseholder de-rating.

Product Characteristics			
Compatible Fuses	MICRO™/TR3®		
Description	RF-shielded and drip-proof screw-on knob design enables use of Littelfuse MICRO™/TR3® fuses when presence of moisture exists at front of panels		
Electrical Specs	Rated at 5 amperes for any voltage up to 125 volts.		
Mounting Specs	Front panel mount, maximum panel thickness: .093". Rear panel mount, maximum panel thickness: .125".		
Ambient Temp.	-40°C to +125°C.		
Mounting Gasket Options	Neoprene (282001, 282002) or Conductive Silicone (282007, 282008)		
Retaining Hardware Options	Threaded Hex Nut (282002, 282008) or Threaded Knurled Nut (282001, 282007)		
Molded Material	Black thermoset.		
Housing, Knob and Nut Material	Aluminum, untreated.		
Terminal Material	Beryllium copper with silver plating		
Knob Seal	Buna "N" O-ring inside the knob.		

Note: Ensure proper fuseholder de-rating.



Radial Leaded Fuse Holders

Ordering Information Ordering Number 0281 0001

Ordering Information				
Ordering Number				
Rear Mounting (Threaded Knurled Nut)	Front Mounting (Threaded Hex Nut)	Gasket Type		
0282 0002	0282 0001	Neoprene		
0282 0008	0282 0007	Conductive Silicone		

Note: These products are shipped unassembled and without fuse device

Additional Information



Datasheet 281 Series



Datasheet 282 Series



Resources 281 Series



Resources 282 Series



Samples 281 Series



Samples 282 Series