

## NOTES:

- 1. © REPRESENTS A CRITICAL DIMENSION.
- 2. MINIMUM PUSHOUT FORCE: 4.44N[1.0 LB]
- 3. POST HEIGHT VARIATION BETWEEN ANY TWO PINS: 0.13[.005] MAXIMUM
- 4. MAXIMUM PIN ROTATION IN BODY TO BE 2°
- 5. DUAL POLARIZATION SLOT NOT AVAILABLE ON CONNECTOR WITH LESS THAN 5 POSITIONS.
- 6. MINIMUM RETENTION FORCE FOR WELD TABS: 4.44N[1.0 LB].

### UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS. TOLERANCES ARE:

**DECIMALS ANGLES** 2 ° X.X: ±0.3 [.01] X.XX: ±0.13 [.005]

KAPTON: POLYIMIDE FILM

X.XXX: ±0.051 [.0020]

DO NOT SCALE DRAWING INSULATOR: LCP, COLOR: BLACK TERMINAL: PHOS BRONZE WELD TAB: PHOS BRONZE

# SHEET SCALE: 2:1

THIS DOCUMENT CONTAINS CONFIDENTIAL AND

PROPRIETARY INFORMATION AND ALL DESIGN.

MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC,

INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE
OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR

REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY

OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS

520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

### DESCRIPTION


2mm SHROUDED TERMINAL STRIP


DWG. NO


T2M-1XX-XX-X-D-XX-XX

BY: J. BORGELT 3/23/09 SHEET 1 OF 3

F:\DWG\MISC\MKTG\T2M-1XX-XX-D-XX-XX-MKT.SLDDRW












FIG 6 T2M-105-01-X-D-TH-DS SHOWN (SAME AS FIG 1, EXCEPT AS SHOWN) (ONLY AVAILABLE WITH -TH & -SM OPTION)

| TABLE 1     |                |       |
|-------------|----------------|-------|
| OPTIONS     | PACKAGING TUBE | PLUG  |
| -TH, -TH-WT | PT-1-24-01-103 | TP-09 |
| -SM, -SM-WT | PT-T2M002      | TP-09 |
| -RA, -RA-WT | PT-T2M001      | TP-07 |
| -TH-DS      | PT-1-24-01-103 | TP-09 |
| -SM-DS      | PT-T2M002      | TP-09 |







-TR PACKAGING VIEW
ALL PARTS ARE LOADED WITH POSITIONS 1
TOWARDS ROUND HOLE




<u>-TH, -TH-WT OPTION</u>

-PT-T2M001







-SM-DS OPTION

PACKAGING
ALL PARTS ARE LOADED WITH POSITIONS 1
TOWARDS ARROW

# \* PROPRIETARY NOTE THIS DOCUMENT CONTAINS CONFIDENTIAL AND

PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMITEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON DE REITTY MOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMITEC, INC.

DO NOT SCALE DRAWING

SHEET SCALE: 2:1



520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

DESCRIPTION:

2mm SHROUDED TERMINAL STRIP

DWG. NO. T2M-1XX-XX-X-D-XX-XX

J. BORGELT 3/23/09 SHEET 3 OF 3

F:\DWG\MISC\MKTG\T2M-1XX-XX-D-XX-XX-MKT.SLDDRW