

Economy Power 2.5

TE Internal #: 1969590-4

Housing, Receptacle, Wire-to-Panel / Wire-to-Wire, 4 Position, 2.5 mm [.098 in] Centerline, Crimp, 1 Row, White, Wire & Cable,

Economy Power 2.5

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings











Connector Product Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Panel, Wire-to-Wire

Number of Positions: 4

Centerline (Pitch): 2.5 mm [.098 in]

Features

Product Type Features

busing
eceptacle
ire-to-Panel, Wire-to-Wire
ire & Cable
0 VAC
hite
ir o

Contact Features



Contact Base Material	Brass
Contact Type	Pin
Contact Current Rating (Max)	7.5 A
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Strain Relief	Without
Panel Mount Feature	With
Mating Retention Type	Latch
PCB Mount Retention	Without
Mating Retention	With
Connector Mounting Type	Panel Mount
Housing Features	
Housing Material	Nylon - GF
Housing Entry Configuration	Both Ends Closed
Centerline (Pitch)	2.5 mm[.098 in]
Dimensions	
Connector Width	18.17 mm[.715 in]
Compatible Insulation Diameter Range	1.3 – 1.7 mm[.051 – .067 in]
Connector Height	6.6 mm[.26 in]
Wire Size	26 – 22 AWG
Connector Length	12.5 mm[.492 in]
Connector Length Usage Conditions	
Usage Conditions	12.5 mm[.492 in]
Usage Conditions Operating Temperature Range	12.5 mm[.492 in]
Usage Conditions Operating Temperature Range Operation/Application	12.5 mm[.492 in] -25 - 105 °C[-13 - 221 °F]
Usage Conditions Operating Temperature Range Operation/Application Circuit Application	12.5 mm[.492 in] -25 - 105 °C[-13 - 221 °F]
Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards	12.5 mm[.492 in] -25 – 105 °C[-13 – 221 °F] Power & Signal
Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards UL Flammability Rating	12.5 mm[.492 in] -25 – 105 °C[-13 – 221 °F] Power & Signal UL 94V-0
Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards UL Flammability Rating Glow Wire Rating	12.5 mm[.492 in] -25 – 105 °C[-13 – 221 °F] Power & Signal UL 94V-0



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts













TE Part # 1969590-3 HSG, REC, PANEL MOUNT, SINGLE ROW,EP2.5



TE Part # 1969590-7 HSG, REC, PANEL MOUNT, SINGLE ROW,EP2.5



TE Part # 1969590-8 HSG, REC, PANEL MOUNT, SINGLE ROW,EP2.5



TE Part # 1969590-9 HSG, REC, PANEL MOUNT, SINGLE ROW,EP2.5



TE Part # 1-1969590-4

HSG, REC, PANEL MOUNT, SINGLE

ROW,EP2.5



TE Part # 1-1969590-0 HSG, REC, PANEL MOUNT, SINGLE ROW,EP2.5



TE Part # 1969590-2 HSG, REC, PANEL MOUNT, SINGLE ROW,EP2.5



TE Part # 1-1969590-3 HSG, REC, PANEL MOUNT, SINGLE ROW,EP2.5



TE Part # 1-1969590-2 HSG, REC, PANEL MOUNT, SINGLE ROW,EP2.5




TE Part # 1-1969590-1 HSG, REC, PANEL MOUNT, SINGLE ROW,EP2.5



TE Part # 1969590-6 HSG, REC, PANEL MOUNT, SINGLE ROW,EP2.5


Also in the Series | Economy Power 2.5



Connector Contacts(6)




Connector Hardware(49)



PCB Headers & Receptacles(533)



Wire-to-Board Connector Assemblies & Housings(305)



Customers Also Bought





TE Part #1744417-6 6 POS EP 2.5 HSG, GLOW WIRE



TE Part #1740261-2 NECTOR S RING CLIP BLACK



TE Part #293284-1 NECTOR S BUS BAR BOOT





TE Part #1969590-2 HSG, REC, PANEL MOUNT, SINGLE ROW,EP2.5



TE Part #1740260-2 NECTOR S TUBE BLACK



TE Part #1969442-4 EP 2.5 TPA Housing, 4 Pos



TE Part #2232905-1
EP 2.5 LIF RCPT CONTACT, 26-22
AWG





Documents

Product Drawings

HSG, REC, PANEL MOUNT, SINGLE ROW, EP2.5

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1969590-4_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1969590-4_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1969590-4_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Housing, Receptacle, Wire-to-Panel / Wire-to-Wire, 4 Position, 2.5 mm [.098 in] Centerline, Crimp, 1 Row, White, Wire & Cable, Economy Power 2.5



Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

VDE Certificate

English