



## SPECIFICATIONS

Current Rating: 1.5 Amps  
Insulation Resistance:  $1000M\ \Omega$  Min  
Contact Resistance:  $20m\Omega$  Max  
Withstanding Voltage: AC 500V  
Operation Temperature:  $-40^{\circ}$  to  $+105^{\circ}$   
Contact Material: Brass  
Standard: PA6T  
Insulator Material: Polyester (UL 94V-0)  
Contact Plating: Gold Flash  
Max. Processing Temp:  $240^{\circ}$  C for 30-60 seconds  
( $260^{\circ}$  C for 5 seconds)

## RECOMMEND P. C. B LAYOUT

PCB TOLERANCE:  $\pm 0.05$  (TOP VIEW)



深圳市韩下电子有限公司

UNLESS OTHERWISE SPECIFIED TOLERANCE

X :  $\pm 0.30$  X° :  $\pm 5^{\circ}$   
X.X :  $\pm 0.25$  X.X° :  $\pm 1^{\circ}$   
X.XX :  $\pm 0.20$  X.XX° :  $\pm 0.5^{\circ}$

DRAWN NAME:

HX PZ2.0-2x9P WT

SIZE

A4

SCALE

N:1

PROUCT NO.

REV

A

UNIT

mm

PROJECT

PAGE

1/1

DRAW

黄彬

2022/07/19

CHECKED:

张伟

2022/07/19

APPROVED:

罗小春

2022/07/19

No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B
1	0.00	2.00	11	20.00	22.00	21	40.00	42.00	31	60.00	62.00
2	2.00	4.00	12	22.00	24.00	22	42.00	44.00	32	62.00	64.00
3	4.00	6.00	13	24.00	26.00	23	44.00	46.00	33	64.00	66.00
4	6.00	8.00	14	26.00	28.00	24	46.00	48.00	34	66.00	68.00
5	8.00	10.00	15	28.00	30.00	25	48.00	50.00	35	68.00	70.00
6	10.00	12.00	16	30.00	32.00	26	50.00	52.00	36	70.00	72.00
7	12.00	14.00	17	32.00	34.00	27	52.00	54.00	37	72.00	74.00
8	14.00	16.00	18	34.00	36.00	28	54.00	56.00	38	74.00	76.00
9	16.00	18.00	19	36.00	38.00	29	56.00	58.00	39	76.00	78.00
10	18.00	20.00	20	38.00	40.00	30	58.00	60.00	40	78.00	80.00