

EKMC(VZ) series

Current consumption **170μA**

Digital output



Standard detection type



Long distance detection type



Wall installation type

○Economy type suitable for a wide range of applications

Recommended applications

Lighting control, lighting equipment, heaters, ventilators or air conditioners, security equipment for IP cameras, intrusion alarms, digital signage, vending machines, multi-function printers, display panels for meeting rooms, PCs

Lensless type available

170μA type: EKMC1600100

Specifications

Detection performance	Model no.	Current consumption	Lens color	Output type	Detection distance	Detection area		Detection zones
						Horizontal	Vertical	
Standard detection type 	EKMC1601111	170μA	White	Digital	5m	94°	82°	64
	EKMC1601112		Black					
	EKMC1601113		Pearl white					
Long distance detection type 	EKMC1603111		White		12m	102°	92°	92
	EKMC1603112		Black					
	EKMC1603113		Pearl white					
Wall installation type 	EKMC1604111		White		12m (1st step lens)	40°	105°	68
	EKMC1604112		Black		6m (2nd step lens)			
	EKMC1604113		Pearl white		3m (3rd step lens)			

Ordering information

EKMC16 **1**

●PaPIRs motion sensor

●Detection (Lens)

00: Lensless / 01: 5m distance standard /
03: 12m long distance / 04: Wall installation type

●Lens color

0: Lensless / 1: White /
2: Black / 3: Pearl white

●Lens

0: Lensless / 1: with lens

Characteristics

Maximum rated values

Items	Value
Power supply voltage	-0.3 to 7V
Ambient temperature	-20 to +60°C (no frost, no condensation)
Storage temperature	-20 to +70°C


Electrical characteristics

Items		Symbol	EKMC (VZ) type	Conditions
Operating voltage	Max	Vdd	6.0V	—
	Min		3.0V	
Current consumption (in standby mode) Note 1)	Ave	Iw	170μA	Ambient temperature: 25°C Iout=0 Vdd: 5V
Output current (during detection) Note 2)	Max	Iout	100μA	Ambient temperature: 25°C Vout≥Vdd-0.5
Output voltage (during detection period)	Min	Vout	Vdd-0.5V	Ambient temperature: 25°C Open at no detection
Circuit stability time (when voltage is applied)	Max	Twu	30 sec	Ambient temperature: 25°C Iout=0 Vdd: 5V

Note 1) Current consumption during detection period is the total value of current consumption in standby mode add to output current.

Note 2) Please select an output resistors (pull-down concept) in accordance with Vout so that the output current is lower than or equal to 100μA. If the output current is more than 100μA, this may cause false alarms.

Timing chart



[Explanation of the timing]



Twu: Circuit stability time: max. 30 sec

During this stage, the output's status is undefined (ON/OFF) and detection is therefore not guaranteed.

EKMB series



Detection characteristics

CAD data






Detection distance	Max. 5m
Field of view	94°×82°
Detection zone	64 beams
Detection condition	·The temperature difference between the target and the surroundings must be higher than 4℃. ·Movement speed: 1.0m/s ·Target concept: Human body with an approx. size of 700×250mm ·Target moving direction: Crossing the detection beam.

CAD data





Detection distance	Max. 12m
Field of view	102°×92°
Detection zone	92 beams
Detection condition	·The temperature difference between the target and the surroundings must be higher than 4℃. ·Movement speed: 1.0m/s ·Target concept: Human body with an approx. size of 700×250mm ·Target moving direction: Crossing the detection beam.

CAD data



Detection distance	1st step lens	Max. 12m
	2nd step lens	Max. 6m
	3rd step lens	Max. 3m
Field of view	40°×105°	
Detection zone	68 beams	
Detection condition	·The temperature difference between the target and the surroundings must be higher than 4℃. ·Movement speed: 1.0m/s ·Target concept: Human body with an approx. size of 700×250mm ·Target moving direction: Crossing the detection beam.	


■ PIR element



Detection sensitivity	Average: $5.6 \mu\text{W}/\text{cm}^2$ Maximum: $7.6 \mu\text{W}/\text{cm}^2$
-----------------------	---

※Detection sensitivity is measured by following system

■ Test setup



Panasonic PaPIRs

Search

Please refer to the formal specification for the dimension, and the tolerance ※Please note that the horizontal and vertical field of view depends on the position of the metal tab on which the lens is mounted.

Horizontally wide detection type

Current consumption **1/2/6/170μA**

Digital output

> World's first PIR with "Approach Sensing" technology


Panasonic presents the world's first PIR sensor in the shape of a hammerhead with a special optic, which is more sensitive to radial motion.

NEW



Recommended applications

Wall switches, thermostats, IP cameras, wake-up switch for displays, intrusion alarm sensors (e.g. for windows and doors), door intercom systems, entrance and garden lamps, automatic door systems, vending machines



Horizontally wide detection type

Current consumption in standby mode (1μA type: in sleep mode)		1μA	2μA	6μA	170μA
Output		Digital (open collector)			
Lens color	White	EKMB1105111	EKMB1205111	EKMB1305111K	EKMC1605111
	Black	EKMB1105112	EKMB1205112	EKMB1305112K	EKMC1605112
	Pearl white	EKMB1105113	EKMB1205113	EKMB1305113K	EKMC1605113

Dimension (mm)	Detection zone	Detection characteristics																					
CAD data by request		<table border="1"> <tr> <th>Detection distance</th><th colspan="2">Max. 5m*</th></tr> <tr> <th>Field of view</th><td>Area A</td><td>122° x 35°</td></tr> <tr> <th></th><td>Area B</td><td>150° x 20°</td></tr> <tr> <th>Detection zone</th><td>Area A</td><td>88</td></tr> <tr> <th></th><td>Area B</td><td>16</td></tr> <tr> <th>Detection condition ▲</th><td>Area A</td><td> - The temperature difference between the target and the surroundings must be higher than 4°C. - Movement speed: 1m/s - Target concept: human head with an approx. size of 700x250mm - Target moving direction: crossing 2 detection zones </td></tr> <tr> <th></th><td>Area B</td><td> - The temperature difference between the target and the surroundings must be higher than 8°C. - Movement speed: 1m/s - Target concept: human body with an approx. size of 700x250mm - Target moving direction: crossing 2 detection zones </td></tr> </table>	Detection distance	Max. 5m*		Field of view	Area A	122° x 35°		Area B	150° x 20°	Detection zone	Area A	88		Area B	16	Detection condition ▲	Area A	- The temperature difference between the target and the surroundings must be higher than 4°C. - Movement speed: 1m/s - Target concept: human head with an approx. size of 700x250mm - Target moving direction: crossing 2 detection zones		Area B	- The temperature difference between the target and the surroundings must be higher than 8°C. - Movement speed: 1m/s - Target concept: human body with an approx. size of 700x250mm - Target moving direction: crossing 2 detection zones
Detection distance	Max. 5m*																						
Field of view	Area A	122° x 35°																					
	Area B	150° x 20°																					
Detection zone	Area A	88																					
	Area B	16																					
Detection condition ▲	Area A	- The temperature difference between the target and the surroundings must be higher than 4°C. - Movement speed: 1m/s - Target concept: human head with an approx. size of 700x250mm - Target moving direction: crossing 2 detection zones																					
	Area B	- The temperature difference between the target and the surroundings must be higher than 8°C. - Movement speed: 1m/s - Target concept: human body with an approx. size of 700x250mm - Target moving direction: crossing 2 detection zones																					
		* Under specified detection conditions ▲ Please refer to "Cautions for use" (page 18) and "Basic principles" (page 18, point 5), for more details																					

Please contact your local sales representative for detailed specifications.

Standard and slight motion detection type

Current consumption **1/2/6/170µA**

Digital output



> 2 functions in 1 lens

High Sensitivity Centre ZONE: Optimized for detecting small movements and small objects
Normal Sensitivity Outer ZONE: Optimized for detecting larger movements of larger objects


Recommended applications

Lighting control, heaters, ventilators or air conditioners, IP cameras, intrusion alarms, digital signage, vending machines, multi-function printers, display panels for meeting rooms, PCs

NEW



Standard and slight motion detection type



Current consumption in standby mode (1µA type: in sleep mode)		1µA	2µA	6µA	170µA
Output		Digital (open collector)			
Lens color	White	EKMB1193111	EKMB1293111	EKMB1393111K	EKMC1693111
	Black	EKMB1193112	EKMB1293112	EKMB1393112K	EKMC1693112
	Pearl white	EKMB1193113	EKMB1293113	EKMB1393113K	EKMC1693113

Dimension (mm)	Detection zone	Detection characteristics
CAD data by request		
Detection distance Max. 2.2m*		
Field of view Slight motion: 44° x 44° Standard motion: 90° x 90°		
Detection zone Slight motion: 36 Standard motion: 48		
Detection condition ▲ Slight motion - The temperature difference between the target and the surroundings must be higher than 4°C. - Movement speed: 0.5m/s - Target concept: human head with an approx. size of 200x200mm - Target moving direction: crossing 1 detection zone		
Standard motion - The temperature difference between the target and the surroundings must be higher than 4°C. - Movement speed: 1.0m/s - Target concept: human body with an approx. size of 400x200mm - Target moving direction: crossing 2 detection zones		
* Under specified detection conditions ▲ Please refer to "Cautions for use" (page 18) and "Basic principles" (page 18, point 5), for more details		