



Dimension

Dim A	N×3.81
Dim B	N×3.81+0.88
Dim C	(N-1)×3.81

N=Number of poles

POLES	Tolerance
2p-6p	±0.15
7p-13p	±0.20
14p-18p	±0.30
19p-24p	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
△	12/14'11	Add is cULus Mark	ChenMing
△	12/14'11	Torque(Lb-In) is changed from 2.0(Lb-In) to 2.6(Lb-In)	ChenMing
△	12/14'11	The dimension are added	ChenMing
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

Material

- Item ① Insulator (Body):Thermoplastic (UL94V-0)
- Item ② Insulator (Cover):Thermoplastic (UL94V-0)
- Item ③ Terminal screw:Steel Zinc plating "-" slot type
- Item ④ Terminal body:Brass(CuZn) Ni plating
- Item ⑤ Contact Pin: Brass, Tin plated

Electrical cULus

- Voltage rating: 300VAC
- Current rating: 8A
- Solid wire(AWG): 14-30
- Stranded wire(AWG): 14-30
- △ ● Torque(Lb-In): 2.6
- Screw: M2
- Wire strip length: 7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- △ ● Safety Approval: cULus
- Critical dimension: ▽

V8 xx 31 x 0 xxxx G

No. OF POLES
02 2 CONTACTS
03 3 CONTACTS
... ..
24 24 CONTACTS

Color
0 Black (RAL9005)
2 Red (RAL3001/D)
3 Orange(RAL2011/P)
4 Yellow(RAL1018/A)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7035/D)
9 White(RAL1102)
C Green(RAL6018/U)

RoHS compliant
(lead<4%)
In copper Alloy

0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by
customer request.
please contact sales
department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		V8- 3.81 Series 2P-24P W/O flange				
PART NO.		V8xx31x0xxxxG		DWG NO.	8V80101	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		
		Aaron 2011.12.20	ChenMing 2011.12.14		UNIT: mm	X. ±0.5
				SCALE: NONE		X.X ±0.3
				SHEET: 01/01	REV.: C	X.XX ±0.1
						X° ±1°