






SIGN	DATE	DESCRIPTION	APPROVER
△	1/31/07	The soldering temperature from 245° to 250°	Aaron
△	05/28/13	change the structure	Da cheng
△	05/28/13	update the drawing	Da cheng
△			
△			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item ① Insulator body: Thermoplastic (UL94V-0)
- Item ② Insulating cover : Thermoplastic (UL94V-0)
- Item ③ Contact pin : Brass.Tin plated
- Item ④ Wire guard: Stainless steel
- Item ⑤ Pad board: Thermoplastic (UL94V-0)

Electrical:

- Voltage rating: 250V
- Current rating: 8A
- Wire range: 12-28
- Solid wire(AWG): 12-28
- Stranded wire(AWG): 8-9mm
- Wire strip length: 1.5KV
- Withstanding Voltage: -40°C to +115°C
- Operating temperature: cULus
- Safety Approval: cULus
- Critical dimension: △


HM xx 80 x 1 xxxx G

No. OF POLES
01: 1 POLES
02: 2 POLES
12: 12 POLES

△ COLOR
0 Black (RAL9005)
2 Red (RAL3007/D)
3 Orange(RAL2011/P)
4 Yellow(RAL1018/A)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7004/P)
9 White(RAL102)
C Multiple colors

0000 Standard @ Logo
000A Standard ANY Logo
Any special item by customer request,
please contact sales department.

△ RoHS compliant (lead<4%)
In copper Alloy



△ N=NUMBER OF POLES
Dim L (N-1)×10.0-6.5
Dim B (N-1)×10.0

△ (metal-plated hole)

P.C.B LAYOUT
Top view

POLES	Dim L	Dim B
1p	±0.15	
2p-4p	±0.2	±0.15
5p-7p	±0.3	±0.25
8p-10p	±0.4	±0.35
11p-12p	±0.45	±0.4

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	HM 10.0mm Series Press fit Type	DWG NO.	8HM0006	Tolerance
PART NO.	HMxx80x1xxxxG			X. ±0.50
APPROVED	CHECKED	DESIGNED	DRAWN	X.X ±0.30
				X.XX ±0.10
				X° ±1°

Da cheng 2013.05.28

SHEET: 01/01