




TNC / TNC 18 GHz series

R143 / R144

RADIAL 
The next conneXion

Pages

TNC

Introduction	11-4
Interface	11-4
Characteristics	11-6

TNC 50Ω

Plugs	11-8 to 11-9
Jacks	11-9 to 11-11
Receptacles	11-11 to 11-12
Caps	11-13
Adapters	11-13

TNC 75Ω

Plugs	11-17
Jacks	11-17

TNC 18 GHz

Interface	11-5
Characteristics	11-7
Plugs	11-14
Jacks	11-14 to 11-15
Receptacles	11-15
Adapters	11-16

Panel drilling	11-18
----------------------	-------

INTRODUCTION



50Ω	DC - 11 GHz (standard) DC - 18 GHz (TNC 18 GHz)
75Ω	DC - 1.5 GHz DC - 1 GHz (recommended)
50 and 75Ω	DC - 1.5 GHz (commercial)

GENERAL

- Screw-on equivalent to BNC bayonet series
- Good RF performance
- Suitable for high power levels
- Long life and high strength
- 3 ranges:
 - Standard TNC series (50 and 75Ω fully intermateable)
 - Commercial TNC series (50 and 75Ω)
 - 18 GHz TNC series (50Ω)

APPLICABLE STANDARDS


- MIL-C-39012 / MIL STD 348A/313
- IEC 60169-17
- CECC 22200

APPLICATIONS


- Avionics
- Aeronautics
- Countermeasures
- Telecommunications

INTERFACE TNC

PLUG



JACK




INTERFACE TNC

Letter	mm		inch	
	min.	max.	min.	max.
A	1.32	1.37	0.052	0.054
B	4.83	-	0.190	-
D	11.40	-	0.449	-
E	-	2.20	-	0.087
F	0.35	0.65	0.014	0.025
G	7.00	7.05	0.275	0.277
1	4.9	5.70	0.193	0.224
2	5.28	5.79	0.208	0.228
3	0.15	-	0.006	-
4	1.8	-	0.071	-
5	0.15	-	0.006	-
6	0.08	1.02	0.003	0.040
7	5.33	5.84	0.210	0.230
8	0.70	1.98	0.027	0.078


Letter	mm		inch	
	min.	max.	min.	max.
A	-	4.72	-	0.186
B	8.10	8.10	0.319	0.321
C	8.31	8.46	0.327	0.333
D	8.79	9.04	0.346	0.356
E	9.60	9.68	0.378	0.381
F	-	2.20	-	0.087
H	-	5.90	-	0.232
1	8.30	8.50	0.327	0.335
2	1.73	2.24	0.068	0.088
3	4.75	-	0.187	-
4	-	0.15	-	0.006
5	4.72	5.23	0.186	0.206
6	4.78	5.28	0.188	0.208
7	10.7	-	0.421	-
8	0.38	0.76	0.015	0.030
9	4.95	-	0.195	-

INTERFACE TNC 18 GHz

PLUG



JACK



Letter	mm		inch	
	min.	max.	min.	max.
A	6.18	6.22	0.243	0.245
B	8.03	8.09	0.316	0.319
C	11.40	11.60	0.449	0.457
D	1.34	1.36	0.053	0.054
E	0.35	0.65	0.014	0.026
F	1.62	1.66	0.064	0.065
G	5.28	5.32	0.208	0.210
1	5.28	5.38	0.208	0.212
2	5.35	5.50	0.211	0.217
3	-0.30	0.55	-0.012	0.022
4	0.35	0.90	0.014	0.065

Letter	mm		inch	
	min.	max.	min.	max.
A	4.68	4.72	0.184	0.186
B	8.10	8.15	0.319	0.321
C	8.32	8.46	0.328	0.333
D	9.61	9.68	0.379	0.381
E	6.93	6.98	0.273	0.275
F	5.28	5.32	0.208	0.210
G	1.62	1.66	0.064	0.065
H	2.14	2.18	0.084	0.086
1	4.98	5.23	0.196	0.206
2	8.36	8.46	0.329	0.333
3	0.48	1.02	0.019	0.040
4	1.80	2.20	0.071	0.087
5	10.60	11.00	0.417	0.432
6	5.18	5.28	0.204	0.208
7	-0.10	0.05	0.004	0.002
8	5.20	5.70	0.204	0.224

TNC/TNC 18 GHz

CHARACTERISTICS TNC

Test/characteristics	MIL-C-39012 A	Values/remarks
ELECTRICAL CHARACTERISTICS		
Impedance		50Ω 75Ω
Frequency range		DC - 11 GHz DC - 1.5 GHz
V.S.W.R.	3-14	1.30 max
Insertion loss	3-27	0.18 dB max at 9 GHz
RF leakage	3-26	-60 dB min from 2 to 3 GHz
Insulation resistance	3-11	5000 MΩ min
Contact resistance	3-16	Initial 1.5 0.2
		After proof 2 -
Working voltage		At sea level: 500 V rms at 70000 ft (21000 m): 125 V rms
Dielectric withstanding voltage	3-17	At sea level: 1500 V rms at 70000 ft (21000 m): 375 V rms
RF withstanding voltage	3-23	At sea level: 1000 V rms (5 MHz sine wave)

MECHANICAL CHARACTERISTICS

Durability	3-15	500 matings
Mating / unmating		axial force: not applicable torque: 1.96 inch pounds (22.6 N.cm)
Recommended mating torque		3.99 to 5.98 inch pounds (46 to 69 N.cm)
Proof torque		14.74 inch pounds (170 N.cm)
Coupling mechanism retention force	3-25	100 Lbf (44.5 daN)
Cabling retention force	3-24	cable clamp: 40.6 Lbf (181 N min) (all cables) crimped: 51 Lbf (227 N min) (cable dia. 189 (4.8) to 228 (5.8)) 764 Lbf (340 N min) (cable dia. 250 (6.35) and above)
Center contact retention		Axial: 6.06 Lbf (27 N)

ENVIRONMENTAL CHARACTERISTICS

Temperature range		-65°C / + 165°C
standard models		-65°C / +100°C
hermetic sealed models		-65°C / +105°C
models for semi-rigid cables		
Thermal shock	3-20	MIL-STD-202, method 107, condition B
High temperature endurance		MIL-STD-202, method 108
Corrosion (salt spray)	3-13	MIL-STD-202, method 101, condition B
Vibrations	3-18	MIL-STD-202, method 204, condition B
Shocks	3-19	MIL-STD-202, method 213, condition G
Moisture resistance	3-21	MIL-STD-202, method 106
Low pressure	3-22	Not applicable
Hermetic seal		Applied vacuum 10 ⁻⁶ mm of Hg (Torrs) leakage rate < 10 ⁻⁶ atm/cm ³ /s
Leakage		Pressure 3.5 bars; duration 2 mn; temperature 15°C to 25°C

MATERIALS AND PLATING

Body and center pin contact	Brass as per QQ-B-626	Nickel plated
Center socket contact	Beryllium copper as per QQ-C-530	Gold plated
Ferrules	Brass	
Insulators	PTFE teflon	
Gaskets	Silicone elastomer	

All dimensions are given in mm

CHARACTERISTICS COMMERCIAL TNC

Test/characteristics	Values/remarks
ELECTRICAL AND ENVIRONMENTAL CHARACTERISTICS	
Impedance	50Ω or 75Ω
Frequency range	DC - 1.5 GHz
Test voltage	1500 V rms
Operating voltage	500 V rms
Insulation resistance	5000 mΩ min (500 V)
Contact resistance	10 mΩ max
Temperature range	-35°C / +70°C

PLATING

Body	Nickel
Center contacts	Gold

Test/characteristics	MIL-C-39012 A	Values/remarks
----------------------	---------------	----------------

ELECTRICAL CHARACTERISTICS

Impedance		50Ω
Frequency range		DC - 18 GHz
V.S.W.R.	3-14	Semi-rigid cable: 1.17 max Flexible cable: 1.35 at 124 GHz In series adapter: 1.35 max
Insertion loss	3-27	0.18 dB max at 9 GHz
RF leakage	3-26	-60 dB min from 2 to 3 GHz
Insulation resistance	3-11	5000 MΩ min
Contact resistance	3-16	Initial 1.5 0.2 After proof 2 -
Working voltage		At sea level: 500 V rms at 70000 ft (21000 m): 125 V rms
Dielectric withstanding voltage	3-17	At sea level: 1500 V rms at 70000 ft (21000 m): 375 V rms
RF withstanding voltage	3-23	At sea level: 1000 V rms (5 MHz sine wave)

MECHANICAL CHARACTERISTICS

Durability	3-15	500 matings
Mating / unmating		axial force: not applicable torque: 1.96 inch pounds (22.6 N.cm)
Recommended mating torque		22.98 inch pounds (265 N.cm)
Proof torque		29.40 inch pounds (339 N.cm)
Coupling mechanism retention force	3-25	100 Lbf (44.5 daN)
Cabling retention force	3-24	51 Lbf (227 N min) (cable dia. .189 (4.8) to .228 (5.8)) 76.4 Lbf (340 N min) (cable dia. .250 (6.35) and above)
Center contact retention		Axial: 6.06 Lbf (27 N)

ENVIRONMENTAL CHARACTERISTICS

Temperature range		-65°C / + 165°C
standard models		-65°C / +100°C
hermetic sealed models		-65°C / +105°C
models for semi-rigid cables		
Combined climate tests		
Thermal shock	3-20	MIL-STD-202, method 107, condition B
High temperature endurance		MIL-STD-202, method 108
Corrosion (salt spray)	3-13	MIL-STD-202, method 101, condition B
Vibrations	3-18	MIL-STD-202, method 204, condition B
Shocks	3-19	MIL-STD-202, method 213, condition G
Moisture resistance	3-21	MIL-STD-202, method 106
Low pressure	3-22	Not applicable
Hermetic seal		Applied vacuum 10 ⁻⁶ mm of Hg (Torrs) Leakage rate < 10 ⁻⁶ atm/cm ³ /s
Leakage		Pressure 3.5 bars; duration 2 mn; temperature 15°C to 25°C

MATERIALS

Body		Stainless steel
Center socket contact	male	Brass
	female	Bronze
Ferrules		Brass
Insulators		PTFE teflon
Gaskets		Silicone elastomer

PLATING

Body		Passivated
Center contacts		Gold plated

Standard packaging = unit

All dimensions are given in mm (inch)

STRAIGHT PLUGS CRIMP TYPE FOR FLEXIBLE CABLE




Fig. 1




Fig. 2




Fig. 3




Fig. 4

Cable group	Cable group dia.	Part number	Fig	Dimensions mm				Captive center contact	Packaging	Note
				A	B	C	D			
RG174/RG316	2.6/50/S	R143 075 000	1	0.6	1.75	3.25	29.6	yes	100 pieces	
	3.85/50/S	R143 088 101	4	1.15	3	4.2	47	no	unit	
RG58/RG141	5/50/S	R143 082 000	2					yes	100 pieces	full crimp
		R143 082 161								commercial version, full crimp
		R143 072 000	3	1.05	3.1	5.55		no	unit	
RG142/RG223/RG400	5/50/D	R143 073 000	1	1.05	3.075	5.5		yes		
		R143 083 000	1	1.05	3.1	5.5	26.6			
RG59/RG62	6/75+93	R143 074 000	3	0.75	3.9	6.6				

STRAIGHT PLUGS CLAMP TYPE FOR FLEXIBLE AND SEMI RIGID CABLE




Fig. 1




Fig. 2




Fig. 3

Cable group	Cable group dia.	Part number	Fig	Dimensions mm			Captive center contact	Packaging	Note
				A	B	C			
RG174/RG316/RD316 RG179/RD179	2.6/50+75	R143 004 000	1	26.5	0.6	3.1	yes	unit	
RG58/RG141/RG142 RG223/RG400	5/50/S+D	R143 008 000		27.1	1.2	5.6	no	100 pieces	conical braid clamp
RG59/RG62	6/75+93	R143 012 000		27	1.05	6.65			
RG213/RG393/RG214	10+11/50	R143 018 000	2				yes	unit	
		R143 018 500							safety coupling nut
RG402	.141"	R143 052 000	3				no		

RIGHT ANGLE PLUGS CRIMP TYPE FOR FLEXIBLE CABLE




Fig. 1




Fig. 2




Fig. 3





Fig. 4

Cable group	Cable group dia.	Part number	Fig	Captive center contact	Packaging	Note
RG174/RG316	2.6/50/S	R143 181 161	1	yes	100 pieces	commercial version
RG58/RG141	5/50/S	R143 182 161	2		unit	
		R143 182 000	3		100 pieces	
RG142/RG223/RG400	5/50/D	R143 183 300	4			

RIGHT ANGLE PLUG CLAMP TYPE FOR FLEXIBLE CABLE



Cable group	Cable group dia.	Part number	Captive center contact	Packaging
RG58/RG141/RG142/RG223/RG400	5/50/S+D	R143 156 000	yes	unit

STRAIGHT JACKS CRIMP TYPE FOR FLEXIBLE CABLE




Fig. 1





Fig. 2

Cable group	Cable group dia.	Part number	Fig	Captive center contact	Panel drilling	Packaging	Note
RG58/RG141	5/50/S	R143 235 161	1	yes		100 pieces	commercial version, full crimp
	8.07/50	R143 293 390	2		P01	unit	square flange

To download data sheets and assembly instructions, visit www.radiall.com & enter the part number in the Search box.
Bold part numbers represent products typically in stock & available for immediate shipment.
 See page 8 and 9 for packaging information.

STRAIGHT BULKHEAD JACKS CRIMP TYPE FOR FLEXIBLE CABLE



Cable group	Cable group dia.	Part number	Dimensions mm				Captive center contact	Panel drilling	Packaging	Note
			A	B	C	D				
RG174/RG316	2.6/50/S	R143 331 161	38	0.6	1.75	3.10	yes	P09+P11	100 pieces	commercial version, panel sealed
RG58/RG141	5/50/S	R143 332 161	35	1.05	3.10	5.55				commercial version, panel sealed, full crimp

STRAIGHT JACKS CLAMP TYPE FOR FLEXIBLE CABLE





Fig. 1





Fig. 2


Cable group	Cable group dia.	Part number	Fig	Dimensions mm			Captive center contact	Panel drilling	Packaging	Note
				A	B	C				
RG174/RG316/RD316/RG179/RD179	2.6/50+75	R143 254 000	1	29.8	0.6	3.1	yes	P04	Unit	Square flange Also for screws type 3-56 UNF 2A
RG58/RG141/RG142/RG223/RG400	5/50/S+D	R143 258 000		30.2	1.05	5.6	no			
RG58/RG141	5/50/S	R143 207 000	2							

SQUARE FLANGE STRAIGHT JACK SOLDER TYPE FOR SEMI-RIGID CABLE



Cable group	Cable group dia.	Part number	Captive center contact	Panel drilling	Packaging
RG405	.085"	R143 257 440	no	P01	Unit

STRAIGHT BULKHEAD JACKS PANEL SEALED REAR MOUNT



Cable group	Cable group dia.	Part number	Dimensions (mm)		Captive center contact	Panel drilling	Packaging
			A	B			
RG178/RG196	2/50/S	R143 323 000	29.9	2.2	yes	P09	Unit
RG174/RG316/RD316	2.6/50	R143 324 000	29.6	3.1			100 pieces
RG58/RG141	5/50/S	R143 325 000	30.17	5.6			Unit
RG402	.141"	R143 337 000	30.8	3.7	no		100 pieces

SQUARE FLANGE STRAIGHT FEMALE RECEPTACLES




Fig. 1




Fig. 2





Fig. 3




Fig. 4

Part number	Fig	Dimensions A (mm)	Captive center contact	Panel drilling	Packaging	Note
R143 404 000	1	M2.5 x 0.45	yes	P05	Unit	Solder pot
R143 405 000		2.6			100 pieces	17.5 mm square flange
R143 406 000	2		no	P13	Unit	Insulated
R143 420 000	3			P02		18.5 mm square flange
R143 453 000	4		yes	P07		Slotted contact
						19 mm square flange
						Solder pot contact
						2 holes flange

RECEPTACLES

BULKHEAD STRAIGHT FEMALE RECEPTACLES




Fig. 1





Fig. 2


Part number	Fig	Captive center contact	Panel drilling	Packaging	Note
R143 557 000	1	yes	P08	Unit	Front mount, solder pot contact
R143 603 000	2		P10		Panel sealed, front mount, solder pot contact

RF POWER SWITCHING CONNECTORS





Part number	Type
R143 422 947	left
R143 422 957	right

SQUARE FLANGE RIGHT ANGLE FEMALE RECEPTACLE



Part number	Captive center contact	Panel drilling	Packaging	Note
R143 654 000	yes	P06	Unit	Solder pot contact

SQUARE FLANGE STRAIGHT MALE RECEPTACLE



Part number	Captive center contact	Panel drilling	Packaging	Note
R143 440 000	yes	P03	Unit	Solder pot contact

PROTECTIVE CAPS




Fig. 1




Fig. 2




Fig. 3

Part number	Fig	Finish	Packaging	Note
R143 805 000	1	Black chromium	Unit	Male with cord
R143 812 000	2	Nickel		Male with chain
R143 835 000	3		100 pieces	Female with chain

IN SERIES ADAPTERS




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10

Part number	Fig	Captive center contact	Panel drilling	Packaging	Note
R143 703 000	1	yes	P01	Unit	Male-male
R143 704 000	2				Female-female
R143 710 000	3			100 pieces	Square flange female-female
R143 713 000	4				Square flange slide on type male-female
R143 753 000	5		P09	100 pieces	Bulkhead hermetic, panel sealed female-female
R143 720 000	6				Commercial version, bulkhead female-female
R143 753 120	7				Bulkhead hermetic, panel sealed female-female
R143 770 000	8			Unit	Right angle male-female
R143 780 000	9				Female female male
R143 782 000	10				Female female female

To download data sheets and assembly instructions, visit www.radiall.com & enter the part number in the Search box.

Bold part numbers represent products typically in stock & available for immediate shipment.

See page 8 and 9 for packaging information.

PLUGS AND JACKS

STRAIGHT PLUGS CRIMP TYPE FOR FLEXIBLE CABLE




Fig. 1





Fig. 2


Cable group	Cable group dia.	Part number	Fig	Dimensions mm (inch)			
				A	B	C	D
RG142/RG223/RG400	5/50/D	R143 082 700	1	30 (1.181)	1.05 (0.041)	3.2 (.126)	5.5 (.218)
		R143 097 700	2	43.5 (1.713)	3 (.118)	5 (.197)	
	8.07/50	R143 092 790	2	49.7 (1.957)	6.3 (.248)	8.4 (.331)	

STRAIGHT PLUGS SOLDER TYPE FOR SEMI-RIGID CABLE





Cable group	Cable group dia.	Part number	Dimensions mm (inch)		
			A	B	C
RG402	.141"	R143 051 700	1 (.039)	3.65 (.144)	5 (.197)
RG401	.250"	R143 054 700	1.7 (.067)	6.45 (.254)	8 (.315)

STRAIGHT JACKS SOLDER TYPE FOR SEMI-RIGID CABLE




Cable group	Cable group dia.	Part number	Dimensions mm (inch)		
			A	B	C
RG402	.141"	R143 227 700	1 (.039)	3.65 (.143)	5 (.197)

STRAIGHT SQUARE FLANGE JACK CRIMP TYPE FOR FLEXIBLE CABLE




Cable group	Cable group dia.	Part number	Panel drilling
RG142/RG223/RG400	5/50/D	R143 292 700	P01

STRAIGHT SQUARE FLANGE JACKS SOLDER TYPE FOR SEMI-RIGID CABLE




Cable group	Cable group dia.	Part number	Dimensions mm (inch)			Panel drilling
			A	B	C	
RG405	.085"	R143 272 700	4 (.157)	0.6 (.024)	2.25 (.089)	P12
RG402	.141"	R143 273 700	5 (.197)	1 (.039)	3.65 (.144)	

STRAIGHT BULKHEAD JACK SOLDER TYPE FOR SEMI-RIGID CABLE



Cable group	Cable group dia.	Part number	Dimensions mm (inch)			Panel drilling
			A	B	C	
RG402	.141"	R143 321 700	1 (.039)	3.65 (.144)	5 (.197)	P09

SQUARE FLANGE STRAIGHT FEMALE RECEPTACLE (extended dielectric - stub contact)



Part number	Captive center contact	Panel drilling
R143 412 700	yes	P13

To download data sheets and assembly instructions, visit www.radiall.com & enter the part number in the Search box.
Bold part numbers represent products typically in stock & available for immediate shipment.
 See page 8 and 9 for packaging information.

ADAPTERS

IN SERIES ADAPTERS




Fig. 1




Fig. 2




Fig. 3




Fig. 4





Fig. 5


Part number	Fig	Captive center contact	Panel drilling	Note
R143 703 700	1	yes		Male - male
R143 704 700	2			Female - female
R143 705 700	3			Male - female
R143 710 700	4		P16	Square flange female - female
R143 730 700	5		P09	Bulkhead panel sealed female - female

STRAIGHT PLUGS CRIMP TYPE FOR FLEXIBLE CABLE




Cable group	Cable group dia.	Part number	Captive center contact	Note
RG59/RG62	6/75 + 93	R144 085 000	no	Full crimp
		R144 085 161	yes	Commercial version - full crimp

STRAIGHT PLUG CLAMP TYPE FOR FLEXIBLE CABLE



Cable group	Cable group dia.	Part number	Captive center contact	Packaging
RG6	8/75	R144 017 000	yes	Unit


STRAIGHT BULKHEAD JACKS CRIMP TYPE FOR FLEXIBLE CABLE



Cable group	Cable group dia.	Part number	Captive center contact	Panel drilling	Packaging	Note
RG59/RG62	6/75 + 93	R144 334 000	no	P09 or P11	Unit	Panel sealed
		R144 334 161	yes		100 pieces	Commercial version Panel sealed


PANEL DRILLING

P01




	MM		INCH	
	maxi	mini	maxi	mini
A	11.3	11.2	0.445	0.441
B	2.7	2.6	0.106	0.102
C	12.75	12.65	0.502	0.498

P02




	MM		INCH	
	maxi	mini	maxi	mini
A	11.3	11.2	0.445	0.441
B	3.7	3.6	0.146	0.142
C	12.75	12.65	0.502	0.498

P03



	MM		INCH	
	maxi	mini	maxi	mini
A	7.9	7.8	0.311	0.307
B	2.7	2.6	0.106	0.102
C	12.75	12.65	0.502	0.498

P04




	MM		INCH	
	maxi	mini	maxi	mini
A (F. Mount)	13	12.9	0.512	0.508
A (R. Mount)	11.3	11.2	0.445	0.441
B	2.7	2.6	0.106	0.102
C	12.75	12.65	0.502	0.498

P05




	MM		INCH	
	maxi	mini	maxi	mini
A F.mount	8	7.9	0.315	0.311
A R.mount	11.3	11.2	0.445	0.441
B	2.8	2.7	0.11	0.106
C	12.75	12.65	0.502	0.498

P06




	MM		INCH	
	maxi	mini	maxi	mini
A	8.3	8.2	0.327	0.323
B	2.7	2.6	0.106	0.102
C	12.75	12.65	0.502	0.498

P07




	MM		INCH	
	maxi	mini	maxi	mini
A (F. Mount)	8.3	8.2	0.327	0.323
A (R. Mount)	11.4	11.2	0.449	0.441
B	2.7	2.6	0.106	0.102
C	18.1	17.9	0.713	0.705

P08




	MM		INCH	
	maxi	mini	maxi	mini
A	9.8	9.7	0.386	0.382
B	8.93	8.81	0.352	0.347

P09




	MM		INCH	
	maxi	mini	maxi	mini
A	12.8	12.7	0.504	0.5
B	12.1	12	0.476	0.472

P10




	MM		INCH	
	maxi	mini	maxi	mini
A	9.75	9.65	0.384	0.38
B	8.65	8.55	0.341	0.337

P11



	MM		INCH	
	maxi	mini	maxi	mini
C	12.8	12.7	0.504	0.5
D	10.9	10.8	0.429	0.425

P12



	mm		inch	
	Maxi	mini	Maxi	mini
A F.mount	9.1	9	.358	.354
A R.mount	11.3	11.2	.445	.441
B	2.7	2.6	.106	.102
C	12.75	12.65	.502	.498

P13



	mm	
	Maxi	mini
A	13.4	13.3
B	2.7	2.6
C	12.75	12.65

P14



	mm		inch	
	Maxi	mini	Maxi	mini
A	5.5	5.4	.217	.213
B	3.3	3.2	.130	.126
C	13.55	13.45	.533	.530

P15



	mm		inch	
	Maxi	mini	Maxi	mini
A	7.1	7	.280	.276
B	3.3	3.1	.130	.122
C	12.75	12.65	.502	.498

P16



	MM		INCH	
	maxi	mini	maxi	mini
A	11.3	11.2	0.445	0.441
B	3.3	3.2	.130	.126
C	12.75	12.65	0.502	0.498



AEROSPACE



AUTOMOTIVE



DEFENSE



INDUSTRIAL



INSTRUMENTATION



MEDICAL



SPACE



TELECOM

EUROPE

France - RADIALL S.A.

101, Rue Ph. Hoffmann
93116 ROSNY sous BOIS (Paris)
Tel.: +33 1 49 35 35 35 - Fax: +33 1 48 54 63 63
E-Mail: info@radiall.com

Finland - RADIALL SF

P.O. Box 202 - 90101 OULU
Tel.: +358 407 522 412
E-Mail: infofi@radiall.com

Germany - RADIALL GmbH

Carl-Zeiss Str. 10 Postfach 200143
D63307 - RÖDERMARK (Frankfurt)
Tel.: +49 60 74 91 07 0 - Fax: +49 60 74 91 07 70
E-Mail: infode@radiall.com

Italy - RADIALL Elettronica S.R.L.

Via Concordia, 5 - 20090 ASSAGO MILANO
Tel.: +39 02 48 85 121 - Fax: +39 02 48 84 30 18
E-Mail: infoit@radiall.com
Regional office: Roma

Netherlands - RADIALL B.V.

Hogebrinkerweg 15b - 3871 KM HOEVELAKEN
Tel.: +31 33 253 40 09 - Fax: +31 33 253 45 12
E-Mail: infofl@radiall.com

Sweden - RADIALL A.B.

Sjöängsvägen 2 - SE-192 72 SOLLENTUNA (Stockholm)
Tel.: +46 844 434 10 - Fax: +46 875 449 16
E-Mail: infose@radiall.com

U.K. - RADIALL Ltd.

Ground Floor, 6 The Grand Union Office Park,
Packet Boat Lane
UXBRIDGE Middlesex UB8 2GH (London)
Tel.: +44 1895 425 000 - Fax: +44 1895 425 010
E-Mail: infouk@radiall.com

NORTH AMERICA

USA - RADIALL USA, Inc.

6825 West Galveston Street
CHANDLER, Arizona 85226
Tel.: +1 480 682 9400 - Fax: +1 480 682 9403
E-Mail: infousa@radiall.com

ALSO REPRESENTED IN

Australia	Hungary	Poland
Austria	Indonesia	Russia
Belgium	Israel	Singapore
Brazil	Korea	Spain
Czech Republic	Latvia	Switzerland
Denmark	Lithuania	Taiwan
Estonia	Malaysia	Thailand
Greece	Norway	Vietnam
	Philippines	South Africa

For the above countries, please contact the local agent or RADIALL at info@radiall.com

ASIA

China - SHANGHAI RADIALL Electronic Co., Ltd.

N° 390 Yong He Road 200072 - SHANGHAI
Tel.: +86 21 66 52 37 88 - Fax: +86 21 66 52 11 77
E-Mail: infozh@radiall.com

Japan - NIHON RADIALL

Shibuya-ku Ebisu 1-5-2, Kougetsu Bldg 405
TOKYO 150-0013
Tel.: +81 3 3440 6241 - Fax: +81 3 3440 6242
E-Mail: infojp@radiall.com

Hong Kong - RADIALL Electronics Ltd.

Flat D, 6/F, Ford Glory Plaza,
37-39 Wing Hong Street
Cheung Sha Wan
KOWLOON HONG KONG
Tel: +852-2959-3833 - Fax: +852-2959-2636
E-Mail: infohk@radiall.com

India - RADIALL India Pvt. Ltd.

25 D, II Phase, Peenya Industrial Area
BANGALORE 560058
Tel.: +91 80 83 95 271 - Fax: +91 80 83 97 228
E-Mail: infoin@radiall.com

