SIGN	DATE	DESCRIPTION	APPROVER
1	11/10'10	Current is changed from 75A to 65A	Aaron
2	11/10'10	Wire range is changed from 10-4 AWG to 10-6 AWG	Aaron
3	11/10'10	Add is cULus Mark	Aaron
4	12/12'12	Change the screw plating specification	Jacky
5	12/12'12	Change the dimensional tolerance	Jacky
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			



MATERIALS ELECTRICAL

RATED VOLTAGE & CURRENT:	600 V, 65A 1
WITHSTAND VOLTAGE:	AC 3000 V/Min
INSULATION RESISTANCE:	1000 MΩ OR MORE AT DC 500 V
OPERATING TEMPERATURE RANG:	-40 °C ~+115°C
SCREW TORQUE VALUE:	26 Lb-In.
WIRE RANGE:	10 - 6 AWG 2
1) BODY:	THERMOPLASTICS, UL94-V0 BLACK
2) TERMINAL:	BRASS, 1.6t, Tin PLATED
4 3) TERMINAL SCREWS WITH WASHER:	STEEL, M6.0
4) TERMINAL NUT:	STEEL Ni PLATED M6.0

APPROVAL: c UL us 3

Critical dimension: C

PART NO.:

YK 901 xx 0 x x 00G

NO. OF POLES
- 02: 2 POLES
- 03: 3 POLES
- 04: 4 POLES
- ⋮
- 10: 10 POLES

MARK
- 0: "@" MARK
- 1: "ANY" MARK

TERMINAL & SCREW PLATED
- 0: TERMINAL & SCREW: G/F
- 4 1: TERMINAL: G/F, SCREW: Zinc
- 2: TERMINAL: Sn, SCREW: G/F
- 4 3: TERMINAL: Sn, SCREW: Zinc

RoHS compliant (lead<4%) In copper Alloy



P.C.B LAYOUT(Top View)

N= Number of poles

Dim.B= (N-1)x16.0

Dim.L= (N-1)x16.0+20.0 5

POLE	2P~6P	7P~10P
Dim.B	±0.40	±0.50
Dim.L	±0.40	±0.50

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	YK901 W/o cover and W/o flange SERIES				
PART NO.	YK901xx0xx00G			DWG NO.	8YK0002-901
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Jacky 2012.12.12	Jacky 2012.12.12	UNIT: mm / SCALE: NONE / SHEET: 01/01	REV.: D

Tolerance	
X.	±0.50
X.X	±0.30
X.XX	±0.10
X°	±1°