







PCB LAYOUT
Top view



△ N=Number of Poles
Dim.P=(N-1)×10.16
Dim.L=(N-1)×10.16+6.08

Poles Dim.	2P-6P	7P-12P
Dim.L	±0.25	±0.40
Dim.P	±0.25	±0.35

SIGN	DATE	DESCRIPTION	APPROVER
△	10/30'09	The dimension changed from 19.1 to 19.1±0.50	Kind
△	10/30'09	Add tolerance table for Dim.L and Dim.P	Kind
△	10/30'09	Terminal lever material changed to thermoplastic (UL94-HB)	Kind
△	04/23'13	Update the drawing	Da cheng

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Material**
- Item 1 Solder pin : Brass , Tin plated
 - Item 2 Spring clamp : Stainless steel
 - Item 3 Terminal housing: Thermoplastic (UL94V-0)
 - Item 4 Terminal cover: Thermoplastic (UL94V-0)
 - △ ● Item 5 Terminal lever: Thermoplastic (UL94V-HB)
 - Item 6 Terminal pad: Thermoplastic (UL94V-0)

- Electrical** cULus
- Voltage rating: 300V
 - Current rating: 15A
 - Wire range:
 - Solid wire(AWG): 12-28
 - Stranded wire(AWG): 12-28
 - Wire strip length: 6-7mm
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -40°C to +115°C
 - △ ● Soldering temperature: 260°C±5°C/5 Sec
 - Safety Approval: cULus
 - △ ● Critical dimension: ▽

HT xx 40 x 0 xxxx G

- △ G: RoHs compliant (lead<4%) In copper Alloy
- △ Color
 - 0 Black (RAL9005)
 - 2 Red (RAL3001/D)
 - 3 Orange(RAL2011/P)
 - 4 Yellow(RAL1018/A)
 - 5 Green(RAL6018/T)
 - 6 Blue (RAL5015/A)
 - 8 Grey(RAL7004/P)
 - 9 White(RAL1102)
 - C Multiple colors
- 000 0 Standard @ Logo
- 000 A Standard ANY Logo
- 009 1 Standard ANY Logo
- Any special item by customer request, please contact sales department.

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		HT-10.16 Series					
PART NO.		HTxx40x0xxxxG			DWG NO.		8HT0501
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		
			Da cheng 2013.04.23	Da cheng 2013.04.23			
				SHEET: 01/01		Tolerance	
				UNIT: mm		X. ±0.50	
				SCALE: NONE		X.X ±0.30	
				REV.: D		X.XX ±0.10	
						X° ±1°	