



注 記


1. 嵌合相手品番: 7114-4221-08, 7114-4221-02
 △ 2. 適用ゴム栓品番: 7158-3070-80
 △ 3. () 内品番は、エアバック (A/B) 回路及び特別管理回路に使用する時に適用すること。

NOTES


1. MATING PART NO. : 7114-4221-08, 7114-4221-02
 △ 2. APPLICABLE RUBBER STOPPER NO. : 7158-3070-80
 △ 3. PART NUMBERS IN PARENTHESIS SHALL BE USED FOR
 AIR BAG (A/B) CIRCUITS AND OTHER CIRCUITS
 DESIGNATED FOR SPECIAL MONITORING.



PART NO. AND CH. CODE	TREATMENT	WIRE SIZE
7116-4221-08 △(7B16-4221-08)	△ GOLD PLATING TIN PLATING	CAVS0.3~CAVS0.5
7116-4221-02	TIN PLATING	



SEC. A-A



SEC. B-B

ISSUE MARK

△	02.02.10	ADDED PART NO., NOTE	C02-X189	Y. S	CUSTOMER					MATL. COPPER ALLOY				TREAT. & FIN.		
△	98.08.04	CHANGED FORM, NOTE & DIMENSION	C97-N443	H. K	CUSTOMER PART NO.			CUSTOMER DWG NO.			SPEC. (t=0.25)					
	97.03.10	NEW	C97-L453	H. K	OFFICE			TRIAL PART NO.			NAME 1.0Ⅲ (040Ⅲ) SEALED TERMINAL					
LET	DATE	REVISION RECORD	NO.	CHKD	VENDOR						FEMALE					
GENERAL TOLERANCE					VENDOR NO.											
	10MAX	50MAX	100MAX	250MAX	2500VR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE	PART NO. △ 7116-4221-08 ETC. (7B16-4221-08)		
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1	R	NEW	97.03.10	mm	5/1	3	CH. CODE △ 7116-4221-08 ETC. (7B16-4221-08)		
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN	DWG NO. 7116-4221-08:R			SET DWG NO.
③	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15	山梨		福		ISHIJIMA				
SPECIFIED					MASS		g		02.02.15		02.02.13		02.02.10		96.04.02 02.02.10	
														YAZAKI CORPORATION		