

	REV	E.C.N NO.	CONTENT	CHK	DATE
NOTES1:					
UL Standard					
1.					
	Use group	B	C	D	
	Rated Current	15A	/	10A	
	Rated Voltage	300V	/	300V	
3.Torque value: M2.5, 3.54Lb.in					
4.Wire range: 28~12AWG					
IEC Standard					
1.	Pollution Degree	3	2	2	
	Overtoltage Category	III	II	I	
	Rate Impulse Voltage(KV)	/	4.0KV	/	
	Rate Voltage(V)	/	320V	/	
	Rate Current(A)	/	15A	/	
2. Torque value: M2.5, 0.4Nm					
3.wire range: 0.2~2.5mm ²					
NOTES2:					
1.Housing: PA66 (UL94V-0)					
2.Cover: PA66 (UL94V-0)					
3.Cage: Brass (Ni Plated)					
4.Conductor: Copper alloy (Sn Plated)					
5.Screw: Steel (M2.5,Zn Plated)					
NOTES3:					
1.Pitch: 5.08mm Poles: 02-24P					
2.Stripping length: 7-8mm					
3.Operating temperature: -40℃~+105℃					
4.RoHS Compliance					
How to order					
MX2EDGRKF - 5.08 - XXP - XXXX - XX - X - X					
产品型号 间距 极数 颜色: 灰色:GY 橙色:OE 02-99: 蓝色:BU 红色:RD 定制颜色 黑色:BK 透明色:TT 绿色:GN 黄色:YW 白色:WE					
Cu:铜方块 A-Z其他定制 Fe:铁方块 0:Y一字螺丝 1:S十字螺丝 2:PS平头十字螺丝					

Pitch Range In mm			Nominal Dimension Range In mm					-	∩	◇
To	Over 6 To 10	Over 10 To 24	To 30	Over 30 To 60	Over 60 To 100	Over 100 To 150	Over 150	0.1/10		
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°	<	

ITEM	NAME OF PART	N.O. OF PART	Q'TY	MATERIAL	NOTE
DWG.	CKK	DATE 23.11.09	UNITS	MM	SHEET/OFF 1/1
CHK.		DATE	SCALE	1 : 1	A4
APP.		DATE			
CIXI MAIXU ELECTRONICS CO., LTD. 慈溪市迈旭电子有限公司			NAME	MX2EDGRKF-5.08-XXP	
			DWNGO.		

[illegible]

	REV	E.C.N NO.	CONTENT	CHK	DATE
NOTES1:					
UL Standard					
1.					
Use group	B	C	D		
Rated Current	15A	/	10A		
Rated Voltage	300V	/	300V		
3.Torque value:	M2.5,	3.54Lb.in			
4.Wire range:	28~	12AWG			
IEC Standard					
1.	Pollution Degree	3	2	2	
Overvoltage Category	III	III	II		
Rate Impulse Voltage(KV)	/	4.0KV	/		
Rate Voltage(V)	/	320V	/		
Rate Current(A)	/	15A	/		
2. Torque value:	M2.5,	0.4Nm			
3.wire range:	0.2~	2.5mm ²			
NOTES2:					
1.Housing:	PA66 (UL94V-0)				
2.Cover:	PA66 (UL94V-0)				
3.Cage:	Brass (Ni Plated)				
4.Conductor:	Copper alloy (Sn Plated)				
5.Screw:	Steel (M2.5,Zn Plated)				
NOTES3:					
1.Pitch:	5.08mm Poles: 02-24P				
2.Stripping length:	7-8mm				
3.Operating temperature:	-40℃~+105℃				
4.RoHS Compliance					
How to order					
MX2EDGRKF - 5.08 - XXP - XXXX - XX - X - X					
产品型号	间距	极数	颜色:	01:常规颜色	A-Z其他定制
			灰色:GY	橙色:OE	02-99:
			蓝色:BU	红色:RD	定制颜色
			黑色:BK	透明色:TT	
			绿色:GN	黄色:YW	
			白色:WE		
				Cu:铜方块	0:Y一字螺丝
				Fe:铁方块	1:S十字螺丝
					2:PS平头十字螺丝
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	CKK	DATE	23.11.09	UNITS	MM
CHK.		DATE		SCALE	1:1
APP.		DATE		NAME	MX2EDGRKF-5.08-XXP
				DWNGO.	

[illegible][illegible][illegible]

	6	5	4	3	2	1																																				
注:	未经允许禁止传播、复制、编辑该文档，以及利用其内容进行交流																																									
						REV																																				
						E.C.N NO.																																				
						CONTENT																																				
						CHK																																				
						DATE																																				
	NOTES1:																																									
	UL Standard																																									
	1.																																									
	<table border="1"><thead><tr><th>Use group</th><th>B</th><th>C</th><th>D</th></tr></thead><tbody><tr><td>Rated Current</td><td>15A</td><td>/</td><td>10A</td></tr><tr><td>Rated Voltage</td><td>300V</td><td>/</td><td>300V</td></tr></tbody></table>						Use group	B	C	D	Rated Current	15A	/	10A	Rated Voltage	300V	/	300V																								
Use group	B	C	D																																							
Rated Current	15A	/	10A																																							
Rated Voltage	300V	/	300V																																							
	3.Torque value: M2.5, 3.54Lb.in																																									
	4.Wire range: 28~12AWG																																									
	IEC Standard																																									
	1.																																									
	<table border="1"><thead><tr><th>Pollution Degree</th><th>3</th><th>2</th><th>2</th></tr></thead><tbody><tr><td>Overvoltage Category</td><td>III</td><td>III</td><td>II</td></tr><tr><td>Rate Impulse Voltage(KV)</td><td>/</td><td>4.0KV</td><td>/</td></tr><tr><td>Rate Voltage(V)</td><td>/</td><td>320V</td><td>/</td></tr><tr><td>Rate Current(A)</td><td>/</td><td>15A</td><td>/</td></tr></tbody></table>						Pollution Degree	3	2	2	Overvoltage Category	III	III	II	Rate Impulse Voltage(KV)	/	4.0KV	/	Rate Voltage(V)	/	320V	/	Rate Current(A)	/	15A	/																
Pollution Degree	3	2	2																																							
Overvoltage Category	III	III	II																																							
Rate Impulse Voltage(KV)	/	4.0KV	/																																							
Rate Voltage(V)	/	320V	/																																							
Rate Current(A)	/	15A	/																																							
	2. Torque value: M2.5, 0.4Nm																																									
	3.wire range: 0.2~2.5mm ²																																									
	NOTES2:																																									
	1.Housing: PA66 (UL94V-0)																																									
	2.Cover: PA66 (UL94V-0)																																									
	3.Cage: Brass (Ni Plated)																																									
	4.Conductor: Copper alloy (Sn Plated)																																									
	5.Screw: Steel (M2.5,Zn Plated)																																									
	NOTES3:																																									
	1.Pitch: 5.08mm Poles: 02-24P																																									
	2.Stripping length: 7-8mm																																									
	3.Operating temperature: -40℃~+105℃																																									
	4.RoHS Compliance																																									
	How to order																																									
	MX2EDGRKF - 5.08 - XXP - XXXX - XX - X - X																																									
	<table border="1"><thead><tr><th>产品型号</th><th>间距</th><th>极数</th><th>颜色</th><th>01:常规颜色</th><th>A-Z其他定制</th></tr></thead><tbody><tr><td></td><td></td><td></td><td>灰色:GY</td><td>橙色:OE</td><td>02-99:</td></tr><tr><td></td><td></td><td></td><td>蓝色:BU</td><td>红色:RD</td><td>定制颜色</td></tr><tr><td></td><td></td><td></td><td>黑色:BK</td><td>透明色:TT</td><td></td></tr><tr><td></td><td></td><td></td><td>绿色:GN</td><td>黄色:YW</td><td></td></tr><tr><td></td><td></td><td></td><td>白色:WE</td><td></td><td></td></tr></tbody></table>						产品型号	间距	极数	颜色	01:常规颜色	A-Z其他定制				灰色:GY	橙色:OE	02-99:				蓝色:BU	红色:RD	定制颜色				黑色:BK	透明色:TT					绿色:GN	黄色:YW					白色:WE		
产品型号	间距	极数	颜色	01:常规颜色	A-Z其他定制																																					
			灰色:GY	橙色:OE	02-99:																																					
			蓝色:BU	红色:RD	定制颜色																																					
			黑色:BK	透明色:TT																																						
			绿色:GN	黄色:YW																																						
			白色:WE																																							
	<table border="1"><thead><tr><th>ITEM</th><th>NAME OF PART</th><th>NO. OF PART</th><th>Q'TY</th><th>MATERIAL</th><th>NOTE</th></tr></thead><tbody><tr><td>DWG.</td><td>CKK</td><td>DATE</td><td>23.11.09</td><td>UNITS</td><td>MM</td></tr><tr><td>CHK.</td><td></td><td>DATE</td><td></td><td>SCALE</td><td>1:1</td></tr><tr><td>APP.</td><td></td><td>DATE</td><td></td><td>NAME</td><td>MX2EDGRKF-5.08-XXP</td></tr><tr><td colspan="4"></td><td>DWNGO.</td><td></td></tr></tbody></table>						ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE	DWG.	CKK	DATE	23.11.09	UNITS	MM	CHK.		DATE		SCALE	1:1	APP.		DATE		NAME	MX2EDGRKF-5.08-XXP					DWNGO.							
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE																																					
DWG.	CKK	DATE	23.11.09	UNITS	MM																																					
CHK.		DATE		SCALE	1:1																																					
APP.		DATE		NAME	MX2EDGRKF-5.08-XXP																																					
				DWNGO.																																						

The technical drawing illustrates the MX2EDGRKF terminal block from three perspectives: top, side, and front views. The top view shows a rectangular component with six circular terminals arranged in two rows of three. Key dimensions include a width of 15.10 mm, a pitch of 5.08 mm between terminals, and overall lengths defined by formulas like 5.08XP+1.50 and 5.08X(P-1)+19.28. The side view highlights the height profile, with a total height of 19.20 mm and a mounting flange height of 9.40 mm. The front view details the terminal arrangement, showing a central pitch of 5.08 mm and terminal diameters of 4.00 mm. A small inset shows the product logo and model number MX2EDGRKF-5.08.

Pitch Range In mm	Nominal Dimension Range In mm	-	∩	◇				
TO 6	Over 6 TO 10	TO 10	TO 24		0.1/10			
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°

[illegible]

	REV	E.C.N NO.	CONTENT	CHK	DATE
NOTES1:					
UL Standard					
1.					
	Use group	B	C	D	
	Rated Current	15A	/	10A	
	Rated Voltage	300V	/	300V	
3.Torque value:	M2.5,	3.54Lb.in			
4.Wire range:	28~	12AWG			
IEC Standard					
1.	Pollution Degree	3	2	2	
	Overtoltage Category	III	II	I	
	Rate Impulse Voltage(KV)	/	4.0KV	/	
	Rate Voltage(V)	/	320V	/	
	Rate Current(A)	/	15A	/	
2. Torque value:	M2.5,	0.4Nm			
3.wire range:	0.2~	2.5mm ²			
NOTES2:					
1.Housing:	PA66	(UL94V-0)			
2.Cover:	PA66	(UL94V-0)			
3.Cage:	Brass	(Ni Plated)			
4.Conductor:	Copper alloy	(Sn Plated)			
5.Screw:	Steel	(M2.5,Zn Plated)			
NOTES3:					
1.Pitch:	5.08mm	Poles: 02-24P			
2.Stripping length:	7-8mm				
3.Operating temperature:	-40℃~+105℃				
4.RoHS Compliance					
How to order					
MX2EDGRKF - 5.08 - XXP - XXXX - XX - X - X					
产品型号	间距	极数 颜色:	01:常规颜色 灰色:GY 橙色:OE 02-99: 蓝色:BU 红色:RD 定制颜色 黑色:BK 透明色:TT 绿色:GN 黄色:YW 白色:WE	A-Z其他定制 0:Y一字螺丝 1:S十字螺丝 Cu铜方块 Fe铁方块	
ITEM	NAME OF PART	N.O. OF PART	Q'TY	MATERIAL	NOTE
DWG.	CKK	DATE 23.11.09	UNITS	MM	SHEET/OF 1/1
CHK.		DATE	SCALE	1 : 1	A4
APP.		DATE			
			NAME	MX2EDGRKF-5.08-XXP	
			DWNGO.		

[illegible][illegible][illegible][illegible][illegible][illegible]

	6	5	4	3	2	1																																	
注:	未经允许禁止传播、复制、编辑该文档，以及利用其内容进行交流																																						
					REV E.C.N NO.	CONTENT																																	
					CHK	DATE																																	
	NOTES1: UL Standard <table border="1"><tr><td>Use group</td><td>B</td><td>C</td><td>D</td></tr><tr><td>Rated Current</td><td>15A</td><td>/</td><td>10A</td></tr><tr><td>Rated Voltage</td><td>300V</td><td>/</td><td>300V</td></tr></table> 3.Torque value: M2.5, 3.54Lb.in 4.Wire range: 28~12AWG IEC Standard <table border="1"><tr><td>Pollution Degree</td><td>3</td><td>2</td><td>2</td></tr><tr><td>Overvoltage Category</td><td>III</td><td>III</td><td>II</td></tr><tr><td>Rate Impulse Voltage(KV)</td><td>/</td><td>4.0KV</td><td>/</td></tr><tr><td>Rate Voltage(V)</td><td>/</td><td>320V</td><td>/</td></tr><tr><td>Rate Current(A)</td><td>/</td><td>15A</td><td>/</td></tr></table> 2. Torque value: M2.5, 0.4Nm 3.wire range: 0.2~2.5mm ²						Use group	B	C	D	Rated Current	15A	/	10A	Rated Voltage	300V	/	300V	Pollution Degree	3	2	2	Overvoltage Category	III	III	II	Rate Impulse Voltage(KV)	/	4.0KV	/	Rate Voltage(V)	/	320V	/	Rate Current(A)	/	15A	/	
Use group	B	C	D																																				
Rated Current	15A	/	10A																																				
Rated Voltage	300V	/	300V																																				
Pollution Degree	3	2	2																																				
Overvoltage Category	III	III	II																																				
Rate Impulse Voltage(KV)	/	4.0KV	/																																				
Rate Voltage(V)	/	320V	/																																				
Rate Current(A)	/	15A	/																																				
	NOTES2: 1.Housing: PA66 (UL94V-0) 2.Cover: PA66 (UL94V-0) 3.Cage: Brass (Ni Plated) 4.Conductor: Copper alloy (Sn Plated) 5.Screw: Steel (M2.5,Zn Plated)																																						
	NOTES3: 1.Pitch: 5.08mm Poles: 02-24P 2.Stripping length: 7-8mm 3.Operating temperature: -40℃~+105℃ 4.RoHS Compliance																																						
	How to order MX2EDGRKF - 5.08 - XXP - XXXX - XX - X - X 产品型号 间距 极数 颜色 01:常规颜色 A-Z其他定制 灰色:GY 橙色:OE 02-99: 蓝色:BU 红色:RD 定制颜色 黑色:BK 透明色:TT Cu:铜方块 0:Y一字螺丝 绿色:GN 黄色:YW Fe:铁方块 1:S十字螺丝 白色:WE 2:PS平头十字螺丝																																						
	<table border="1"><thead><tr><th colspan="2">Pitch Range In mm</th><th colspan="6">Nominal Dimension Range In mm</th><th>-</th><th>∩</th><th>◇</th></tr></thead><tbody><tr><td></td><td>Over 6 TO 10</td><td>Over 10 TO 24</td><td>Over 30 TO 60</td><td>Over 60 TO 100</td><td>Over 100 TO 150</td><td>Over 150</td><td></td><td>0.1/10</td><td></td><td></td></tr><tr><td>TO 6</td><td>±0.15</td><td>±0.20</td><td>±0.30</td><td>±0.30</td><td>±0.50</td><td>±0.70</td><td>±1.00</td><td>±1.30</td><td>±2°</td><td></td></tr></tbody></table>						Pitch Range In mm		Nominal Dimension Range In mm						-	∩	◇		Over 6 TO 10	Over 10 TO 24	Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	Over 150		0.1/10			TO 6	±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°	
Pitch Range In mm		Nominal Dimension Range In mm						-	∩	◇																													
	Over 6 TO 10	Over 10 TO 24	Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	Over 150		0.1/10																															
TO 6	±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°																														
							ITEM NAME OF PART NO. OF PART Q'TY MATERIAL NOTE DWG. CKK DATE 23.11.09 UNITS MM SHEET/OF 1/1 CHK. DATE SCALE 1: 1 A4 APP. DATE NAME MX2EDGRKF-5.08-XXP CIXI MAIXU ELECTRONICS CO.,LTD. 慈溪市迈旭电子有限公司 DWGNO.																																

The technical drawing illustrates a terminal block from three perspectives: top, side, and front views. The top view shows a rectangular component with six circular terminals arranged in two rows of three. Dimensions include a total width of 15.10mm, a pitch of 5.08mm between terminals, and overall lengths defined by formulas like 5.08XP+1.50 and 5.08X(P-1)+19.28. The side view shows a height of 9.40mm and a depth of 19.20mm. The front view details the terminal profile with diameters of 4.00mm and 3.29mm, and a mounting hole diameter of 6.50mm. A small inset shows the product logo and model number MX2EDGRKF-5.08.

[illegible][illegible][illegible][illegible][illegible]

REV E.C.N NO.

CONTENT

CHK DATE

NOTES1:

UL Standard						
-------------	--	--	--	--	--	--

1.

Use group	B	C	D
Rated Current	15A	/	10A
Rated Voltage	300V	/	300V

3.Torque value: M2.5, 3.54Lb.in
4.Wire range: 28~12AWG

IEC Standard						
--------------	--	--	--	--	--	--

1.

Pollution Degree	3	2	2
Overtoltage Category	III	II	I
Rate Impulse Voltage(KV)	/	4.0KV	/
Rate Voltage(V)	/	320V	/
Rate Current(A)	/	15A	/

2. Torque value: M2.5, 0.4Nm
3.wire range: 0.2~2.5mm²

NOTES2:						
---------	--	--	--	--	--	--

1.Housing: PA66 (UL94V-0)
2.Cover: PA66 (UL94V-0)
3.Cage: Brass (Ni Plated)
4.Conductor: Copper alloy (Sn Plated)
5.Screw: Steel (M2.5,Zn Plated)

NOTES3:						
---------	--	--	--	--	--	--

1.Pitch: 5.08mm Poles: 02-24P
2.Stripping length: 7-8mm
3.Operating temperature: -40℃~+105℃
4.RoHS Compliance

How to order						
--------------	--	--	--	--	--	--

MX2EDGRKF - 5.08 - XXP - XXXX - XX - X - X

产品型号 间距 极数 颜色: 01:常规颜色 A-Z其他定制

灰色:GY 橙色:OE 02-99:
蓝色:BU 红色:RD 定制颜色
黑色:BK 透明色:TT
绿色:GN 黄色:YW
白色:WE

Cu:铜方块 0:Y—字螺丝
Fe:铁方块 1:S十字螺丝
 2:PS平头十字螺丝

ITEM	NAME OF PART	N.O. OF PART	Q'TY	MATERIAL	NOTE
------	--------------	--------------	------	----------	------

DWG. CKK DATE 23.11.09 UNITS MM SHEET/OF 1/1

CHK. DATE SCALE 1 : 1 A4

APP.	DATE	NAME	MX2EDGRKF-5.08-XXP
		DWNGO.	

CIXI MAIXU ELECTRONICS CO.,LTD.
 慈溪市迈旭电子有限公司

ITEM	NAME OF PART	N.O. OF PART	Q'TY	MATERIAL	NOTE
------	--------------	--------------	------	----------	------

DWG. CKK DATE 23.11.09 UNITS MM SHEET/OF 1/1

CHK. DATE SCALE 1 : 1 A4

APP.	DATE	NAME	MX2EDGRKF-5.08-XXP
		DWNGO.	

CIXI MAIXU ELECTRONICS CO.,LTD.
 慈溪市迈旭电子有限公司

ITEM	NAME OF PART	N.O. OF PART	Q'TY	MATERIAL	NOTE
------	--------------	--------------	------	----------	------

DWG. CKK DATE 23.11.09 UNITS MM SHEET/OF 1/1

CHK. DATE SCALE 1 : 1 A4

APP.	DATE	NAME	MX2EDGRKF-5.08-XXP
		DWNGO.	

CIXI MAIXU ELECTRONICS CO.,LTD.
 慈溪市迈旭电子有限公司

ITEM	NAME OF PART	N.O. OF PART	Q'TY	MATERIAL	NOTE
------	--------------	--------------	------	----------	------

DWG. CKK DATE 23.11.09 UNITS MM SHEET/OF 1/1

CHK. DATE SCALE 1 : 1 A4

APP.	DATE	NAME	MX2EDGRKF-5.08-XXP
		DWNGO.	

CIXI MAIXU ELECTRONICS CO.,LTD.
 慈溪市迈旭电子有限公司

ITEM	NAME OF PART	N.O. OF PART	Q'TY	MATERIAL	NOTE
------	--------------	--------------	------	----------	------

DWG. CKK DATE 23.11.09 UNITS MM SHEET/OF 1/1

CHK. DATE SCALE 1 : 1 A4

APP.	DATE	NAME	MX2EDGRKF-5.08-XXP
		DWNGO.	

CIXI MAIXU ELECTRONICS CO.,LTD.
 慈溪市迈旭电子有限公司

ITEM	NAME OF PART	N.O. OF PART	Q'TY	MATERIAL	NOTE
------	--------------	--------------	------	----------	------

DWG. CKK DATE 23.11.09 UNITS MM SHEET/OF 1/1

CHK. DATE SCALE 1 : 1 A4

APP.	DATE	NAME	MX2EDGRKF-5.08-XXP
		DWNGO.	

CIXI MAIXU ELECTRONICS CO.,LTD.
 慈溪市迈旭电子有限公司

ITEM	NAME OF PART	N.O. OF PART	Q'TY	MATERIAL	NOTE
------	--------------	--------------	------	----------	------

[illegible]

	6	5	4	3	2	1																																																																																																																																							
注:	未经允许禁止传播、复制、编辑该文档，以及利用其内容进行交流。					REV	E.C.N NO.	CONTENT	CHK	DATE																																																																																																																																			
D	<div><p>NOTES1: UL Standard <table border="1"><tr><td>Use group</td><td>B</td><td>C</td><td>D</td></tr><tr><td>Rated Current</td><td>15A</td><td>/</td><td>10A</td></tr><tr><td>Rated Voltage</td><td>300V</td><td>/</td><td>300V</td></tr></table> 3.Torque value: M2.5, 3.54Lb.in 4.Wire range: 28~12AWG</p><p>IEC Standard <table border="1"><tr><td>Pollution Degree</td><td>3</td><td>2</td><td>2</td></tr><tr><td>Overtoltage Category</td><td>III</td><td>III</td><td>II</td></tr><tr><td>Rate Impulse Voltage(KV)</td><td>/</td><td>4.0KV</td><td>/</td></tr><tr><td>Rate Voltage(V)</td><td>/</td><td>320V</td><td>/</td></tr><tr><td>Rate Current(A)</td><td>/</td><td>15A</td><td>/</td></tr></table> 2. Torque value: M2.5, 0.4Nm 3.wire range: 0.2~2.5mm²</p><p>NOTES2: 1.Housing: PA66 (UL94V-0) 2.Cover: PA66 (UL94V-0) 3.Cage: Brass (Ni Plated) 4.Conductor: Copper alloy (Sn Plated) 5.Screw: Steel (M2.5,Zn Plated)</p><p>NOTES3: 1.Pitch: 5.08mm Poles: 02-24P 2.Stripping length: 7-8mm 3.Operating temperature: -40℃~+105℃ 4.RoHS Compliance</p><p>How to order MX2EDGRKF - 5.08 - XXP - XXXX - XX - X - X 产品型号 间距 极数 颜色: 01:常规颜色 A-Z其他定制 灰色:GY 橙色:OE 02-99: 蓝色:BU 红色:RD 定制颜色 黑色:BK 透明色:TT 绿色:GN 黄色:YW 白色:WE</p><table border="1"><tr><td>ITEM</td><td colspan="2">NAME OF PART</td><td>N.O. OF PART</td><td>Q'TY</td><td>MATERIAL</td><td colspan="2">NOTE</td></tr><tr><td>DWG.</td><td>CKK</td><td>DATE</td><td>23.11.09</td><td>UNITS</td><td>MM</td><td>SHEET/OF</td><td>1 / 1</td></tr><tr><td>CHK.</td><td></td><td>DATE</td><td></td><td>SCALE</td><td>1 : 1</td><td>A4</td><td></td></tr><tr><td>APP.</td><td></td><td>DATE</td><td></td><td rowspan="5">NAME</td><td colspan="3">MX2EDGRKF-5.08-XXP</td></tr><tr><td colspan="7"> CIXI MAIXU ELECTRONICS CO.,LTD. 慈溪市迈旭电子有限公司</td><td>DWNGO.</td></tr></table></div> <div data-kind="ghost"></div> <tr><td>C</td><td colspan="8"><div><p>Dimensions diagram showing top view, side view, and front view of the terminal block with various measurements like pitch (5.08), width (15.10), height (19.20), etc.</p></div></td></tr> <tr><td>B</td><td colspan="8"><div><table border="1"><tr><td colspan="2">Pitch Range In mm</td><td colspan="6">Nominal Dimension Range In mm</td><td>-</td><td>∩</td><td>▱</td></tr><tr><td>To 6</td><td>Over 6 To 10</td><td>Over 10 To 24</td><td>To 30</td><td>Over 30 To 60</td><td>Over 60 To 100</td><td>Over 100 To 150</td><td>Over 150</td><td>0.1/10</td><td><</td><td>±2°</td></tr><tr><td>±0.15</td><td>±0.20</td><td>±0.30</td><td>±0.30</td><td>±0.50</td><td>±0.70</td><td>±1.00</td><td>±1.30</td><td></td><td></td><td></td></tr></table></div></td></tr> <tr><td>A</td><td colspan="8"><div></div></td></tr> <tr><td></td><td>3</td><td>2</td><td>1</td><td colspan="4"></td></tr>	Use group	B	C	D	Rated Current	15A	/	10A	Rated Voltage	300V	/	300V	Pollution Degree	3	2	2	Overtoltage Category	III	III	II	Rate Impulse Voltage(KV)	/	4.0KV	/	Rate Voltage(V)	/	320V	/	Rate Current(A)	/	15A	/	ITEM	NAME OF PART		N.O. OF PART	Q'TY	MATERIAL	NOTE		DWG.	CKK	DATE	23.11.09	UNITS	MM	SHEET/OF	1 / 1	CHK.		DATE		SCALE	1 : 1	A4		APP.		DATE		NAME	MX2EDGRKF-5.08-XXP			CIXI MAIXU ELECTRONICS CO.,LTD. 慈溪市迈旭电子有限公司							DWNGO.	C	Dimensions diagram showing top view, side view, and front view of the terminal block with various measurements like pitch (5.08), width (15.10), height (19.20), etc.								B	<table border="1"><tr><td colspan="2">Pitch Range In mm</td><td colspan="6">Nominal Dimension Range In mm</td><td>-</td><td>∩</td><td>▱</td></tr><tr><td>To 6</td><td>Over 6 To 10</td><td>Over 10 To 24</td><td>To 30</td><td>Over 30 To 60</td><td>Over 60 To 100</td><td>Over 100 To 150</td><td>Over 150</td><td>0.1/10</td><td><</td><td>±2°</td></tr><tr><td>±0.15</td><td>±0.20</td><td>±0.30</td><td>±0.30</td><td>±0.50</td><td>±0.70</td><td>±1.00</td><td>±1.30</td><td></td><td></td><td></td></tr></table>								Pitch Range In mm		Nominal Dimension Range In mm						-	∩	▱	To 6	Over 6 To 10	Over 10 To 24	To 30	Over 30 To 60	Over 60 To 100	Over 100 To 150	Over 150	0.1/10	<	±2°	±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30				A										3	2	1				
Use group	B	C	D																																																																																																																																										
Rated Current	15A	/	10A																																																																																																																																										
Rated Voltage	300V	/	300V																																																																																																																																										
Pollution Degree	3	2	2																																																																																																																																										
Overtoltage Category	III	III	II																																																																																																																																										
Rate Impulse Voltage(KV)	/	4.0KV	/																																																																																																																																										
Rate Voltage(V)	/	320V	/																																																																																																																																										
Rate Current(A)	/	15A	/																																																																																																																																										
ITEM	NAME OF PART		N.O. OF PART	Q'TY	MATERIAL	NOTE																																																																																																																																							
DWG.	CKK	DATE	23.11.09	UNITS	MM	SHEET/OF	1 / 1																																																																																																																																						
CHK.		DATE		SCALE	1 : 1	A4																																																																																																																																							
APP.		DATE		NAME	MX2EDGRKF-5.08-XXP																																																																																																																																								
CIXI MAIXU ELECTRONICS CO.,LTD. 慈溪市迈旭电子有限公司							DWNGO.																																																																																																																																						
C	Dimensions diagram showing top view, side view, and front view of the terminal block with various measurements like pitch (5.08), width (15.10), height (19.20), etc.																																																																																																																																												
B	<table border="1"><tr><td colspan="2">Pitch Range In mm</td><td colspan="6">Nominal Dimension Range In mm</td><td>-</td><td>∩</td><td>▱</td></tr><tr><td>To 6</td><td>Over 6 To 10</td><td>Over 10 To 24</td><td>To 30</td><td>Over 30 To 60</td><td>Over 60 To 100</td><td>Over 100 To 150</td><td>Over 150</td><td>0.1/10</td><td><</td><td>±2°</td></tr><tr><td>±0.15</td><td>±0.20</td><td>±0.30</td><td>±0.30</td><td>±0.50</td><td>±0.70</td><td>±1.00</td><td>±1.30</td><td></td><td></td><td></td></tr></table>								Pitch Range In mm		Nominal Dimension Range In mm						-	∩	▱	To 6	Over 6 To 10	Over 10 To 24	To 30	Over 30 To 60	Over 60 To 100	Over 100 To 150	Over 150	0.1/10	<	±2°	±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30																																																																																																							
Pitch Range In mm		Nominal Dimension Range In mm						-	∩	▱																																																																																																																																			
To 6	Over 6 To 10	Over 10 To 24	To 30	Over 30 To 60	Over 60 To 100	Over 100 To 150	Over 150	0.1/10	<	±2°																																																																																																																																			
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30																																																																																																																																						
A																																																																																																																																													
	3	2	1																																																																																																																																										

[illegible][illegible]