

Harvatek 3.0mm Round LED LAMP with Holder

HV-341644/260/SYGTUYSUBCSYGT-C0028

Official Product	HV-341644/260/SYGTUYSUBCSYGT-C0028	Customer Part No.		Data Sheet No.
	*****	*****		HV-341644/260/SYGTUYSUBCSYGT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		Jun.19 2024	Version of 1.1	Page 1/16

DISCLAIMER

HARVATEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. HARVATEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

LIFE SUPPORT POLICY

HARVATEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of HARVATEK or HARVATEK INTERNATIONAL. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Official Product	HV-341644/260/SYGTUYSUBCSYGT -C0028	Customer Part No.		Data Sheet No.
	*****	*****		HV-341644/260/SYGTUYSUBCSY GT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		Jun.19 2024	Version of 1.1	Page 2/16

Compliance and Certification

ISO9002, QS9000 and ISO14001 Certified

RoHS Compliant



Orderable Information

H V - 341644 / 260 / SYGTUYSUBCSYGT - C0028

Series Name	Color Code	Remark
HV : HARVATEK	341644: Array 4 Lamp 260: 3.0mm Round LED LAMP. SYGUYSUB: AlGaInP 570nm Green Chip. AlGaInP 590nm Yellow Chip. InGaN 470nm Blue Chip. T: Green Transparent. C: Water Clear.	C0028: Customer Product Code

Features:

- Stable Color.
- Popular 3.0mm through hole package.
- Green Transparent lens and Yellow Diffused lens and Water Clear lens and Green Transparent lens.

Official Product	HV-341644/260/SYGTUYSUBCSYGT -C0028	Customer Part No.	Data Sheet No.
	*****	*****	HV-341644/260/SYGTUYSUBCSY GT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		Jun.19 2024	Version of 1.1
			Page 3/16

Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol		Rating	Unit
Forward Current	I _F	SYG/UY/SUB	30	mA
Operating Temperature	T _{opr}	SYG/UY/SUB	-40to+85	°C
Storage Temperature	T _{stg}	SYG/UY/SUB	-40to+85	°C
Soldering Temperature*1	T _{sol}	SYG/UY/SUB	260	°C
Power Dissipation	P _d	SYG/UY	75	mW
		SUB	100	
Reverse Voltage	V _R	SYG/UY/SUB	5	V
Peak Forward Current*2	I _{FP}	SYG/UY	75	mA
		SUB	100	

*1: Soldering time $\leq$ 5 seconds. *2: Pulse Width $\leq$ 100 μ s and Duty $\leq$ 1% .

Official Product	HV-341644/260/SYGTUYSUBCSYGT-C0028	Customer Part No.		Data Sheet No.
	*****	*****		HV-341644/260/SYGTUYSUBCSYGT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		Jun.19 2024	Version of 1.1	Page 5/16

Electrical and Optical Characteristic

Parameter	Symbol	Condition		Min.	Typ.	Max.	Unit
Forward Voltage	V_F	$I_F=20\text{ mA}$	SYG/UY	/	2.0	2.4	V
			SUB	/	3.0	3.4	
Reverse Current	I_R	$V_R=5\text{ V}$	SYG	/	/	10	μA
			UY				
			SUB				
Luminous Intensity	I_v	$I_F=20\text{ mA}$	SYG	60	150	/	mcd
			UY	160	350	/	
			SUB	600	1800	/	
Viewing Angle	$2\theta_{1/2}$	$I_F=20\text{ mA}$	SYG	/	55	/	deg
			UY	/	60	/	
			SUB	/	50	/	
Dominant Wavelength	λ_d	$I_F=20\text{ mA}$	SYG	/	570	/	nm
			UY	/	590	/	
			SUB	/	470	/	
Peak Wavelength	λ_p	$I_F=20\text{ mA}$	SYG	/	575	/	nm
			UY	/	595	/	
			SUB	/	465	/	
Spectrum Radiation Bandwidth	$\Delta\lambda$	$I_F=20\text{ mA}$	SYG	/	30	/	nm
			UY	/	30	/	
			SUB	/	35	/	

Notes:

$\theta_{1/2}$ is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.

Official Product	HV-341644/260/SYGTUYSUBCSYGT-C0028	Customer Part No.		Data Sheet No.
	*****	*****		HV-341644/260/SYGTUYSUBCSYGT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		Jun.19 2024	Version of 1.1	Page 6/16

Specifications for Bin Grading:(SYG)

Iv (mcd)		
Grade	Min.	Max.
Q	60	125
R	100	200
S	160	320

λ_d (nm)		
Grade	Min.	Max.
5	566	569
6	568	571
7	570	573
8	572	575
9	574	577

Notes:

1.Luminous intensity: +/-15%.

2.Wavelength: +/-1nm.

Official Product	HV-341644/260/SYGTUYSUBCSYGT-C0028	Customer Part No.		Data Sheet No.
	*****	*****		HV-341644/260/SYGTUYSUBCSYGT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		Jun.19 2024	Version of 1.1	Page 7/16

Specifications for Bin Grading:(UY)

Iv (mcd)		
Grade	Min.	Max.
S	160	320
T	250	500

λ_d (nm)		
Grade	Min.	Max.
3	585	588
4	587	590
5	589	592
6	591	594
7	593	595

Notes:

- 1.Luminous intensity: +/-15%.
- 2.Wavelength: +/-1nm.

Official Product	HV-341644/260/SYGTUYSUBCSYGT-C0028	Customer Part No.		Data Sheet No.
	*****	*****		HV-341644/260/SYGTUYSUBCSYGT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		Jun.19 2024	Version of 1.1	Page 8/16

Specifications for Bin Grading:(SUB)

Iv (mcd)		
Grade	Min.	Max.
V	600	1250
W	1000	2000
X	1600	3200


λ_d (nm)		
Grade	Min.	Max.
2	463.5	466.5
3	465.5	468.5
4	467.5	470.5
5	469.5	472.5
6	471.5	474.5

Notes:

- 1.Luminous intensity: +/-15%.
- 2.Wavelength: +/-1nm.


Official Product	HV-341644/260/SYGTUYSUBCSYGT-C0028	Customer Part No.		Data Sheet No.
	*****	*****		HV-341644/260/SYGTUYSUBCSYGT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		Jun.19 2024	Version of 1.1	Page 9/16

Typical Electro-Optical Characteristics Curve(SYG)




Official Product	HV-341644/260/SYGTUYSUBCSYGT-C0028	Customer Part No.	Data Sheet No.
	*****	*****	HV-341644/260/SYGTUYSUBCSYGT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.	Jun.19 2024	Version of 1.1	Page 10/16

Typical Electro-Optical Characteristics Curve(UY)



Official Product	HV-341644/260/SYGTUYSUBCSYGT-C0028	Customer Part No.	Data Sheet No.
	*****	*****	HV-341644/260/SYGTUYSUBCSYGT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		Jun.19 2024	Page 11/16

Typical Electro-Optical Characteristics Curve(SUB)




Official Product	HV-341644/260/SYGTUYSUBCSYGT-C0028	Customer Part No.	Data Sheet No.
	*****	*****	HV-341644/260/SYGTUYSUBCSYGT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		Jun.19 2024	Page 12/16

Soldering condition

- Careful attention should be paid during soldering. When soldering, leave more than 2mm from solder joint to Led, and soldering beyond the base of the tie bar is recommended.
- Avoiding applying any stress to the lead frame while the LED are at high temperature particularly when soldering.
- Dip and hand soldering should not be done more than one time.
- After soldering the LED, the epoxy bulb should be protected from mechanical shock or vibration until the LED return to room temperature.
- A rapid-rate process is not recommended for cooling the LED down from the peak temperature.
- Although the recommended soldering conditions are specified in the above table, dip or hand soldering at the lowest possible temperature is desirable for the LED.
- Wave soldering parameter must be set and maintain according to recommended temperature and dwell time in the solder wave.

• Recommended soldering conditions

Hand Soldering		Wave Soldering	
Temp. at tip of iron	300°C Max. (30W Max.)	Preheat temp.	100°C Max. (60 sec Max.)
Soldering time	3 sec Max.	Bath temp. & time	260°C Max., 5 sec Max
Distance	2mm Min.(From solder joint to Led)	Distance	2mm Min. (From solder joint to Led)



Official Product	HV-341644/260/SYGTUYSUBCSYGT-C0028	Customer Part No.	Data Sheet No.
	*****	*****	HV-341644/260/SYGTUYSUBCSYGT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		Jun.19 2024	Version of 1.1
		Page 13/16	

Reliability test items and conditions:

The reliability of products shall be satisfied with items listed below.

Confidence level: 97%.

LTPD:3%.

No	Item	Test Conditions	Test Hours/Cycle	Sample Size	Failure Judgment Criteria	Ac/Er
1	Solder Heat	TEMP:260℃±5℃	10 SEC	76 PCS	$I_v \leq I_{vt} * 0.5$ or $V_f \geq U$ or $V_f \leq L$	0/1
2	Temperature Cycle	H:+100℃ 15min ∫ 5min L:-40℃ 15min	300 CYCLES	76 PCS		0/1
3	Thermal Shock	H:+100℃ 5min ∫ 10sec L:-10℃ 5min	300 CYCLES	76 PCS		0/1
4	High Temperature Storage	TEMP:100℃	1000 HRS	76 PCS		0/1
5	Low Temperature Storage	TEMP:-40℃	1000 HRS	76 PCS		0/1
6	DC Operating Life	TEMP:25℃ IF=20mA	1000 HRS	76 PCS		0/1
7	High Temperature / High Humidity	85℃/85%RH	1000 HRS	76 PCS		0/1

Note: I_{vt} : To test I_v value of the chip before the reliability test.


I_v : The test value of the chip that has completed the reliability test.

U: Upper Specification Limit.

L: Lower Specification Limit.

Official Product	HV-341644/260/SYGTUYSUBCSYGT-C0028	Customer Part No.		Data Sheet No.
	*****	*****		HV-341644/260/SYGTUYSUBCSYGT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		Jun.19 2024	Version of 1.1	Page 14/16

Packing Specification:



	HARVATEK	
CPN:		RoHs
P/N:		
	HV-341644/260/SYGTUYSUBCSYGT-C0028	
QTY:		CAT:
		HUE:
LOT NO:		REF:
		

Official Product	HV-341644/260/SYGTUYSUBCSYGT-C0028	Customer Part No.	Data Sheet No.
	*****	*****	HV-341644/260/SYGTUYSUBCSYGT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.	Jun.19 2024	Version of 1.1	Page 15/16

Revision History

Revision	Page	Version No.	Revision Date
Initial Release		1.0	07-04-2022
Modify the furnace conditions	13	1.1	06-19-2024

Official Product	HV-341644/260/SYGTUYSUBCSYGT-C0028	Customer Part No.	Data Sheet No.
	*****	*****	HV-341644/260/SYGTUYSUBCSYGT-C0028
Specifications are subject to change without notice. Data and drawings herein are copyrighted.		Jun.19 2024 Version of 1.1	Page 16/16