



60V, 80A, 5.3mΩ Fast Switching MOSFETs

Features


- Super Low Gate Charge
- Advanced high cell density Trench technology
- Excellent CdvV/dt effect decline
- 100% EAS Guaranteed

Applications


- PWM applications
- Load Switch
- Power management

RoHS

TO252-3L



Equivalent Circuit



Absolute Maximum Ratings (T_C=25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V _{DS}	60	V
Gate-Source Voltage	V _{GS}	±20	V
Continuous Drain Current	I _D @T _C =25°C	80	A
	I _D @T _C =100°C	52	A
Pulsed Drain Current ¹	I _{DM}	320	A
Single Pulse Avalanche Energy ²	EAS	169	mJ
Total Power Dissipation	P _D	108	W
Storage Temperature Range	T _{STG}	-55 to 175	°C
Operating Junction Temperature Range	T _J	-55 to 175	°C
Thermal Resistance Junction-ambient	R _{θJA}	-	°C/W
Thermal Resistance Junction-Case	R _{θJC}	1.4	°C/W



Electrical Characteristics($T_J=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	60	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=60V, V_{GS}=0V$	-	-	1	μA
Gate to Body Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$	-	-	± 100	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	2	3	4	V
Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=30A$	-	5.3	7	m Ω
Input Capacitance	C_{iss}	$V_{GS}=0V, V_{DS}=30V,$ $f=1.0MHz$	-	4136	-	pF
Output Capacitance	C_{oss}		-	286	-	
Reverse Transfer Capacitance	C_{rss}		-	257	-	
Total Gate Charge	Q_g	$V_{DS}=30V, I_D=30A,$ $V_{GS}=10V$	-	90	-	nC
Gate-Source Charge	Q_{gs}		-	9	-	
Gate-Drain("Miller")Charge	Q_{gd}		-	18	-	
Turn-on Delay Time	$T_{d(on)}$	$V_{GS}=10V,$ $R_G=1.8\Omega, V_{DD}=30V,$ $I_D=30A$	-	9	-	nS
Turn-on Rise Time	t_r		-	7	-	
Turn-Off Delay Time	$T_{d(off)}$		-	40	-	
Turn-Off Fall Time	T_f		-	15	-	
Diode Forward Voltage	V_{SD}	$V_{GS}=0V, I_S=30A$	-	-	1.2	V
Maximum Pulsed Drain to Source Diode Forward Current	I_{SM}	-	-	-	320	A
Continuous Source Current ^{1,5}	I_S		-	-	80	A
Reverse Recovery Time	T_{rr}	$I_F=30A, di/dt=100A/\mu s$	-	33	-	Ns
Reverse Recovery Charge	Q_{rr}	-	-	46	-	nC

Note :

- 1.Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.
- 2.EAS condition : $T_J=25^{\circ}\text{C}, V_{DD}=30V, V_G=10V, L=0.5mH, R_G=25\Omega, I_{AS}=26A$.
- 3.Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 0.5\%$.



Typical Performance Characteristics

Figure 1: Output Characteristics




Figure 2: Typical Transfer Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 4: Body Diode Characteristics




Figure 5: Gate Charge Characteristics




Figure 6: Capacitance Characteristics






Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 8: Normalized on Resistance vs. Junction Temperature




Figure 9: Maximum Safe Operating Area




Figure 10: Maximum Continuous Drain Current vs. Case Temperature






Figure 11: Maximum Effective Transient Thermal Impedance, Junction-to-Case






Package Mechanical Data TO252-3L



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	2.10		2.50	0.083		0.098
A2	0		0.10	0		0.004
B	0.66		0.86	0.026		0.034
B2	5.18		5.48	0.202		0.216
C	0.40		0.60	0.016		0.024
C2	0.44		0.58	0.017		0.023
D	5.90		6.30	0.232		0.248
D1	5.30REF			0.209REF		
E	6.40		6.80	0.252		0.268
E1	4.63			0.182		
G	4.47		4.67	0.176		0.184
H	9.50		10.70	0.374		0.421
L	1.09		1.21	0.043		0.048
L2	1.35		1.65	0.053		0.065
V1		7°			7°	
V2	0°		6°	0°		6°

Reel Specification-TO252-3L



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
W	15.90	16.00	16.10	0.626	0.630	0.634
E	1.65	1.75	1.85	0.065	0.069	0.073
F	7.40	7.50	7.60	0.291	0.295	0.299
D0	1.40	1.50	1.60	0.055	0.059	0.063
D1	1.40	1.50	1.60	0.055	0.059	0.063
P0	3.90	4.00	4.10	0.154	0.157	0.161
P1	7.90	8.00	8.10	0.311	0.315	0.319
P2	1.90	2.00	2.10	0.075	0.079	0.083
A0	6.85	6.90	7.00	0.270	0.271	0.276
B0	10.45	10.50	10.60	0.411	0.413	0.417
K0	2.68	2.78	2.88	0.105	0.109	0.113
T	0.24		0.27	0.009		0.011
t1	0.10			0.004		
10P0	39.80	40.00	40.20	1.567	1.575	1.583