



SOT-23 Bipolar Transistor 双极型三极管


■Features 特点



NPN High Voltage Switching 高压开关

SOT-23

- 1. BASE
- 2. EMITTER
- 3. COLLECTOR



■Absolute Maximum Ratings 最大额定值

Characteristic 特性参数	Symbol 符号	Rat 额定值	Unit 单位
Collector-Base Voltage 集电极基极电压	V_{CBO}	600	V
Collector-Emitter Voltage 集电极发射极电压	V_{CEO}	400	V
Emitter-Base Voltage 发射极基极电压	V_{EBO}	7	V
Collector Current 集电极电流	I_C	200	mA
Power dissipation 耗散功率	$P_C(T_a=25^{\circ}C)$	350	mW
Thermal Resistance Junction-Ambient 热阻	$R_{\theta JA}$	357	$^{\circ}C/W$
Junction and Storage Temperature 结温和储藏温度	T_J, T_{stg}	-55to+150 $^{\circ}C$	

■Device Marking 产品打标

13001-6AF=8D




■Electrical Characteristics 电特性

(TA=25℃ unless otherwise noted 如无特殊说明, 温度为 25℃)

Characteristic 特性参数	Symbol 符号	Min 最小值	Type 典型值	Max 最大值	Unit 单位
Collector-Base Breakdown Voltage 集电极基极击穿电压($I_C=100\mu A$, $I_E=0$)	BV_{CBO}	600	—	—	V
Collector-Emitter Breakdown Voltage 集电极发射极击穿电压($I_C=1mA$, $I_B=0$)	BV_{CEO}	400	—	—	V
Emitter-Base Breakdown Voltage 发射极基极击穿电压($I_E=100\mu A$, $I_C=0$)	BV_{EBO}	7	—	—	V
Collector-Base Leakage Current 集电极基极漏电流($V_{CB}=600V$, $I_E=0$)	I_{CBO}	—	—	100	μA
Collector-Emitter Leakage Current 集电极发射极漏电流($V_{CE}=400V$, $I_B=0$)	I_{CEO}	—	—	200	μA
Emitter-Base Leakage Current 发射极基极漏电流($V_{EB}=7V$, $I_C=0$)	I_{EBO}	—	—	100	μA
DC Current Gain 直流电流增益($V_{CE}=10V$, $I_C=250\mu A$)	$H_{FE}(1)$	5	—	—	
DC Current Gain 直流电流增益($V_{CE}=20V$, $I_C=20mA$)	$H_{FE}(2)$	20	—	30	
DC Current Gain 直流电流增益($V_{CE}=10V$, $I_C=250mA$)	$H_{FE}(3)$	5	—	—	
Collector-Emitter Saturation Voltage 集电极发射极饱和压降($I_C=50mA$, $I_B=10mA$)	$V_{CE(sat)}$	—	—	0.5	V
Base-Emitter Saturation Voltage 基极发射极饱和压降($I_C=50mA$, $I_B=10mA$)	$V_{BE(sat)}$	—	—	1.2	V
Transition Frequency 特征频率($V_{CE}=20V$, $I_C=20mA$)	f_T	8	—	—	MHz
Fall Time 下降时间 ($V_{CC}=45V, I_C=50mA, I_{B1}=-I_{B2}=5mA$)	t_f	—	—	300	ns
Storage Time 贮存时间 ($V_{CC}=45V, I_C=50mA, I_{B1}=-I_{B2}=5mA$)	t_s	—	—	1.5	μs

■Dimension 外形封装尺寸



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.050	0.055
E1	2.250	2.550	0.089	0.100
e	0.900	1.00	0.035	0.039
e1	1.800	2.000	0.071	0.079
L	0.500	0.600	0.020	0.024
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°