

| | 1 | 2 | 3 | 4 | 5 | 6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-----|------|------|-----------------|--------------------------------|--------------------------------------|------|----|------|-----|-----|--------|-------|------|----|------|-----|-----|-----|----------------|--|-----|------|------|-----|------------|--------------------------------------|--|---|--|--|----------|-----------------------------|------|--|--|--|--|-----------------|--------------------------------|------------|--|--|--|--|-----------|-------|------------|
| A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| B | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| D | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>The technical drawing shows a U-shaped metal component. A callout labeled "M4*0.7 拉伸孔" indicates a hole with a diameter of M4 and a thickness of 0.7. Other dimensions shown include 11.2, 0.8, 8.5, 7.1, 1.6, 5, and 3.1.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>RoHS2.0 Compliant</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>11.20 3.55 3.1 5 1.6 7.1 11.20 3.55</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>未注公差</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"><thead><tr><th>变更记录</th><th>X.</th><th>±0.8</th><th>X'.</th><th>±8'</th><th>单位: mm</th><th>客户确认:</th></tr></thead><tbody><tr><td>变更内容</td><td>X.</td><td>±0.5</td><td>X'.</td><td>±5'</td><td>日期:</td><td>日期: 2024/01/18</td></tr><tr><td></td><td>.XX</td><td>±0.3</td><td>.XX'</td><td>±3'</td><td>材料: 黄铜 H62</td><td>雄和料号: 4F07-40D-CTS 规格: M4x8.5x1.2</td></tr><tr><td></td><td>/</td><td></td><td></td><td>包装方式: 散装</td><td>审核: 王家祥 制图: 熊贺光 客户: /</td><td>版本 A</td></tr><tr><td></td><td></td><td></td><td></td><td>表面处理: / 电镀雾锡</td><td>制图依据: 客户图纸 参考标准: CUSTOM DWG</td><td>规格: / A</td></tr><tr><td></td><td></td><td></td><td></td><td>额定电流: 40A</td><td>比例: /</td><td>页码: 1 OF 1</td></tr></tbody></table> | | | | | | | 变更记录 | X. | ±0.8 | X'. | ±8' | 单位: mm | 客户确认: | 变更内容 | X. | ±0.5 | X'. | ±5' | 日期: | 日期: 2024/01/18 | | .XX | ±0.3 | .XX' | ±3' | 材料: 黄铜 H62 | 雄和料号: 4F07-40D-CTS 规格: M4x8.5x1.2 | | / | | | 包装方式: 散装 | 审核: 王家祥 制图: 熊贺光 客户: / | 版本 A | | | | | 表面处理: / 电镀雾锡 | 制图依据: 客户图纸 参考标准: CUSTOM DWG | 规格: / A | | | | | 额定电流: 40A | 比例: / | 页码: 1 OF 1 |
| 变更记录 | X. | ±0.8 | X'. | ±8' | 单位: mm | 客户确认: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 变更内容 | X. | ±0.5 | X'. | ±5' | 日期: | 日期: 2024/01/18 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | .XX | ±0.3 | .XX' | ±3' | 材料: 黄铜 H62 | 雄和料号: 4F07-40D-CTS 规格: M4x8.5x1.2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | / | | | 包装方式: 散装 | 审核: 王家祥 制图: 熊贺光 客户: / | 版本 A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 表面处理: / 电镀雾锡 | 制图依据: 客户图纸 参考标准: CUSTOM DWG | 规格: / A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 额定电流: 40A | 比例: / | 页码: 1 OF 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>1 2 3 4 5 6</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |