

Description:


This N-Channel MOSFET uses advanced SGT technology and

design to provide excellent $R_{DS(on)}$ with low gate charge.

It can be used in a wide variety of applications.

Features:

- 1) $V_{DS}=100V, I_D=75A, R_{DS(ON)} < 11m\Omega @ V_{GS}=10V$
- 2) Low gate charge.
- 3) Green device available.
- 4) Advanced high cell density trench technology for ultra low $R_{DS(ON)}$.
- 5) Excellent package for good heat dissipation.



Package Marking and Ordering Information:

Part NO.	Marking	Package	Packing
DOP75N10-L	75N10-L	TO- 220	50 pcs/Tube

Absolute Maximum Ratings: ($T_C=25^{\circ}C$ unless otherwise noted)

Symbol	Parameter	Ratings	Units
V_{DS}	Drain-Source Voltage	100	V
V_{GS}	Gate-Source Voltage	± 20	V
I_D	Continuous Drain Current	75	A
	Continuous Drain Current- $T_C=100^{\circ}C$	48	
P_D	Power Dissipation	104	W
I_{DM}	Pulsed Drain Current ¹	300	A
E_{AS}	Single pulse avalanche energy ²	71	mJ
T_J, T_{STG}	Operating and Storage Junction Temperature Range	-55-+150	$^{\circ}C$

Thermal Characteristics:

Symbol	Parameter	Max	Units
$R_{\theta JC}$	Thermal Resistance, Junction to Case	1.2	$^{\circ}C/W$
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	60	$^{\circ}C/W$

Electrical Characteristics: ($T_C=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
Off Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250 μ A	100	---	---	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{GS} =0V, V _{DS} =100V	---	---	1	μ A
I _{GSS}	Gate-Source Leakage Current	V _{GS} =± 20V, V _{DS} =0A	---	---	± 100	nA
On Characteristics						
V _{GS(th)}	Gate-Source Threshold Voltage	V _{GS} =V _{DS} , I _D =250 μ A	1	1.8	2.5	V
R _{DS(on)}	Drain-Source On Resistance ³	V _{GS} =10V, I _D =10A	---	9	11	m Ω
		V _{GS} =4.5V, I _D =10A	---	12	16	m Ω
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{DS} =50V, V _{GS} =0V, f=1MHz	---	1615	---	pF
C _{oss}	Output Capacitance		---	441	--	
C _{rss}	Reverse Transfer Capacitance		---	7.8	---	
Switching Characteristics						
t _{d(on)}	Turn-On Delay Time	V _{DD} =50V, R _D =5 Ω R _{ENG} =10 Ω, V _{GS} =10V	---	9.4	---	ns
t _r	Rise Time		---	4.2	---	ns
t _{d(off)}	Turn-Off Delay Time		---	25.2	---	ns
t _f	Fall Time		---	4.2	---	ns
Q _g	Total Gate Charge	V _{GS} =10V, V _{DD} =50V, I _D =20A	---	31.5	---	nC
Q _{gs}	Gate-Source Charge		---	3.1	---	nC
Q _{gd}	Gate-Drain “Miller” Charge		---	14.7	---	nC
Drain-Source Diode Characteristics						
V _{SD}	Diode Forward Voltage	V _{GS} =0V, I _{SD} =20A	---	0.9	1.3	V
I _S	Continuous Drain Curren	V _D =V _G =0V	---	---	75	A

Notes:

1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature
2. EAS condition: $T_J=25^{\circ}\text{C}$, $V_{DD}=50V$, $V_G=10V$, $L=0.5mH$
3. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 0.5\%$

Typical Characteristics: ($T_c=25^{\circ}\text{C}$ unless otherwise noted)




Fig1. Typical Output Characteristics




Fig2. Typical Transfer Characteristics




Fig3. On-Resistance Vs. Temperature




Fig4. Typical Source-Drain Diode Forward Voltage




Fig5. Typical Capacitance




Fig6. Typical Gate Charge




Fig7. Safe Operating Area





Fig8. Normalized transient thermal impedance

TO-220 Package Information:



UNIT: mm

SYMBOLS	A	A1	A2	b	b1	c	D	D1	D2	E	E1	e
MIN	4.25	1.25	2.35	0.7	1.15	0.45	14.35	8.80	13.05	9.90	7.85	2.540
MAX	4.65	1.35	2.55	0.9	1.75	0.60	15.95	9.50	13.65	10.35	8.85	BSC
SYMBOLS	e1	H1	L	L1	Q	φP						
MIN	5.080	6.30	12.85	2.85	2.70	3.50						
MAX	BSC	6.65	13.50	3.25	2.90	3.70						

Marking Information:

①. Doingter LOGO


②. Date Code(YWWG / R)

Y : Year Code , last digit of the year

WW : Week Code(01-53)

G/R : G(Green) /R(Lead Free)

③. Part NO.



Previous Version

Version	Date	Subjects (major changes since last revision)
1.0	2024-09-10	Release of final version

Attention :

- Information furnished in this document is believed to be accurate and reliable. However, Shenzhen Doingter Semiconductor Co.,Ltd. assumes noresponsibility for the consequences of use without consideration for such information nor use beyond it.
- Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Shenzhen Doingter complies with the agreement. Products and information provided in this document have no infringement of patents.
- Shenzhen Doingter assumes noresponsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



Is a registered trademark of Shenzhen Doingter Semiconductor Co., Ltd. Copyright © 2013 Shenzhen DoingterSemiconductor Co.,Ltd. Printed All rights reserved.