

SPTECH Silicon NPN Power Transistor

2SC3281

DESCRIPTION


- Collector-Emitter Breakdown Voltage-
: $V_{(BR)CEO} = 200V(\text{Min})$
- Collector-Emitter Saturation Voltage-
: $V_{CE(sat)} = 3.0V(\text{Max}) @ I_C = 10A, I_B = 1A$
- High Power Dissipation

APPLICATIONS

- Power amplifier applications
- Recommend for 100W high fidelity audio frequency amplifier output stage applications

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	200	V
V_{CEO}	Collector-Emitter Voltage	200	V
V_{EBO}	Emitter-Base voltage	5	V
I_C	Collector Current-Continuous	15	A
I_B	Base Current-Continuous	1.5	A
P_C	Collector Power Dissipation @ $T_c=25^\circ\text{C}$	150	W
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^\circ\text{C}$



SPTECH Silicon NPN Power Transistor

2SC3281

ELECTRICAL CHARACTERISTICS

 $T_c=25^{\circ}\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	$I_C=50\text{mA}$; $I_B=0$	200			V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=10\text{A}$; $I_B=1\text{A}$			3.0	V
$V_{BE(on)}$	Base-Emitter On Voltage	$I_C=8\text{A}$; $V_{CE}=5\text{V}$			1.5	V
I_{CBO}	Collector Cutoff Current	$V_{CB}=200\text{V}$; $I_E=0$			5.0	μA
I_{EBO}	Emitter Cutoff Current	$V_{EB}=5\text{V}$; $I_C=0$			5.0	μA
h_{FE-1}	DC Current Gain	$I_C=1\text{A}$; $V_{CE}=5\text{V}$	55		160	
h_{FE-2}	DC Current Gain	$I_C=8\text{A}$; $V_{CE}=5\text{V}$	35			
f_T	Current-Gain—Bandwidth Product	$I_C=1\text{A}$; $V_{CE}=5\text{V}$		30		MHz
C_{OB}	Output Capacitance	$I_E=0$; $V_{CB}=10\text{V}$, $f_{test}=1\text{MHz}$		270		pF

◆ h_{FE-1} Classifications

R	O
55-110	80-160