



General Description

The MCP1703T-xx02E/DB family of a linear voltage linear regulators developed utilizing BM unique BiCMOS technology featured low quiescent current (90uA), low dropout voltage, high output voltage accuracy. The space-efficient SOT-223 package is attractive for “Pocket” and “HandHeld” applications.

Output voltages are set at the factory and trimmed to 1.5% accuracy. Voltages from 1.8V to 5.0V are available.

These rugged devices have both Thermal Shutdown, and Current Fold-back to prevent device failure under the “Worst” of operating conditions.

The MCP1703T-xx02E/DB is stable with an output capacitance of 10 μ F or greater.


Features

- ◆ Very Low Dropout Voltage , <800mV when 0.8A
- ◆ Low Current Consumption: Typ. 90uA
- ◆ High Accuracy Output Voltage: +/- 1.5%
- ◆ Guaranteed 0.8A (if $V_{in}-V_{out}<1700mV$ in SOT223)
- ◆ Output up to 0.3A if down 12V to +5V in SOT223
- ◆ Compact Package: SOT-223
- ◆ Factory Pre-set Output Voltages
- ◆ Short Circuit Current Fold-Back
- ◆ Low Temperature Coefficient

Applications

- ◆ Battery-powered devices
- ◆ Personal communication devices
- ◆ Home electric/electronic appliances
- ◆ PC peripherals , hard-disk

PIN Configuration




Order Information

Orderable Device	Package	Output Voltage	Packing Option
MCP1703T-xx02E/DB	SOT-223	2.5V, 2.8V, 3.0V, 3.3V, 5.0V	1000/Reel

Note: xx is 25, 28, 30, 33, 50



Bkock Diagram



Absolute Maximum Ratings

Description	Symbol	Value Range	Unit
Input Voltage	V_{IN}	+18	V
Output Current	I_{out}	1.2	A
Output Voltage	V_{out}	GND-0.3 to $V_{IN} + 0.3$	V
ESD Classification		B	



Operating Ratings

Description	Symbol	Value Range	Unit
Supply Voltage	V_{IN}	+2 to +16	V
Ambient Temperature Range	T_A	-40 to +85	°C
Junction Temperature Range	T_J	-40 to +125	°C

Thermal Information

Parameter	Maximum	Unit
Thermal Resistance (Θ_{jc})	160	°C/W
Internal Power Dissipation (P_D) ($\Delta T = 100^\circ\text{C}$)	625	mW
Maximum Junction Temperature	150	°C
Maximum Lead Temperature (10 Sec)	300	°C

*With Junction sink capable of twice times of Θ_{jc}

Caution: Stress above the listed absolute rating may cause permanent damage to the device.

Electrical Characteristics

$T_A = +25^\circ\text{C}$; unless otherwise noted

Parameter	Symbol	Test Conditions	MCP1703T-xx02E/DB			Unit
			Min.	Typ.	Max.	
Input Voltage	V_{IN}		+2		+18	V
Output Voltage Accuracy	V_{OUT}	$I_O = 1\text{mA to } 1.5\text{A}$	-1.5		1.5	%
Dropout Voltage	$V_{DROPOUT}$	$V_{OUT}=V_{O(NOM)}-4\%$, $I_{OUT}=0.8\text{A}$	700			mV
					700	mV
					200	mV
Output Current	I_O	$V_{OUT} > 1.5\text{V}$		800		mA
Current Limit	I_{LIM}	$V_{OUT} > 1.5\text{V}$		1200		mA
Short Circuit Current	I_{SC}	$V_{OUT} < 0.4\text{V}$		750	1200	mA
Quiescent Current	I_Q	$I_O = 0\text{mA}$		90		uA
Ground Pin Current	I_{GND}	$I_O = 1\text{mA to } 1\text{A}$		90		uA
Line Regulation	REG_{LINE}	$I_{OUT}=5\text{mA}$	$V_{OUT} \leq 4.0\text{V}$		1.5	%
			$V_{OUT} > 4.0\text{V}$	2		%
Load Regulation	REG_{LOAD}	$I_O = 0 \sim 0.8\text{A}$		0.2	1.5	%
Over Temperature Shutdown	OTS			150		°C
Over Temperature Hysteresis	OTH			30		°C
V_{OUT} Temperature Coefficient	TC			30		ppm/°C
Power Supply Reject	PSRR	$I_O = 100\text{mA}$ $C_O=22\mu\text{F}$ ceramic	$f=1\text{kHz}$	72		dB
			$f=10\text{kHz}$	60		
			$f=100\text{kHz}$	45		
Output Voltage Noise	eN	$f=10\text{Hz to } 100\text{kHz}$ $I_O = 10\text{mA}$	$C_O=22\mu\text{F}$	30		μVrms
			$C_O=47\mu\text{F}$	20		

Note 1. $V_{IN(MIN)} = V_{OUT} + V_{DROPOUT}$



Detailed Description

The MCP1703T-xx02E/DB family of BiCMOS regulators contain a pass transistor, voltage reference, error amplifier, over-current protection, thermal shutdown, and short circuit protection.

The P-channel pass transistor receives data from the error amplifier, over-current shutdown, short output protection, and thermal protection circuits. During normal operation, the error amplifier compares the output voltage to a precision reference. Over-current and Thermal shutdown circuits become active when the junction temperature exceeds 150°C, or the current exceeds 1.2A. During thermal shutdown the output voltage remains low. Normal operation is restored when the junction temperature drops below 120°C.

The MCP1703T-xx02E/DB behaves like a current source when the load reaches 1.2A. However, if the load impedance drops below 0.3Ω, the current drops back to 600mA to prevent excessive power dissipation. Normal operation is restored when the load resistance exceeds 0.75Ω.

External Capacitor


The MCP1703T-xx02E/DB is stable with an output capacitor to ground of 22μF or greater. Ceramic capacitors have the lowest ESR, and will offer the best AC performance. Conversely, Aluminum Electrolytic capacitors exhibit the highest ESR, resulting in the poorest AC response. Unfortunately, large value ceramic capacitors are comparatively expensive. One option is to parallel a 0.1μF ceramic capacitor with a 22μF Aluminum Electrolytic. The benefit is low ESR, high capacitance, and low overall cost.

A second capacitor is recommended between the input and ground to stabilize VIN. The input capacitor should be larger than 22μF to have a beneficial effect. All capacitors should be placed in close proximity to the pins. A “quiet” ground termination is desirable.




Typical Electrical Characteristics


Minimum Operating Current




Short-Circuit Current




Load Regulation




Ripple Rejection vs. Current



Temperature Stability





GND Pin Current





Package Dimension

SOT-223 (M223)



SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.50	---	1.80	0.0591	---	0.0709
B	0.60	---	0.838	0.0236	---	0.033
B1	2.895	---	3.15	0.114	---	0.124
D	6.299	---	6.706	0.248	---	0.264
E	3.30	---	3.708	0.1299	---	0.146
e	---	2.30BSC	---	---	0.0908C	---
e1	---	4.80BSC	---	---	0.181BSC	---
H	6.70	---	7.30	0.2638	---	0.2874
L	---	0.91MIN	---	---	0.036MIN	---
L1	---	2.00MAX	---	---	0.0787MAX	---
(θ)	---	---	13°	---	---	13°



Attention

- Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.
- HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.
- Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.