

自主封測 品質把控 售後保障


WEB | WWW.TDSEMIC.COM




電源管理





顯示驅動



二三極管 LDO穩壓器




觸摸芯片



MOS管




運算放大器



存儲芯片



MCU



串口通信

SMF5.0A


產品規格說明書

Features

- For surface mounted applications in order to optimize board space.
- Low profile package.
- Glass passivated junction.
- Low inductance.
- Plastic package has Underwriters Laboratory Flammability.

SOD-123FL
(SMF)**Mechanical Data**

- Case: JEDEC SOD-123FL/SMF molded plastic body
- Terminals: Solderable per MIL-STD-750, Method 2026A
- Polarity: Polarity symbol marking on body
- Mounting Position: Any
- Weight: 0.00 \pm 7ounce, 0.02grams
- Marking: Date Code and Marking Code See Page 2

Part Number Code**Applications**

- I/O interface
- AC/D Cpower supply
- Low frequency signal transmission line (RS232, RS485, etc.)

Maxmim Ratings (Ta=25°C unless otherwise noted)

Peak pulse power dissipation at 10/1000 μ s waveform (Note1, Note2, Fig.1)	P _{PPM}	200	W
Peak pulse current of at 10/1000 μ s waveform (Note 1, Fig.3)	I _{PPM}	See Tale	A
Steady state power dissipation at T _A =50°C (Fig.5)	P _{M(AV)}	1.0	W
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load, (JEDEC Method) (Note3, Fig.6)	I _{FSM}	30	A
Operating junction and Storage Temperature Range.	T _J , T _{STG}	-65 to +150	°C
Typical thermal resistance junction to lead	R _{θJL}	38	°C/W
Typical thermal resistance junction to ambient	R _{θJA}	180	°C/W

Notes:1. Non-repetitive current pulse, per Fig.3 and derated above T_A=25°C per Fig.2.

2. Mounted on 5.0mm×5.0mm (0.03mm thick) copper pads to each terminal.

3. 8.3ms single half sine-wave, or equivalent square wave, duty cycle=4 pulses per minutes maximum.

Electrical Characteristics (Ta=25°C)

Type		Marking		VRMW	Breakdown Voltage		Test Current	Reverse Leakage	Max. Clamp Voltage	Peak Pulse Current				
					VBR @T									
					Min	Max								
Uni	Bi	Uni	Bi	V	V	V	mA	µA	V	A				
SMF5.0A	SMF5.0CA	AE	NE	5	6.4	7	10	400	9.2	21.7				
SMF6.0A	SMF6.0CA	AG	NG	6	6.67	7.37	10	400	10.3	19.4				
SMF6.5A	SMF6.5CA	AK	NK	6.5	7.22	7.98	10	250	11.2	17.9				
SMF7.0A	SMF7.0CA	AM	NM	7	7.78	8.6	10	100	12	16.7				
SMF7.5A	SMF7.5CA	AP	NP	7.5	8.33	9.21	1	50	12.9	15.5				
SMF8.0A	SMF8.0CA	AR	NR	8	8.89	9.83	1	25	13.6	14.7				
SMF8.5A	SMF8.5CA	AT	NT	8.5	9.44	10.4	1	10	14.4	13.9				
SMF9.0A	SMF9.0CA	AV	NV	9	10	11.1	1	5	15.4	13				
SMF10A	SMFI0CA	AX	NX	10	11.1	12.3	1	2.5	17	11.8				
SMF11A	SMF11CA	AZ	NZ	11	12.2	13.5	1	2.5	18.2	11				
SMF12A	SMF12CA	BE	OE	12	13.3	14.7	1	2.5	19.9	10.1				
SMF13A	SMF13CA	BG	OG	13	14.4	15.9	1	1	21.5	9.3				
SMF14A	SMF14CA	BK	OK	14	15.6	17.2	1	1	23.2	8.6				
SMF15A	SMF15CA	BM	OM	15	16.7	18.5	1	1	24.4	8.2				
SMF16A	SMF16CA	BP	OP	16	17.8	19.7	1	1	26	7.7				
SMF17A	SMF17CA	BR	OR	17	18.9	20.9	1	1	27.6	7.2				
SMF18A	SMF18CA	BT	OT	18	20	22.1	1	1	29.2	6.8				
SMF20A	SMF20CA	BV	OV	20	22.2	24.5	1	1	32.4	6.2				
SMF22A	SMF22CA	BX	OX	22	24.4	26.9	1	1	35.5	5.6				
SMF24A	SMF24CA	BZ	OZ	24	26.7	29.5	1	1	38.9	5.1				
SMF26A	SMF26CA	CE	PE	26	28.9	31.9	1	1	42.1	4.8				
SMF28A	SMF28CA	CG	PG	28	31.1	34.4	1	1	45.4	4.4				
SMF30A	SMF30CA	CK	PK	30	33.3	36.8	1	1	48.4	4.1				
SMF33A	SMF33CA	CM	PM	33	36.7	40.6	1	1	53.3	3.8				
SMF36A	SMF36CA	CP	PP	36	40	44.2	1	1	58.1	3.4				
SMF40A	SMF40CA	CR	PR	40	44.4	49.1	1	1	64.5	3.1				
SMF43A	SMF43CA	CT	PT	43	47.8	52.8	1	1	69.4	2.9				
SMF45A	SMF45CA	CV	PV	45	50	55.3	1	1	72.7	2.8				
SMF48A	SMF48CA	CX	PX	48	53.3	58.9	1	1	77.4	2.6				
SMF51A	SMF51CA	CZ	PZ	51	56.7	62.7	1	1	82.4	2.4				
SMF54A	SMF54CA	DE	PA	54	60	66.3	1	1	87.1	2.3				
SMF58A	SMF58CA	DG	PC	58	64.4	71.2	1	1	93.6	2.1				
SMF60A	SMF60CA	DK	CDK	60	66.7	73.7	1	1	96.8	1.8				
SMF64A	SMF64CA	DM	CDM	64	71.1	78.6	1	1	103	1.7				
SMF70A	SMF70CA	DP	CDP	70	77.8	86	1	1	113	1.5				
SMF75A	SMF75CA	DR	CDR	75	83.3	92.1	1	1	121	1.4				
SMF78A	SMF78CA	DT	CDT	78	86.7	95.8	1	1	126	1.4				
SMF85A	SMF85CA	DV	CDV	85	94.4	104	1	1	137	1.3				
SMF90A	SMF90CA	DX	CDX	90	100	111	1	1	146	1.2				
SMF100A	SMF100CA	DZ	CDZ	100	111	123	1	1	162	1.1				
SMF110A	SMF110CA	EE	CEE	110	122	135	1	1	177	1				
SMF120A	SMF120CA	EG	CEG	120	133	147	1	1	193	0.9				
SMF130A	SMF130CA	EK	CEK	130	144	159	1	1	209	0.8				
SMF150A	SMF150CA	EM	CEM	150	167	185	1	1	243	0.7				
SMF160A	SMF160CA	EP	CEP	160	178	197	1	1	259	0.7				
SMF170A	SMF170CA	ER	CER	170	189	209	1	1	275	0.6				
SMF180A	SMF180CA	ET	CET	180	201	222	1	1	292	0.5				
SMF190A	SMF190CA	EV	CEV	190	211	232	1	1	308	0.5				
SMF200A	SMF200CA	EX	CEX	200	224	247	1	1	324	0.5				
SMF220A	SMF220CA	E22	CE22	220	246	272	1	1	356	0.5				
SMF250A	SMF250CA	E25	CE25	250	279	309	1	1	405	0.5				
SMF300A	SMF300CA	E30	CE30	300	335	371	1	1	486	0.45				
SMF350A	SMF350CA	E35	CE35	350	391	432	1	1	567	0.4				
SMF400A	SMF400CA	E40	CE40	400	447	494	1	1	648	0.35				
SMF440A	SMF440CA	E44	CE44	440	492	543	1	1	713	0.3				

Ratings and Characteristic Curves ($T_A=25^\circ C$ unless otherwise noted)

Fig.1 Peak Pulse Power Rating Curve




Fig.2 Forward Current Derating Curve




Fig.3 Pulse Waveform





Fig.4 Maximum Non-Repetitive Peak Forward Surge Current



Package Outline Dimensions
SOD-123FL(SMF)

