

片式防浪涌用压敏电阻器—SDVL-HS 系列

Chip Varistor for Surge Suppression – SDVL-HS Series



工作温度
Operating Temp

◆ -55°C ~ +125°C

特征 Features

- ◆ SMD 结构, 体积小, 适合高密度安装, 可定制
- ◆ 高浪涌型, 抗浪涌能力强
- ◆ 良好的焊接性能 (镍、锡电镀)
- ◆ SMD type, small size suitable for high density mounting
- ◆ High surge and strong capability of voltage surge suppression
- ◆ Excellent solderability (Ni, Sn plating)

用途 Applications

- ◆ 电源、网通等二次电源的浪涌过电压防护
- ◆ 安防、基站雷电及浪涌过电压防护
- ◆ 智能电表和工业仪表盘雷电及浪涌过压防护
- ◆ Voltage surge suppression for power supply, network interface and secondary power supply
- ◆ Voltage surge suppression for security system, base station
- ◆ Voltage surge suppression for industrial instrument, smart meters, etc.

产品型号 Product Identification

1	2	3	4	5	6	7	8	9
SDVL	5650	S	D	480	P	T	HS	901

1	分类 Type
SDVL	片式防浪涌用 压敏电阻器 Chip Varistor for Surge Suppression

2	外形尺寸 (L×W) (mm) External Dimensions (L×W) (mm)
1608 [0603]	1.6×0.8
2016 [0806]	2.2×1.6
3216 [1206]	3.2×1.6
3225 [1210]	3.2×2.5
4532 [1812]	4.5×3.2
5650 [2220]	5.9×5.1

3	压敏电压公差 Tolerance of Varistor Voltage
S	Special

7	包装 Packing
T	编带 Tape & Reel

8	系列代码 Series Code
HS	高浪涌型 High-Surge Type


4	工作电压类型 Type of Working Voltage
D	直流工作电压 DC Working Voltage

5	最大持续工作电压 Max. Continuous Working Voltage
Example	Nominal Value
090	9V
140	14V
480	48V

6	端头代号 Terminal Code
P	Ni, Sn Plating

9	脉冲电流 Peak Surge Current
Example	Nominal Value
300	30A
901	900A
502	5000A

外观尺寸 Shape and Dimensions



Type	L	W	T	a
SDVL1608 [0603]	1.6±0.15 [0.063±0.006]	0.8±0.15 [0.031±0.006]	1.0 Max. [0.039]	0.10~0.50 [0.004~0.020]
SDVL2016 [0806]	2.2±0.2 [0.087±0.008]	1.6+0.4/-0.2 [0.063+0.016/-0.008]	2.0 Max. [0.079]	0.25~0.75 [0.010~0.029]
SDVL3216 [1206]	3.2±0.2 [0.126±0.008]	1.6±0.2 [0.063±0.008]	2.0 Max. [0.079]	0.25~0.75 [0.010~0.029]
SDVL3225 [1210]	3.2±0.3 [0.126±0.012]	2.5±0.25 [0.098±0.010]	2.5 Max. [0.098]	0.25~0.75 [0.010~0.029]
SDVL4532 [1812]	4.5±0.4 [0.177±0.016]	3.2±0.3 [0.126±0.012]	3.2 Max. [0.126]	0.25~1.0 [0.010~0.039]
SDVL5650 [2220]	5.9±0.2 [0.232±0.008]	5.1±0.2 [0.201±0.008]	3.2 Max. [0.126]	0.25~1.3 [0.010~0.051]

规格特性 Specifications

SDVL1608-HS TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		
测试条件 Test Condition	<40μA		@1mA DC	8/20μs		Energy 10/1000μs	Peak Current 8/20μs	Nominal ACurrent 8/20μs
	DC	AC RMS						
单位 Units	Volts	Volts	Volts	Volts	Amps	Joules	Amps	Amps
符号 Symbol	V _{WDC}	V _{WRMS}	V _B	V _C	I _C	E _T	I _P	I _N
SDVL1608SD090PTHS101	9	6.4	14.0 [11.0-16.0]	30	1.0	0.10	100	60
SDVL1608SD140PTHS300	14	10.0	19.0 [16.0-22.0]	40	1.0	0.05	30	20
SDVL1608SD180PTHS101	18	12.7	25.0 [22.0-28.0]	45	1.0	0.10	100	60
SDVL1608SD180PTHS121	18	12.7	25.0 [22.0-28.0]	45	1.0	0.10	120	70
SDVL1608SD220PTHS300	22	15.6	30.0 [26.0-34.0]	50	1.0	0.05	30	20
SDVL1608SD300PTHS300	30	21.3	42.0 [37.0-46.0]	70	1.0	0.05	30	20
SDVL1608SD300PTHS101	30	21.3	42.0 [37.0-46.0]	70	1.0	0.10	100	60
SDVL1608SD380PTHS300	38	30.0	50.0 [46.0-54.0]	80	1.0	0.05	30	20
SDVL1608SD380PTHS800	38	30.0	50.0 [46.0-54.0]	80	1.0	0.08	80	50
SDVL1608SD480PTHS600	48	34.1	60.0 [54.0-67.0]	110	1.0	0.08	60	40
SDVL1608SD560PTHS300	56	40.0	68.0 [61.0-75.0]	125	1.0	0.05	30	20
SDVL1608SD600PTHS300	60	46.0	76.0 [69.0-83.0]	130	1.0	0.05	30	20
SDVL1608SD650PTHS300	65	50.0	82.0 [73.0-91.0]	135	1.0	0.05	30	20
SDVL1608SD850PTHS200	85	60.0	100.0 [90.0-110.0]	165	1.0	0.03	20	12
SDVL1608SD101PTHS200	100	75.0	120.0 [108.0-132.0]	200	1.0	0.03	20	12

SDVL2016-HS TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		
测试条件 Test Condition	<40μA		@1mA DC	8/20μs		Energy 10/1000μs	Peak Current 8/20μs	Nominal Current 8/20μs
	DC	AC RMS						
单位 Units	Volts	Volts	Volts	Volts	Amps	Joules	Amps	Amps
符号 Symbol	V _{WDC}	V _{WRMS}	V _B	V _C	I _C	E _T	I _P	I _N
SDVL2016SD090PTHS401	9	6.4	14.0 [11.0-16.0]	30	5.0	0.5	400	250
SDVL2016SD180PTHS401	18	12.7	25.0 [22.0-28.0]	45	5.0	0.5	400	250
SDVL2016SD180PTHS601	18	12.7	25.0 [22.0-28.0]	45	5.0	0.8	600	400
SDVL2016SD300PTHS600	30	21.3	42.0 [37.0-46.0]	70	5.0	0.08	60	40
SDVL2016SD300PTHS401	30	21.3	42.0 [37.0-46.0]	70	5.0	0.5	400	250
SDVL2016SD380PTHS401	38	30.0	50.0 [46.0-54.0]	80	5.0	0.7	400	250
SDVL2016SD480PTHS301	48	34.1	60.0 [54.0-67.0]	110	5.0	0.7	300	200
SDVL2016SD560PTHS301	56	40.0	68.0 [61.0-75.0]	125	5.0	0.7	300	200
SDVL2016SD600PTHS301	60	46.0	76.0 [69.0-83.0]	130	5.0	0.7	300	200
SDVL2016SD650PTHS301	65	50.0	82.0 [73.0-91.0]	135	5.0	0.7	300	200
SDVL2016SD850PTHS201	85	60.0	100.0 [90.0-110.0]	165	5.0	0.7	200	120
SDVL2016SD101PTHS201	100	75.0	120.0 [108.0-132.0]	200	5.0	0.7	200	120
SDVL2016SD121PTHS700	125	95.0	150.0 [135.0-165.0]	260	5.0	0.3	70	45
SDVL2016SD121PTHS151	125	95.0	150.0 [135.0-165.0]	260	5.0	0.5	150	100
SDVL2016SD151PTHS101	150	115	180.0 [162.0-198.0]	325	5.0	0.5	100	70

规格特性
Specifications

SDVL3216-HS TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		
测试条件 Test Condition	<40μA		@1mA DC	8/20μs		Energy 10/1000μs	Peak Current 8/20μs	Nominal Current 8/20μs
	DC	AC RMS						
单位 Units	Volts	Volts	Volts	Volts	Amps	Joules	Amps	Amps
符号 Symbol	V _{WDC}	V _{WRMS}	V _B	V _C	I _C	E _T	I _P	I _N
SDVL3216SD090PTHS501	9	6.4	14.0 [12.0-16.0]	30	5.0	0.5	500	300
SDVL3216SD140PTHS151	14	10	19.0 [16.0-22.0]	40	5.0	0.2	150	100
SDVL3216SD140PTHS251	14	10	19.0 [16.0-22.0]	40	5.0	0.3	250	150
SDVL3216SD180PTHS251	18	12.7	25.0 [22.0-28.0]	45	5.0	0.3	250	150
SDVL3216SD180PTHS501	18	12.7	25.0 [22.0-28.0]	45	5.0	0.5	500	300
SDVL3216SD300PTHS201	30	21.3	42.0 [37.0-46.0]	70	5.0	0.4	200	120
SDVL3216SD300PTHS501	30	21.3	42.0 [37.0-46.0]	70	5.0	0.8	500	300
SDVL3216SD380PTHS201	38	30.0	50.0 [46.0-54.0]	80	5.0	0.4	200	120
SDVL3216SD380PTHS501	38	30.0	50.0 [46.0-54.0]	80	5.0	1.0	500	300
SDVL3216SD420PTHS151	42	32.0	53.0 [48.0-58.0]	100	5.0	0.4	150	100
SDVL3216SD420PTHS181	42	32.0	53.0 [48.0-58.0]	100	5.0	0.4	180	120
SDVL3216SD480PTHS151	48	34.1	60.0 [54.0-67.0]	110	5.0	0.4	150	100
SDVL3216SD480PTHS501	48	34.1	60.0 [54.0-67.0]	110	5.0	1.2	500	300
SDVL3216SD560PTHS101	56	40.0	68.0 [61.0-75.0]	125	5.0	0.4	100	70
SDVL3216SD560PTHS151	56	40.0	68.0 [61.0-75.0]	125	5.0	0.4	150	100
SDVL3216SD560PTHS181	56	40.0	68.0 [61.0-75.0]	125	5.0	1	180	120
SDVL3216SD560PTHS501	56	40.0	68.0 [61.0-75.0]	125	5.0	1.2	500	300
SDVL3216SD600PTHS151	60	46.0	76.0 [69.0-83.0]	130	5.0	0.4	150	100
SDVL3216SD600PTHS501	60	46.0	76.0 [69.0-83.0]	130	5.0	1.2	500	300
SDVL3216SD650PTHS151	65	50.0	82.0 [73.0-91.0]	135	5.0	0.6	150	100
SDVL3216SD650PTHS181	65	50.0	82.0 [73.0-91.0]	135	5.0	0.6	180	120
SDVL3216SD650PTHS201	65	50.0	82.0 [73.0-91.0]	135	5.0	0.6	200	140
SDVL3216SD650PTHS501	65	50.0	82.0 [73.0-91.0]	135	5.0	1.2	500	300
SDVL3216SD850PTHS151	85	60.0	100.0 [90.0-110.0]	165	5.0	0.6	150	100
SDVL3216SD850PTHS401	85	60.0	100.0 [90.0-110.0]	165	5.0	1.2	400	250
SDVL3216SD101PTHS151	100	75.0	120.0 [108.0-132.0]	200	5.0	0.6	150	100
SDVL3216SD101PTHS401	100	75.0	120.0 [108.0-132.0]	200	5.0	1.2	400	250

SDVL3225-HS TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		
测试条件 Test Condition	<40μA		@1mA DC	8/20μs		Energy 10/1000 μ s	Peak Current 8/20μs	Nominal Current 8/20μs
	DC	AC RMS						
单位 Units	Volts	Volts	Volts	Volts	Amps	Joules	Amps	Amps
符号 Symbol	V _{WDC}	V _{WRMS}	V _B	V _C	I _C	E _T	I _P	I _N
SDVL3225SD090PTHS401	9	6.4	14.0 [12.0-16.0]	30	5.0	0.5	400	250
SDVL3225SD180PTHS401	18	12.7	25.0 [22.0-28.0]	45	5.0	0.5	400	250
SDVL3225SD180PTHS102	18	12.7	25.0 [22.0-28.0]	45	5.0	1.5	1000	700
SDVL3225SD220PTHS401	22	15.6	30.0 [26.0-34.0]	50	5.0	0.5	400	250
SDVL3225SD300PTHS301	30	21.3	42.0 [37.0-46.0]	70	5.0	0.5	300	200
SDVL3225SD300PTHS401	30	21.3	42.0 [37.0-46.0]	70	5.0	0.5	400	250
SDVL3225SD300PTHS102	30	21.3	42.0 [37.0-46.0]	70	5.0	2.0	1000	700
SDVL3225SD380PTHS301	38	30.0	50.0 [46.0-54.0]	80	5.0	0.8	300	200
SDVL3225SD380PTHS401	38	30.0	50.0 [46.0-54.0]	80	5.0	0.8	400	250
SDVL3225SD380PTHS102	38	30.0	50.0 [46.0-54.0]	80	5.0	2.5	1000	700
SDVL3225SD420PTHS301	42	32.0	53.0 [48.0-58.0]	100	5.0	0.8	300	200
SDVL3225SD480PTHS301	48	34.1	60.0 [54.0-67.0]	110	5.0	0.8	300	200

规格特性 Specifications

SDVL3225-HS TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐受量 Rated Single Pulse Transient		
测试条件 Test Condition	<40μA		@1mA DC	8/20μs		Energy 10/1000 μs	Peak Current 8/20μs	Nominal Current 8/20μs
	DC	AC RMS						
单位 Units	Volts	Volts	Volts	Volts	Amps	Joules	Amps	Amps
符号 Symbol	V _{WDC}	V _{WRMS}	V _B	V _C	I _C	E _T	I _P	I _N
SDVL3225SD480PTHS102	48	34.1	60.0 [54.0-67.0]	110	5.0	3.0	1000	700
SDVL3225SD560PTHS151	56	40.0	68.0 [61.0-75.0]	125	5.0	0.5	150	100
SDVL3225SD560PTHS301	56	40.0	68.0 [61.0-75.0]	125	5.0	1.0	300	200
SDVL3225SD560PTHS122	56	40.0	68.0 [61.0-75.0]	125	5.0	4.0	1200	800
SDVL3225SD600PTHS301	60	46.0	76.0 [69.0-83.0]	130	5.0	1.0	300	200
SDVL3225SD600PTHS801	60	46.0	76.0 [69.0-83.0]	130	5.0	4.0	800	500
SDVL3225SD600PTHS122	60	46.0	76.0 [69.0-83.0]	130	5.0	4.0	1200	800
SDVL3225SD650PTHS201	65	50.0	82.0 [73.0-91.0]	135	5.0	1.4	200	120
SDVL3225SD650PTHS301	65	50.0	82.0 [73.0-91.0]	135	5.0	1.6	300	200
SDVL3225SD650PTHS601	65	50.0	82.0 [73.0-91.0]	135	5.0	2.0	600	400
SDVL3225SD650PTHS801	65	50.0	82.0 [73.0-91.0]	135	5.0	2.0	800	500
SDVL3225SD650PTHS102	65	50.0	82.0 [73.0-91.0]	135	5.0	4.0	1000	700
SDVL3225SD650PTHS122	65	50.0	82.0 [73.0-91.0]	135	5.0	4.0	1200	800
SDVL3225SD850PTHS201	85	60.0	100.0 [90.0-110.0]	165	5.0	0.7	200	140
SDVL3225SD850PTHS401	85	60.0	100.0 [90.0-110.0]	165	5.0	1.6	400	250
SDVL3225SD850PTHS152	85	60.0	100.0 [90.0-110.0]	165	5.0	4.0	1500	1000
SDVL3225SD101PTHS201	100	75.0	120.0 [108.0-132.0]	200	5.0	1.0	200	140
SDVL3225SD101PTHS102	100	75.0	120.0 [108.0-132.0]	200	5.0	5.0	1000	700

SDVL4532-HS TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐受量 Rated Single Pulse Transient		
测试条件 Test Condition	<40μA		@1mA DC	8/20μs		Energy 10/1000μs	Peak Current 8/20μs	Nominal Current 8/20μs
	DC	AC RMS						
单位 Units	Volts	Volts	Volts	Volts	Amps	Joules	Amps	Amps
符号 Symbol	V _{WDC}	V _{WRMS}	V _B	V _C	I _C	E _T	I _P	I _N
SDVL4532SD090PTHS801	9	6.4	14.0 [12.0-16.0]	30	5.0	0.5	800	500
SDVL4532SD180PTHS801	18	12.7	25.0 [22.0-28.0]	45	5.0	0.5	800	500
SDVL4532SD180PTHS202	18	12.7	25.0 [22.0-28.0]	45	5.0	1.3	2000	1200
SDVL4532SD260PTHS142	26	18.4	35.0 [31.0-38.0]	60	5.0	1.0	1400	1000
SDVL4532SD300PTHS801	30	21.3	42.0 [37.0-46.0]	70	5.0	0.7	800	500
SDVL4532SD300PTHS152	30	21.3	42.0 [37.0-46.0]	70	5.0	1.0	1500	1000
SDVL4532SD300PTHS202	30	21.3	42.0 [37.0-46.0]	70	5.0	2.0	2000	1200
SDVL4532SD380PTHS801	38	30.0	50.0 [46.0-54.0]	80	5.0	1.0	800	500
SDVL4532SD380PTHS202	38	30.0	50.0 [46.0-54.0]	80	5.0	2.5	2000	1200
SDVL4532SD420PTHS601	42	32.0	53.0 [48.0-58.0]	100	5.0	1.0	600	400
SDVL4532SD480PTHS601	48	34.1	60.0 [54.0-67.0]	110	5.0	1.1	600	400
SDVL4532SD480PTHS202	48	34.1	60.0 [54.0-67.0]	110	5.0	3.0	2000	1200
SDVL4532SD560PTHS601	56	40.0	68.0 [61.0-75.0]	125	5.0	1.1	600	400
SDVL4532SD560PTHS202	56	40.0	68.0 [61.0-75.0]	125	5.0	3.5	2000	1200
SDVL4532SD600PTHS601	60	46.0	76.0 [69.0-83.0]	130	5.0	1.1	600	400
SDVL4532SD600PTHS202	60	46.0	76.0 [69.0-83.0]	130	5.0	3.0	2000	1200
SDVL4532SD650PTHS601	65	50.0	82.0 [73.0-91.0]	135	5.0	1.5	600	400
SDVL4532SD650PTHS202	65	50.0	82.0 [73.0-91.0]	135	5.0	5.0	2000	1200
SDVL4532SD650PTHS302	65	50.0	82.0 [73.0-91.0]	135	5.0	7.5	3000	1800
SDVL4532SD750PTHS501	75	55.0	94.0 [85.0-103.0]	160	5.0	2.0	500	300
SDVL4532SD850PTHS501	85	60.0	100.0 [90.0-110.0]	165	5.0	2.0	500	300
SDVL4532SD850PTHS152	85	60.0	100.0 [90.0-110.0]	165	5.0	7.0	1500	1000

规格特性
Specifications

SDVL4532-HS TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		
测试条件 Test Condition	<40μA		@1mA DC	8/20μs		Energy 10/1000μs	Peak Current 8/20μs	Nominal Current 8/20μs
	DC	AC RMS						
单位 Units	Volts	Volts	Volts	Volts	Amps	Joules	Amps	Amps
符号 Symbol	V _{WDC}	V _{WAC}	V _B	V _C	I _C	E _T	I _P	I _N
SDVL4532SD101PTHS501	100	75.0	120.0 [108.0-132.0]	200	5.0	2.0	500	300
SDVL4532SD101PTHS152	100	75.0	120.0 [108.0-132.0]	200	5.0	7.0	1500	1000
SDVL4532SD121PTHS801	125	95.0	150.0 [135.0-165.0]	260	5.0	0.5	800	500
SDVL4532SD151PTHS501	150	115	180.0 [162.0-198.0]	325	5.0	0.5	500	300

SDVL5650-HS TYPE

型号 Part Number	最大工作电压 Max. Working Voltage		压敏电压 Varistor Voltage	限制电压 Max. Clamping Voltage		额定脉冲耐量 Rated Single Pulse Transient		
测试条件 Test Condition	<40μA		@1mA DC	8/20μs		Energy 10/1000μs	Peak Current 8/20μs	Nominal Current 8/20μs
	DC	AC RMS						
单位 Units	Volts	Volts	Volts	Volts	Amps	Joules	Amps	Amps
符号 Symbol	V _{WDC}	V _{WAC}	V _B	V _C	I _C	E _T	I _P	I _N
SDVL5650SD090PTHS122	9	6.4	14.0 [12.0-16.0]	30	10.0	1.5	1200	800
SDVL5650SD180PTHS122	18	12.7	25.0 [22.0-28.0]	45	10.0	1.5	1200	800
SDVL5650SD180PTHS302	18	12.7	25.0 [22.0-28.0]	45	10.0	4.0	3000	2000
SDVL5650SD300PTHS122	30	21.3	42.0 [37.0-46.0]	70	10.0	2.6	1200	800
SDVL5650SD300PTHS302	30	21.3	42.0 [37.0-46.0]	70	10.0	7.0	3000	2000
SDVL5650SD330PTHS122	33	23.4	44.0 [39.0-49.0]	75	10.0	2.6	1200	800
SDVL5650SD380PTHS122	38	30.0	50.0 [46.0-54.0]	80	10.0	2.6	1200	800
SDVL5650SD380PTHS302	38	30.0	50.0 [46.0-54.0]	80	10.0	8.0	3000	2000
SDVL5650SD380PTHS502	38	30.0	50.0 [46.0-54.0]	80	10.0	10.0	5000	3000
SDVL5650SD480PTHS901	48	34.1	60.0 [54.0-67.0]	110	10.0	3.0	900	600
SDVL5650SD480PTHS102	48	34.1	60.0 [54.0-67.0]	110	10.0	3.0	1000	700
SDVL5650SD480PTHS302	48	34.1	60.0 [54.0-67.0]	110	10.0	10.0	3000	2000
SDVL5650SD560PTHS901	56	40.0	68.0 [61.0-75.0]	125	10.0	3.0	900	600
SDVL5650SD560PTHS502	56	40.0	68.0 [61.0-75.0]	125	10.0	17.0	5000	3000
SDVL5650SD600PTHS901	60	46.0	76.0 [69.0-83.0]	130	10.0	2.7	900	600
SDVL5650SD600PTHS502	60	46.0	76.0 [69.0-83.0]	130	10.0	15.0	5000	3000
SDVL5650SD650PTHS801	65	50.0	82.0 [73.0-91.0]	135	10.0	3.0	800	500
SDVL5650SD650PTHS901	65	50.0	82.0 [73.0-91.0]	135	10.0	3.0	900	600
SDVL5650SD650PTHS152	65	50.0	82.0 [73.0-91.0]	135	10.0	5.0	1500	1000
SDVL5650SD650PTHS202	65	50.0	82.0 [73.0-91.0]	135	10.0	7.5	2000	1200
SDVL5650SD650PTHS302	65	50.0	82.0 [73.0-91.0]	135	10.0	10.0	3000	2000
SDVL5650SD650PTHS502	65	50.0	82.0 [73.0-91.0]	135	10.0	18.0	5000	3000
SDVL5650SD850PTHS801	85	60.0	100.0 [90.0-110.0]	165	10.0	4.0	800	500
SDVL5650SD850PTHS252	85	60.0	100.0 [90.0-110.0]	165	10.0	10.0	2500	1500
SDVL5650SD850PTHS452	85	60.0	100.0 [90.0-110.0]	165	10.0	21.0	4500	3000
SDVL5650SD101PTHS801	100	75.0	120.0 [108.0-132.0]	200	10.0	4.0	800	500
SDVL5650SD101PTHS302	100	75.0	120.0 [108.0-132.0]	200	10.0	10.0	3000	2000
SDVL5650SD101PTHS402	100	75.0	120.0 [108.0-132.0]	200	10.0	21.0	4000	2500
SDVL5650SD121PTHS202	125	95.0	150.0 [135.0-165.0]	260	5.0	12.0	2000	1200
SDVL5650SD151PTHS152	150	115	180.0 [162.0-198.0]	325	5.0	12.0	1500	1000

※V_{WDC} : 压敏电阻的最大直流工作电压必须超过或等于应用电路电压的 1.2 倍, V_{WDC}≥1.2V_{no}
※V_{WDC} : Max DC working voltage of varistor must exceed or equal to 1.2 times that of the application circuit voltage, V_{WDC}≥1.2V_{no}
※I_P : 压敏电阻 8/20us 额定单脉冲电流必须大于或等于应用电路脉冲电流的 1.2 倍, I_P≥1.2 I_{Pno}
※I_P : Rated single pulse current at 8/20us of Varistor must exceed or equal to 1.2 times that of the application circuit pulse current, I_P≥1.2 I_{Pno}
※ 可根据客户需求提供其他电气特性产品, 请联系您当地的销售人员。
※ Products with other electrical characteristics can be provided upon customer's request. Please contact your local sales.