

SOT-89 Plastic-Encapsulate Transistors


Features

- Complementary to 2SA1213
- Power dissipation of 500mW
- High stability and high reliability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260°C


Mechanical Data

- Case: SOT-89
Molding compound meets UL 94V-0 flammability rating, RoHS-compliant,halogen-free
- Terminals: Solder plated, solderable per MIL-STD-750,Method 2026

Function Diagram



Collector-Base Voltage
VCBO 50V
Collector Current
2.0 Ampere



Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	VALUE
Collector-Base Voltage	V _{CBO}	V	50
Collector-Emitter Voltage	V _{CEO}		50
Emitter-Base Voltage	V _{EBO}		5.0
Collector Current	I _C	A	2.0
Collector Power Dissipation	P _C	mW	500
Storage temperature	T _{stg}	°C	-55 ~+150
Junction temperature	T _j	°C	-55 ~+150
Typical Thermal Resistance	R _{θJA}	°C /W	250

Electrical Characteristics (Ta=25°C Unless otherwise noted)

PARAMETER	SYMBOL	UNIT	Condition	Min	Max
Collector-Base Breakdown Voltage	V _{(BR)CBO}	V	I _C =100μA, I _E =0	50	—
Collector-Emitter Breakdown Voltage	V _{(BR)CEO}		I _C =1mA, I _B =0	50	—
Emitter-Base Breakdown Voltage	V _{(BR)EBO}		I _E =100μA, I _C =0	5.0	—
Collector-Base cut-off current	I _{CBO}	nA	V _{CB} =50V, I _E =0	—	100
Emitter-Base cut-off current	I _{EBO}		V _{EB} =5.0V, I _C =0	—	100
DC Current Gain	h _{FE(1)}	—	I _C =500mA V _{CE} =2.0V	70	240
	h _{FE(2)}		I _C =2A V _{CE} =2.0V	20	—
Collector-Emitter Saturation Voltage	V _{CE(sat)}	V	I _C =1A I _B =50mA	—	0.5
Base-Emitter Saturation Voltage	V _{BE(sat)}	V	I _C =1A I _B =50mA	—	1.2

● Classification Of h_{FE}

RANK	2SC2873-O	2SC2873-Y
Range	70-140	120-240





● Small-signal Characteristics

ITEM	SYMBOL	Condition	UNIT	Min	Typ	Max
Transition frequency	f_T	$I_C=500\text{mA}$, $V_{CE}=2\text{V}$	MHz	—	120	—

● Ordering Information

PACKAGE	PACKAGE CODE	UNIT WEIGHT(g)	REEL(pcs)	BOX(pcs)	CARTON(pcs)	DELIVERY MODE
SOT-89	R1	0.055	1000	7000	21000	7"

● Ratings And Characteristics Curves (Ta=25°C Unless otherwise specified)



● Ratings And Characteristics Curves (Ta=25°C Unless otherwise specified)




Fig.5 Base-Emitter On Voltage






Fig.6 Cob/Cib- V_{cb}

● Package Outline Dimensions (SOT-89)



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.4	4.6	0.176	0.184
B	1.6	1.8	0.064	0.072
C	3.9	4.1	0.156	0.164
D	2.4	2.6	0.096	0.104
E	2.9	3.1	0.116	0.124
a	0.41	0.43	0.0164	0.018
b	0.35	0.45	0.014	0.018
L	0.95	1.05	0.037	0.041
G	0.3	0.5	0.012	0.020
H	1.4	1.5	0.055	0.059

● Suggested Pad Layout



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
c	0.80	1.00	0.032	0.04
d	1.30	1.50	0.052	0.060
e	0.70	0.90	0.028	0.036
J	1.80	2.00	0.072	0.080
K	1.40	1.60	0.056	0.064
X	2.50	2.70	0.100	0.108
X1	1.30	1.50	0.052	0.060
Y	4.30	4.50	0.172	0.180
Y1	3.10	3.30	0.124	0.132
θ	-	45°	-	45°