

## 1.Description

The PTVSHC3D7VU protects sensitive semiconductor components from damage or upset due to electrostatic discharge (ESD) and other voltage induced transient events.

The PTVSHC3D7VU is available in a SOD-323 package with working voltages of 7 volt.

## 3.Features

- 1100W Peak pulse power per line ( $t_p=8/20\mu s$ )
- Response time is typically  $< 1ns$
- Protect one I/O or power line
- Low clamping Voltage
- Transient protection for data lines to IEC 61000-4-2(ESD)
- $\pm 30KV$ (air),  $\pm 30KV$ (contact); IEC 61000-4-4 (EFT) 40A (5/50ns)


## 2.Mechanical Characteristics

- Lead finish: 100% matte Sn(Tin)
- Mounting position: Any
- Qualified max reflow temperature:  $260^{\circ}C$
- Pure tin plating:  $7 \sim 17 \mu m$
- Pin flatness:  $\leq 3mi$

## 4.Applications


- Cell phone handsets and accessories
- Personal digital assistants (PDA's)
- Notebooks, desktops, and servers
- Portable instrumentation
- Cordless phones
- Digital cameras
- Peripherals
- MP3 players

## 5.Pinning information





6.Electrical Parameters (T<sub>A</sub>=25°C unless otherwise noted )



Symbol	Parameter
V <sub>RWM</sub>	Peak Reverse Working Voltage
I <sub>R</sub>	Reverse Leakage Current @ V <sub>RWM</sub>
V <sub>BR</sub>	Breakdown Voltage @ I <sub>T</sub>
I <sub>T</sub>	Test Current
I <sub>PP</sub>	Maximum Reverse Peak Pulse Current
V <sub>C</sub>	Clamping Voltage @ I <sub>PP</sub>
P <sub>PP</sub>	Peak Pulse Power
C <sub>J</sub>	Junction Capacitance
I <sub>F</sub>	Forward Current
V <sub>F</sub>	Forward Voltage @ I <sub>F</sub>



## 7. Electrical Characteristic ( $T_A=25^{\circ}\text{C}$ unless otherwise noted)


Parameter	Symbol	Conditions	Min	Typ	Max	Units
Working Voltage	$V_{RWM}$				7	V
Breakdown Voltage	$V_{BR}$	$I_T=1\text{mA}$		8	9.5	V
Reverse Leakage Current	$I_R$	$V_{RWM}=7\text{V}$			1	$\mu\text{A}$
Clamping Voltage	$V_C$	$I_{PP}=60\text{A}$ , $t_p=8/20\mu\text{s}$		18	25	V
Junction Capacitance	$C_J$	$V_R=0\text{V}$ , $f=1\text{MHz}$	470	500	550	pF

## 8. Absolute maximum rating @ $25^{\circ}\text{C}$

Parameter	Symbol	Value	Units
Peak Pulse Power ( $t_p=8/20\mu\text{s}$ )	$P_{PP}$	1100	W
Lead Soldering Temperature	$T_L$	260 (10 sec)	$^{\circ}\text{C}$
Junction Temperature	$T_J$	-55 to 125	$^{\circ}\text{C}$
Storage Temperature	$T_{STG}$	-55 to 150	$^{\circ}\text{C}$



9. Typical characteristic





## 10.Solder Reflow Recommendation





Figure 6: Peak Temp=257°C, Ramp Rate=0.802deg. °C/sec



11.SOD-323 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	b <sub>p</sub>	C	D	E	H <sub>E</sub>	A <sub>1</sub>	P
Min	0.90	0.25	0.10	1.60	1.15	2.30	0.01	0.20
Max	1.20	0.40	0.15	1.80	1.35	2.80	0.10	0.50



12.Ordering information



ww: Batch Code

Order Code	Package	Base QTY	Delivery Mode
UMW PTVSHC3D7VU	SOD-323	3000	Tape and reel



## **13.Disclaimer**

---

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.