

09 66 111 6503
D-Sub - S PCB connector

Other applications

gender	female connector, straight
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	9 way
Board fixing	without grounding board locks
flange	with screw lock UNC 4-40
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 111 5503
D-Sub - S PCB connector

Other applications

gender	female connector, straight
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	9 way
Board fixing	without grounding board locks
flange	with screw lock UNC 4-40
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.



Data sheets are available in following formats
2D files

Typenblatt

Typenblatt

09 66 111 7503
D-Sub - S PCB connector

Other applications

gender	female connector, straight
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	9 way
Board fixing	without grounding board locks
flange	with screw lock UNC 4-40
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF