

Board Level Products

Board to Board Interconnect Solutions

Amphenol



Connecting people + technology

www.pcb-interconnect.com

Table of Contents



About Amphenol	4
Quick Selection Guide.....	6
Amphenol Socapex Box Capabilities.....	7
HiLinx - The 100% modular and hybrid connector	
HiLinx product range.....	8
HiLinx 2.54	10
Female signal contacts for receptacles	12
Male signal contacts for plugs	14
Special contacts for hybrid connectors	16
Non keying guides	18
Keying guides / Connector polarization	19
Locking: fixed jacksets, hexagonal turning jacksets & slotted turning jacksets	20
Realignment capability / Mating sequence	22
Signal version: compatibility with the MIL-DTL-55302	23
Signal version: typical arrangements 2 rows	24
Signal version: layouts 2 rows	25
Signal version: typical arrangements 3 rows	26
Signal version: layouts 3 rows	27
Hybrid version: typical arrangements 2 rows	28
Hybrid version: layouts 2 rows	29
Hybrid version: typical arrangements 3 rows	30
Hybrid version: layouts 3 rows	31
HiLinx 1.905	32
Female signal contacts for receptacles	34
Male signal contacts for plugs	36
Special contacts for 3-row hybrid connectors.....	38
Non keying guides	40
Keying guides / Connector polarization	41
Locking: fixed jacksets, hexagonal turning jacksets & slotted turning jacksets	42
Realignment capability / Mating sequence	44
Signal version: compatibility with the MIL-DTL-55302	45
Signal version: typical arrangements 2 & 3 rows	46
Signal version: layouts 2 & 3 rows	47
Hybrid version: dimensions	48
Hybrid version: layouts	49
Tooling	50
HDAS - The high density monolithic connector	
HDAS product range.....	52
Female signal contacts for receptacles	56
Male signal contacts for plugs.....	57
Female & Male fittings	58
Realignment capability / Mating sequence	59
Typical arrangements 3 & 4 rows	60
Layouts 3 & 4 rows.....	61
Typical arrangement 5 rows.....	62
Layout 5 rows	63
Tooling.....	64
SMASH - The high density interconnect system for harsh environment applications	
SMASH product range	66
Standard technology of contacts.....	70
Special technology of contacts.....	71
Standard housings and shells	72

Table of Contents



Special housings and shells/ Mating sequence	73
Typical arrangements & layouts 150 signal contacts	74
Typical arrangements & layouts 300 signal contacts	75
Typical arrangements & layouts 450 signal contacts	76
Typical arrangements & layouts 396 signal contacts	77

SIAL - The hybrid connector for use with thermal clamps

SIAL product range	80
Signal contacts	84
Special contacts	86
Signal modules	88
Hybrid modules	88
Fittings and guiding	89
Keying	89
Realignment capability	89
Mating sequence	89
SIAL signal version typical arrangements	90
SIAL signal version layouts	92
SIAL coaxial version typical arrangements	93
SIAL coaxial version layouts	94
Tooling	96

SIHD - The monolithic connector for use with thermal clamps

SIHD product range	98
Female signal contacts for plugs	102
Male signal contacts for receptacles	103
Ground strips	103
Guiding / Keying	104
Mating sequence	104
Realignment capability	104
Fixing accessories	105
SIHD without ground strip typical arrangements	106
SIHD with ground strip typical arrangements	107
SIHD without ground strip layouts	108
SIHD with ground strip layouts	109

127 Series - The proven, reliable, and robust connector

127/HE8 product range	110
Signal contacts	114
Special contacts	116
Female fittings for receptacles	118
Male fittings for plugs	122
Typical arrangement and layout, signal connectors (HE801 & HE804)	126
Typical arrangement and layout, hybrid connectors (HE807)	128
Fittings & contacts compatibility	131
Tooling	134

Other Amphenol Board Level Interconnect

Amphenol Aerospace Operations – HDB ³ / HSB ³ / LRM / VME64x interconnects	136
Amphenol Backplane Systems – VIPER - VITA46, VITA 48, VITA 60 footprint compatible interconnects	139
Amphenol Teradyne Connection Systems – The widest high speed interconnect solutions	140
Amphenol Printed Circuits – Rigid, flexible and rigid-flex printed circuit board capabilities	142

Amphenol in brief

Amphenol is one of the largest manufacturers of interconnect products in the world. The Company designs, manufactures and markets electrical, electronic and fiber optic connectors, coaxial and flat-ribbon cable, and interconnect systems.

The primary end markets for the Company's products are communications and information processing markets, including cable television, cellular telephone and data communication and information processing systems; aerospace and military electronics; and automotive, rail and other transportation and industrial applications.



Amphenol Socapex in brief

Amphenol Socapex is part of Amphenol Corporate. The company has subsidiaries in France, India, China, and in the United States. Amphenol Socapex is a market leader of MIL-DTL-38999 and derived products, high density board level connectors, field bus and rugged Ethernet solutions, harsh environment optical connectors, MIL-DTL-26482 Series I rugged industrial solutions and EN2997 connectors.

Amphenol Socapex is able to meet customer satisfaction through:

- Agile & Lean Organization
- Global Sourcing
- State-of-the-Art Manufacturing
- Custom design capability
- Competitive Independent Workshops

Amphenol Socapex is aware of environmental issues. Indeed, most of our product solutions are compliant with the European RoHS directive concerning electrical and electronic equipment.

Amphenol Socapex Markets

Military & Aerospace markets:

- Military and commercial avionics and airframe: engines, airframes, cockpit, landing gears...
- C4ISR Land: communication systems, radio...
- Ground vehicles
- Marine applications
- Weapons / Munitions
- Space: communications satellites




Industrial markets:

- Oil & Gas: geophysics, drilling, production
- Small Urban Electrical Vehicle
- Mining: surface and underground mining, ...
- Factory Automation: Machine tool, Networks, Field Buses,...
- Railway: Signaling, Ground and On Board Equipments,...
- Homeland security: CCTV (video), access control,...
- Entertainment



Quick Selection Guide

						
	HiLinX	HDAS	SMASH	SIAL	SIHD	HE8/127
MARKETS						
	INDUSTRIAL	X	X			X
	COMMERCIAL AVIONICS & AIRFRAME	X	X	X	X	X
	MILITARY AVIONICS & AIRFRAME	X	X	X	X	X
	GROUND VEHICLE		X			X
	C4ISR	X	X	X		X
	NAVY	X	X		X	
	SPACE				X	X
APPLICATIONS						
	RADAR			X	X	X
	ON BOARD COMPUTER		X		X	X
	DISPLAY UNITS	X	X			X
	ACTUATORS		X		X	X
	ENGINE	X	X	X		
	POWER UNITS	X	X			X
	LANDING GEAR / BRAKING SYSTEMS	X	X			X
	ORDNANCE	X		X		
GENERAL CHARACTERISTICS						
PLUG/RECEPTACLE GENDER	Male / Female	Male / Female	Male / Female	Male / Female	Male / Female	All possible
CONTACT TECHNOLOGY	Female Starclip / Male Turned	Female Starclip / Male Turned	Female Starclip / Male Turned	Female cross cavity / Male lateral displacement	Female cross cavity / Male lateral displacement	Female Tuning fork / Male Blade
PLUG CONTACT TERMINATION	90° & straight PC tail / Solder cup / Crimping tail	90° & straight PC tail / Solder cup	SMT straddle mount	90° & straight PC tail / SMT	90° & straight PC tail / SMT / Crimping tail	SMT / 90° & straight PC tail / Crimp / Solder cup
RECEPTACLE CONTACT TERMINATION	90° & Straight PC tail / Solder cup /Press fit / Crimping tail	90° & Straight PC tail / Press fit	Straight PC tail / Press fit	Straight PC tail	Straight PC tail / Wire wrap	SMT / 90° & straight PC tail / Crimp / Solder cup
MODULARITY	Yes	No	Yes	Yes	No	No
HF / POWER / OPTICAL OPTION	Coax Size16 / Power 20A / Radsok® / Amphenlux™	No	Coax Size16 / Power 20A / Radsok® / Amphenlux™	Coax Size 12 or 16	No	Coax Size16 / Power 20A
DENSITY	HiLinX ^{1,905} : 0.16cts / mm ² [103 cts / in ²] HiLinX ^{2,54} : 0.11 cts/ mm ² [71 cts / in ²]	0.16 cts / mm ² [103cts / inch ²]	0,34cts / mm ² [130cts / inch ²]	0.14 cts / mm ² [90 cts / inch ²]	0.14 cts / mm ² [90 cts / inch ²]	0,11 cts / mm ² [71cts / inch ²]
SIGNAL CONTACTS COUNT	0-206	50-402	132-450	18-392	102-390	17-144
LATERAL FLOATMENT FEATURE	Consult us	Consult us	Yes	Yes	Yes	No
SEE PAGE	8	52	66	80	98	110

Amphenol Socapex Box Capabilities

1

HiLinX Series (see page 8)

Unique M55302 modular interconnect. System of interlocking signal, power, fiber optics, and HF modules for dedicated board level mixed solution.

2

HDAS Series (see page 52)

Monolithic high density PCB interconnect. Provides higher current rate capability, and extreme withstanding to harsh environments, such as very high temperature and vibrations level.

3

SMASH Series (see page 66)

High density rack and panel for rectangular in and out solutions. Possibilities of hybrid inserts, EMI shielding, as well as sealing and rear potting.

4

SMASH Derivated (see page 66)

High density rack and panel for rectangular in and out solutions. Possibilities of hybrid inserts, EMI shielding, as well as sealing and rear potting.

5

SIAL Series (see page 80)

Modular PCB interconnect, which provides various combinations of both signal and HF contacts inserts.

6


SIHD Series (see page 98)

Monolithic staggered grid connector, with floating capability feature.

7

127 / HE8 Series (see page 110)

Proven legacy product, which meets various worldwide standard. Various features, including a wide range of hardware and locking devices.



8

I/O Cylindrical connectors (consult us)

Amphenol Socapex provides cylindrical I/O front panel connectors per various standards, including MIL DTL 38999, Series I, II, and III, HE308, EN3645, VG96912 / EN2997 / MIL DTL 26482 Series I, VG95328. Numerous platings and arrangements available, in addition to unique custom design capabilities (snatch release, rack and panel, high density, PC tail stand-offs, HF contacts, hybrid optical / electrical solutions ...).

9

RJ Field (consult us)

Transforms all standard existing RJ45 Cat5e cordset into an environmental connector, without any cabling operation, and without any tool. Other infocom connectors such as USB, USBB, RJ11, RJ12, IEEE1394, MTRJ, LC, can also be rugged with the same concept.

10

Thermal Clamps (consult us)

Chassis devices, which both help to dissipate components heating and block the daughter cards into the box slots grooves.

11

Printed Circuit Boards for backplanes & daughter cards (see pages 142 & 143)

Fabrication capabilities include a wide variety of materials to enable increasing signal speeds, deep microvias, buried, blind and backdrilled vias, sequential lamination, panel sizes from 18" x 24" up to 24" x 54", and layer counts up to 60 with a board thickness of 0.400".

13

Rigid and rigid-flex PCBs (see pages 142 & 143)

Rigid-Flex circuit interconnects featuring blind and buried vias, microvias, bookbinder and other cutting-edge technologies including large format panels.

HiLinX

Create the connector you need

Amphenol has engineered a complete range of high & medium density, staggered grid, modular connectors with both 1.905x1.905[.075x.075] & 2.54x2.54 [.100x.100] pitches.

The HiLinX range provides a unique choice of solutions by allowing a mix of various contact types: signal, power, fiber optics and coaxial lines.

The concept


With our HiLinX, build your own connector the way you want it! The HiLinX is a system of modules, metal rails and fittings. Thanks to this modularity, a wide range of contact combinations can be made at the board level. Whatever types of signals required, from power to fiber optics, almost all existing contacts on the market can be adapted to our connector.

Let's maximize the PC board capabilities!

Modularity for custom connector design!

With the HiLinX series, you specify:

- The density of signal contacts
- The type and number of signal contacts
- The type, the number and the position of special contacts
- The guiding, keying or locking system



With the HiLinX series, the design of the connector is up to you!

With HiLinX, feel free to create your own product. Amphenol remains the only provider of both assembly and delivery.

MIL-DTL-55302
/190 to /193

MIL-DTL-55302
/57 to /66, /138, /139

Some HiLinX arrangements are fully compatible with the MIL DTL 55302
(/57 to /66, /138, /139 & /190 to /193 detailed sheets) (see pages 23 & 45).

QUICK SELECTION GUIDE

Density	Signal contacts ①	Special contacts* ②	Guiding, keying & locking ③	Housing ④	See Section
Medium density: HiLinX 2.54	FEMALE MALE <small>For solder cup, SMT, soldering on flex, female right angle PC tail, male straight PC tail, consult us.</small>	POWER 20A AMPHELUX™ RADSOK® 70A* COAXIAL <small>*For RADSOK® contact, consult us.</small>	GUIDING 8 possibilities 65 to 72 KEYING 128 possibilities 01 to 64 & 201 to 264 LOCKING jackscrew, jackset & jacksocket available	2 ROWS 0 to 70* contacts with or without special contacts 3 ROWS 0 to 170* contacts with or without special contacts	HiLinX 2.54 pages 10 to 31
High density: HiLinX 1.905	FEMALE MALE <small>For solder cup, SMT, soldering on flex, female right angle PC tail, male straight PC tail, consult us.</small>	POWER 20A AMPHELUX™ RADSOK® 70A COAXIAL 	GUIDING 8 possibilities 65 to 72 KEYING 64 possibilities 01 to 64 LOCKING jackscrew, jackset & jacksocket available	2 ROWS 10 to 100 contacts 3 ROWS 0 to 206 contacts with or without special contacts	HiLinX 1.905 pages 32 to 49

*Important note: HiLinX 1.905: special contacts are available for 3-row version only.

HiLinX Series

The 100% modular and hybrid connector



Table of contents

HiLinX product range	8
HiLinX 2.54	10
Female signal contacts for receptacles	12
Male signal contacts for plugs.....	14
Special contacts for hybrid connectors	16
Non keying guides	18
Keying guides / Connector polarization	19
Locking: fixed jacksets, hexagonal turning jacksets, slotted turning jacksets.....	20
Realignment capability / Mating sequence	22
Signal version: compatibility with MIL-DTL-55302..	23
Signal version: typical arrangements 2 rows	24
Signal version: layouts 2 rows	25
Signal version: typical arrangements 3 rows.....	26
Signal version: layouts 3 rows	27
Hybrid version: typical arrangements 2 rows	28
Hybrid version: layouts 2 rows	29
Hybrid version: typical arrangements 3 rows	30
Hybrid version: layouts 3 rows	31
HiLinX 1.905	32
Female signal contacts for receptacles	34
Male signal contacts for plugs.....	36
Special contacts for 3-row hybrid connectors.....	38
Non keying guides.....	40
Keying guides / Connector polarization	41
Locking: fixed jacksets, hexagonal turning jacksets, slotted turning jacksets.....	42
Realignment capability / Mating sequence	44
Signal version: compatibility with MIL-DTL-55302..	45
Signal version: typical arrangements 2 & 3 rows ..	46
Signal version: layouts 2 & 3 rows	47
Hybrid version: dimensions	48
Hybrid version: layouts	49
Tooling	50

The HiLinX series serves various **markets**, including:




Commercial Avionics
& Airframe



Military Avionics & Airframe



C4ISR



Navy



Industrial

HILINX 2.54 >>> GENERAL SPECIFICATIONS



- A unique connector, both hybrid and modular
- Cost effective, easy to install, highly reliable
- More current through each contact
- Greater performance and optimal protection in harsh environments
- Compatible with signal connectors on the market (MIL-DTL-55302/57 to /66, /138, /139)
- 2.54 [.100] staggered grid (1.27 [.050] offset), 2.54 [.100] between rows

Main characteristics

- Medium density: 0.11 cts/mm² [71 cts/inch²]
- From 2 to 3 rows, 10 to 170* signal contacts
- 5 A per signal contact (up to 6A current rating available upon request)
- Press-fit solderless attachment technology and crimp contact available
- Some signal contact versions are 100% compatible with the M55302 /57 to /66, /138 & /139


Markets



Main applications




Terminations



Special contacts




Recommended configurations



Standard

MIL-DTL-55302
/57 to /66, /138, /139

How to order



Number of signal contacts (see pages 24 to 31)

	Signal version						Hybrid version	
2 rows	010	024	040	056			To be defined Divided by 10	
	014	030	044	060				
3 rows	016	034	046	064			To be defined Divided by 12 or 18	
	020	036	050	066				
	006*	032*	062*	092*	122*	152*		
	008*	036*	066*	096*	126*	156*		
	012*	042*	072*	102*	132*	158*		
	014	044	074	104	134	164*		
	018*	048*	078*	108*	138*	162*		
	020*	050	080	110	140	168*		
	024*	054*	084*	114*	144*	170		
	026	056	086	116*	146			
	030*	060*	090*	120*	150*			

Special module (see page 16)

	Male	Female
POWER 20A*	PM1	PF1
RADSOK 70A	<i>Consult us</i>	
COAXIAL*	CM1	CF1
AMPHELUX™ *	AXM	AXF

* 2 contacts or cavities per module
Number of special modules (X) + type of the module (XXX)
X XXX (blank = signal contacts only)
Ex: 2PM1 3CM1
2 male power modules and 3 male coaxial modules

Keying, guiding, locking (see pages 18 to 22)

D-shape guides ?	YES	01 to 64 201* to 264* according to MIL DTL 55302
Round guides ?	YES	65 to 68 69* to 72*
Locking ?	YES	73* to 96* 101* to 124*

01 by default

Deviation

Standard?	YES	-000
	NO - Consult us	
		-100* w/o mounting ears
		-200* with middle fitting
		-400* with middle fitting w/o mounting ears
		-800* monolithic version w/o mounting ears
		-900* monolithic version

-000 by default


Important note

RADSOK®, coaxial and Amphilux™ contacts have to be ordered separately


* available upon request

HILINX 2.54 >> TECHNICAL SPECIFICATIONS

Dimensional characteristics



$H = 8.5 [.335]$ for receptacles
 $H = 10.2_{MAX} [.401]$ for plugs
 $I = 6.4_{MAX} [.252]$ for 2-row connectors
 $I = 8.95_{MAX} [.352]$ for 3-row connectors
 $L = 34.29 [1.350]$ to $110.49 [4.350]$ for 2-row connectors
 $L = 63.5 [2.500]$ to $165.1 [6.500]$ for 3-row connectors
 $B = 7 + X [.276 + X]$ for 2-row connectors
 $B = 9.55 + X [.376 + X]$ for 3-row connectors
 $X = \text{Board thickness} + \text{hardware thickness}$
 $d = 17 [.670]$
 $e = 1.8 [.071]$ to $3.4 [.134]$ or $2.5_{MIN} [.098]$ (for YP contacts)



Female contact



Starclip* female technology: 6 times for better reliability

- 6 contact tines instead of 4
- Excellent mechanical and electrical reliability
- Better resistance to high vibrations
- Improved electrical conductivity
- 100% compatible with other connectors


Material

- Hood: machined brass alloy
- Starclip: CuBe [BeCu], stamped and formed

Plating

- Hood: tin lead or lead free
- Starclip: gold over nickel

Male contact



- **Mating end diameter:** Ø 0.76 [.030]
- **Contact section** (mating side): $0.45 \text{ mm}^2 [.0007 \text{ in}^2]$
- **Material:** machined brass alloy
- **Plating:** gold over nickel

Materials

- **Guiding devices:** electroless nickel plating over brass CuZn or passivated stainless steel 303
- **Rails:** passivated stainless steel 316L
- **Plastic insert:** thermoplastic LCP, 30% glass-fiber filled

MECHANICAL CHARACTERISTICS

Backoff¹ (mm)	> 0.9 [.035]***	N/A
Mating force per contact (N)	0.98_{MAX}	§ 4.5.3
Unmating force per contact (N)	0.981_{MAX}	§ 4.5.3
Durability cycles	500	§ 4.5.9
Sinusoidal vibrations (10 to 2000 Hz) micro discontinuity 2ns	15 g	§ 4.5.10
Random vibrations (5 to 2000 Hz) micro discontinuity 2ns	$0.5 \text{ g}^2 / \text{Hz}$	§ 4.5.10
Shocks 6ms ½ sinus 2ns	100 g	§ 4.5.10

¹: When both connectors are fully mated, the backoff is the maximum distance the connectors can be unmated while functioning properly

ENVIRONMENTAL CHARACTERISTICS

Thermal shocks (°C)	-65 / +150	§ 4.5.13
Salt Spray (hours)	96	§ 4.5.11

Humidity

Days	10	
Temperature (°C)	25/65	§ 4.5.15
Humidity rate (%)	90-95	

ELECTRICAL CHARACTERISTICS

Current rating per contacts (A)	5**	§ 4.5.5
Insulation resistance (at 500Vdc) (GΩ)	5_{MIN}	§ 4.5.8
Contact resistance (mΩ)	10_{MAX}	§ 4.5.12
Dielectric Withstanding Voltage (Vrms)	1000_{MIN}	§ 4.5.7.1


* Except for crimp contacts

** Other, please consult us

*** 0.9 [.035] for crimp contact
 $1.3 \pm 0.1 [.051 \pm .004]$ for other contacts

HILINX 2.54 >>> SIGNAL CONTACTS (1)

FEMALE CONTACTS FOR RECEPTACLES



Starclip** female technology




- 6 contact tines instead of 4
- Excellent mechanical and electrical reliability
- Better resistance to high vibrations
- Improved electrical conductivity
- 100% compatible with other connectors

- Size 22: high average current
- Clip for male contact $\varnothing 0.76 \pm 0.025$ [.030 ± .001]
- **Plating** on active part (clip)

Cu	Ni	Au
1 [.039]	3.5 [.138]	1.3 [.051]

Press-fit




- Solderless assembly
- Mother board or mezzanine connection
- PCB thickness: $2.5_{\text{MIN}} [.098]$
- Insertion forces: 65 N typical



Termination style

YP

Crimp barrel




- Crimping on wire
- AWG gauge 22 to 24 recommended
- Terminations protected by a casing cemented to the moulding



Termination style

X

SMT*




- SMT soldering
- PCB thickness: specific, *consult us*

Consult us

T

Solder cup*




- Hard-soldering on wire
- Mother board
- Cable to board or cable to cable connection
- Solder cup for 20 to 24 AWG wire



Consult us

Z

Soldering on flex*



- Hard soldering on flexible circuit
- PCB thickness: specific, *consult us*





Consult us

YS/Y

	YP	X	Z*	YS*/Y*
L_{MAX}	$2.8 \pm 0.2 [.110 \pm .008]$	$6.3 \pm 0.2 [.248 \pm .008]$	$4.9 \pm 0.2 [.193 \pm .008]$	YS: $1.5 \pm 0.2 [.059 \pm .008]$ Y: $2.4 \pm 0.2 [.093 \pm .008]$
Termination section	$\varnothing 0.82 [.032]$	$\varnothing 1.22 [.048]$	$1.6_{\text{MAX}} [.063]$	$0.45 \pm 0.3 [.018 \pm .001]$
Barrel standard termination plating μm [μin]	$2 [.079] \text{ Ni electrolytic} + 15.2 [.598] \text{ Ni electroless} + 10 [.394] \text{ Sn Pb}$	$1 [.039] \text{ Cu} + 3.5 [.138] \text{ Ni} + 1.3 [.051] \text{ Au}$		$3 [.118] \text{ Ni} + 10 [.394] \text{ Sn Pb}$
Barrel RoHS termination plating** μm [μin]	N/A	N/A		$2.5 [.089] \text{ Ni} + 5 [.197] \text{ bright pure Sn}$

** Except for crimp contacts

* Consult us


HILINX 2.54 >>> SIGNAL CONTACTS (1)**FEMALE CONTACTS FOR RECEPTACLES****Short straight PC tail**

- Thru hole soldering
- Mother board or mezzanine connection
- PCB thickness: 2.5 [.098] for 2-row version
1.8 [.071] for 3-row version



Termination style

YDS


Standard straight PC tail

- Thru hole soldering
- Mother board or mezzanine connection
- PCB thickness: 3.5 [.138] for 2-row version
2.5 [.098] for 3-row version



Termination style

YD

Long straight PC tail

- Thru hole soldering
- Mother board or mezzanine connection
- PCB thickness: 5 [.197] for 2-row version
3.5 [.138] for 3-row version



Termination style

YDL

Short right angle PC tail*

- Thru hole soldering
- Extender card
- PCB thickness: *consult us*

Consult us

YCS

Standard right angle PC tail*

- Thru hole soldering
- Extender card
- PCB thickness: *consult us*

Consult us

YC

Long right angle PC tail*

- Thru hole soldering
- Extender card
- PCB thickness: *consult us*

Consult us


YCL

L_{MAX}	YDS	YD	YDL	YCS*	YC*	YCL*	
	2-row: 3.5 ± 0.20 [.140 ± .010] 3-row: 2.8 ± 0.20 [.110 ± .010]	2-row: 4.4 ± 0.20 [.172 ± .010] 3-row: 3.5 ± 0.20 [.140 ± .010]	2-row: 5.9 ± 0.20 [.234 ± .010] 3-row: 4.4 ± 0.20 [.172 ± .010]	<i>Consult us</i>			
Termination section	$\varnothing 0.68_{MAX}$ [.027]						
Barrel standard termination plating μm [μin]	3 [.118] Ni + 10 [.394] Sn Pb						
Barrel RoHS termination plating* μm [μin]	2.5 [.089] Ni + 6 [.197] bright pure Sn						


* *Consult us*

HILINX 2.54 >>> SIGNAL CONTACTS (1)

MALE CONTACTS FOR PLUGS



Short right angle PC tail




- Thru hole soldering
- Daughter board or extender card
- PCB thickness: $1.8_{\text{MAX}} [.071]$

Termination style

YCS

Standard right angle PC tail




- Thru hole soldering
- Daughter board or extender card
- PCB thickness: $2.5_{\text{MAX}} [.098]$

Termination style

YC

Short right angle PC tail




- Thru hole soldering
- Daughter board or extender card
- PCB thickness: $3.5_{\text{MAX}} [.138]$

Termination style

YCL

SMT*



- SMT soldering
- Daughter board or extended card
- PCB thickness: specific, consult us



Consult us

T


	YCS	YC	YCL
L_{MAX}	2.8 ± 0.20 [.110 ± .010]	3.5 ± 0.20 [.140 ± .010]	4.4 ± 0.20 [.172 ± .010]
Termination section	$\varnothing 0.68_{\text{MAX}} [.027]$		
Mating end diameter	$\varnothing 0.76 \pm 0.025 [.030 \pm .001]$		
Plating ($\mu\text{m} [\mu\text{in}]$)	1 [.039] Cu + 3.5 [.138] Ni + 1.3 [.051] Au		

* Consult us


All dimensions are given for information only and are in mm [inch], except as otherwise specified

HILINX 2.54 >>> SIGNAL CONTACTS (1)**MALE CONTACTS FOR PLUGS****Crimp barrel**


- Crimping on wire
- AWG gauge 22 to 24 recommended
- Terminations protected by a casing cemented to the moulding
- For 3-row version only

[Consult us](#)**Short straight PC tail***


- Thru hole soldering
- Daughter board or mezzanine connection
- PCB thickness: 1.8_{MAX} [.071]
- For 3-row version only

[Consult us](#)**YDS****Standard straight PC tail***

- Thru hole soldering
- Daughter board or mezzanine connection
- PCB thickness: 2.5_{MAX} [.098]
- For 3-row version only

[Consult us](#)**Long straight PC tail***

- Thru hole soldering
- Daughter board or mezzanine connection
- PCB thickness: 3.5_{MAX} [.138]
- For 3-row version only

[Consult us](#)**YDL****Solder cup***

- Hard soldering on wire
- Daughter board
- Cable to board or cable to cable connection
- Solder cup for 20 to 24 AWG wire
- For 3-row version only


[Consult us](#)**Z**

	X*	YDS*	YD*	YDL*	Z*
L_{MAX}	6.3 ± 0.20 [.248 ± .010]	2.8 ± 0.20 [.110 ± .010]	3.5 ± 0.20 [.140 ± .010]	4.4 ± 0.20 [.172 ± .010]	2.54 ± 0.25 [.100 ± .010]
Termination section	Ø 1.22 [.048]		Ø 0.68 _{MAX} [.027]		Ø 1.6 _{MAX} [.063]
Mating end diameter			Ø 0.76 ± 0.025 [.030 ± .001]		
Plating (μm [μin])			1 [.039] Cu + 3.5 [.138] Ni + 1.3 [.051] Au		

*** Consult us***All dimensions are given for information only and are in mm [inch], except as otherwise specified*


HILINX 2.54 >>> SPECIAL CONTACTS (2)

FOR 2-ROW CONNECTORS *



POWER contacts

Straight female power contact




- Thru hole soldering
- Mother board
- 2 straight female contacts
- 20A / contact
- PCB thickness: 1.8 [.071] to 2.5 [.098]
- Termination section \varnothing 1.4_{MAXI}[.055]

Module designation

PF1

Right angle male power contact




- Thru hole soldering
- Daughter board
- 2 right angle male contacts
- 20A / contact
- PCB thickness: 1.8 [.071] to 2.5 [.098]
- Termination section: \varnothing 1.2_{MAXI}[.047]

Module designation

PM1

AMPHELUX™ ARINC 801 termini

Female amphenlux™ contact




- 2 amphenlux™ termini
- Multi-mode
- Modules are supplied less contacts, *consult us*
- Complied with the ARINC 801 specification
- Keyed to provide anti-rotation

Module designation

AXF

Male amphenlux™ contact




- 2 amphenlux™ termini
- Multi-mode
- Modules are supplied less contacts, *consult us*
- Complied with the ARINC 801 specification
- Keyed to provide anti-rotation

Module designation

AXM

COAXIAL contacts

Straight female coaxial contact




- Thru hole soldering
- Mother board or mezzanine connection
- 2 cavities for straight coaxial female contacts
- For more information, *consult us*
- Modules are supplied less contacts
- Data rate: up to 1.4 GHz / 3 Gbit.s⁻¹

Module designation

CF1

Right angle male coaxial contact



- Thru hole soldering
- Daughter board or extender card
- 2 cavities for right angle coaxial male contacts
- For more information, *consult us*
- Modules are supplied less contacts
- Data rate: up to 1.4 GHz / 3 Gbit.s⁻¹

Module designation

CM1

RADSOK® contacts

Female cavity module for RADSOK® contact

- 1 cavity for male RADSOK® contact
- Mother board
- 70A / contact
- Termination section: the body shape, the section and the length of the termination are specific to your need: *consult us*

Consult us

-

Right angle male RADSOK® contact


- Fixing with retainer
- Daughter board
- 1 male RADSOK® contact
- 70A / contact
- Termination section: the body shape, the section and the length of the termination are specific to your need: *consult us*

Consult us

-


HILINX 2.54 >>> SPECIAL CONTACTS (2)

FOR 3-ROW CONNECTORS *



POWER contacts

Straight female power contact




- Thru hole soldering
- Mother board
- 2 straight female contacts
- 20A / contact
- PCB thickness: 1.8 [.071] to 2.5 [.098]
- Termination section Ø 1.4_{MAXI}[.055]

Module designation

PF1

Right angle male power contact




- Thru hole soldering
- Daughter board
- 2 right angle male contacts
- 20A / contact
- PCB thickness: 1.8 [.071] to 2.5 [.098]
- Termination section: Ø 1.2_{MAXI}[.047]

Module designation

PM1

AMPHELUX™ ARINC 801 termini

Female amphelux™ contact




- 2 amphelux™ termini
- Multi-mode
- Modules are supplied less contacts, *consult us*
- Complied with the ARINC 801 specification
- Keyed to provide anti-rotation

Module designation

AXF

Male amphelux™ contact




- 2 amphelux™ termini
- Multi-mode
- Modules are supplied less contacts, *consult us*
- Complied with the ARINC 801 specification
- Keyed to provide anti-rotation

Module designation

AXM

COAXIAL contacts

Straight female coaxial contact




- Thru hole soldering
- Mother board or mezzanine connection
- 2 cavities for straight coaxial female contacts
- For more information, *consult us*
- Modules are supplied less contacts
- Data rate: up to 1.4 GHz / 3 Gbit.s⁻¹

Module designation

CF1

Right angle male coaxial contact



- Thru hole soldering
- Daughter board or extender card
- 2 cavities for right angle coaxial male contacts
- For more information, *consult us*
- Modules are supplied less contacts
- Data rate: up to 1.4 GHz / 3 Gbit.s⁻¹

Module designation

CM1

RADSOK® contacts

Female cavity module for RADSOK® contact

- 1 cavity for male RADSOK® contact
- Mother board
- 70A / contact
- Termination section: the body shape, the section and the length of the termination are specific to your need: *consult us*

Consult us

-

Right angle male RADSOK® contact

- Fixing with retainer
- Daughter board
- 1 male RADSOK® contact
- 70A / contact
- Termination section: the body shape, the section and the length of the termination are specific to your need: *consult us*

Consult us

-

L _{MAX}	PF1	PM1	AXF	AXM	CF1	CM1
2 rows	3.4 [.134]	3.825 [.151]	20.47 [.806]	13.4 [.528]	3 [.118]	4.365 [.172]
3 rows	3.4 [.134]	3.55 [.140]	20.47 [.806]	13.4 [.528]	3 [.118]	3 [.118]


* Hybrid modules will be preferably positioned on the connector sides

COAXIAL CONTACTS	
Impedance (Ω)	50
Voltage rating (V _{RMS})	180
Current rating (mA)	500
Contact retention (N)	50 _{MIN}
Frequency range (GHz)	0 to 1
Contact resistance (mΩ)	12 _{MAX}
VSWR at 1 (GHz)	1.3 _{MAX}
Insertion and extraction force per contact (N)	1 ≤ F ≤ 15


All dimensions are given for information only and are in mm [inch], except as otherwise specified

HILINX 2.54 >>> KEYING & GUIDING (3)

FULL ROUND GUIDES




Standard




- 1 female socket and 1 male pin
- Non keying
- Nickel over brass
- Mating with 65 or 69 keying
- MIL-DTL-55302 PN: X

For receptacle:




65

Reversed




- 1 male pin and 1 female socket
- Non keying
- Nickel over brass
- Mating with 66 or 70 keying

For receptacle:



66

Two male guide pins




- 2 male guide pins
- Non keying
- Nickel over brass
- Mating with 68 or 72 keying




67

Two female guide sockets




- 2 female guide sockets
- Non keying
- Nickel over brass
- Mating with 67 or 71 keying



68

LONG FULL ROUND GUIDES


6.2738 [.247] standard



- 1 female socket and 1 male pin
- Non keying
- For receptacle and straight plug w/o mounting ears
- Nickel over brass
- Mating with 69 or 65 keying
- MIL-DTL-55302/63 & /64 P/N: X

69


6.2738 [.247] reversed



- 1 male pin and 1 female socket
- Non keying
- For receptacle and straight plug w/o mounting ears
- Nickel over brass
- Mating with 70 or 66 keying

70


6.2738 [.247] two male guide pins



- Non keying
- For receptacle and straight plug w/o mounting ears
- Nickel over brass
- Mating with 72 or 68 keying

71

6.2738 [.247] two female guide sockets




- Non keying
- For receptacle and straight plug w/o mounting ears
- Nickel over brass
- Mating with 71 or 67 guides

72


Important note: all dimensions are in inch, except as otherwise specified.

HILINX 2.54 >>> KEYING & GUIDING (3)

D SHAPED GUIDES




Standard male guide pin



- 4 keying possibilities
- Electroless nickel over brass
- MIL-DTL-55302 PN: Y[-01 thru 64]

01 thru 64


Standard female guide socket



- 4 keying possibilities
- Electroless nickel over brass
- MIL-DTL-55302, PN: Y[-01 thru 64]

01 thru 64


6.2738 [.247] Long male guide pin



- 4 keying possibilities
- For receptacle and straight plug w/o mounting ears
- Electroless nickel over brass
- Mating with 01 thru 64 or 201 thru 264 keying
- MIL-DTL-55302/63 & /64 PN: Y[-01 thru -64]

201 thru 264



6.2738 [.247] Long female guide socket



- 4 keying possibilities
- For receptacle and straight plug w/o mounting ears
- Electroless nickel over brass
- Mating with 01 thru 64 or 201 thru 264 keying
- MIL-DTL-55302/63 & /64 PN: Y[-01 thru -64]

201 thru 264

CONNECTOR POLARIZATION WITH 'D' SHAPED GUIDE PINS AND SOCKETS




-1		-9		-17		-25		-33		-41		-49		-57	
-2		-10		-18		-26		-34		-42		-50		-58	
-3		-11		-19		-27		-35		-43		-51		-59	
-4		-12		-20		-28		-36		-44		-52		-60	
-5		-13		-21		-29		-37		-45		-53		-61	
-6		-14		-22		-30		-38		-46		-54		-62	
-7		-15		-23		-31		-39		-47		-55		-63	
-8		-16		-24		-32		-40		-48		-56		-64	

Important note: all dimensions are in inch, except as otherwise specified.


HILINX 2.54 >>> KEYING & GUIDING (3)

LOCKING

Fixed jacksets



Standard fixed jackset



73: standard

- Mating with 81, 85, 89, 93, 101, 105, 109, 113, 117 & 121 fittings
- MIL-DTL-55302/58, /59, /60, /61, /66, /138 & /139 PN: F

74: reversed

- Mating with 82, 86, 90, 94, 102, 106, 110, 114, 118 & 122 fittings

75: two jackscrews


- Mating with 84, 88, 92, 96, 104, 108, 112, 116, 120 & 124 fittings

76: two jacksockets

- Mating with 83, 87, 91, 103, 107, 111, 115, 119 & 123 fittings

6.2738 [.247] Long fixed jackset

For receptacle and straight plug, w/o mounting ears



77: standard

- Mating with 81, 85, 89, 93, 101, 105, 109, 113, 117 & 121 fittings
- MIL-DTL-55302/63 & /64 PN: F

78: reversed

- Mating with 82, 86, 90, 94, 102, 106, 110, 114, 118 & 122 fittings

79: two jackscrews

- Mating with 84, 88, 92, 96, 104, 108, 112, 116, 120, & 124 fittings

80: two jacksockets

- Mating with 83, 87, 91, 103, 107, 111, 115, 119 & 123 fittings


73 thru 76

77 thru 80

Hexagonal turning jacksets

3.43 [.135] Xtrashort hexagonal turning jackset

For right angle plug



101: standard

- Mating with 73 & 77 fittings
- MIL-DTL-55302/57, /59 & /138 PN: H

102: reversed

- Mating with 74 & 78 fittings

103: two jackscrews

- Mating with 76 & 80 fittings


104: two jacksockets

- Mating with 75 & 79 fittings

101 thru 104

5.08 [.200] short hexagonal turning jackset

For crimping version



117: standard

- Mating with 73 & 77 fittings
- MIL-DTL-55302/65 & /66 PN: H

118: reversed

- Mating with 74 & 78 fittings

119: two jackscrews

- Mating with 76 & 80 fittings

120: two jacksockets

- Mating with 75 & 79 fittings

117 thru 120

105: standard

- Mating with 73 & 77 fittings
- MIL-DTL-55302/58, /60, /62, /63 & /139 PN: H

106: reversed

- Mating with 74 & 78 fittings

107: two jackscrews

- Mating with 76 & 80 fittings


108: two jacksockets

- Mating with 75 & 79 fittings


105 thru 108

Important note

- All dimensions are in inch, except as otherwise specified.
- All the fittings are in passivated stainless except as otherwise specified.

HILINX 2.54 >> KEYING & GUIDING (3)**LOCKING****Slotted turning jacksets****3.43 [.135] Xtrashort slotted turning jackset**

For right angle plug

**89: standard**

- Mating with 73 & 77 fittings

- MIL-DTL-55302/57, /59 & /138 PN: S

90: reversed

- Mating with 74 & 78 fittings

91: two jackscrews


- Mating with 76 & 80 fittings

92: two jacksockets

- Mating with 75 & 79 fittings

89 thru 92**Standard Slotted turning jackset**

For straight plug and receptacle w/o crimp contacts

**5.08 [.200]****Short slotted turning jackset****93: standard**

- Mating with 73 & 77 fittings

- MIL-DTL-55302/58, /60, /62, /63 & /139 PN: S

94: reversed

- Mating with 74 & 78 fittings

95: two jackscrews

- Mating with 76 & 80 fittings

96: two jacksockets

- Mating with 75 & 79 fittings

12.70 [.500]**Medium slotted turning jackset****81: standard**

- Mating with 73 & 77 fittings

- MIL-DTL-55302/62 & /63 PN: M

82: reversed

- Mating with 74 & 78 fittings

83: two jackscrews

- Mating with 76 & 80 fittings

84: two jacksockets

- Mating with 75 & 79 fittings

17.78 [.700]**Long slotted turning jackset****85: standard**

- Mating with 73 & 77 fittings

- MIL-DTL-55302/62 & /63 PN: L

86: reversed

- Mating with 74 & 78 fittings

87: two jackscrews


- Mating with 76 & 80 fittings

88: two jacksockets

- Mating with 75 & 79 fittings

93 thru 96**81 thru 84****85 thru 88****Crimping version, slotted turning jackset**

For crimping connector

**5.08 [.200]****Short slotted turning jackset****121: standard**

- Mating with 73 & 77 fittings

- MIL-DTL-55302/65 & /66 PN: S

122: reversed

- Mating with 74 & 78 fittings

123: two jackscrews

- Mating with 76 & 80 fittings

124: two jacksockets

- Mating with 75 & 79 fittings

12.70 [.500]**Medium slotted turning jackset****113: standard**

- Mating with 73 & 77 fittings

- MIL-DTL-55302/66 PN: M

114: reversed

- Mating with 74 & 78 fittings

115: two jackscrews

- Mating with 76 & 80 fittings

116: two jacksockets

- Mating with 75 & 79 fittings

17.78 [.700]**Long slotted turning jackset****109: standard**

- Mating with 73 & 77 fittings

- MIL-DTL-55302/66 PN: L

110: reversed

- Mating with 74 & 78 fittings

111: two jackscrews

- Mating with 76 & 80 fittings

112: two jacksockets

- Mating with 75 & 79 fittings

121 thru 124**113 thru 116****109 thru 112****Important note**


- All dimensions are in inch, except as otherwise specified.
- All the fittings are in passivated stainless except as otherwise specified.

HILINX^{2.54} >>> KEYING & GUIDING (3)






REALIGNMENT CAPABILITY

In the longitudinal axis




In the lateral axis




MATING SEQUENCE*


Guiding



Signal contact



Mated connector



6.6 ± 0.1 [.260 ± .004]

5.6 ± 0.1 [.220 ± .004]

1.3 ± 0.1 [.051 ± .004]

1.3 ± 0.1 [.051 ± .004]

* Except for crimp contacts. Backoff is 0.9 [.035] only for crimp contacts.

HILINX^{2.54} >>> SIGNAL VERSION ONLY

MIL-DTL-55302

/57 to /66, /138 & /139

COMPATIBILITY WITH THE MIL DTL 55302/57 TO /66, /138 & /139
Detailed sheets


MIL-DTL-55302	Series	Number of contacts	Type of contacts	Hardware	Deviation	Comments
MIL-DTL-55302/57	HLX2 P 2	10, 20, 30, 40, 50, 60, 70 14, 24, 44, 54 26, 36, 56, 66	A = YCS B = YC C = YCL	X = 65 Y[-1 thru -64] = 01 thru 64 S = 89 H = 101	-000	X = full round guides Y = D-shaped S = .135 slotted turning jackset H = .135 hexagonal turning jackset
MIL-DTL-55302/59	HLX2 P 2	90, 100, 120	A = YCS B = YC C = YCL	X = 65 Y[-1 thru -64] = 01 thru 64 F = 73 S = 89 H = 101	-200	X = full round guides Y = D-shaped F = fixed jackset S = .135 slotted turning jackset H = .135 hexagonal turning jackset
MIL-DTL-55302/138	HLX2 P 3	160	A = YCS B = YC C = YCL	X = 65 Y[-1 thru -64] = 01 thru 64 F = 73 S = 89 H = 101	-200	X = full round guides Y = D-shaped F = fixed jackset S = .135 slotted turning jackset H = .135 hexagonal turning jackset
MIL-DTL-55302/61	HLX2 P 2	10, 20, 30, 40, 50, 60, 70 14, 24, 44, 54 26, 36, 56, 66	A = YCS B = YC C = YCL	Blank = 73	-000	Blank = fixed jackset
MIL-DTL-55302/58	HLX2 R 2	10, 20, 30, 40, 50, 60, 70 14, 24, 44, 54 26, 36, 56, 66	A = Z* B = YDS C = YD D = W* E = Y* F = YDL	X = 65 Y[-1 thru -64] = 01 thru 64 F = 73 S = 93 H = 105	-000	X = full round guides Y = D-shaped F = fixed jackset S = .200 slotted turning jackset H = .200 hexagonal turning jackset
MIL-DTL-55302/60	HLX2 R 2	90, 100, 120	A = Z* B = YDS C = YD D = W* E = Y* F = YDL	X = 65 Y[-1 thru -64] = 01 thru 64 F = 73 S = 93 H = 105	-200	X = full round guides Y = D-shaped F = fixed jackset S = .200 slotted turning jackset H = .200 hexagonal turning jackset
MIL-DTL-55302/139	HLX2 R 3	160	A = Z* B = YDS C = YDL D = W* E = YDL F = Y* H = YL*	X = 65 Y[-1 thru -64] = 01 thru 64 F = 73 S = 93 H = 105	-200	X = full round guides Y = D-shaped F = fixed jackset S = .200 slotted turning jackset H = .200 hexagonal turning jackset
MIL-DTL-55302/62 MIL-DTL-55302/62 L	HLX2 R 2	10, 20, 30, 40, 50, 60, 70 14, 24, 44, 54 26, 36, 56, 66	A = Z* B = YDS C = YD D = Y* E = YDL F = YL*	L = 85 M = 81 S = 93 H = 105	-100	L = .700 slotted turning jackset M = .500 slotted turning jackset S = .200 slotted turning jackset H = .200 hexagonal turning jackset Without mounting ears
MIL-DTL-55302/64 MIL-DTL-55302/64 L	HLX2 R 2	10, 20, 30, 40, 50, 60, 70 14, 24, 44, 54 26, 36, 56, 66	A = Z* B = YDS C = YD D = W* E = Y* F = YL*	F = 77 X = 69 Y[-1 thru -64] = 201 thru 264	-100	F = .247 fixed jackset X = .247 full round guides Y = .247 D-shaped Without mounting ears
MIL-DTL-55302/65 MIL-DTL-55302/65 L	HLX2 R 2	10, 20, 30, 40, 50, 60, 70 14, 24, 44, 54 26, 36, 56, 66	Blank = X	X = 65 Y[-1 thru -64] = 01 thru 64 F = 73 S = 121 H = 117	-000	X = full round guides Y = D-shaped F = fixed jackset S = .200 slotted turning jackset H = .200 hexagonal turning jackset
MIL-DTL-55302/66 MIL-DTL-55302/66 L	HLX2 R 2	10, 20, 30, 40, 50, 60, 70 14, 24, 44, 54 26, 36, 56, 66	Blank = X	L = 109 M = 113 F = 73 S = 121 H = 117	-100	L = .700 slotted turning jackset M = .500 slotted turning jackset F = fixed jackset S = .200 slotted turning jackset H = .200 hexagonal turning jackset Without mounting ears

* Consult us


HILINX 2.54 >>> SIGNAL CONTACT VERSION (4)

TYPICAL ARRANGEMENTS 2 ROWS

n indicates the total number of signal contacts**




2-row signal contact receptacles, from 10 to 70 contacts*



n = 10, 14, 16, 20, 24, 26, 30, 34, 36, 40, 44,
46, 50, 54, 56, 60, 64, 66, 70**

C	$n \times 1.27 - 2.54$
D	C + 6.35
E	D + 5.08
F	E + 6.35
G	F + 6.35
h	6.4 _{MAX}
I	8.5 _{MAX}
R	3.1

2-row signal contact plugs, from 10 to 70 contacts*



n = 10, 14, 20, 24, 26, 30, 34, 36, 40, 44,
46, 50, 54, 56, 60, 64, 66, 70**

C	$n \times 1.27 - 2.54$
D	C + 6.35
E	D + 5.08
F	E + 6.35
G	F + 6.35
h	6.4 _{MAX}
I	10.2 _{MAX}


* in mm. 1mm = 0.03937 inch

** Further arrangements up to 160 contacts, with or without central fitting, are available, consult us

HILINX 2.54 >>> SIGNAL CONTACT VERSION (4)

LAYOUTS 2 ROWS

The boards are shown from the connector side
All contact locations are equidistant.



n		YD/YDS/YDL & YP CONTACT (female for receptacle)*						
2 ROWS		FROM 10 TO 70 CONTACTS**						
		$n = 10, 14, 20, 24, 26, 30, 34, 36, 40, 44, 46, 50, 54, 56, 60, 64, 66, 70^{**}$						
		<table border="1"> <tr> <td>C</td> <td>$n \times 1.27 - 2.54$</td> </tr> <tr> <td>D</td> <td>$C + 6.35$</td> </tr> <tr> <td>F</td> <td>$C + 17.78$</td> </tr> </table>	C	$n \times 1.27 - 2.54$	D	$C + 6.35$	F	$C + 17.78$
C	$n \times 1.27 - 2.54$							
D	$C + 6.35$							
F	$C + 17.78$							

n		YC/YCS/YCL CONTACT (male for plug)*				
2 ROWS		FROM 10 TO 70 CONTACTS**				
		$n = 10, 14, 20, 24, 26, 30, 34, 36, 40, 44, 46, 50, 54, 56, 60, 64, 66, 70^{**}$				
		<table border="1"> <tr> <td>C</td> <td>$n \times 1.27 - 2.54$</td> </tr> <tr> <td>F</td> <td>$C + 17.78$</td> </tr> </table>	C	$n \times 1.27 - 2.54$	F	$C + 17.78$
C	$n \times 1.27 - 2.54$					
F	$C + 17.78$					

P	p/2	p/4	p1	R1	R2	R4	d1	h0	h1
2.54 [.100]	1.27 [.050]	0.635 [.025]	3.05 [.120]	To be defined by customer Hardware is not provided with connector	Not compulsory 3.75 ± 0.1 [.150 ± .004]	$\varnothing 0.8_{\text{MIN}} [.031]$ With metallization	8.255 [.325]	5.3 _{MAX} [.209]	1.27 [.050]

*in mm. 1mm = 0.03937 inch


**Further arrangements up to 160 contacts, with or without central fitting, are available, consult us

All dimensions are given for information only and are in mm [inch], except as otherwise specified


HILINX 2.54 >>> SIGNAL CONTACT VERSION (4)

TYPICAL ARRANGEMENTS 3 ROWS

n indicates the total number of signal contacts**




3-row signal contact receptacles, from 50 to 170 contacts*




$n = 14, 26, 32, 38, 44, 50, 56, 62, 68, 74, 80, 86, 92, 98, 104, 110, 122, 134, 140, 146, 158, 170^{**}$

C	$(n - 2) \times 2.54 / 3$
D	$C + 5.08$
E	$D + 5.08$
F	$E + 6.35$
G	$F + 6.35$
h	8.95 _{MAX}
I	8.5
R	3.1




3-row signal contact plugs, from 50 to 170 contacts*



$n = 14, 26, 32, 38, 44, 50, 56, 62, 68, 74, 80, 86, 92, 98, 104, 110, 122, 134, 140, 146, 158, 170^{**}$

C	$(n - 2) \times 2.54 / 3$
D	$C + 5.08$
E	$D + 5.08$
F	$E + 6.35$
G	$F + 6.35$
h	8.95 _{MAX}
I	10.16




*in mm. 1mm = 0.03937 inch

** Further arrangements up to 188 contacts, with or without central fitting, are available, consult us

HILINX^{2.54} >>> SIGNAL CONTACT VERSION (4)

LAYOUTS 3 ROWS

The boards are shown from the connector side
All contact locations are equidistant.



YD/YDS/YDL & YP CONTACT (female for receptacle or male for plug)*

n ROWS
FROM 50 TO 170 CONTACTS**

n = 14, 26, 32, 38, 44, 50, 56, 62, 68, 74, 80, 86, 92, 98, 104, 110, 122, 134, 140, 146, 158, 170**

C	$(n - 2) \times 2.54 / 3$
D	$C + 5.08$
F	$C + 16.51$

**3 ROWS
FROM 50 TO 170 CONTACTS****

n **YC/YCS/YCL CONTACT (male for plug)***

$n = 14, 26, 32, 38, 44, 50, 56, 62, 68, 74, 80, 86, 92, 98, 104,$
 $110, 122, 134, 140, 146, 158, 170^{**}$

C $(n - 2) \times 2.54 / 3$
F $C + 16.51$

p	p/2	p1	R1	R2	R4	d1	h0
2.54 [.100]	1.27 [.050]	3.175 [.125]	To be defined by customer Hardware is not provided with connector	Not compulsory 3.75 ± 0.1 [.150 ± .004]	\emptyset 0.8 _{MIN} [.031] With metallization	8.255 [.325]	3.5 _{MIN} [.138]

* in mm: 1mm = 0.03937 inch


****Further arrangements up to 188 contacts, with or without central fitting, are available, consult us**

All dimensions are given for information only and are in mm [inch], except as otherwise specified


HILINX 2.54 >>> HYBRID VERSION (4)

DIMENSIONS 2 ROWS**

s indicates the total number of special contacts.
n indicates the total number of signal contacts




Power contacts 20A*




C	$s = 2, 4, 6\dots$
D	$8.89 + s \times 7.62 + n \times 1.27$
E	$D + 5.08$
F	$E + 6.35$
G	$F + 6.35$
H	6.4_{MAX}
d1	8.25 [.325]
d2	7.62 [.300]
d3	4.445 [.175]
d4	0.635 [.025]
R	$3.1 + 0.1 [.122 + .004]$
p/2	1.27 [.050]

AMPHELUX™ contacts*



C	$s = 2, 4, 6\dots$
D	$8.89 + s \times 8.89 + n \times 1.27$
E	$D + 5.08$
F	$E + 6.35$
G	$F + 6.35$
H	6.4_{MAX}
d1	10.035 [.395]
d2	6.6 [.260]
d3	6.225 [.245]
d4	0.635 [.025]
d5	11.18 [.440]
R	$3.1 + 0.1 [.122 + .004]$
p/2	1.27 [.050]

Coaxial contacts*



C	$n \times 1.27 - 2.54$
D	$8.89 + s \times 7.62 + n \times 1.27$
E	$D + 5.08$
F	$E + 6.35$
G	$F + 6.35$
H	6.4_{MAX}
d1	8.25 [.325]
d2	7.62 [.300]
d3	4.445 [.175]
d4	0.635 [.025]
R	$3.1 + 0.1 [.122 + .004]$
p/2	1.27 [.050]

RADSOK® contacts 70A*

Please consult us


* in mm: 1mm = 0.03937 inch

** Hybrid modules will be preferably positionned on the connector sides

HILINX 2.54 >>> HYBRID VERSION (4)

LAYOUTS 2 ROWS**

The boards are shown from the connector side
All contact locations are equidistant.



With YD/YDS/YDL & YP CONTACT (female for receptacle)*

WITH POWER CONTACT 20A																																																					
WITH AMPHELUX™ CONTACT	<table border="1"> <tr> <td>C</td><td colspan="7">n x 1.27 – 2.54</td><td></td></tr> <tr> <td>D</td><td colspan="7">8.89 + s x 7.62 + n x 1.27</td><td></td></tr> <tr> <td>F</td><td colspan="7">D + 11.43</td><td></td></tr> </table>							C	n x 1.27 – 2.54								D	8.89 + s x 7.62 + n x 1.27								F	D + 11.43																										
C	n x 1.27 – 2.54																																																				
D	8.89 + s x 7.62 + n x 1.27																																																				
F	D + 11.43																																																				
WITH COAXIAL CONTACT	<table border="1"> <tr> <td>C</td><td colspan="7">n x 1.27 – 2.54</td><td></td></tr> <tr> <td>D</td><td colspan="7">8.89 + s x 8.89 + n x 1.27</td><td></td></tr> <tr> <td>F</td><td colspan="7">D + 11.43</td><td></td></tr> <tr> <td>L</td><td colspan="7">6.45 _{MIN}</td><td></td></tr> <tr> <td>M</td><td colspan="7">Depending on s</td><td></td></tr> </table>							C	n x 1.27 – 2.54								D	8.89 + s x 8.89 + n x 1.27								F	D + 11.43								L	6.45 _{MIN}								M	Depending on s								
C	n x 1.27 – 2.54																																																				
D	8.89 + s x 8.89 + n x 1.27																																																				
F	D + 11.43																																																				
L	6.45 _{MIN}																																																				
M	Depending on s																																																				

YDS/YD/YDL & YP	d_1	d_2	d_3	d_4	R_1	R_2	R_3	R_4	$p/2$	p
Power	8.25 [.325]	7.62 [.300]	4.445 [.175]							
Amphelux™	6.61 _{MAX} [.260]		2.8 _{MAX} [.110]	0.635 [.025]	Not compulsory	3.75 ± 0.1 [.150 ± .004]	1.5 _{MIN} [.059]	Ø 0.8 _{MIN} [.031] with metallization	1.27 [.050]	2.54 [.100]
Coaxial	8.25 [.325]	7.62 [.300]	4.445 [.175]							

With YC/YCS/YCL CONTACT (male for plug)*

WITH POWER CONTACT 20A																										
WITH AMPHELUX™ CONTACT	<table border="1"> <tr> <td>C</td><td colspan="7">n x 1.27 – 2.54</td><td></td></tr> <tr> <td>F</td><td colspan="7">20.32 + s x 7.62 + n x 1.27</td><td></td></tr> </table>							C	n x 1.27 – 2.54								F	20.32 + s x 7.62 + n x 1.27								
C	n x 1.27 – 2.54																									
F	20.32 + s x 7.62 + n x 1.27																									
WITH COAXIAL CONTACT	<table border="1"> <tr> <td>C</td><td colspan="7">n x 1.27 – 2.54</td><td></td></tr> <tr> <td>F</td><td colspan="7">20.32 + s x 8.89 + n x 1.27</td><td></td></tr> </table>							C	n x 1.27 – 2.54								F	20.32 + s x 8.89 + n x 1.27								
C	n x 1.27 – 2.54																									
F	20.32 + s x 8.89 + n x 1.27																									

YC/YCS/YCL	d_1	d_2	d_3	R_1	R_3	R_4	p	p_1	h_1	h_0	h_2
Power	13.97 [.550]	7.62 [.300]	4.445 [.175]								
Amphelux™				See Note below	1.5 _{MIN} [.059]						
Coaxial	13.97 [.550]	7.62 [.300]	4.445 [.175]			Ø 0.8 _{MIN} [.031] with metallization	2.54 [.100]	3.048 [.120]	1.2954 [.051]	3.5 _{MIN} [.138]	5.8 [.228]

Note : to be defined by the customer. Hardware is not provided with connector.

* in mm: 1mm = 0.03937 inch


** Hybrid modules will be preferably positionned on the connector sides

All dimensions are given for information only and are in mm [inch], except as otherwise specified


HILINX 2.54 >>> HYBRID VERSION (4)

DIMENSIONS 3 ROWS**

s indicates the total number of special contacts.
n indicates the total number of signal contacts




Power contacts 20A*




	$s = 2, 4, 6\dots$
C	$(n - 2) \times 2.54 / 3$
D	7.62 + $s \times 7.62 + n \times 0.847$
E	D + 5.08
F	E + 6.35
G	F + 6.35
H	8.95 _{MAX}
d1	8.255 [.325]
d2	7.62 [.300]
d3	4.445 [.175]
d4	6.985 [.275]
R	3.1 ^{+0.1} [.122 ^{+.004}]
p	2.54 [.100]

AMPHELUX™ contacts*



	$s = 2, 4, 6\dots$
C	$(n - 2) \times 2.54 / 3$
D	7.62 + $s \times 8.89 + n \times 0.847$
E	D + 5.08
F	E + 6.35
G	F + 6.35
H	8.95 _{MAX}
d1	9.4 [.370]
d2	6.6 [.260]
d3	6.86 [.270]
d4	11.18 [.440]
R	3.1 ^{+0.1} [.122 ^{+.004}]
p	2.54 [.100]

Coaxial contacts*



	$s = 2, 4, 6\dots$
C	$(n - 2) \times 2.54 / 3$
D	7.62 + $s \times 7.62 + n \times 0.847$
E	D + 5.08
F	E + 6.35
G	F + 6.35
H	8.95 _{MAX}
d1	8.255 [.325]
d2	7.62 [.300]
d3	4.445 [.175]
d4	6.985 [.275]
R	3.1 ^{+0.1} [.122 ^{+.004}]
p	2.54 [.100]

RADSOK® contacts 70A*

Please consult us


* in mm: 1mm = 0.03937 inch

** Hybrid modules will be preferably positionned on the connector sides

HILINX 2.54 >>> HYBRID VERSION (4)

LAYOUTS 3 ROWS**

The boards are shown from the connector side
All contact locations are equidistant.



With YD/YDS/YDL & YP CONTACT (female for receptacle)*																			
WITH POWER CONTACT 20A					<table border="1"> <tr> <td>C</td><td>$(n - 2) \times 2.54 / 3$</td></tr> <tr> <td>D</td><td>$7.62 + s \times 7.62 + n \times 0.847$</td></tr> <tr> <td>F</td><td>$D + 11.43$</td></tr> </table>						C	$(n - 2) \times 2.54 / 3$	D	$7.62 + s \times 7.62 + n \times 0.847$	F	$D + 11.43$			
C	$(n - 2) \times 2.54 / 3$																		
D	$7.62 + s \times 7.62 + n \times 0.847$																		
F	$D + 11.43$																		
				<table border="1"> <tr> <td>C</td><td>$(n - 2) \times 2.54 / 3$</td></tr> <tr> <td>D</td><td>$7.62 + s \times 8.89 + n \times 0.847$</td></tr> <tr> <td>F</td><td>$D + 11.43$</td></tr> <tr> <td>L</td><td>6.45_{MIN}</td></tr> <tr> <td>M</td><td>Depending on s</td></tr> </table>						C	$(n - 2) \times 2.54 / 3$	D	$7.62 + s \times 8.89 + n \times 0.847$	F	$D + 11.43$	L	6.45_{MIN}	M	Depending on s
C	$(n - 2) \times 2.54 / 3$																		
D	$7.62 + s \times 8.89 + n \times 0.847$																		
F	$D + 11.43$																		
L	6.45_{MIN}																		
M	Depending on s																		
				<table border="1"> <tr> <td>C</td><td>$(n - 2) \times 2.54 / 3$</td></tr> <tr> <td>D</td><td>$7.62 + s \times 7.62 + n \times 0.847$</td></tr> <tr> <td>F</td><td>$D + 11.43$</td></tr> </table>						C	$(n - 2) \times 2.54 / 3$	D	$7.62 + s \times 7.62 + n \times 0.847$	F	$D + 11.43$				
C	$(n - 2) \times 2.54 / 3$																		
D	$7.62 + s \times 7.62 + n \times 0.847$																		
F	$D + 11.43$																		
YDS/YD/YDL & YP	d ₁	d ₂	d ₃	d ₄	R ₁	R ₂	R ₃	R ₄	p/2	p									
Power	8.255 [.325]	7.62 [.300]	4.445 [.175]	6.985 [.275]	Not compulsory		1.5 _{MIN} [.059]	Ø 0.8 _{MIN} [.031]		2.54									
Amphelux™	5.55 _{MAX} [.219]		3.0 _{MAX} [.118]		3.75 ± 0.1		with metallization		[.050]	[.100]									
Coaxial	8.255 [.325]	7.62 [.300]	4.445 [.175]	6.985 [.275]	[.150 ± .004]														

With YC/YCS/YCL CONTACT (male for plug)*														
WITH POWER CONTACT 20A					<table border="1"> <tr> <td>C</td><td>$(n - 2) \times 2.54 / 3$</td> </tr> <tr> <td>F</td><td>$19.05 + s \times 7.62 + n \times 1.27$</td> </tr> </table>						C	$(n - 2) \times 2.54 / 3$	F	$19.05 + s \times 7.62 + n \times 1.27$
C	$(n - 2) \times 2.54 / 3$													
F	$19.05 + s \times 7.62 + n \times 1.27$													
				<table border="1"> <tr> <td>C</td><td>$(n - 2) \times 2.54 / 3$</td> </tr> <tr> <td>F</td><td>$19.05 + s \times 8.89 + n \times 1.27$</td> </tr> </table>						C	$(n - 2) \times 2.54 / 3$	F	$19.05 + s \times 8.89 + n \times 1.27$	
C	$(n - 2) \times 2.54 / 3$													
F	$19.05 + s \times 8.89 + n \times 1.27$													
				<table border="1"> <tr> <td>C</td><td>$(n - 2) \times 2.54 / 3$</td> </tr> <tr> <td>F</td><td>$19.05 + s \times 7.62 + n \times 1.27$</td> </tr> </table>						C	$(n - 2) \times 2.54 / 3$	F	$19.05 + s \times 7.62 + n \times 1.27$	
C	$(n - 2) \times 2.54 / 3$													
F	$19.05 + s \times 7.62 + n \times 1.27$													
YC/YCS/YCL	d ₁	d ₂	d ₃	d ₄	R ₁	R ₃	R ₄	p	p ₁	h ₁	h ₀			
Power	13.97 [.550]	7.62 [.300]	4.445 [.175]	12.7 [.500]	See Nota below		1.5 _{MIN} [.059]	Ø 0.8 _{MIN} [.031]		5.545 [.218]	5.3 _{MIN} [.209]			
Amphelux™					with metallization				[.100]	[.120]				
Coaxial	13.97 [.550]	7.62 [.300]	4.445 [.175]	12.7 [.500]										

Nota : to be defined by the customer. Hardware is not provided with connector.

* in mm: 1mm = 0.03937 inch

** Hybrid modules will be preferably positionned on the connector sides

All dimensions are given for information only and are in mm [inch], except as otherwise specified

HILINX 1.905 >>> GENERAL SPECIFICATIONS



HIGH DENSITY

- A unique connector, both hybrid and modular
- Cost effective, easy to install, highly reliable
- More current through each contact
- Greater performance and optimal protection in harsh environments
- Compatible with signal connectors on the market (MIL-DTL-55302/190 to /193)
- 1.905[.075] staggered grid (0.9525[.0375] offset), 1.905[.075] between rows

Main characteristics

- High density: 0.16 cts / mm² [103 cts / inch²]
- From 2 to 3 rows, 10 to 206 signal contacts
- 3A per signal contact (up to 5A current rating available upon request)
- Press-fit solderless attachment technology available
- Some signal contact versions are 100% compatible with the M55302 /190 to /193.


Markets



Main applications




Terminations



Special contacts



How to order




Important note

- RADSOK®, coaxial and Amphilux™ contacts have to be ordered separately
- * Special modules are available for 3-row connectors only


All dimensions are given for information only and are in mm [inch], except as otherwise specified

HILINX 1.905 >>> TECHNICAL SPECIFICATIONS

Dimensional characteristics



$H = 7.62_{MAX} [.300]$
 $A = 5.12_{MAX} [.202]$ for 2-row connectors
 $A = 7_{MAX} [.276]$ for 3-row connectors
 $B = 5.72 + X [.225 + X]$ for 2-row connectors
 $B = 7.6 + X [.300 + X]$ for 3-row connectors
 $X = \text{Board thickness} + \text{hardware thickness}$
 $d = 15.24_{MAX} [.600]$
 $e = 1.8 [.071] \text{ to } 3.4 [.134] \text{ or } 2.5_{MIN} [.098] \text{ (for YP contacts)}$



Female contact



Starclip female technology: 6 tines for better reliability

- 6 contact tines instead of 4
- Excellent mechanical and electrical reliability
- Better resistance to high vibrations
- Improved electrical conductivity
- 100% compatible with other connectors


Material

- Hood: machined brass alloy
- Starclip: CuBe[BeCu], stamped and formed

Plating

- Hood: tin lead or lead free
- Starclip: gold over nickel

Male contact



- Mating end diameter:** Ø 0.635 [.025]
- Contact section (mating side):** 0.32 mm² [.0005 in²]
- Material:** machined brass alloy
- Plating:** gold over nickel

Materials

- Guiding devices:** electroless nickel plating over brass CuZn or passivated stainless steel 303
- Rails:** passivated stainless steel 316L
- Plastic insert:** thermoplastic LCP, 30% glass-fiber filled

MECHANICAL CHARACTERISTICS

		MIL-DTL-55302 sections
Backoff¹ (mm)	0.8 _{MAX} [.031]	N/A
Mating force per contact (N)	0.85 _{MAX}	§ 4.5.3
Unmating force per contact (N)	0.35 < F < 0.85	§ 4.5.3
Durability cycles	500	§ 4.5.9
Sinusoidal vibrations (10 to 2000 Hz) micro discontinuity 2ns	15 g	§ 4.5.10
Random vibrations (5 to 2000 Hz) micro discontinuity 2ns	0.5 g ² / Hz	§ 4.5.10
Shocks 6ms ½ sinus 2ns	100 g	§ 4.5.10

ENVIRONMENTAL CHARACTERISTICS

Thermal shocks (°C)	-65 / +150	§ 4.5.13
Salt Spray (hours)	96	§ 4.5.11

Humidity

Days	10	
Temperature (°C)	25/65	§ 4.5.15
Humidity rate (%)	90-95	

ELECTRICAL CHARACTERISTICS

Current rating per contacts (A)	3*	§ 4.5.5
Insulation resistance (at 500Vdc) (GΩ)	5 _{MIN}	§ 4.5.8
Contact resistance (mΩ)	10 _{MAX}	§ 4.5.12
Dielectric Withstanding Voltage (Vrms)	750 _{MIN}	§ 4.5.7.1

¹: When both connectors are fully mated, the backoff is the maximum distance the connectors can be unmated while functioning properly

* Other, please consult us

HILINX 1.905 >>> SIGNAL CONTACTS (1)

FEMALE CONTACTS FOR RECEPTACLES



Starclip female technology




- 6 contact tines instead of 4
- Excellent mechanical and electrical reliability
- Better resistance to high vibrations
- Improved electrical conductivity
- 100% compatible with other connectors

- Size 23: high average current
- Clip for male contact Ø 0.635 [.025]
- **Plating** on active part (clip)

Cu	Ni	Au
1 [.039]	3.5 [.138]	1.3 [.051]

Press-fit




- Solderless assembly
- Mother board or mezzanine connection
- PCB thickness: 2.5_{MIN} [.098]
- Insertion forces: 65 N typical




Termination style

YP

Solder cup*




- Hard soldering on wire
- Mother board for cable to board connection
- Solder cup for 24 to 28 AWG wire



Consult us

Z

SMT*




- SMT soldering
- PCB thickness: specific, *consult us*

Consult us

T

Soldering on flex*



- Hard soldering on flexible circuit
- PCB thickness: specific, *consult us*


Consult us

Y

	YP	Z*	T*	Y*
L _{MAX}	2.8 ± 0.2 [.110 ± .008]	5.5 ± 0.2 [.217 ± .008]	1.85 [.073]	2.4 ± 0.2 [.094 ± .008]
Termination section	Ø 0.82 [.032]	Ø 0.75 _{MAX} [.030]		Ø 0.51 _{MAX} [.020]
Barrel standard termination plating μm [μin]	2 [.079] Ni electrolytic + 15.2 [.598] Ni electroless + 10 [.394] Sn Pb		3 [.118] Ni + 10 [.394] Sn Pb	
Barrel RoHS termination plating* μm [μin]	N/A		2.5 [.089] Ni + 5 [.197] bright pure Sn	

* Consult us

All dimensions are given for information only and are in mm [inch], except as otherwise specified


HILINX 1.905 >>> SIGNAL CONTACTS (1)**FEMALE CONTACTS FOR RECEPTACLES****Short straight PC tail**

- Thru hole soldering
- Mother board or mezzanine connection
- PCB thickness: 1.8_{MAX} [.071]



Termination style

YDS


Standard straight PC tail

- Thru hole soldering
- Mother board or mezzanine connection
- PCB thickness: 2.5_{MAX} [.098]



Termination style

YD

Long straight PC tail

- Thru hole soldering
- Mother board or mezzanine connection
- PCB thickness: 3.5_{MAX} [.138]



Termination style

YDL

Short right angle PC tail*

- Thru hole soldering
- Extender card
- PCB thickness: *consult us*

Consult us

YCS

Standard right angle PC tail*

- Thru hole soldering
- Extender card
- PCB thickness: *consult us*

Consult us

YC

Long right angle PC tail*

- Thru hole soldering
- Extender card
- PCB thickness: *consult us*

Consult us

YCL

	YDS	YD	YDL	YCS*	YC*	YCL*
L_{MAX}	2.8 ± 0.2 [.110 ± .008]	3.5 ± 0.2 [.140 ± .008]	4.4 ± 0.2 [.172 ± .008]			Consult us
Termination section		Ø 0.51 _{MAX} [.020]				
Barrel standard						
termination plating µm [µin]				3 [.118] Ni + 10 [.394] Sn Pb		
Barrel RoHS						
termination plating* µm [µin]				2.5 [.089] Ni + 6 [.197] bright pure Sn		

*Consult us


All dimensions are given for information only and are in mm [inch], except as otherwise specified

HILINX 1.905 >>> SIGNAL CONTACTS (1)

MALE CONTACTS FOR PLUGS




Short right angle PC tail



- Thru hole soldering
- Daughter board or extender card
- PCB thickness: 1.8_{MAX} [.071]

Termination style

Standard right angle PC tail




- Thru hole soldering
- Daughter board or extender card
- PCB thickness: 2.5_{MAX} [.098]

Termination style

YC

Long right angle PC tail




- Thru hole soldering
- Daughter board or extender card
- PCB thickness: 3.5_{MAX} [.138]

Termination style

YCL

Soldering on flex*



- Hard soldering on flexible circuit
- SMT connection
- PCB thickness: consult us


Consult us

Y


	YCS	YC	YCL	Y*
L_{MAX}	2.8 ± 0.2 [.110 ± .008]	3.5 ± 0.2 [.140 ± .008]	4.4 ± 0.2 [.172 ± .008]	2.4 ± 0.2 [.094 ± .008]
Termination section		Ø 0.51 _{MAX} [.020]		
Mating end diameter		Ø 0.635 ± 0.02 [.025 ± .001]		
Plating µm [µin]		1 [.039] Cu + 3.5 [.138] Ni + 1.3 [.051] Au		

*Consult us


All dimensions are given for information only and are in mm [inch], except as otherwise specified

HILINX 1.905 >>> SIGNAL CONTACTS (1)**MALE CONTACTS FOR PLUGS****Short straight PC tail***


- Thru hole soldering
- Daughter board or mezzanine connection
- PCB thickness: 1.8_{MAX} [.071]

*Consult us***YDS****Standard straight PC tail***

- Thru hole soldering
- Daughter board or mezzanine connection
- PCB thickness: 2.5_{MAX} [.098]

*Consult us***YD****Long straight PC tail***

- Thru hole soldering
- Daughter board or mezzanine connection
- PCB thickness: 3.5_{MAX} [.138]

*Consult us***YDL****Solder cup***

- Hard soldering on wire
- Daughter board for cable to board connection
- Solder cup for 24 to 28 AWG wire

*Consult us***Z**

	YDS*	YD*	YDL*	Z*
L_{MAX}	2.8 ± 0.2 [.110 ± .008]	3.5 ± 0.2 [.140 ± .008]	4.4 ± 0.2 [.173 ± .008]	5 _{MAX} ± 0.2 [.197 ± .008]
Termination section		Ø 0.51 _{MAX} [.020]		Ø 0.8 _{MAX} [.032]
Mating end diameter			Ø 0.635 ± 0.02 [.025 ± .001]	
Plating µm [µin]				1 [.039] Cu + 3.5 [.138] Ni + 1.3 [.051] Au


Consult usAll dimensions are given for information only and are in mm [inch], except as otherwise specified*

HILINX 1.905 >>> SPECIAL CONTACTS (2)

HYBRID MODULES FOR 3-ROW CONNECTORS*

POWER contacts

Straight female power module




- Thru hole soldering
- Mother board
- 2 straight female contacts
- 20A / contact
- PCB thickness: 1.8 [.071] to 3.4 [.134]
- Termination section \varnothing 1.4_{MAX} [.055]

Module designation

PF1

Right angle male power module




- Thru hole soldering
- Daughter board
- 2 right angle male contacts
- 20A / contact
- PCB thickness: 1.8 [.071] to 3.4 [.134]
- Termination section \varnothing 1.2_{MAX} [.047]

Module designation

PM1

RADSOOK® contacts

Female cavity module for RADSOOK® contact




- 1 cavity for male RADSOOK® contact
- Mother board
- 70A / contact
- Termination section: the body shape, the section and the length of the termination are specific to your need: *consult us*

Module designation

PF2

Right angle male RADSOOK® contact




- Fixing with retainer
- Daughter board
- 1 male RADSOOK® contact
- 70A / contact
- H: the body shape, the section and the length of the termination are specific to your need: *consult us*

Module designation

PM2

AMPHELUX™ ARINC 801 termini

Female amphenlux™ module




- 2 amphenlux™ termini
- Multimode
- Modules are supplied less contacts, *consult us*
- Complied with the ARINC 801 specification
- Keyed to provide anti-rotation

Module designation

AXF

Male amphenlux™ module




- 2 amphenlux™ termini
- Multimode
- Modules are supplied less contacts, *consult us*
- Complied with the ARINC 801 specification
- Keyed to provide anti-rotation

Module designation

AXM

	PF1	PF2	PM1	PM2	AXF	AXM
A	4.1 ± 0.2 [.161 ± .008]	7.62_{MAX} [.300]	2.8 ± 0.2 [.110 ± .008] 3.5 ± 0.2 [.140 ± .008] 4.4 ± 0.2 [.172 ± .008]	6.5 [.256]	28.5 ± 0.2 [1.122 ± .008]	23.6 ± 0.2 [.929 ± .008]
B				8.23 [.324]		
C				10.1_{MAX} [.398]		

HILINX 1.905 >>> SPECIAL CONTACTS (2)**HYBRID MODULES FOR 3-ROW CONNECTORS*****COAXIAL contacts****Straight female coaxial module**

- Thru hole soldering
- Mother board or mezzanine connection
- 2 cavities for straight coaxial female contacts
- For more information, *consult us*
- Modules are supplied less contacts

Module designation **CF1 F041****Straight male coaxial module**

- Thru hole soldering
- Mezzanine connection
- 2 cavities for straight coaxial male contacts
- For more information, *consult us*
- Modules are supplied less contacts

Module designation **CF1 M041****Right angle female coaxial module**

- Thru hole soldering
- Extended card
- 2 cavities for right angle coaxial female contacts
- For more information, *consult us*
- Modules are supplied less contacts

Module designation **CM1 F032****Right angle male coaxial module**

- Thru hole soldering
- Daughter board or extended card
- 2 cavities for right angle coaxial male contacts
- For more information, *consult us*
- Modules are supplied less contacts

Module designation **CM1 M032****TECHNICAL CHARACTERISTICS**

Impedance (Ω)	50
Voltage rating (V RMS)	180
Current rating (mA)	500
Contact retention (N)	50 _{MIN}
Frequency range (GHz)	0 to 1
Contact resistance (mΩ)	12 _{MAX}
SWR (at 1 GHz)	1.3
Insertion and extraction force per contact (N)	1 ≤ F ≤ 15


* Hybrid modules will be preferably positioned on the connector sides

HILINX 1.905 >>> KEYING & GUIDING (3)




FULL ROUND GUIDES

Standard




For receptacle:




- 1 female socket and 1 male pin
- Non keying
- Nickel over brass
- Mating with 65 or 69 keying
- MIL-DTL-55302 PN: X

65

Reversed





For receptacle:



- 1 male pin and 1 female socket
- Non keying
- Nickel over brass
- Mating with 66 or 70 keying

66



Two male guide pins



- 2 male guide pins
- Non keying
- Nickel over brass
- Mating with 68 or 72 keying

67

Two female guide sockets



- 2 female guide sockets
- Non keying
- Nickel over brass
- Mating with 67 or 71 keying

68

LONG FULL ROUND GUIDES

Long

- 1 female socket and 1 male pin
- Non keying
- Nickel over brass
- Mating with 69 or 65 keying

69

Long reversed

- 1 male pin and 1 female socket
- Non keying
- Nickel over brass
- Mating with 70 or 66 keying

70

Long, two male guide pins

- 2 male guide pins
- Non keying
- Nickel over brass
- Mating with 72 or 68 keying

71

Long, two female guide sockets

- 2 female guide sockets
- Non keying
- Nickel over brass
- Mating with 71 or 67 keying

72

Non keying male pin guide

Non keying female socket guide

Keying male pin guide

Keying female socket guide

d

 2.7 ± 0.2 [$1.06 \pm .008$]

Important note


All dimensions are in inch, except as otherwise specified.

HILINX 1.905 >>> KEYING & GUIDING (3)



D SHAPED GUIDES


D shaped male guide pin



- 4 keying possibilities
- Realignment capability: 1 [.039]
- Nickel over brass
- MIL-DTL-55302 PN: Y[-01 thru -64]

01 thru 64



D shaped female guide socket



- 4 keying possibilities
- Realignment capability: 1 [.039]
- Nickel over brass
- MIL-DTL-55302 PN: Y[-01 thru -64]

01 thru 64

CONNECTOR POLARIZATION WITH 'D' SHAPED GUIDE PINS AND SOCKETS



-1		-9		-17		-25		-33		-41		-49		-57	
-2		-10		-18		-26		-34		-42		-50		-58	
-3		-11		-19		-27		-35		-43		-51		-59	
-4		-12		-20		-28		-36		-44		-52		-60	
-5		-13		-21		-29		-37		-45		-53		-61	
-6		-14		-22		-30		-38		-46		-54		-62	
-7		-15		-23		-31		-39		-47		-55		-63	
-8		-16		-24		-32		-40		-48		-56		-64	

Important note

All dimensions are in inch, except as otherwise specified.


HILINX 1.905 >>> KEYING & GUIDING (3)

LOCKING



Fixed jacksets

Standard fixed jackset



73: standard

- Mating with 81, 85, 89, 93, 97, 101 & 105 fittings
- MIL-DTL-55302/190, /191, /192 & /193 PN: F
- 74: reversed**
- Mating with 82, 86, 90, 94, 98, 102 & 106 fittings
- 75: two jackscrews**
- Mating with 84, 88, 92, 96, 100, 104 & 108 fittings
- 76: two jacksockets**
- Mating with 83, 87, 91, 95, 99, 103 & 107 fittings

73 thru 76

Long fixed jackset

For receptacle and straight plug, w/o mounting ears

77: standard

- Mating with 81, 85, 89, 93, 97, 101 & 105 fittings

78: reversed

- Mating with 82, 86, 90, 94, 98, 102 & 106 fittings

79: two jackscrews

- Mating with 84, 88, 92, 96, 100, 104 & 108 fittings


80: two jacksockets

- Mating with 83, 87, 91, 95, 99, 103 & 107 fittings

77 thru 80

Hexagonal turning jacksets

For receptacle



5.08 [.200] short hexagonal turning jackset

105: standard

- Mating with 73 & 77 fittings
- MIL-DTL-55302/190, /191, /192 & /193 PN: S

106: reversed

- Mating with 74 & 78 fittings

107: two jackscrews

- Mating with 76 & 80 fittings

108: two jacksockets

- Mating with 75 & 79 fittings

12.45 [.490] medium hexagonal turning jackset

93: standard

- Mating with 73 & 77 fittings

94: reversed

- Mating with 74 & 78 fittings


95: two jackscrews

- Mating with 76 & 80 fittings

96: two jacksockets

- Mating with 75 & 79 fittings

For plug



105 thru 108

93 thru 96

13.84 [.545] hexagonal turning jackset

97: standard

- Mating with 73 & 77 fittings
- MIL-DTL-55302/190, /191, /192 & /193 PN: N

98: reversed

- Mating with 74 & 78 fittings

99: two jackscrews

- Mating with 76 & 80 fittings

100: two jacksockets

- Mating with 75 & 79 fittings

17.78 [.700] hexagonal turning jackset

101: standard

- Mating with 73 & 77 fittings

102: reversed

- Mating with 74 & 78 fittings

103: two jackscrews

- Mating with 76 & 80 fittings

104: two jacksockets

- Mating with 75 & 79 fittings

105 thru 108

5.08 [.200]

93 thru 96

12.45 [.490]

97 thru 100

13.84 [.545]

101 thru 104


17.78 [.700]

97 thru 100

101 thru 104

Important note

- All dimensions are in inch, except as otherwise specified.
- All the fittings are in passivated stainless except as otherwise specified.

HILINX 1.905 >>> KEYING & GUIDING (3)**LOCKING****Slotted turning jacksets***For receptacle***12.45 [.490] short slotted turning jackset****13.84 [.545] medium slotted turning jackset****85: standard**

- Mating with 73 & 77 fittings
- MIL-DTL-55302/190, /191, /192 & /193 PN: M

86: reversed

- Mating with 74 & 78 fittings

87: two jackscrews

- Mating with 76 & 80 fittings

88: two jacksockets

- Mating with 75 & 79 fittings

89: standard

- Mating with 73 & 77 fittings

90: reversed


- Mating with 74 & 78 fittings

91: two jackscrews

- Mating with 76 & 80 fittings

92: two jacksockets

- Mating with 75 & 79 fittings

For plug**85 thru 88****89 thru 92****17.78 [.700] slotted turning jackset****81: standard**

- Mating with 73 & 77 fittings
- MIL-DTL-55302/190, /191, /192, & /193 PN: L

82: reversed

- Mating with 74 & 78 fittings

83: two jackscrews

- Mating with 76 & 80 fittings

84: two jacksockets

- Mating with 75 & 79 fittings

	L +0.5 -0.36 [+.020 -.014]
85 thru 88	12.45 [.490]
89 thru 92	13.84 [.545]
81 thru 84	17.78 [.700]

81 thru 84**Important note**





- All dimensions are in inch, except as otherwise specified.
- All the fittings are in passivated stainless except as otherwise specified.

HILINX 1.905 >>> KEYING & GUIDING (3)



REALIGNMENT CAPABILITY

In the longitudinal axis In the lateral axis



MATING SEQUENCE

Guiding	Signal contact	Mated connector
<p>5.4 [0.213]</p>	<p>0.8 ± 0.1 [0.031 ± .004]</p>	<p>0 [0]</p>

HILINX 1.905 >>> SIGNAL VERSION ONLY**COMPATIBILITY WITH THE MIL DTL 55302/190 TO /193 DETAILED SHEETS****MIL-DTL-55302
/190 to /193**

MIL-DTL-55302	Series	Number of contacts	Type of contacts	Hardware	Deviation	Comments
MIL-DTL-55302/191	HLX P 2	10, 20, 30, 40, 50, 60, 70 80, 90, 100	A = YDS B = YD C = YDL	X = 65 Y = 01 thru 64 F = 73 S = 105 N = 97 L = 81 M = 85	-000	X = full round guides Y = D-shaped F = fixed jackset S = .200 short turning hexagonal jackset N = .545 turning hexagonal jackset L = .700 turning slotted jackset M = .490 short turning slotted jackset
MIL-DTL-55302/193	HLX P 3	122, 152	A = YCS B = YC C = YCL	X = 65 Y = 01 thru 64 F = 73 S = 105 N = 97 L = 81 M = 85	-000	X = full round guides Y = D-shaped F = fixed jackset S = .200 short turning hexagonal jackset N = .545 turning hexagonal jackset L = .700 turning slotted jackset M = .490 short turning slotted jackset
MIL-DTL-55302/190 MIL-DTL-55302/190 L	HLX R 2	10, 20, 30, 40, 50, 60, 70 80, 90, 100		X = 65 Y = 01 thru 64 F = 73 S = 105 N = 97 L = 81 M = 85	-000	X = full round guides Y = D-shaped F = fixed jackset S = .200 short turning hexagonal jackset N = .545 turning hexagonal jackset L = .700 turning slotted jackset M = .490 short turning slotted jackset
MIL-DTL-55302/192 MIL-DTL-55302/192 L	HLX R 3	122, 152	A = Z* B = YDS C = YD D = YDL E = Y* F = WS* G = W* H = WL*	X = 65 Y = 01 thru 64 F = 73 S = 105 N = 97 L = 81 M = 85	-000	X = full round guides Y = D-shaped F = fixed jackset S = .200 short turning hexagonal jackset N = .545 turning hexagonal jackset L = .700 turning slotted jackset M = .490 short turning slotted jackset


HILINX 1.905 >>> SIGNAL CONTACT VERSION (4)

TYPICAL ARRANGEMENTS 2 & 3 ROWS

n indicates the total number of signal contacts.




Signal contacts on 2 rows*, from 10 to 100 contacts*



n = 10, 20, 30, 40, 50, 60, 70, 80, 90 or 100

C	$n \times 0.9525 - 1.905$
D	$C + 8.0525$
E	$D + 4.6$
F	$E + 4.29$
G	$F + 4.41$
h	5.12
I	7.62

Signal contacts on 3 rows from 11 to 206 contacts*




n = 011, 023, 035, 047, 059, 071, 080, 092, 104, 122, 140, 152, 182 or 206

C	$n \times 0.635 - 1.27$
D	$C + 6.35$
E	$D + 4.84$
F	$E + 4.29$
G	$F + 4.41$
h	7
I	7.62

HILINX 1.905 >>> SIGNAL CONTACT VERSION (4)

LAYOUTS 2 & 3 ROWS

The boards are shown from the connector side.
All contact outputs are equidistant.



n		YD/YDS/YDL & YP CONTACT (female for receptacle)*																				
2 ROWS FROM 10 TO 100 CONTACTS																						
		$n = 10, 20, 30, 40, 50, 60, 70, 80, 90 \text{ or } 100$																				
		$\begin{matrix} C \\ F \end{matrix} \quad n \times 0.9525 - 1.905$ $C + 16.9425$																				
3 ROWS FROM 11 TO 206 CONTACTS																						
		$n = 011, 023, 035, 047, 059, 071, 080, 092, 104, 122, 140, 152, 182 \text{ or } 206$																				
		$\begin{matrix} C \\ F \end{matrix} \quad n \times 0.635 - 1.27$ $C + 15.48$																				
2 ROWS FROM 10 TO 100 CONTACTS		n	YC/YCS/YCL CONTACT (male for plug)*																			
		$n = 10, 20, 30, 40, 50, 60, 70, 80, 90 \text{ or } 100$																				
		$\begin{matrix} C \\ F \end{matrix} \quad n \times 0.635 - 1.27$ $C + 16.9425$																				
3 ROWS FROM 11 TO 206 CONTACTS																						
		$n = 011, 023, 035, 047, 059, 071, 080, 092, 104, 122, 140, 152, 182 \text{ or } 206$																				
		$\begin{matrix} C \\ F \end{matrix} \quad n \times 0.635 - 1.27$ $C + 15.48$																				

R ₁	R ₂	R ₄	d ₁	d' ₁	p	p / 2	p ₁	h ₀	h ₁
2.8 [.110]	Not compulsory 3.75 ± 0.1 [.148 ± .004]	0.65 _{MIN} [.026]	8 [.315]	7.747 [.305]	1.905 [.075]	0.9525 [.037]	2.54 [.100]	4.7 _{MAX} [.185]	0.32 [.013]

*in mm: 1mm = 0.03937 inch

All dimensions are given for information only and are in mm [inch], except as otherwise specified


HILINX 1.905 >>> HYBRID VERSION (4)

DIMENSIONS 3 ROWS**

s indicates the total number of special contacts.
n indicates the total number of signal contacts.



Power contacts 20A*




s = 2, 4, 6...

$$0,635 * n - 1,27$$

C	6,985 + s*5,575 + n*0,635
D	D + 4,84
E	E + 4,29
F	F + 4,41
G	5,08
d2	6,07
d3	4,1625
d4	3,81
d5	6,032
d6	6,39
d7	7

RADSOK® contacts 70A*




s = 1, 2, 3...

$$0,635 * n - 1,27$$

C	6,985 + s*7,62 + n*0,635
D	D + 4,84
E	E + 4,29
F	F + 4,41
G	7
h	6,985
d1	3,81
d2	7,62
d3	5,7155

AMPHELUX™ contacts*



s = 2, 4, 6...

$$0,635 * n - 1,27$$

C	6,985 + s*7,55 + n*0,635
D	D + 4,84
E	E + 4,29
F	F + 4,41
G	7
h	6,924
d1	6,65
d2	4,702
d3	7,876
d4	8,45

Coaxial contacts

Please consult us


* in mm: 1mm = 0.03937 inch

** Hybrid modules will be preferably positioned on the connector sides

HILINX 1.905 >>> HYBRID VERSION (4)

LAYOUTS 3 ROWS**

The boards are illustrated from the connector side
All contacts outputs are equidistant.



With YDS/YD/YDL & YP CONTACT (female for receptacle)*

WITH POWER CONTACT 20A		C 0.635 x n - 1.27 D 6.985 + n x 0.635 + s x 5.575 F D + 9.13
WITH RADSOK® CONTACT 70A		C 0.635 x n - 1.27 D 6.985 + n x 0.635 + s x 7.62 F D + 9.13 L (s - 1) x 7.62 M 6.5 ± 0.1
WITH AMPHELUX™ CONTACT		C 0.635 x n - 1.27 D 6.985 + n x 0.635 + s x 7.55 F D + 9.13 L (s - 2) x 7.55 M 7.8 ± 0.1

YDS/YD/YDL YP	d1	d'1	d2	d3	d4	d5	d8	d9	p	R1	R2	R3	R4
Power		10.605 [.418]	5.080 [.200]	6.072 [.239]		3.810 [.150]	10.963 [.432]	3.210 [.126]	1.905 [.075]	2.8 ± 0.1 [.110 ± 0.004]	3.75 [.148]	1.5 MIN [.059 MIN]	0.65 MIN [.026 MIN]
RADSOK®		11.557 [.455]	3.810 [.150]		7.620 [.300]								
Amphelux™	8 MAX [.315 MAX]		8.8 MAX [.346 MAX]	1.2 MAX [.047 MAX]	1.2 MAX [.047 MAX]								

With YC/YCS/YCL CONTACT (male for plug)*

WITH POWER CONTACT 20A		C 0.635 x n - 1.27 F 16.115 + n x 0.635 + s x 5.575
WITH RADSOK® CONTACT 70A		C 0.635 x n - 1.27 F 16.115 + n x 0.635 + s x 7.62
WITH AMPHELUX™ CONTACT		C 0.635 x n - 1.27 F 16.115 + n x 0.635 + s x 7.55

YCS/YC/YCL	h0	h1	h2	d'1	d2	d3	d4	d5	d8	d9	p1	R1	R3	R4	R5
Power		1.680 [.066]	10.605 [.418]	5.080 [.200]	6.072 [.239]	x	3.810 [.150]	10.963 [.432]	3.210 [.126]		2.8 ± 0.1 [.110 ± 0.004]	1.5 MIN [.059 MIN]	0.65 MIN [.026 MIN]		
RADSOK®	4.7 MAX [.185 MAX]	0.320 [.013]	11.557 [.455]	3.810 [.150]	4.763 [.187]	7.620 [.300]								3.8 MIN [.150 MIN]	
Amphelux™															

* in mm: 1mm = 0.03937 inch

** Hybrid modules will be preferably positioned on the connector sides

All dimensions are given for information only and are in mm [inch], except as otherwise specified

HILINX >>> TOOLING

TOOLING

HLX ODP



- Screw driver for guiding devices

Part number

HLX ODP

23550



- Removal tool
- For coaxial contacts
- Rear release
- HiLinX^{2.54}

Part number

23550

CRIMPING TOOL

809801




- For male and female contacts X
- AWG 26 to 22
- Additional turret for female contacts
PN M22520/2-06
- Military reference : M22520/2-01

Part number

809801

INSERTION AND REMOVAL TOOLS

809819 - Insertion tool



- For female contacts X
- Metallic tool (22D)
- Straight type

Part number

809819

809856 - Insertion & removal tool



- For male and female contacts X
- Plastic tool (22D)
- Military reference : M81969/14-01

Part number

809856

NOTES

HDAS

The high competitive connector


Amphenol reduces the pitch and increases the density of contacts with the brand new HDAS range.

1.905 x 1.905 [.075 x .075] staggered grid pattern, from 3 to 6 rows*.

With its robust and simple design, high density, and high performance to extreme conditions, HDAS is the right connector when installation, cost, and reliability must be considered.

100% cost effective

The press-fit technology allows significant assembly cost reduction on the backplane while ensuring an extreme reliability, even for the thickest motherboards. No more solder joints, pre-baking, or cleaning.



100% optimized

- The guiding/keying devices can be polarized in 6 positions within their own cavities, i.e. 36 keying possibilities per connector.
- The lateral rails on the male connector provide optimal protection to the contacts.
- The mechanical protection of the female contacts is provided per design.

100% performing

- The proven starclip technology of the socket provides a higher current rate, as well as an improved robustness as compare to the traditional technologies.
- LCP material allows all types of soldering processes as well as a higher temperature rating.
- HDAS has surpassed all MIL-DTL-55302 requirements as well as the new demands for military transportation.

QUICK SELECTION GUIDE


Signal contacts *

①

FEMALE



MALE



Keying & Guiding *

②

FEMALE FITTING

Keying & guiding

MALE FITTING

Guiding only
or
Keying & guiding

Other fitting, guiding or
keying devices, consult us.

Housing

③

3 ROWS

50, 77, 119, 152

4 ROWS

102, 202

5 ROWS

253

6 ROWS

303*, 402*

PAGE 56

PAGE 57

PAGE 58

PAGE 60

* For special terminations of contacts (SMT, solder-cup, ...), special fittings and guiding devices or special arrangements, do not hesitate to consult us.

HDAS Series

The high density monolithic connector



HDAS Series

Table of contents

HDAS product range	52
Female signal contacts for receptacles	56
Male signal contacts for plugs	57
Female & Male fittings	58
Realignment capability / Mating sequence	59
Typical arrangements 3 & 4 rows	60
Layouts 3 & 4 rows	61
Typical arrangement 5 rows	62
Layout 5 rows	63
Tooling	64

The HDAS series serves various **markets**, including:




Commercial Avionics & Airframe



Military Avionics & Airframe



C4ISR



Navy




Ground vehicles



Industrial

HDAS>>> GENERAL SPECIFICATIONS



- Robust technology
- Dedicated to harsh environment (high temperature and vibration levels)
- The most effective
- 1.905[.075] staggered grid (0.9525[.0375] offset), 1.905[.075] between rows

Main characteristics

- High density: 0.16 cts/mm² [103 cts/inch²]
- 9 sizes from 3 to 6* rows, 50 to 402* signal contacts
- 4.5A per signal contact
- DWV: 750 Vrms
- Press-fit solderless attachment technology available
- Lateral rails to protect male pins from external damage


Markets



Main applications



Terminations



Recommended configurations




Standard

Exceeds some MIL-DTL-55302 requirements.

MIL-DTL-55302

How to order




Female	Male	Description
Consult us	YC	Right angle PC tail standard length
Consult us	YCS	Right angle PC tail short length
	YD	Straight PC tail standard length
	YDS	Straight PC tail short length
YP	Consult us	Press fit
Consult us	Z	Solder cup

Signal contact (see pages 56 to 57)

HDAS - --- - --- - --- - ---

Number of signal contacts (see pages 60 to 63)	
3 rows	050 077 119 152
4 rows	102 202
5 rows	253
6 rows	303* 402*




Termination plating
Blank Tin lead on female terminations Gold on male terminations
LF Lead free on female terminations (for receptacle - YD & YDS only)

* Consult us


All dimensions are given for information only and are in mm [inch], except as otherwise specified

HDAS >>> TECHNICAL SPECIFICATIONS

Dimensional characteristics

 $H = 8_{\text{MAX}} [.315]$ $B_{\text{MIN}} = L + X$

X = Board thickness + hardware thickness

 $d = 16_{\text{MAX}} [.630]$ $e = 1.6 [.063] \text{ to } 5.5 [.217] \text{ or } 2.5_{\text{MIN}} [.098] \text{ (for YP contacts)}$ 

L	3 rows	4 rows	5 rows	6 rows*
	8.21 _{MAX} [.323]	10.11 _{MAX} [.398]	12.02 _{MAX} [.473]	13.72 _{MAX} [.540]

Female contact



Starclip female technology: 6 tines for better reliability

- 6 contact tines instead of 4
- Excellent mechanical and electrical reliability
- Better resistance to high vibrations
- Improved electrical conductivity
- 100% compatible with other connectors


Material

- Hood: machined brass alloy
- Starclip: CuBe[BeCu], stamped and formed

Plating

- Hood: tin lead or lead free
- Starclip: gold over nickel

Male contact



- Mating end diameter:** $\emptyset 0.68 [.027]$
- Contact section** (mating side): $0.36 \text{ mm}^2 [.0006 \text{ inch}^2]$
- Material:** machined brass alloy
- Plating:** gold over nickel

Materials

- Guiding devices:** electroless nickel plating over brass
- Plastic insert:** thermoplastic LCP, 30% glass-fiber filled

MECHANICAL CHARACTERISTICS

Backoff¹ (mm)	1.2 [.0472] _{MAX}
Mating force per contact (N)	$0.6 < F < 0.8$
Unmating force per contact (N)	$0.3 < F < 0.5$
Durability cycles	500
Sinusoidal vibrations (20 to 2000 Hz) micro discontinuity 2ns	15 g
Random vibrations (600 to 700 Hz) micro discontinuity 2ns	$2.682 \text{ g}^2 / \text{Hz}$
Shocks micro discontinuity 2ns	100 g

MIL-DTL-55302 sections

N/A
§ 4.5.3
§ 4.5.3
§ 4.5.9
§ 4.5.10
§ 4.5.10
§ 4.5.10
§ 4.5.10

¹: When both connectors are fully mated, the backoff is the maximum distance the connectors can be unmated while functioning properly

ENVIRONMENTAL CHARACTERISTICS


Thermal shocks (°C)	-65 / +150
Salt Spray (hours)	96
Humidity	
Days	10
Temperature (°C)	25/65
Humidity rate (%)	90-95

§ 4.5.13
§ 4.5.11

ELECTRICAL CHARACTERISTICS

Current rating per contacts (A)	4.5 (see derating curve)
Insulation resistance (GΩ)	5_{MIN}
Contact resistance (mΩ)	10_{MAX}
Dielectric Withstanding Voltage (Vrms)	750 _{MIN}


§ 4.5.5
§ 4.5.8
§ 4.5.12
§ 4.5.7.1



All dimensions are given for information only and are in mm [inch], except as otherwise specified

HDAS >>> SIGNAL CONTACTS (1)

FEMALE CONTACTS FOR RECEPTACLES



Starclip female technology



- 6 contact tines instead of 4
- Excellent mechanical and electrical reliability
- Better resistance to high vibrations
- Improved electrical conductivity
- 100% compatible with other connectors




- Size 23: high average current
- Clip for male contact Ø 0.68 [.027]
- **Plating** on active part (clip)

Cu	Ni	Au
1 [.039]	3.5 [.138]	1.3 [.051]

Female contacts

Standard straight PC tail




- Thru hole soldering
- Mother board or mezzanine connection
- PCB thickness: 5.5_{MAX} [.217]



Termination style

YD

Short straight PC tail




- Thru hole soldering
- Mother board or mezzanine connection
- PCB thickness: 3.5_{MAX} [.138]



Termination style

YDS

Press-fit





- For solderless assembly
- Mother board or mezzanine connection
- PCB thickness: 2.5_{MIN} [.098]



Termination style

YP


	YD	YDS	YP
A_{MAX}	6.85 ± 0.2 [.270 ± .008]	4.65 ± 0.2 [.183 ± .008]	2.6 ± 0.2 [.102 ± .008]
Termination section	Ø 0.45 _{MAX} [.018]		Ø 0.82 [.032]
Standard termination plating µm [µin]	2.5 [.098] Ni + 5 [.197] Sn Pb		2 [.079] Ni electroless + 2 [.079] Ni electrolytic + 10 [.394] Sn Pb
RoHS termination plating* µm [µin]	3 [.118] Ni + 10 [.394] bright pure Sn		

HDAS >>> SIGNAL CONTACTS (1)**MALE CONTACTS FOR PLUGS****Standard straight PC tail**

- Thru hole soldering
- Daughter board or mezzanine connection
- PCB thickness: 5.5 _{MAX} [.217]




Termination style

Short straight PC tail

- Thru hole soldering
- Daughter board or mezzanine connection
- PCB thickness: 3.3 _{MAX} [.130]




Termination style

YDS**Standard right angle PC tail**

- Thru hole soldering
- Daughter board
- PCB thickness: 2.8 _{MAX} [.110]




Termination style

Short right angle PC tail

- Thru hole soldering
- Daughter board
- PCB thickness: 1.6 _{MAX} [.063]



Termination style

YCS**Solder cup**

- Hard-soldering on wire
- AWG gauge 26 to 22



Termination style

Z

	YD	YDS	YC	YCS	Z
A _{MAX}	6.6 ± 0.2 [.260 ± .008]	4.4 ± 0.2 [.173 ± .008]	4 ± 0.2 [.157 ± .008]	2.85 ± 0.2 [.112 ± .008]	5 ± 0.2 [.197 ± .008]
Termination section	$\varnothing 0.45$ _{MAX} [.018]				$\varnothing 0.93$ _{MAX} [.037]
Mating end diameter	$\varnothing 0.68$ _{MAX} [.027] 23 (according to MIL DTL 55302)				
Plating μm [μin]	1 [.039] Cu + 3.5 [.138] Ni + 1 [.039] Au				


HDAS >> KEYING & GUIDING (2)



FEMALE FITTINGS FOR RECEPTACLES

Keying & guiding

000 style - For YD/YDS/YP female contacts




- Standard female fitting
- Chassis or mother board
- Fixed receptacle
- Nickel over brass

HDAS E *** *** -000

To order the fitting alone: HDAS E 000

004 style - For YD/YDS/YP female contacts




- Intermediate female fitting
- Chassis or mother board
- Fixed receptacle
- Nickel over brass

HDAS E *** *** -004

MALE FITTINGS FOR PLUGS

Guiding only


002 style - For YC/YCS male contacts



- Daughter board
- Free plug
- Nickel over brass

HDAS F *** YC* -002

002 style - For YD/YDS male contacts




- Daughter board or mezzanine connection
- Nickel over brass

HDAS F *** YD* -002

Keying & guiding


000 style - For YC/YCS male contacts



- Daughter board
- Free plug
- 6 keying positions
- Nickel over brass

HDAS F *** YC* -000

000 style - For YD/YDS male contacts



- Daughter board or mezzanine connection
- 6 keying positions
- Nickel over brass

HDAS F *** YD* -000

	Female fittings		Male fittings			
	000 style for YD / YDS / YP female contacts	004 style for YD / YDS / YP female contacts	002 style Guiding for YC / YCS male contacts	002 style Guiding for YD / YDS male contacts	000 style Keying for YC / YCS male contacts	000 style Keying for YD / YDS male contacts
A			Hex 4 [.157]	Hex 5 [.197]	Hex 4 [.157]	Hex 5 [.197]
C	M 2.5 [.098]			M 2.5 [.098]		M 2.5 [.098]
D	7.15 ±0.2 [.281 ±.008]	5.5 ± 0.2 [.217 ± .008]	1.2 _{MAX} [.472]	6 _{MAX} [.236]	1.2 _{MAX} [.472]	6 _{MAX} [.236]
E	3.2 _{MAX} [.126]	D -2.8 [.117]				

Fitting compatibility table





	Male fittings for plugs	
	002	000
Female fittings for receptacles	000	OK
	004	OK

HDAS >>> KEYING & GUIDING (2)



REALIGNMENT CAPABILITY

In the longitudinal axis In the lateral axis



MATING SEQUENCE

Keying / Guiding	Rails	Electrical contact	Mated connector
 $1.6 \pm 0.35 [0.063 \pm .014]$	 $1.3 [0.051]$	 $0.5 \pm 0.3 [0.020 \pm .012]$	 $1.1 \pm 0.3 [0.043 \pm .012]$

HDAS >>> 3 & 4 ROWS (3)

TYPICAL ARRANGEMENTS 3 & 4 ROWS

n is the total number of signal contacts.




Signal contacts on 3 rows*		
receptacle	n	050, 077, 119
receptacle	C	(n - 2) x 0.635
receptacle	D	C + 11.43
receptacle	E	D + 9.325
receptacle	h_3	7.01 _{MAX} [.276]
receptacle	h_3'	8.21 _{MAX} [.323]
receptacle	h_3''	9.36 _{MAX} [.369]
plug	n	152
plug	C	95.25 [3.750]
plug	D	106.68 [4.200]
plug	E	116.5 [4.586]

Signal contacts on 4 rows*		
receptacle	n	102
receptacle	C	47.625 [1.875]
receptacle	D	59.175 [2.330]
receptacle	E	68.50 [2.697]
receptacle	h_4	8.91 _{MAX} [.351]
receptacle	h_4'	10.11 _{MAX} [.398]
receptacle	h_4''	11.26 _{MAX} [.443]
plug	n	202
plug	C	95.25 [3.750]
plug	D	106.68 [4.200]
plug	E	116.5 [4.586]

HDAS >>> 3 & 4 ROWS (3)

LAYOUTS 3 & 4 ROWS

The boards are shown from the connector side.
All contact outputs are equidistant.




n 50 / 77 / 119 / 152 3 rows		YD/YDS CONTACT (male and female for plug and receptacle)* YP CONTACT (female for receptacle)										
			<table border="1"> <tr> <td>n</td><td>050, 077, 119, 152</td></tr> <tr> <td>C</td><td>$(n - 2) \times 0.635$</td></tr> <tr> <td>D</td><td>$C + 11.43$</td></tr> </table>	n	050, 077, 119, 152	C	$(n - 2) \times 0.635$	D	$C + 11.43$			
n	050, 077, 119, 152											
C	$(n - 2) \times 0.635$											
D	$C + 11.43$											
102 / 102 4 rows			<table border="1"> <tr> <td>n</td><td>102</td><td>202</td></tr> <tr> <td>C</td><td>47.625 [1.875]</td><td>95.25 [3.750]</td></tr> <tr> <td>D</td><td>59.175 [2.330]</td><td>106.68 [4.200]</td></tr> </table>	n	102	202	C	47.625 [1.875]	95.25 [3.750]	D	59.175 [2.330]	106.68 [4.200]
n	102	202										
C	47.625 [1.875]	95.25 [3.750]										
D	59.175 [2.330]	106.68 [4.200]										
YC/YCS CONTACT (male for plug)*												
50 / 77 / 119 / 152 3 rows			<table border="1"> <tr> <td>n</td><td>050, 077, 119, 152</td></tr> <tr> <td>C</td><td>$(n - 2) \times 0.635$</td></tr> <tr> <td>D</td><td>$C + 11.43$</td></tr> </table>	n	050, 077, 119, 152	C	$(n - 2) \times 0.635$	D	$C + 11.43$			
n	050, 077, 119, 152											
C	$(n - 2) \times 0.635$											
D	$C + 11.43$											
102 / 102 4 rows			<table border="1"> <tr> <td>n</td><td>102</td><td>202</td></tr> <tr> <td>C</td><td>47.625 [1.875]</td><td>95.25 [3.750]</td></tr> <tr> <td>D</td><td>59.175 [2.330]</td><td>106.68 [4.200]</td></tr> </table>	n	102	202	C	47.625 [1.875]	95.25 [3.750]	D	59.175 [2.330]	106.68 [4.200]
n	102	202										
C	47.625 [1.875]	95.25 [3.750]										
D	59.175 [2.330]	106.68 [4.200]										



	h_0	h_1	d_2	$d_2/2$	P	$p/2$	d_1	$2d_1$	R_1	R_2
102							5.7775 [.227]	11.555 [.455]		
50, 77, 119	2.1 _{MAX} [.083]	5.08 [.200]	2.54 [.100]	1.27 [.050]	1.905 [.075]	0.9525 [.0375]			$\emptyset 2.8^{+.01}_{-.01} [.110^{+.004}]$	$\emptyset 0.6_{-.05} [.024]$ with metallization
152							5.715 [.225]	11.43 [.450]		$\emptyset 0.6 \pm 0.05$ for YP contacts
202										$[\emptyset 0.024 \pm .002]$

HDAS >>> 5 ROWS (3)

TYPICAL ARRANGEMENT 5 ROWS




Signal contacts on 5 rows

receptacle		253
plug		
	n	253
	C	95.25 [3.750]
	D	106.68 [4.200]
	E	116.5 _{MAX} [4.587]
	h₅	10.82 _{MAX} [.426]
	h_{5'}	12.02 _{MAX} [.473]
	h_{5''}	13.17 _{MAX} [.519]


HDAS >>> 5 ROWS (3)

LAYOUT 5 ROWS



YD/YDS CONTACT (male and female for plug and receptacle) YP CONTACT (female for receptacle)


253 contacts



n	253
C	95.25 [3.750]
D	106.68 [4.200]

YC/YCS CONTACT (male for plug)

253 contacts





n	253
C	95.25 [3.750]
D	106.68 [4.200]

h₀	h₁	d₂	p	p/2	d1	R₁	R₂
2.1 _{MAXI} [.083]	5.08 [.200]	2.54 [.100]	1.905 [.075]	0.9525 [.0375]	5.715 [.225]	$\varnothing 2.8^{+.01}_{-.004}$ [.110 ^{+.004} _{-.004}]	$\varnothing 0.6_{-.05}$ MIN [.024] with metallization $\varnothing 0.6 \pm 0.05$ for YP contacts [$0.024 \pm .002$]

HDAS >>> TOOLING

MOUNTING OF A STRAIGHT PLUG (YD) ON A BOARD





- Assemble alignment spacers (C and D) with tooth chamfers facing up, then insert positioning pins (E) into holes on spacers.
- Align the connector (A) on the spacers using positioning guide (B).
- Exert slight pressure on the connector so the contact tails pass through the spacer cavities and into the PCB holes
- Remove positioning pins (B and E) and alignment spacers (C and D)
- Exert pressure on the connector until it butts against the board and fasten fixing accessories

Part number

HDAS ODP1 xxx

MOUNTING OF A RIGHT ANGLE (YC) PLUG ON A DAUGHTER BOARD



- Assemble alignment spacers (C and D) with tooth chamfers facing up, then insert positioning pins (E) into holes on spacers.
- Align the connector (A) on the spacers using positioning guide (B).
- Exert slight pressure on the connector so the contact tails pass through the spacer cavities and into the PCB holes
- Remove positioning pins (B and E) and alignment spacers (C and D)
- Exert pressure on the connector until it butts against the board and fasten fixing accessories

Part number

HDAS ODP2 xxx

NOTES

HDAS Series

SMASH

The high density interconnect system for harsh environment applications

The SMASH connector offers extremely high robustness where signal integrity is required. Based on an aluminium shell with 1, 2 or 3 bays, the SMASH connector can house up to 450 contacts, with up to 150 contacts per bay. The chevron grid pattern (1.905 x 1.905 [.075 x .075]) provides high contact density for advanced electronics packaging. The metallic shell is equipped with grounding, guide pins, and keying devices to ensure mechanical reliability.

The modularity

Within the standard SEM E form factor, the SMASH connector provides a wide array of signal transmission combinations. Various inserts can be housed within the robust, modular shell while meeting the standard board and chassis formats.

A connector that is adaptable to all types of mounting and soldering processes


The sculptured flex circuit termination of the daughter card connector can accept the thickest boards. No tooling is required as the design provides good alignment to the solder pads of the daughter card.

A connector dedicated to harsh environment

The Starclip technology of the socket contact (with a 6 tine clip) offers high mechanical and electrical reliability, combined with low insertion force. The SMASH connector is ruggedized to meet extreme conditions such as salt spray, vibration, and contact resistance.

Flexibility

From 1 to 3 bays with 150 or 132 signal contacts per bay, the SMASH connector is available in either chevron grid or staggered grid* patterns. It can provide RF, power, and fiber optic solutions with hybrid arrangements. LVDS signals* are also available.



QUICK SELECTION GUIDE

Signal contacts

①

FEMALE



MALE



For further terminations of contacts, consult us.

PAGE 70

PAGE 70

Housing

②

GRID

Chevron grid



Staggered grid



NUMBER OF ROWS
6 rows / 8 rows


For specific pitches or arrangements, consult us.

PAGE 72

Shell

③


1 BAY



2 BAYS



3 BAYS




With or without ground spring or rackable, consult us.

PAGE 72

*Consult us

SMASH Series

Advanced SEM E modular connector



SMASH Series

Table of contents

SMASH product range	66
Standard technology of contacts	70
Special technology of contacts	71
Standard housings and shells	72
Special housings and shells	73
Mating sequence	73
Typical arrangements & layouts 150 signal contacts	74
Typical arrangements & layouts 300 signal contacts	75
Typical arrangements & layouts 450 signal contacts	76
Typical arrangements & layouts 396 signal contacts	77

The SMASH series serves various **markets**, including:



Military Avionics & Airframe



Commercial Avionics & Airframe



C4ISR

SMASH>>> GENERAL SPECIFICATIONS



ULTRA
HIGH
DENSITY

- No tooling required. SEM E form factor
- Flexible circuit termination of the plug can be used with daughter cards of various thicknesses. Compatible with all soldering processes.
- Excellent mechanical electrical reliability
- Chevron grid pattern 1.905[.075] spacing along the row with 1.905 [.075] between rows, offset 0.635 [.025]

Main characteristics

- 3 versions with 1, 2 or 3 bays
- Each insert can house up 132 or 150 signal contacts depending on contacts sizes
- High density: 0.34 cts/mm² [130 cts/inch²]
- 3 A per contacts / DWV: 1000 Vrms / Insulation resistance: 5Gohms
- Press-fit solderless attachment possible. *Consult us*
- Aluminium shell for electrical enhancements (filters, shell to shell continuity) as well as advanced mechanical robustness.


Markets



Main applications



Recommended configurations




Standard


Exceeds some MIL-DTL-55302 requirements.

MIL-DTL-55302

Terminations



How to order




Female	Male	Description
YD	YD	Straight solder PC tail standard length
Z	Z	Solder cup
-	U01	SMT

Signal contact termination type

HDC - - - - -

Number of signal contacts	
1 cavity	132
	150
2 cavities	264
	300
3 cavities	396
	450





Amphenol Socapex capabilities for specific connector design

The metallic shell concept allows Amphenol to design numerous types of shells with various lengths and specific housings, providing:

- Insertion of specific contacts (RF, optical termini, power, high power)
- Modification of the height or type of signal contact terminations
- Customization of rack and panel shells or the addition of a ceramic plane for high-frequency filtering
- A variety of grid and footprint styles, to comply with density requirements

SMASH >>> TECHNICAL SPECIFICATIONS

Dimensional characteristics



Female contact



Starclip female technology: 6 tines for better reliability

- 6 contact tines instead of 4
- Excellent mechanical and electrical reliability
- Better resistance to high vibrations
- Improved electrical conductivity
- 100% compatible with other connectors


Material

- Hood: machined brass alloy
- Starclip: CuBe[BeCu], stamped and formed

Plating

- Hood: tin lead or lead free plating
- Starclip: gold over nickel

Male contact



- **Mating end diameter:** $\varnothing 0.635$ [.025]
- **Mating end section** (mating side): 0.32 mm^2 [.0005 inch 2]
- **Material:** machined brass alloy
- **Plating:** gold over nickel

Materials

- **Guiding devices:** passivated stainless steel 303
- **Shells:** aluminum 6060 T6
- **Plating shells:** electroless nickel
- **Plastic insert & coding devices:** thermoplastic LCP, 30% glass-fiber filled

MECHANICAL CHARACTERISTICS

Backoff¹ (mm)	1.2 _{MAX} [.047]
Mating force per contact (N)	100g
Unmating force per contact (N)	40g
Durability cycles	500
Sinusoidal vibrations (10 to 2000 Hz) micro discontinuity 2ns	15 g
Random vibrations (600 to 700 Hz) micro discontinuity 2ns	2.682 g ² / Hz
Shocks micro discontinuity 2ns	100 g / 6s

MIL-DTL-55302 sections

N/A
§ 4.5.4
§ 4.5.9
§ 4.5.10
Consult us
§ 4.5.14

¹: When both connectors are fully mated, the backoff is the maximum distance the connectors can be unmated while functioning properly

ENVIRONMENTAL CHARACTERISTICS

Thermal shocks (°C)	-65 / +150
Cycles	5
Salt Spray (hours)	96

§ 4.5.13
§ 4.5.11


ELECTRICAL CHARACTERISTICS

Current rating per contacts (A)	3 _{MAX}
Insulation resistance (GΩ)	5 _{MIN}
Contact resistance (mΩ)	10 _{MIN}
Dielectric Withstanding Voltage (Vrms)	1000 _{MIN}
Service voltage (at 50 Hz) (Vrms)	250

§ 4.5.5
§ 4.5.8
§ 4.5.12
§ 4.5.7.1
N/A

SMASH >>> STANDARD TECHNOLOGY OF CONTACT (1)

FEMALE CONTACTS FOR RECEPTACLES



Starclip female technology




- 6 contact tines instead of 4
- Excellent mechanical and electrical reliability
- Better resistance to high vibrations
- Improved electrical conductivity
- 100% compatible with other connectors

- Size 23: high average current
- Clip for male contact Ø0.635 [.025]
- **Plating** on active part (clip)

Cu	Ni	Au
1 [.039]	3.5 [.138]	1.3 [.051]

Standard straight PC tail




- Thru hole soldering
- Mother board or mezzanine connection
- PCB thickness: up to 5.5 [.217]
- **Plating** (µm [µin])

Version	Ni	Pure Sn	Sn Pb
RoHS	2.5 [.098]	5 [.197]	
Standard	3 [.118]		10 [.394]

Termination style

YD

Press-fit



- For solderless assembly
- Mother board or mezzanine connection
- PCB thickness: 2.5_{MIN} [.098]
- **Plating** (µm [µin])


Ni electrolytic	Ni electroless	Sn Pb
2 [.079]	15.2 [.598]	10 [.394]

Termination style

YP

MALE CONTACT FOR PLUGS

SMT



- Flexible circuit for double sided SMT mounting
- Daughter card or extended card
- PCB thickness: specific, *consult us*
- **Plating** (µm [µin])

	YD	YP	U01
L_{MAX}	6.5 [.256]	2.5 _{MIN} [.098]	2.4 ± 0.3 [.094 ± .012]

Cu	Ni	Au
1 [.039]	3.5 [.138]	1.3 [.051]

Consult us

U01

AMPHENOL SIGNAL CONTACTS CAPABILITIES

- Male contacts attached to flexible circuit for double sided SMT mounting on daughter card
Consult us
- Female contacts with straight PC tails for thru hole soldering, with numerous contact lengths available
- Male and female solder cup termination for soldering on a cable
- Specific plating

SMASH >>> SPECIAL TECHNOLOGY OF CONTACT (1)



Power contacts 20A

			<ul style="list-style-type: none"> - Thru hole soldering - Mother board or daughter board - 20A / contact <p>Consult us</p>
--	--	--	--

RADSOK® contact 350A

		<ul style="list-style-type: none"> - High power contact - Mother board or daughter board - 350A / contact <p>Consult us</p>
--	--	--

Optical contacts

		<ul style="list-style-type: none"> - 2x12 optical channels (MT ferrules) <p>Consult us</p>
--	--	---

AMPHENOL CUSTOM DESIGN CAPABILITIES


- Development of housings and shells for specific arrangement or special contacts
[Consult us](#)
- Numerous types of special contacts, various lengths and mounting processes
- Various platings (Tin Lead, Gold, Pure bright tin ...)
- Proven knowledge in custom design for tailor-made applications
- Development of coaxial contacts

SMASH >>> STANDARD HOUSINGS AND SHELLS (2 & 3)

HOUSINGS 6-ROW CHEVRON GRID PATTERN



150 signal contacts insert



132 signal contacts insert



STANDARD SHELLS WITH 1, 2 OR 3 BAYS

1 bay connector / 150 signal contacts



1 bay connector / 132 signal contacts



2 bays connector / 300 signal contacts



2 bays connector / 264 signal contacts




3 bays connector / 450 signal contacts



3 bays connector / 396 signal contacts



KEYING AND GUIDING




Connectors are supplied with non-assembled keying and guiding devices.

SMASH >>> SPECIAL HOUSINGS AND SHELLS (2 & 3)



AMPHENOL CAPABILITIES: HOUSINGS

Specific grid: Square grid pattern, 1.905 [.075] x 1.905 [.075] staggered grid pattern, 1.588 [.063] x 1.588 [.063] staggered grid pattern, 2.54 mm...



Housings for specific contacts



[Consult us](#)

AMPHENOL CAPABILITIES: SHELLS

Rackable shells




Specific shells



[Consult us](#)


MATING SEQUENCE



All dimensions are given for information only and are in mm [inch], except as otherwise specified



SMASH >>> 150 SIGNAL CONTACTS

TYPICAL ARRANGEMENTS & LAYOUTS




Dimensions are in mm

Receptacle with straight PC tails YD





Layouts for 150 signal contacts connector with YD/YP contacts





Part number : **HDC E 150 YD-000**

Plug with SMT flexible circuit technology U01



Layouts for 150 signal contacts connector with U01 contacts



Part number : HDC F 150 U01-000


For further arrangements, consult us

All dimensions are given for information only and are in mm, except as otherwise specified



SMASH >>> 300 SIGNAL CONTACTS

TYPICAL ARRANGEMENTS & LAYOUTS


Dimensions are in mm



Receptacle with straight PC tails




Layouts for 300 signal contacts connector with YD/YP contacts




Part number : HDC E 300 YD-000

Plug with SMT flexible circuit technology



Layouts for 300 signal contacts connector with U01 contacts




Part number : HDC F 300 U01-000

For further arrangements, consult us

All dimensions are given for information only and are in mm, except as otherwise specified


SMASH >>> 450 SIGNAL CONTACTS

TYPICAL ARRANGEMENTS & LAYOUTS




Dimensions are in mm

Receptacle with straight PC tails YD





Layouts for 450 signal contacts connector with YD/YP contacts

PCB FACE A



Part number : HDC E 450 YD-000

Plug with SMT flexible circuit technology U01




Part number : HDC F 450 U01-000



SMASH >>> 396 SIGNAL CONTACTS

TYPICAL ARRANGEMENTS & LAYOUTS


Dimensions are in mm



Receptacle with straight PC tails YD





Layouts for 396* signal contacts connector with YD/YP contacts





Part number : HDC E 396 YD-000

Plug with SMT flexible circuit technology U01



Layouts for 396* signal contacts connector with U01 contacts



Part number : HDC F 396 U01-000

NOTES**SMASH Series**

NOTES

SMASH Series

SIAL

The hybrid connector for use with thermal clamps

SIAL is a modular high density interconnection system that has the capability to mix signal and coax contacts. The contact technology developed for this connector allows the use of thermal clamps. With 3 sizes of modules, the SIAL connectors provide the arrangement needed, from 18 to 392 contacts. In a staggered grid pattern (2.54 x 1.905 [.100x.075]), this connector houses 5 rows of contacts in a low profile board to board format. Additionally, SIAL connectors provide shielding on both plug & receptacle, which allows the dissipation of all the electrical charge while mating.

The concept

3 standard modules are available with 18, 58 and 98 signal contacts on 5 rows. These allow arrangements up to 392 contacts. The various modules are maintained in a metallic shell, allowing both protection of male contacts on the plug, and a mix of signal and coax modules.

Compatible with the use of thermal clamps

Its standard contact technology, already used in the monolithic SIHD connector, permits the lateral displacement (± 0.25 [.010]) of the pin into the socket without generating any stress on the contact termination on the PCB.

This feature allows the use of thermal clamps to keep the daughter board in position after mating, as well as the dissipation of energy generated by the components on the board from the heat sink (thermal drain) to the cold wall (liquid cooled) or to the chassis. The locking of the thermal clamps provides the lateral movement of the plug into the receptacle. The SIAL allows this lateral displacement of ± 0.25 [.010] without creating stress on the solder joints or on the contact area.

A complete range for test, programming, maintenance


E = Female receptacle for mother board

F = Male plug for daughter board

T = Female test receptacle for daughter board

S = Male test plug

P = Female extender receptacle



QUICK SELECTION GUIDE

Signal contacts ①	Coax contacts ②	Modules ③	Fittings & Guiding ④	Keying ⑤
FEMALE for receptacles  MALE for plugs  for extender receptacles  for test plugs 	COAX SIZE 12  COAX SIZE 16  3 COAX / MODULE  5 COAX / MODULE 	NUMBER OF SIGNAL CONTACTS 018, 036, 058, 076, 098, 116, 156, 196, 214, 254, 312, 370, 392 NUMBER OF COAX CONTACTS Size 12: 03, 06, 09, 12 Size 16: 05, 10	FITTING  FEMALE SOCKET GUIDE  MALE GUIDE PIN 	5 polarizing pins / connector 

[PAGE 85](#) | [PAGE 84](#)

[PAGE 86](#)

[PAGE 88](#)

[PAGE 89](#)

[PAGE 89](#)

The SIAL series serves various markets, including:



Commercial avionics & airframe



Military avionics & airframe



Space

SIAL Series

Lateral displacement compatibility



Table of contents

SIAL product range	80
Signal contacts	84
Special contacts	86
Signal modules	88
Hybrid modules	88
Fittings and guiding	89
Keying	89
Realignment capability	89
Mating sequence	89
SIAL signal version typical arrangements	90
SIAL signal version layouts	92
SIAL coaxial version typical arrangements	93
SIAL coaxial version layouts	94
Tooling	96

The SIAL series serves various **markets**, including:



Commercial Avionics
& Airframe



Military Avionics & Airframe



Space

SIAL>>> GENERAL SPECIFICATIONS



- Modular connector mixing signal and coax contacts in many arrangements
- Lateral displacement capability allowing the use of thermal clamps: ± 0.25 [$\pm .010$]
- Complete range for test, programming and maintenance
- Designed for severe mechanical environments
- 2.54 [.100] staggered grid (1.27 [.050] offset), 1.905 [.075] between rows

Main characteristics

- Medium density: 0.14 cts/mm^2 [90 cts/inch 2]
- 13 arrangements on 5 rows of contacts, from 18 to 392 signal contacts
- 5 hybrid arrangements mixing coax and signal contacts
- 3 A per signal contacts / DWV: 750 Vrms
- Lateral rails to protect the male contacts from external damage
- Repairable contacts for easy maintenance

Terminations



Markets



Main applications



Recommended configurations



Standard

MIL-DTL-55302

CECC 75101-012

How to order

E	Female receptacle
F	Male plug
T	Female test receptacle
S	Male test plug
P	Female extender receptacle


C	Conductive fitting Standard version For E and F types
Blank	Non conductive fitting Test versions and specifics

Size	Male plug	Female receptacle
Size 12	KX	KT
Size 16	NX	NT
No coaxial contact		Blank

000	Standard
001	ASL F or E with 5 right & left coax
010	ASL E with 2.76_{MAX} mm PCB thickness
011	ASL E with heatshrink sleeve
100	ASL S and E 392 screw locking system
102	ASL F with Y01 contacts without lateral displacement
103	ASL S Y04 straight/flex locking system
200	ASL 39758119 space customer specification
300	ASL MA3401 space customer specification
500	ASL F or E with 5 coax after signal contacts
502	ASL F or E with 5 coax before signal contacts

Deviation

Blank: Tin lead
LF: Lead free
Termination plating



Number of signal contacts (see page 88)		
Signal contacts only		Signal & coaxial contacts
018	156	018 (+3)
036	196	058 (+3)
058	214	098 (+3)
076	254	058 (+5)
098	312	156 (+10)
116	370	196 (+5)
		254 (+5)


	Male contact	Female contact
E		Y09, Y19
F	Y01, Y02, Y04, U04, U05, U06, U07, U08	
T		Y01, Y02, Y04, U04, U05, U06, U07, U08
P		Y01, Y02, Y04, U04, U05, U06, U07, U08
S	Y03 Y02 Y04	

Number of coax contacts (see page 93)	
Size	Number of coax
12	03 06 09 12
16	05 10
No coaxial contact	Blank


All dimensions are given for information only and are in mm [inch], except as otherwise specified

SIAL >>> TECHNICAL SPECIFICATIONS

Dimensional characteristics



L= 22.86[.900] to 231.14[9.100] for signal version
 L= 53.34[2.100] to 180.34[7.100] for hybrid version
 A= 12.1_{MAX} [.476]
 H= 6.41_{MAX} [.252] for plug
 H= 10.26_{MAX} [.404]



Female contact



Cross cavity by Amphenol: lateral displacement compatible


- Cross section of the lateral displacement of the male contact inside the female cavity
- Maintains 2 points of contact
- Allows a ± 0.25 [$\pm .010$] lateral displacement
- No stress on solder joints or on the contact area

Material: beryllium copper (stamped)

Plating:

- Termination: tin lead or lead free
- Active contact area: gold over nickel

Male contact



Mating end size: 0.6 x 1.2 [.047 x .024]

Contact section (mating side): 0.72mm² [.001 in²]

Material: beryllium copper (stamped)

Plating:

- Termination: tin lead or lead free
- Active contact area: gold over nickel

Materials

- **Fixing devices:** anodized aluminium
- **Guiding devices:** passivated stainless steel
- **Polarizing pins:** passivated stainless steel
- **Metallic rails:** passivated stainless steel
- **Plastic inserts:** thermoset DAP, 30% glass-fiber filled

MECHANICAL CHARACTERISTICS	
Backoff¹ (mm)	< 0.8 [.031]
Mating force per contact (N)	0.58 _{MAX}
Unmating force per contact (N)	0.16 < F < 0.58
Durability cycles	500
Sinusoidal vibrations (10 to 2000 Hz) micro discontinuity 2ns	10 g
Random vibrations (10 to 2000 Hz) micro discontinuity 2ns	0.15 g ² / Hz
Shocks micro discontinuity 1ns	100 g
ENVIRONMENTAL CHARACTERISTICS	
Thermal shocks (°C)	-55 / +125
Salt Spray (hours)	144* or 96
ELECTRICAL CHARACTERISTICS	
Current rating per contacts (A)	3
Insulation resistance (at 500Vdc) (GΩ)	5 _{MIN}
Contact resistance (mΩ)	25 _{MAX}
Dielectric Withstanding Voltage (Vrms)	750
Capacitance between contacts (pF)	1.5 _{MAX}
Service voltage (at 50 Hz) (Vrms)	250

* "C" standard version


¹: When both connectors are fully mated, the backoff is the maximum distance the connectors can be unmated while functioning properly

SIAL >>> SIGNAL CONTACTS (1)

MALE CONTACTS FOR PLUGS



Right angle PC tail




- Thru hole soldering
- Daughter board
- PCB thickness: 3.1_{MAX} [.122]

Termination style

Y01

Right angle PC tail




- Thru hole soldering
- Daughter board
- PCB thickness: 2.6_{MAX} [.102]

Termination style

Y02

SMT double side PCB, centered




- SMT soldering
- Double-sided daughter board, centered
- PCB thickness: 2.6 ± 0.235 [.102 ± .009]

Termination style

U04

Straight PC tail




- Thru hole soldering
- Daughter board
- PCB thickness: 4.5 ± 0.45 [.177 ± .018]

Termination style

Y04

SMT double side, centered




- SMT soldering
- Double-sided daughter board, centered
- PCB thickness: 1.6 ± 0.160 [.063 ± .006]

Termination style

U06

SMT double side, centered




- SMT soldering
- Double-sided daughter board, centered
- PCB thickness: 2 ± 0.2 [.079 ± .008]

Termination style

U05

SMT double side, off centered




- SMT soldering
- Double-sided daughter board, offset
- PCB thickness: 2.6 ± 0.235 [.102 ± .009]

Termination style

U08

SMT double side, off centered



- SMT soldering
- Double-sided daughter board, offset
- PCB thickness: 2.44 ± 0.42 [.096 ± .016]

Termination style

U07


	Y01	Y02	Y04	U04	U05	U06	U07	U08						
L_{MAX}	4.2 ± 0.2 [.165 ± .008]	3.7 ± 0.2 [.146 ± .008]	6 [.236]	2.6 ± 0.235 [.102 ± .009]	2 ± 0.2 [.079 ± .008]	1.6 ± 0.160 [.063 ± .006]	2.44 ± 0.42 [.096 ± .016]	2.6 ± 0.235 [.102 ± .009]						
Termination section	Ø 0.4 ± 0.03 [.016 ± .001]		0.3 x 0.8 [.012 x .031]											
Mating end size	1.2 x 0.6 [.047 x .024]													
Active contact area plating µm[µin]	2 [.079] Ni + 1 [.039] Au													
Termination plating µm [µin]	2 [.079] Ni + 3 [.118] SnPb or bright pure Sn for RoHS version		2 [.079] Ni + 7 [.276] SnPb or bright pure Sn for RoHS version											

SIAL >>> SIGNAL CONTACTS (1)

MALE CONTACT FOR TEST PLUGS



Right angle PC tail




- Thru hole soldering
- Daughter board
- PCB thickness: 1.6 ± 0.16 [.063 ± .006]

Termination style

Y03

FEMALE CONTACTS FOR RECEPTACLES

Straight PC tail, standard length




- Thru hole soldering
- Mother board
- PCB thickness: 3.75 ± 0.75 [.148 ± .030]



Termination style

Y09

Straight PC tail, short length



- Thru hole soldering
- Mother board
- PCB thickness: up to 2 ± 0.2 [.079 ± .008]




Termination style

Y19

FEMALE CONTACT FOR EXTENDER RECEPACLES

Right angle PC tail, short length




- Thru hole soldering
- Extender card
- PCB thickness: 2.6_{MAX} [.102]

Termination style

Y02

Right angle PC tail



- Thru hole soldering
- Extender card
- PCB thickness 3.1_{MAX} [.122]

Termination style

Y01

	Y03	Y02	Y01	Y09	Y19
L_{MAX}	2.8 ± 0.2 [.165 ± .008]	3.7 ± 0.2 [.146 ± .008]	4.2 ± 0.2 [.165 ± .008]	6 [.236]	4.5 ± 0.2 [.177 ± .008]
Mating end size	1.2×0.6 [.047 x .024]				
Termination section	$\emptyset 0.4 \pm 0.03$ [.016 ± .001]				
Active contact area plating μm [μin]	$2 [.079] Ni + 1 [.039] Au$				
Termination plating μm [μin]	$2 [.079] Ni + 3 [.118] SnPb$ or bright pure Sn for RoHS version				

SIAL >>> SPECIAL CONTACTS (2)

SIZE 16 COAXIAL CONTACTS

Male contacts for plugs – 5-cavity module

Straight crimp barrel

- For 5-cavity module
- For 2 [.079] cable
- Size 16: 6 GHz depending on cable – 50 Ω

2 [.079]

32008

Straight PC tail - UT47

- For 5-cavity module
- For UT47 semi-rigid cable
- Size 16: 6 GHz depending on cable – 50 Ω

Consult us

320033



Right angle PC tail

- For 5-cavity module
- Size 16: 6 GHz depending on cable – 50 Ω

Consult us

320032

Female contacts for receptacles – 5-cavity module

Straight crimp barrel

- For 5-cavity module
- For 2, 1.2, 2.7 or 2.4 cable [for .079, .047, .106 or .094 cable]
- Size 16: 6 GHz depending on cable – 50 Ω

2 [.079]
1.2 [.047]
2.7 [.106]
2.4 [.094]

320009
320011
320017
320018

Straight PC tail - UT47

- For 5-cavity module
- For UT47 semi-rigid cable
- Size 16: 6 GHz depending on cable – 50 Ω

Consult us

320006

Straight PC tail - Sucoform

- For 5-cavity module
- For Sucoform cable 0.086 [.003]
- Size 16: 6 GHz depending on cable – 50 Ω
- No lateral displacement

Consult us

320021

SIAL >> SPECIAL CONTACTS (2)

SIZE 12 COAXIAL CONTACTS



Male contacts for plugs – 3-cavity module

Right angle PC tail

- For 3-cavity module
- Size 12: 0 to 3 GHz – 50 Ω

Consult us

320000

Straight crimp barrel

- For 3-cavity module
- Size 12: 0 to 3 GHz – 50 Ω
- Standard designation: M39029 / 28 - 211

Consult us

900340

Female contacts for receptacles – 3-cavity module

Right angle crimp barrel – KX22A

- For 3-cavity module
- For KX22A cable
- Size 12: 0 to 3 GHz – 50 Ω

Consult us

320001

Right angle crimp barrel – F 1703/66

- For 3-cavity module
- For F 1703 / 66 cable
- Size 12: 0 to 3 GHz – 50 Ω

Consult us

320004

Straight PC tail

- For 3-cavity module
- For test only, specific application
- Size 12: 0 to 3 GHz – 50 Ω
- No lateral displacement

Consult us

320002

Straight crimp barrel

- For 3-cavity module
- Standard designation: M39029 / 27 - 210
- Size 12: 0 to 3 GHz – 50 Ω
- With lateral displacement

Consult us

900354


	16-SIZE CONTACT	12-SIZE CONTACT
Impedance Ω	50	50
Voltage rating V	180	180
Current rating mA	500	500
Contact retention N	≥ 50	≥ 50
Frequency range GHz	0 to 1	0 to 1
Contact resistance mΩ	≤ 12	≤ 12
VSWR at 1 GHz	1.3 _{MAX}	1.3 _{MAX}
Insertion and extraction force per contact N	1 ≤ F ≤ 15	1 ≤ F ≤ 15
Dielectric and extraction force per contact N		at sea level, 1000 V. at 15240 m, 250 V.

SIAL >> MODULES (3)


SIGNAL MODULES



18 signal contacts




- Arrangement available:
 - 18
 - 18 x 2
 - 18 + 58



58 signal contacts




- Arrangement available:
 - 58
 - 58 + 18
 - 58 x 2
 - 58 + 98
 - 58 x 2 + 98
 - 58 + 98 x 2
 - 58 x 2 + 98 x 2
 - 58 x 3 + 98 x 2



98 signal contacts




- Arrangement available:
 - 98
 - 98 + 58
 - 98 x 2
 - 98 + 2 x 58
 - 98 x 2 + 58
 - 98 x 2 + 58 x 2
 - 98 x 2 + 58 x 3
 - 98 x 4




HYBRID MODULES

3 coax contacts – size 12




- 3-cavity module for 12-size coaxial contact
- Arrangement available:
 - 3 + 18
 - 3 + 58



5 coax contacts – size 16



- 5-cavity module for 16-size coaxial contact
- Arrangement available:
 - 5 + 98
 - 5 x 2 + 98 + 58




	18 signal contacts	58 signal contacts	98 signal contacts	3 coax contacts	5 coax contacts
L	10.16 [.400]	30.48 [1.200]	50.8 [2.1000]		25.4 _{MAX} [1.000]
I		10.05 [.396]	10.8 [.425]		9.95 [.392]
Receptacle					10.8 [.425]
Plug					

SIAL >>> FITTINGS/GUIDING & KEYING (4 & 5)

FITTINGS / GUIDING (4)




A- centered end fittings



- 1 centered end fitting at one end of the connector
- Max length: 6, 35 [.250]
- Male guide pin on receptacle
- Female centered hole on plug
- 4 holes for polarizing

B- end fittings



- 1 end fitting at one end of the connector
- Max length: 6, 35 [.250]
- Male guide pin on receptacle
- Offset hole on plug
- 4 holes for polarizing pin

Central fittings



- Max length: 6, 35 [.250]
- Guiding device: Male guide pin on receptacle
- 2 holes for polarizing pin

Signal version

- 1 fitting for 196, 214, 254 and 312 positions
- 2 fittings for 370 positions
- 3 fittings for 392 positions

With coaxial contacts

- 1 fitting for 18 + 3, 58 + 3 and 98 + 5 positions
- 2 fittings for 98 + 58 + 5 x 2 positions

KEYING (5)

Polarizing pins





- 2 pins at each end fitting for the plug / 2 pins at each end fitting for the receptacle
- 1 pin at each central fitting for the plug / 1 pin at each central fitting for the receptacle
- Identification of keying cavities: clockwise for the plugs, counterclockwise on the receptacle
- A,B,C,D on A fitting, W,X,Y,Z on B fitting





REALIGNMENT CAPABILITY

In the longitudinal axis



In the lateral axis



MATING SEQUENCE

Shell guiding	Coax guiding	Keying	Coax contact	Signal contact	Housing contact
6.8 ± 0.45 [0.268 ± 0.018]	6.56 ± 0.45 [0.258 ± 0.018]	6.27 ± 0.36 [0.247 ± 0.014]	3.26 ± 0.6 [0.128 ± 0.024]	2.14 ± 0.28 [0.084 ± 0.011]	2.14 ± 0.28 [0.084 ± 0.011]
3.3 ± 0.6 [0.130 ± 0.024]	3.3 ± 0.6 [0.130 ± 0.024]	0.24 ± 0.6 [0.009 ± 0.024]	3.3 ± 0.6 [0.130 ± 0.024]	2.9 ± 0.6 [0.114 ± 0.024]	2.9 ± 0.6 [0.114 ± 0.024]
3.7 ± 0.7 [0.121 ± 0.028]	3.7 ± 0.7 [0.121 ± 0.028]	0.24 ± 0.8 [0.010 ± 0.028]	3.3 ± 0.8 [0.130 ± 0.028]	2.14 ± 0.38 [0.084 ± 0.038]	2.14 ± 0.38 [0.084 ± 0.038]


All dimensions are given for information only and are in mm [inch], except as otherwise specified

SIAL >> SIGNAL VERSION (3)


TYPICAL ARRANGEMENTS




18 signal contacts




36 signal contacts




58 signal contacts




76 signal contacts




98 signal contacts



116 signal contacts



156 signal contacts




	18	36	58	76	98	116	156
D	16.51 [.650]	26.67 [1.050]	36.83 [1.450]	46.99 [1.850]	57.15 [2.250]	67.31 [2.650]	87.63 [3.450]
E_{MAX}	22.86 [.900]	33.02 [1.300]	43.18 [1.700]	53.34 [2.100]	63.5 [2.500]	73.66 [2.900]	93.98 [3.700]
a	7.62 [.340]	17.78 [.700]	27.94 [1.100]	38.1 [1.500]	48.26 [1.900]	58.42 [2.300]	81.28 [3.200]

SIAL >> SIGNAL VERSION (3)


TYPICAL ARRANGEMENTS




196 signal contacts




214 signal contacts




254 signal contacts




312 signal contacts



370 signal contacts



392 signal contacts




	196	214	254	312	370	392
D	113.03 [4.450]	123.19 [4.850]	143.51 [5.650]	173.99 [6.850]	209.55 [8.250]	224.79 [8.850]
E_{MAX}	119.38 [4.700]	129.54 [5.100]	149.86 [5.900]	180.34 [7.100]	215.9 [8.500]	231.14 [9.100]
a	48.26 [1.900]	81.28 [3.200]	81.28 [3.200]	81.28 [3.200]	81.28 [3.200]	48.26 [1.900]
a'	56.515 [2.225]	86.995 [3.425]	86.995 [3.425]	86.995 [3.425]	86.995 [3.425]	56.515 [2.225]
b	48.26 [1.900]	27.94 [1.100]	48.26 [1.900]	81.28 [3.200]	27.94 [1.100]	48.26 [1.900]
b'	56.515 [2.225]	36.195 [1.425]	56.515 [2.225]	86.995 [3.425]	35.56 [1.400]	55.88 [2.000]
c					81.28 [3.200]	48.26 [1.900]
c'					86.995 [3.425]	55.88 [2.000]
d						48.26 [1.900]
d'						56.515 [2.225]

All dimensions are given for information only and are in mm [inch], except as otherwise specified

SIAL >> SIGNAL VERSION (3)


LAYOUTS

The boards are shown from the connector side
All contact locations are equidistant.




With YC signal contacts for plug

DAUGHTER BOARD




With U --- signal contacts for plug

DAUGHTER BOARD



With Y -- signal contacts for receptacle

MOTHER BOARD




R ₁	R ₃	R _{3'}	p	p/2	p ₀	p ₂	d ₁	d ₂	d ₈	d ₉	a	b	h ₁	h ₂
Ø 0.6 _{MIN} [.024]	Ø 2.3 ^{+0.15} _{0.1} [.091 ^{+0.06} _{0.04}]	Ø 3.3 [130]	2.54 [.100]	1.27 [.050]	1.905 [.075]	0.85 [.033]	3.81 [.150]	4.445 [.175]	4.02 [.158]	3.39 [.133]	2 _{MAX} [.079]	0.5 _{MAX} [.020]	3.81 [.150]	3.81 [.150]

SIAL >> COAXIAL VERSION (3)


TYPICAL ARRANGEMENTS




18 signal contacts + 3 coax




58 signal contacts + 3 coax




58 signal contacts + 5 coax




98 signal contacts + 3 coax




5 coax + 98 + 58 signal contacts + 5 coax



196 signal contacts + 5 coax



254 signal contacts + 5 coax




	18 + 3	58 + 3	58 + 5	98 + 3	5 + 98 + 58 + 5	196 + 5	254 + 5
D	46.99 [1.850]	67.31 [2.650]	67.31 [2.650]	87.63 [3.450]	148.59 [5.850]	143.51 [5.650]	173.99 [6.850]
E_{MAX}	53.34 [2.100]	73.66 [2.900]	73.66 [2.900]	93.98 [3.700]	154.94 [6.100]	149.86 [5.900]	180.34 [7.100]
a	7.62 [.340]	27.94 [1.100]	27.94 [1.100]	48.26 [1.900]	/	48.26 [1.900]	81.28 [3.200]
a'	15.875 [.625]	36.195 [1.425]	36.195 [1.425]	56.515 [2.225]	31.115 [1.225]	56.515 [2.225]	86.995 [3.425]
b	/	/	/	/	81.28 [3.200]	48.26 [1.900]	48.26 [1.900]
b'	31.115 [1.225]	31.115 [1.225]	31.115 [1.225]	31.115 [1.225]	86.36 [3.400]	55.88 [2.200]	55.88 [2.200]
c					31.115 [1.225]	31.115 [1.225]	31.115 [1.225]

All dimensions are given for information only and are in mm [inch], except as otherwise specified

SIAL >> SIZE 16 COAXIAL VERSION (3)


LAYOUTS

The boards are shown from the connector side
All contact locations are equidistant.




With Y0. male signal contacts and 5 coaxial contacts for plug

NX05-002
DAUGHTER
BOARD




With Y0. male signal contacts and 5 coaxial contacts for plug

NX05-000
DAUGHTER
BOARD




With Y0. male signal contacts and 10 coaxial contacts for plug

NX10-001
DAUGHTER
BOARD




With Y0. male signal contacts and 10 coaxial contacts for plug

NX10-000
DAUGHTER
BOARD




With Y09 female signal contacts and 5 coaxial contacts for receptacle

NT05-002
MOTHER BOARD




With Y09 female signal contacts and 5 coaxial contacts for receptacle

NT05-000
MOTHER BOARD



With Y09 female signal contacts and 10 coaxial contacts for receptacle

NT10-000
MOTHER BOARD




All dimensions are given for information only and are in mm [inch], except as otherwise specified


SIAL >> SIZE 12 COAXIAL VERSION (3)

LAYOUTS


The boards are shown from the connector side
All contact locations are equidistant.

K(2)03-000
DAUGHTER
BOARD


With Y male signal contacts and 3x320000 right angle dip solder coaxial contacts/plug

K(2)06-000
DAUGHTER
BOARD


With Y0 male signal contacts and 6x320000 right angle dip solder coaxial contacts/plug

K(1)03-000
DAUGHTER
BOARD


With Y male signal contacts and 3x900340 crimp coaxial contacts/plug

K(1)06-000
DAUGHTER
BOARD


With Y0 male signal contacts and 6x900340 crimp coaxial contacts/plug

KT03-000
MOTHER BOARD

With Y09 female signal contacts and 3 coaxial contacts/receptacle

KT06-000
MOTHER BOARD

With Y09 female signal contacts and 6 coaxial contacts/receptacle




R ₁	R ₂	R ₃	R _{3'}	p	p/2	p ₁	p ₀	p ₀ /2	L	H
Ø 0.6 _{MIN} [.024]	Ø 0.75 _{MIN} [.340]	Ø 23 _{-0.15} _{+0.06} [.091 _{-0.004}]	Ø 3.3 _{-0.1} _{+0.06} [130 _{-0.04}]	2.54	1.27	6.35	1.905	0.9525	25.4 _{MAX} [1.000] 19 _{MIN} [.748]	6 _{MIN} [.236]

d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	d _{3'}	d _{4'}
3.81 [.150]	4.445 [.175]	7.62 [.300]	8.255 [.325]	15.24 [.600]	30.48 [1.200]	45.72 [1.800]	8.89 [.350]	9.525 [.375]

All dimensions are given for information only and are in mm [inch], except as otherwise specified

SIAL >>> TOOLING

Receptacle mounting on mother board (Y09)




- Insertion of all connector sizes with Y09 dip solder contacts
- Into 0.6 mm [.024] thru plated holes
- Consult us for additional references

ASL ODP 058
ASL ODP 098
ASL ODP 116

ASL ODP 156
ASL ODP 254
ASL ODP 312

Plug mounting on daughter board (Y01 or Y02)



- Insertion of all connector sizes with Y01 or Y02 right angle dip solder contacts
- Into 0.6 mm [.024] thru plated holes
- Consult us for additional references

ASL ODI YC 312
ASL ODI YC 392

Plug mounting on daughter board (SMT)



- Insertion of all connector sizes with U04, U05, U06, U07 or U08 SMT contacts (Surface Mount Terminations)
- Consult us for additional references

ASL ODI SMT

Mounting tool for size 16 coax contacts



- On mother board or daughter board
- Consult us for additional references
- For ASLF *** ** NX05-002 and ASLF *** ** NX05-502 connectors, use the ASL ODP NX10 tool.

ASL ODP NX05

ASL ODP NX10

Extraction tool for coax contacts

Size 12



809839

Size 16



ASL OD COAX FEMELLE TAILLE 16

SIAL >>> TOOLING

CRIMPING TOOL FOR 12-SIZE COAX CONTACTS

Inner contact crimping tool



- For 12-size coaxial contacts
- Additional turret:
- PN 809932 (M22520/2-34)
- Military reference : M22520/2-01

Part number

809801

Outer contact crimping tool



- For 12-size coaxial contacts
- Additional turret:
- PN 809927 (M22520/31-02)
- Military reference : M22520/3-01

Part number

809926

INSERTION AND REMOVAL TOOLS FOR 12-SIZE COAX CONTACTS

Insertion tool



- Size 12
- Metallic

Part number

809838

Removal tool



- Size 12
- Metallic
- For 900340 and 900354 contacts

Part number

809839

Insertion/Removal tool



- Size 12
- Plastic

Part number

809859

Removal tool



- Size 12
- Metallic
- For 320001 contact

Part number

809933

SIHD

The monolithic connector for use with thermal clamps

The SIHD connector combines excellent electrical performances with high contact density within a robust housing, which can withstand extreme environmental conditions. In addition, the lateral displacement capability allows the use of thermal clamps for heat management, as well as a more relaxed positional tolerance on the backplane. The optional central ground strip provides cross talk protection and permits the routing of differential pairs. Contacts can be repaired and replaced individually.


The ability to include ground strips

- Transmission of high-speed signals made easy by reducing self inductance with the inclusion of central ground strips
- Cross talk and self impedance levels reduced impedance 70Ω to 120Ω
- Capacitance distributed along signal contacts

Compatible with the use of thermal clamps

Its standard contact technology, already used in the SIAL connector, permits the lateral displacement (± 0.25 [.010]) of the pin into the socket without generating any stress on the contact termination on the PCB.

This feature allows the use of thermal clamps to keep the daughter board in position after mating, as well as the dissipation of energy generated by the components on the board from the heat sink (thermal drain) to the cold wall (liquid cooled) or to the chassis. The locking of the thermal clamps provides the lateral movement of the plug into the receptacle. The SIHD allows this lateral displacement of ± 0.25 [.010] without creating stress on the solder joints or on the contact area.



QUICK SELECTION GUIDE

Signal contacts ①	Ground Strip ②	Guiding ③	Keying ④	Fittings ⑤	Housings ⑥
FEMALE  MALE 	Reduced cross talk level Reduced self impedance level Capacitance distributed along signal contacts	A STYLE For M1W3 contacts  B STYLE For M1YD contacts  <i>Fixing of receptacle</i>	250 positions available 10 holes 5 pins on the plug 5 pins on the receptacle	For receptacles: style A and B (guiding) For plugs: fixing on thermal drain or on PCB	Without ground strip: 128, 158, 256, 390 With ground strip: 102C, 204C, 230C

PAGE 102 | PAGE 103

PAGE 103

PAGE 104

PAGE 104

PAGE 105

PAGE 106

SIHD Series

Lateral displacement compatibility




Table of contents

SIHD product range	98
Female signal contacts for plugs	102
Male signal contacts for receptacles	103
Ground strips	103
Guiding / Keying	104
Mating sequence	104
Realignment capability	104
Fixing accessories	105
SIHD without ground strip: typical arrangements	106
SIHD with ground strip: typical arrangements	107
SIHD without ground strip: layouts	108
SIHD with ground strip: layouts	109


The SIHD series serves various **markets**, including:



Commercial Avionics & Airframe



Military Avionics & Airframe



Navy



Space

SIHD>>> GENERAL SPECIFICATIONS



- 2.54 [.100] staggered grid (1.27 [.050] offset), 1.905 [.075] between rows
- Lateral displacement capability allowing the use of thermal clamps: ± 0.25 [$\pm .010$]
- Possibility to have a central ground strip
- Designed for severe mechanical environments
- Low weight

MEDIUM DENSITY

Main characteristics

- Medium density: 0.14 cts/mm² [90 cts / inch²]
- 7 variations: 5 rows from 102 to 390 signal contacts
- 3 A per signal contacts / DWV: 750* Vrms
- Lateral rails to protect the male contact from external damage
- Repairable contacts for easy maintenance

Markets



Main applications



Terminations



Recommended configurations



How to order

	Plug with female contacts
F	Receptacle with male contacts
E	Extender card for M1YC contacts (shroud aluminium)
P	Extender card for M1YC contacts (12.7 pitch)
G	Extender card for M1YC contacts (12.7 pitch)
Connector type	

C	Central ground strip
\emptyset	No ground strip
Ground strip (see page 103)	

A	B	C	D	E	F
\emptyset	ABC	DEF			F connector
\emptyset	AB				E connector
Fittings (see page 105)					
Plating (for M1W3 contacts only)					

SIHD - - - - -


Number of signal contacts (see pages 106 to 107)	
Without ground strip	With ground strip
128	102 central ground strip
158	204 central ground strip
256	230 half central ground strip
390	

Signal contacts (see pages 102 to 103)			
F connector	E connector	P connector	G connector
SMT double side: F1U1 / F1U2 / F1U3	Wire wrap connections: M1W3	Extender card: M1YC	Extender card: M1YC
SMT single side: F1TS	Straight PC tail: M1YD		
Right angle PC tail: F1YC			
Straight PC tail: F1TS			
Crimping tail: F1X1			


* 375Vrms only for F1U2 cts

SIHD >>> TECHNICAL SPECIFICATIONS

Dimensional characteristics



H = 16.9 to 17.95 [.665 to .707] for plug
 H = 10.22 to 11.15 [.402 to .439] for receptacle
 A = 11.6 to 15 [.457 to .591]
 L = 77.86 to 221 [3.065 to 8.701]



Female contact



Cross cavity by Amphenol: lateral displacement compatible


- Cross section of the lateral displacement of the male contact inside the female cavity
- Maintains 2 points of contact
- Allows a ± 0.25 [$\pm .010$] lateral displacement
- No stress on solder joints or on the contact area

Material: beryllium copper (stamped)

Plating:

- Terminations: gold over nickel on crimp contacts (F1X1)
 tin lead or lead free on other contacts (F1U1, F1U2, F1U3, F1TS, F1YC)
- Active contact area: gold over nickel

Male contact



Mating end size: 0.6 x 1.2 [.047 x .024]

Contact section (mating side): 0.72 mm² [.001 in²]

Material: phosphorous bronze (stamped)

Plating:

- Terminations - gold over nickel on wire-wrap contacts (M1W3)
 - tin lead or lead free on other contacts (M1YD & M1YC)
- Active contact area - gold over nickel

Materials

- **Guiding devices:** passivated stainless steel 303
- **Polarizing pins:** passivated stainless steel 303
- **Plastic insert:** thermoset DAP, 40% glass fiber filled

MECHANICAL CHARACTERISTICS

Backoff¹ (mm)	1
Mating force per contact (N)	0.58 _{MAX}
Unmating force per contact (N)	0.16 < F < 0.58
Durability cycles	500
Sinusoidal vibrations (10 to 2000 Hz) micro discontinuity 10ns	
- unloaded PCB	20 g
- loaded PCB	10 g
Random vibrations (50 to 2000 Hz) micro discontinuity 10ns	0.1 g ² / Hz
Shocks 6ms 1/2 sinus micro discontinuity 10ns	100 g
Recommended tightening torques	
- nuts for Ø 2 mm screws, brass m.N	0.2
- nuts for Ø 2.5 mm screws, brass m.N	0.25


¹: When both connectors are fully mated, the backoff is the maximum distance the connectors can be unmated while functioning properly

ENVIRONMENTAL CHARACTERISTICS

Thermal shocks (°C)	-55 / +125
Salt Spray (hours)	96
Humidity	
Days	56
Temperature (°C)	40
Humidity rate (%)	90-95

ELECTRICAL CHARACTERISTICS

Current rating per contacts (A)	3 - See derating curve
Insulation resistance (at 500Vdc) (GΩ)	5 _{MIN}
Contact resistance (mΩ)	12 _{MAX}
Dielectric Withstanding Voltage (Vrms)	750*
Capacitance between contacts (pF)	2.5 _{MAX}
Self induction (nH)	25 _{MAX}
Immunity against noise of groundings for connectors with central ground strips	Noise $\leq 400\text{mV}$ for 0.1 A intensity per contact and signal rise time of 2ns




* 375Vrms only for F1U2 cts

SIHD >>> SIGNAL CONTACTS (1)

FEMALE CONTACTS FOR PLUGS WITHOUT GROUND STRIP



Double sided SMT




- SMT soldering
- Double sided daughter board
- Surface mount area: 0.7x0.8 [.028x.031]
- PCB thickness: 2.3 to 3.2 [.091 to .126]

Termination style

F1U1

Double sided SMT




- SMT soldering
- Double sided daughter board
- Surface mount area: 0.7x0.8 [.028x.031]
- PCB thickness: 4.56 to 5.37 [.180 to .211]

Termination style

F1U2

Double sided SMT




- SMT soldering
- Double sided daughter board, offset
- Surface mount area: 0.7x0.8 [.028x.031]
- PCB thickness: 1.8 to 2.65 [.071 to .104]

Termination style

F1U3

Straight solder PC tail




- Straight solder PC tail
- Thru hole soldering
- Daughter board

Termination style

F1TS

Right angle solder PC tail




- Thru hole soldering
- Daughter board
- PCB thickness

With heat sink: 2.9 to 3.41 [.114 to .134]
Without heat sink: 1.4 to 1.8 [.055 to .071]

Termination style

F1YC

Crimp barrel



- Crimping on wire
- AWG gauge 22 to 28

Termination style



F1X1

	F1U1	F1U2	F1U3	F1TS	F1YC	F1X1
L_{MAX}	3.21 [.126]	5.37 [.211]	2.65 [.104]	5.5 [.217]	With heat sink: 4.4 [.173] Without heat sink: 2.8 [.110]	2.9 [.114]
Termination section			0.6 x 0.25 [.024 X .010]		Ø 0.5 ± 0.03 [.020 ± .001]	Ø 1.3 [.051]
Active contact area plating μm [μin]				2 [.080] Ni + 1 [.039] Au		
Termination plating μm [μin]	2 [.080] Ni + 7 [.276] SnPb or bright pure Sn for RoHS version				2 [.080] Ni + 3 [.118] SnPb or bright pure Sn for RoHS version	2 [.080] Ni + 1 [.039] Au

SIHD >>> SIGNAL CONTACTS & GROUND STRIP TECHNOLOGY (1 & 2)

MALE CONTACTS FOR RECEPTACLES WITHOUT GROUND STRIP TECHNOLOGY (1)




Wire-wrap	Straight solder PC tail
 <ul style="list-style-type: none"> - Wire wrap connections - Mother board - AWG gauge 28 to 30 	 <ul style="list-style-type: none"> - Thru hole soldering - Mother board - PCB thickness: up to 4.3 ± 0.3 [.169 ± .012]
Termination style	Termination style

M1W3

M1YD

	M1W3	M1YD
L	14.75 ± 0.45 [.581 ± .018]	5.3 ± 0.3 [.209 ± .012]
Termination section	$\varnothing 0.82 \pm 0.04$ [.032 ± .002]	$\varnothing 0.5 \pm 0.03$ [.020 ± .001]
Mating end size	1.2×0.6 [.024 x .047]	
Active contact area plating μm [μin]	$2 [.080] \text{ Ni} + \mathbf{0.2 [.008] Au}$ for standard version or $2 [.080] \text{ Ni} + 3 [.118] \text{ SnPb}$ for tinned version or $2 [.080] \text{ Ni} + 3 [.118]$ bright pure Sn for RoHS version	
Termination plating μm [μin]		$2 [.080] \text{ Ni} + 3 [.118] \text{ SnPb}$ or bright pure Sn for RoHS version




GROUND STRIP TECHNOLOGY (2)

Ground strip benefits



- Reduced cross talk level
- Impedance 70Ω to 120Ω
- Reduced self impedance level
- Capacitance distributed along signal contacts

Central ground strip technology



Arrangements available: 102 & 204 signal contacts
Compatibility: M1YD, M1W3, F1YC, F1U1, F1U2 & F1U3

Note: ground strip has the same termination and active contact area platings as the contacts with which its mounted

All dimensions are given for information only and are in mm [inch], except as otherwise specified


SIHD >>> GUIDING (3) & KEYING (4)

GUIDING (3)

The guides are the fixing accessories for receptacles




A style



Receptacles with M1W3 contacts are delivered with:
 - 3 guides
 - 3 washers
 - 3 cylindrical nuts
 Passivated stainless steel

SIHD E --- A M1W3

B style




Receptacles with M1YD contacts are delivered with:
 - 3 guides
 - 3 washers
 - 3 hexagonal nuts
 Passivated stainless steel

SIHD E --- B M1YD

B

KEYING (4)




Polarizing pins







- More than 250 different positions available
- 5 pins delivered with each connector – Plug and receptacle have 10 holes
- Among the 10 holes of the plug, 5 of them have to be equipped with one pin
- Among the 10 holes of the receptacle, 5 of them have also to be equipped with one pin
- If pins are located in opposite holes for both plug and receptacle, mating is not possible

MATING SEQUENCE



REALIGNMENT CAPABILITY


In the longitudinal axis




In the lateral axis

SIHD >>> FIXING ACCESSORIES (5)

FIXING ACCESSORIES FOR RECEPTACLES = GUIDING



A style




Receptacles with M1W3 contacts are delivered with:
 - 2 or 3 guides
 - 2 or 3 washers
 - 2 or 3 cylindrical nuts
 Passivated stainless steel

SIHD E --- A M1W3

A

B style



Receptacles with M1YD contacts are delivered with:
 - 2 or 3 guides
 - 2 or 3 washers
 - 2 or 3 hexagonal nuts
 Passivated stainless steel


SIHD E --- B M1YD

B

FIXING ACCESSORIES FOR PLUGS

PCB with a thermal drain

A style - For F1U1/F1U2 female contacts



- Mounted to heat sink
- PCB with a heat sink

Passivated stainless steel


SIHD F --- A F1U1

A

SIHD F --- A F1U2

PCB without a thermal drain

D style - For F1YC female contacts




- Mounted to PCB
- PCB without a heat sink

Passivated stainless steel

SIHD F --- D F1YC

D

B style - For F1U1 female contacts




- Mounted to PCB
- PCB with a heat sink

Passivated stainless steel

SIHD F --- B F1U1

E style - For F1U3 female contacts




- Mounted to PCB
- PCB without a heat sink

Passivated stainless steel

SIHD F --- E F1U3

E

C style - For F1YC/F1T female contacts




- Mounted to PCB
- PCB with a heat sink

Passivated stainless steel

SIHD F --- C F1YC

F style - For F1X1 female contacts



- Mounted to PCB
- PCB without a heat sink

Passivated stainless steel

SIHD F --- F F1X1



F

Fixing accessories for plugs equipped with female contacts

	A style	B style	C style	D style	E style	F style
A_{MIN}	F1U1 4.16 [.164] F1U2 3.08 [.121]	F1U1 4.16 [.164]	F1YC 7.72 [.304]	F1YC 7.62 [.300]	F1U3 7.61 [.300]	F1X1 4.93 [.194]

SIHD >>> WITHOUT GROUND STRIP (6)

TYPICAL ARRANGEMENTS





Nb of contacts	128		158		256		390	
	Plug	Receptacle	Plug	Receptacle	Plug	Receptacle	Plug	Receptacle
C	63.5 [2.500]		78.74 [3.100]		63.5 [2.500]		96.52 [3.800]	
D	71.12 [2.800]		86.36 [3.400]		71.12 [2.800]		106.68 [4.200]	
E_{MAX}	77.86 [3.065]	78.38 [3.086]	93.1 [3.665]	93.62 [3.686]	148.98 [5.865]	149.5 [5.886]	220.35 [8.675]	221 [8.701]
h_{MAX}	11.6 [.457]	12.4 [.488]	11.6 [.457]	13.4 [.528]	11.6 [.457]	12.4 [.488]	11.75 [.463]	15 [.591]
D'	72.39 [2.850]	/	87.63 [3.450]	/	71.755 [2.825]	/	106.68 [4.200]	/
I_{MAX}	16.9 [.665]	10.3 [.406]	16.9 [.665]	11.15 [.439]	16.9 [.665]	10.3 [.406]	17.95 [.707]	10.2 [.402]

All dimensions are given for information only and are in mm [inch], except as otherwise specified

SIHD >>> WITH GROUND STRIP (6)

TYPICAL ARRANGEMENTS



Nb of contacts	Plug			Receptacle				
	102	204	230	102	204	230		
C	63.5 [2.500]							
D	71.12 [2.800]							
E _{MAX}	77.86 [3.065]	148.98 [5.865]		78.38 [3.086]	149.5 [5.886]			
h _{MAX}	11.6 [.457]			12.4 [.488]				
D'	72.39 [2.850]	71.755 [2.825]		/				
I _{MAX}	16.9 [.665]			10.3 [.406]				


SIHD >>> WITH GROUND STRIP (6)

LAYOUTS

The boards are shown from the connector side.

All contact locations are equidistant.


n indicates the total number of signal contacts.



6

F1U1/F1U2 CONTACT (female for plug)*


n = 102, 204 or 230



C₁	C - p = C - 2.54
C₃	(C - 5p) / 2
C	See pages 94 & 95
D	See pages 94 & 95

F1YC CONTACT (female for plug)*


n = 102, 204 or 230



C₁	C - p = C - 2.54
C₃	(C - 5p) / 2
C	See pages 94 & 95
D	See pages 94 & 95

M1W3/M1YD (male for receptacle)*

n = 102, 204 or 230



P₂	C / 2
C	See pages 94 & 95
D	See pages 94 & 95

R1	R2	R3	R4	p1	p	2p	p/2
$\emptyset 2.3^{+0.05}_{-0.02} [.091^{+0.005}_{-0.002}]$	$\emptyset 0.6^{+0.05}_{-0.02} [.024]$ 0.9 _{MIN} for W3 contacts	$\emptyset 2.75^{+0.05}_{-0.02} [.108^{+0.002}_{-0.001}]$	$\emptyset 2.7^{+0.05}_{-0.02} [.106]$	1.905 [.075]	2.54 [.100]	5.08 [.200]	1.27 [.050]
d1	d3	d5	h	h1	h2	h3	h2 _{MAX}
3.81 [.150]	$2.7^{+0.1}_{-0.04} [.106^{+0.004}_{-0.001}]$	$3 \pm 0.1 [.118 \pm .004]$	3.75 [.148]	1.845 [.073]	3.175 [.125]	0.575 [.023]	4.35 _{MAX} [.171]

* in mm: 1mm = 0.03937 inch

All dimensions are given for information only and are in mm [inch], except as otherwise specified

127 / HE8


Proven, reliable and robust connector

The 127 series is a medium-density range of multi-contact plug-in connectors for printed circuit boards. This range of 2.54 [.100] staggered grid, low profile connectors meets the common harsh environmental requirements.

A wide range of fittings and guides, as well as numerous contact terminations, provide more flexibility to PCB designers.

A well-proven technology

- The 127 series uses a 2.54 [.100] staggered grid pitch with 2.54 [.100] between rows. Available in 2 or 3 rows.
- The contact technology is based on the tuning fork and blade concept. Using advanced copper alloys provides optimized electrical conductivity as well as long-term mechanical reliability.



A large choice of attachments on Printed Circuit Boards

- Different styles, from 17 to 144 signal contacts with various terminations: straight, right angled 90°, crimp barrel, solder cup, SMT and wire-wrapping.
- Hybrid patterns, with a combination of 3 to 10 special cavities, permit the usage of coaxial, power contacts, as well as optical termini.

The 127 series connectors are available in 3 different versions: HE801 / HE804 / HE807

This proven range of PCB connectors complies with numerous international standards:


NFC UTE 93424
HE801, HE804 & HE807

BS9525
N0001, F0006, F0007

MIL-DTL-55302
140 to 155

QUICK SELECTION GUIDE

Signal contacts ①



Special contacts ②



Keying & Guiding ③

NON KEYING
KEYING
LOCKING
NON LOCKING

Connector type

HE801
Round male contact
Standard molding size

HE804
Rectangular male contact
Molding smaller in size

HE807
Hybrid cavities

PAGE 114

PAGE 115

PAGE 116

PAGE 118

PAGES 112 & 113

127 / HE8 Series

The well proven technology




Table of contents

127/HE8 product range	110
Signal contacts	114
Special contacts	116
Female fittings for receptacles	118
Male fittings for plugs	122
Typical arrangements and layouts, signal connectors (HE801&HE804)	126
Typical arrangements and layouts, hybrid connectors (HE807)	128
Fittings & contacts compatibility	131
Tooling	134

The 127 / HE8 series serves various **markets**, including:



Military Avionics
& Airframe



Commercial Avionics
& Airframe



C4ISR




Ground vehicles




Industrial

127 / HE8 >>> TECHNICAL SPECIFICATIONS

Dimensional characteristics



H = 7.9 [.311] for HE801 & HE807 connectors
 H = 6.9 [.272] for HE804 connectors
 A = 6.3 [.248] for 2-row connectors
 A = 8.55 to 8.94 [.337 to .352] for 3-row connectors
 E = 37.5 to 144.2 [1.476 to 5.677]



Female contact



Female tuning fork contact

- Compatible with other technologies


Material

- CuSn9P (blade)

Plating

- Terminations: gold on W3, X & X1 and tin lead or lead free on YD, Y, Z, YC, YL, T & U
- Active contact area: gold over nickel

Male contact



- For HE801 & HE807 connectors
Contact section: 0.28mm² [.0004 inch²]
- For HE804 connectors
Contact section: 0.48mm² [.0007 inch²]
- Material: CuZn (blade)
- Plating
 - Terminations: gold on W3, X & X1 and tin lead or lead free on YD, Y, Z, YC, YL, T & U
 - Active contact area: gold over nickel


Materials

- Fittings:** electroless nickel over brass or passivated stainless steel (303 ASTM)
- Plastic insert:** thermoset DAP, 30% glass-fiber filled

MECHANICAL CHARACTERISTICS	HE801	HE804	HE807
Backoff¹ (mm)	1 _{MAX} [.039]	1 _{MAX} [.039]	1 _{MAX} [.039]
Mating force per contact (N)	1.60 _{MAX}	1.60 _{MAX}	1.60 _{MAX}
Unmating force per contact (N)	0.14 _{MIN}	0.14 _{MIN}	0.14 _{MIN}
Durability cycles	500	500	250
Vibrations (20 to 2000 Hz) micro discontinuity 1µs	10 g 100 g	10 g 100 g	10 g 100 g
Shocks micro discontinuity 1µs			
Recommended tightening torques			
- nuts for Ø 2.5mm screws, brass m.N	0.25	0.25	0.25
- nuts for Ø 1.6mm screws, brass m.N	0.15	0.15	0.15
ENVIRONMENTAL CHARACTERISTICS			
Thermal shocks (°C)	-55 / +125	-55 / +125	-55 / +125
Salt Spray hours	96	96	96
ELECTRICAL CHARACTERISTICS			
Current rating per contacts (A)	See derating curve	See derating curve	See derating curve
Insulation resistance (GΩ)	5 _{MIN}	5 _{MIN}	5 _{MIN}
Contact resistance (mΩ)	12 _{MAX}	12 _{MAX}	12 _{MAX}
Dielectric Withstanding Voltage (Vrms)	1 000	1 000	1 000
Capacitance between contacts (pF)	5 _{MAX}	5 _{MAX}	5 _{MAX}
Service voltage at 50 Hz (Vrms)	250	250	250


¹: When both connectors are fully mated, the backoff is the maximum distance the connectors can be unmated while functioning properly

Derating Curve




127 / HE8 >>> SIGNAL CONTACTS (1)

FEMALE CONTACTS




Right angle PC tail



- Thru hole soldering
- Single or double sided daughter board
- Termination section: 0.5×0.2 [.020 x .008]
- PCB thickness: $2.5_{\text{MAX}} [.098]$


Long right angle PC tail



- Thru hole soldering
- Single or double sided daughter board
- Termination section: 0.5×0.2 [.020 x .008]
- PCB thickness: $3.5_{\text{MAX}} [.138]$

Termination style YC


SMT single side



- SMT soldering
- Single side daughter board
- Surface mount area: 1.6×0.5 [.063 x .020]

Termination style YL


SMT double side



- SMT soldering
- Double side daughter board
- Surface mount area: 0.8×0.2 [.032 x .008]
- PCB thickness: 1.6 ± 0.3 [.063±.012]

Termination style T


Straight PC tail



- Thru hole soldering
- Mother board
- Termination section: 0.5×0.2 [.020 x .008]
- PCB thickness: $3.2 [.126]$

Termination style U


Solder cup



- Hard-soldering on wire
- Ø: $1 \text{ mm}_{\text{MAX}} [.039]$ on core section $0.78 \text{ mm}^2 [.0012 \text{ inch}^2]$
- Termination section: 1.5×1.2 [.059 x .047]
- PCB thickness: $3.2 [.126]$

Termination style YD/Y


Wire-wrap



- Wire wrap connections
- AWG gauge 28 to 30
- Termination section: 0.6×0.6 [.024 x .024]
- PCB thickness: $3.2 [.126]$

Termination style Z

Crimp barrel



- Crimping on wire
- AWG gauge 22 to 26
- Terminations protected by a casing cemented to the moulding
- PCB thickness: $3.2 [.126]$

Termination style W3


Termination style X1

	YC	YL	T	U	YD	Y	Z	W3	X1	
A_{MAX} for HE801/HE807	3 [.118]	4 [.157]	2.8 [.110]	5.5 [.217]	4.7 [.185]	4.9 [.193]	4.5 [.177]	14.1 [.555]	7 [.276]	
A_{MAX} for HE804			3.8 [.150]	6.5 [.256]			5.5 [.217]	15 [.591]	8 [.315]	
Active contact area plating μm [μin]	2 [.080] Ni + 1 [.040] Au					2 [.08] Ni + 1 [.040] Au				
Termination plating μm [μin]	2 [.080] Ni + 3 to 6 [.120 to .240] SnPb or bright pure Sn for RoHS version					2 [.08] Ni + 0.2 [.008] Au				


All dimensions are given for information only and are in mm [inch], except as otherwise specified

127 / HE8 >>> SIGNAL CONTACTS (1)

MALE CONTACTS



Right angle PC tail




- Thru hole soldering
- Single or double sided daughter board
- Termination section: 0.35 x 0.35 [.014 x .014]
- PCB thickness: 2.6 [.102]



Termination style

YC

Long right angle PC tail




- Thru hole soldering
- Single or double sided daughter board
- Termination section: 0.35 x 0.35 [.014 x .014]
- PCB thickness: 3.7 [.146]



Termination style

YL

Straight PC tail




- Thru hole soldering
- Mother board
- Termination section: 0.35 x 0.35 [.014 x .014]
- PCB thickness: 3.2 [.126]



Termination style

Y

SMT double side




- SMT soldering
- Double sided daughter board
- Surface mount area: 0.64 x 0.6 [.025 x .024]
- PCB thickness: 1.6 ± 0.3 [.063 ± .012]



Termination style

U

Solder cup




- Hard-soldering on wire
- Ø: 1_{MAX} [.039] on core section 0.78 mm² [.0012inch²]
- PCB thickness: 3.2 [.126]



Termination style

ZC

Wire-wrap




- Wire wrap connections
- AWG gauge 28 to 30
- Termination section: 0.6 x 0.6 [.024 x .024]
- PCB thickness: 3.2 [.126]



Termination style

W3

Crimp barrel



- Crimping on wire
- AWG gauge 22 to 26
- Terminations protected by a casing cemented to the moulding
- PCB thickness: 3.2 [.126]
- Not available for HE801 and HE807 connectors



Termination style

X

A_{MAX} for HE801/HE807

YC YL Y U ZC W3 X

3.1 [.122]

4.2 [.165]

5.05 [.199]

4.2 [.165]

4.3 [.169]

15.05 [.593]

7 [.276]

A_{MAX} for HE804

5 [.197]

5.2 [.205]

5.3 [.209]

13.2 [.520]

8 [.315]

Active contact area plating μm [μin]

2 [.080] Ni + 1 [.040] Au

2 [.080] Ni + 1 [.040] Au

Termination plating μm [μin]

2 [.080] Ni + 3 to 6 [.120 to .240] SnPb or bright pure Sn for RoHS version

2 [.080] Ni + 0.2 [.008] Au


All dimensions are given for information only and are in mm [inch], except as otherwise specified

127 / HE8 >>> SPECIAL CONTACTS (2)

POWER CONTACTS**

Current rating 10A

Solder cup




- Hard soldering on wire
- Wire diameter up to 2 [.079]
- Termination section: Ø 3.6 [.142]
- Current rating 10A



Pin	M121*
Socket	F121*

Straight PC tail




- Thru hole soldering
- Mother board
- Termination section: Ø 1.2 [.047]
- PCB thickness: up to 3.2_{MAX} [.126]
- Current rating 10A



Pin	M141*
Socket	F141*

Right angle PC tail




- Thru hole soldering
- Daughter board
- Termination section: Ø 1.2 [.047]
- PCB thickness: 1.6 to 2.4 [.063 to .095]
- Current rating 10A



Pin	M132*
Socket	F132*

Current rating 20A

Solder cup



- Hard soldering on wire
- Wire diameter up to 1.83 [.072]
- Current rating 20A



Pin	MH1*
Socket	FH1*

Current rating at 5V (A)

10

Maximum current rating at 5V (A)

15

Contact resistance (mΩ)

12_{MAX}

Operating temperature rise (°C)

20_{MAX}


Contact retention (N)

50_{MIN}

Insertion and extraction force per contact (N)

f ≤ F ≤ 15

Right angle PC tail




- Thru hole soldering
- Daughter board
- Termination section: 1.2 [.047]
- PCB thickness: 1.6 to 2.4 [.063 to .095]
- Current rating 20A



Pin	MH3*
Socket	FH3*

Straight PC tail



- Thru hole soldering
- Mother board
- Termination section: 1.4 [.053]
- PCB thickness: up to 3.2_{MAX} [.126]
- Current rating 20A



Pin	MH2*
Socket	FH2*

Current rating at 5V (A)

20

Contact resistance (mΩ)

12_{MAX}

Operating temperature rise (°C)

20_{MAX}

Contact retention (N)

50_{MIN}

Insertion and extraction force per contact (N)

f ≤ F ≤ 15

	M121/F121	M141/F141	M132/F132	MH1/FH1	MH2/FH2	MH3/FH3
A_{MAX}	8.2 [.323]	3.8 [.150]	3.8 [.150]	6.3 [.248]	4.2 [.165]	3.8 [.150]
Central contact area plating µm [µin]				2 [.080] Ni + 1.2 [.047] Au		
Other plating area µm [µin]				2 [.080] Ni + 0.4 [.016] Au		

All dimensions are given for information only and are in mm [inch], except as otherwise specified




127 / HE8 >>> SPECIAL CONTACTS (2)


COAXIAL CONTACTS**



Straight PC tail




- Thru hole soldering
- Mother board
- Termination section: Ø 0.5 [.020]
- PCB thickness: 3.2_{MAX} [.126]




Pin	M041*
Socket	F041*

Right angle PC tail



- Thru hole soldering
- Daughter board
- Termination section: Ø 0.5 [.020]
- PCB thickness: 1.6 to 2.4 [.063 to .095]




- Thru hole soldering
- Daughter board
- Termination section: Ø 0.5 [.020]
- PCB thickness: 1.6 to 2.4 [.063 to .095]



Pin	M032*
Socket	F032*

Straight on flexible cable




- Hard-soldering on flexible cable




Pin	M011*
Socket	F011*

Straight on flexible cable



- Hard-soldering on flexible cable
- Wire outer diameter up to 2 [.079]
- KX 21 A / RG 178 B/U



Pin	M021*
Socket	F021*

COAXIAL CONTACTS

Impedance (Ω)	50
Voltage rating (Vrms)	180
Current rating (mA)	500
Contact retention (N)	50 _{MIN}
Frequency range (GHz)	0 to 1
Contact resistance (mΩ)	12 _{MAX}
SWR (at 1 GHz)	1.3 _{MAX}
Insertion and extraction force per contact (N)	1 ≤ F ≤ 15

OPTICAL TERMINI

Consult us.

	M041/F041	M021/F021	M011/F011	M032/F032
A _{MAX}	3.8 [.150]	9.2 [.362]	2.5 [.098]	6.2 [.244]
B _{MAX}			2.54 [.100]	
Central contact area plating µm [µin]		2 [.080] Ni + 1.2 [.047] Au		
Other plating area µm [µin]		2 [.080] Ni + 0.4 [.016] Au		

* Coaxial contacts and power contacts have to be ordered separately against the here above part number. Example: F011

** These contacts can be mounted in all types of connectors 127H-127C/HE807.

127 / HE8 >>> FEMALE FITTINGS (3)

END FITTINGS FOR RECEPTACLES**




Codable & Non lockable fittings

K				
	- Chassis or mother board - Fixed receptacle Compatibility - Female contact: 801 / 804 / 807 - Male contact: 807 - Nickel over brass*	EF	CF	
	HE 801 / 807	212	229	
	HE 804	201	202	
A				
	- Chassis or mother board - Fixed receptacle Compatibility - Male contact: 801 / 804 - Nickel over brass*	EF	CF	
	HE 801	212	229	
	HE 804	201	202	
P				
	- Chassis - Floating receptacle Compatibility - Female contact: 801 / 804 - Nickel over brass*	EF	CF	
	HE 801	203	202	
	HE 804	203	202	
B				
	- Chassis - Floating receptacle Compatibility - Male contact: 801 / 804 - Nickel over brass*	EF	CF	
	HE 801	203	202	
	HE 804	203	202	
P				
	- Chassis - Floating receptacle Compatibility - Female contact: 807 - Male contact: 807 - Nickel over brass *	EF	CF	
	HE 807	226	202	
L				
	- Chassis or mother board - With insulating washer Compatibility - Female contact: 804 - Nickel over brass *	EF	CF	
	HE 804	228	202	
KE				
	- Daughter board or board to board mating - Free receptacle - with bracket - Connection board to board aligned with each other Compatibility - Female contact: 801 / 807 - Male contact: 807 - Nickel over brass *	EF	CF	
	HE 801	208	209	
	HE 807	208	208	
AE				
	- Daughter board or board to board mating - Free receptacle - with bracket - Connection board to board aligned with each other Compatibility - Male contact: 801 - Nickel over brass *	EF	CF	
	HE 801	208	209	
KE				
	- Daughter board or board to board mating - Free receptacle - with bracket - Connection board to board aligned with each other Compatibility - Female contact: 804 - Nickel over brass *	EF	CF	
	HE 804	209	209	
AE				
	- Daughter board or board to board mating - Free receptacle - with bracket - Connection board to board aligned with each other Compatibility - Male contact: 804 - Nickel over brass *	EF	CF	
	HE 804	209	209	

127 / HE8 >>> FEMALE FITTINGS (3)

END FITTINGS FOR RECEPTACLES**



Non codable & lockable fittings

S		
	- Cables, free receptacle - Locking device-extractor - tapped female fitting - Locking and unlocking shall be carried out simultaneously at both ends	
Compatibility		
- Female contact: 801 / 804 - Nickel over brass *		
	EF	CF
HE 801	219	229
HE 804	220	202

D		
	- Cables, free receptacle - Locking device-extractor - tapped female fitting - Locking and unlocking shall be carried out simultaneously at both ends	
Compatibility		
- Male contact: 801 / 804 - Nickel over brass *		
	EF	CF
HE 801	219	229
HE 804	220	202

SC		
	- Cables, free receptacle - Flex, locking device-extractor	
Compatibility		
- Female contact: 804 - Nickel over brass *		
	EF	CF
HE 804	207	202

DC		
	- Cables, free receptacle - Flex, locking device-extractor	
Compatibility		
- Male contact: 804 - Nickel over brass *		
	EF	CF
HE 804	207	202

SC		
	- Chassis, floating receptacle - Locking device-extractor	
Compatibility		
- Female contact: 801 - Nickel over brass *		
	EF	CF
HE 801	213	229

DC		
	- Chassis, floating receptacle - Locking device-extractor	
Compatibility		
- Male contact: 801 - Nickel over brass *		
	EF	CF
HE 801	213	229

S		
	- Chassis, floating receptacle - Locking device-extractor - tapped female fitting	
Compatibility		
- Female contact: 807 - Male contact: 807 - Nickel over brass *		
	EF	CF
HE 807	213	229

	S 219 220	D 219 220	SC 207	DC 207	SC 213	DC 213	S 213
A	Ø 5.7 [.224]						Ø 5.8 [.228]
D	4.7 _{MAX} [.185]						6 _{MAX} [.236]
E							2.1 _{MAX} [.083]


	K 212/201	A 212/201	P 203	B 203	P 226	L 228	KE 208	AE 208	KE 209	AE 209
A			Ø 6 [.236]		Ø 6 [.236]	Hex 5 [.197]		Ø 3.5 [.138]		Ø 3.5 [.138]
A'								M 2.5 [.098]		Hex 4 [.157]
B			Ø 4.5 [.177]		Hex 4.5 [.177]					1 _{MAX} [.039]
C	M 2.5 [.098]		M 2.5 [.098]			M 2.5 [.098]				
D	6 _{MAX} [.236]		7.2 [.283]		5.9 [.232]	6 _{MAX} [.236]		4.6 [.181]		
E	3.2 _{MAX} [.126]		2.2 [.087]		2.1 _{MAX} [.083]	2.7 _{MAX} [.106]		1.6 to 2.4 [.063 to .094]		
F					2.3 [.091]			2.35 [.093]		3.35 [.132]
G								7.2 _{MAX} [.283]		7.2 _{MAX} [.283]
H								5.5 [.217]		

*To order the same fitting in passivated stainless steel, change the "2" in the HE8 reference to a "4" (2xx => 4xx)

** To order the fitting alone: HE8C + xxx


127 / HE8 >>> FEMALE FITTINGS (3)

END FITTINGS FOR RECEPTACLES**



Codable & lockable fittings

KD




- Chassis or mother board
- Fixed receptacle
- Locking ensuring resistance to vibrations

Compatibility

- Female contact: 801 / 804 / 807
- Male contact: 807
- Nickel over brass*

	EF	CF
HE 801 / 807	221	229
HE 804	221	202

AD




- Chassis or mother board
- Fixed receptacle
- Locking ensuring resistance to vibrations

Compatibility

- Male contact: 801 / 804
- Nickel over brass*

	EF	CF
HE 801 / 804	221	229
HE 804	221	202

KED




- Daughter board
- Free receptacle - with bracket
- Connection board to board aligned with each other
- Locking ensuring resistance to vibrations

Compatibility

- Female contact: 804
- Nickel over brass*

	EF	CF
HE 804	223	209

AED




- Daughter board
- Free receptacle - with bracket
- Connection board to board aligned with each other
- Locking ensuring resistance to vibrations

Compatibility

- Male contact: 804
- Nickel over brass*

	EF	CF
HE 804	223	209

KED




- Daughter board
- Free receptacle - with bracket
- Connection board to board aligned with each other
- Locking ensuring resistance to vibrations

Compatibility

- Female contact: 801 / 807
- Male contact: 807
- Nickel over brass *

	EF	CF
HE 801	224	209
HE 807	224	208

AED




- Daughter board
- Free receptacle - with bracket
- Connection board to board aligned with each other- Locking ensuring resistance to vibrations

Compatibility

- Male contact: 801
- Nickel over brass *

	EF	CF
HE 801	224	209

KT




- Chassis or mother board
- Fixed receptacle
- Quarter turn locking on plug side

Compatibility

- Female contact: 801 / 804/ 807
- Male contact: 807
- Passivated stainless steel only*

	EF	CF
HE 801 / 807	422	429
HE 804	422	402

AT




- Chassis or mother board
- Fixed receptacle
- Quarter turn locking on plug side

Compatibility

- Male contact: 801/ 804
- Passivated stainless steel only

	EF	CF
HE 801	422	429
HE 804	422	402

KET




- Daughter board or board to board mating
- Free receptacle
- Quarter turn locking on plug side

Compatibility

- Female contact: 801/ 804/ 807
- Male contact: 807
- Passivated stainless steel only

	EF	CF
HE 801/804/807	425	425

AET



- Daughter board or board to board mating
- Free receptacle
- Quarter turn locking on plug side


Compatibility

- Male contact: 801/ 804
- Passivated stainless steel only


	EF	CF
HE 801/804	425	425

127 / HE8 >>> FEMALE FITTINGS (3)

CENTRAL FITTINGS FOR RECEPTACLES**



229




Compatibility

- Female contact: 801 / 807
- Male contact: 801 / 807
- **EF:** K / A / P / B / S / D / SC / DC / KD / AD
- Nickel over brass *

HE 801/807

229

202




Compatibility

- Female contact: 804
- Male contact: 804
- **EF:** K / A / P / B / L / S / D / SC / DC / KD / AD
- Nickel over brass *

HE 804

202

429




Compatibility

- Female contact: 801 / 807
- Male contact: 801 / 807
- **EF:** KT / AT
- Passivated stainless steel *

HE 801 / 807

429

402




Compatibility

- Female contact: 804
- Male contact: 804
- **EF:** KT / AT
- Passivated stainless steel *

HE 804

402

208




Compatibility

- Female contact: 801 / 807
- Male contact: 801 / 807
- **EF:** KE / AE / KED / AED
- Nickel over brass *

HE 801 / 807

208

209




Compatibility

- Female contact: 804
- Male contact: 804
- **EF:** KE / AE / KED / AED
- Nickel over brass *

HE 804

209

425



Compatibility

- Female contact: 801 / 804 / 807
- Male contact: 801 / 804 / 807
- **EF:** KET / AET
- Passivated stainless steel *

HE 801 / 804 / 807

EF 224 | CF 208

202 / 229 / 429 / 402

208

209

425

A	Ø 4 [.157]	Ø 3.5 [.138]	Hex 5 [.197]
B		1 _{MAX} [.039]	
D	7 _{MAX} [.276]	4.6 [.181]	4.1 _{MAX} [.161]
E		1.6 to 2.4 [.063 to .094]	
F		2.35 [.093]	3.35 [.132]
G		7.2 _{MAX} [.283]	
H		5.5 [.217]	
A'		M 2.5 [.098]	Hex 4 [.157]
C			Hex 4 [.157]
			M 2.5 [.098]

KD / AD 221

KED / AED 223

KED / AED 224

KT / AT 422

KET / AET 425

A	Ø 5 [.197]	Ø 5 [.197]	Ø 5 [.197]	
C	M 2.5 [.098]	Ø 3.5 [.138]	Ø 3.5 [.138]	M 2.5 [.098]
D	X _{HE804} = 18 _{MAX} [.709] Y _{HE804} = 26.1 _{MAX} [.1028] Z _{HE804} = 14 _{MAX} [.551]	X _{HE801/807} = 17 _{MAX} [.669] Y _{HE801/807} = 25.1 _{MAX} [.988] Z _{HE801/807} = 13 _{MAX} [.512]	Z = 14 _{MAX} [.551]	HE804: 7 _{MAX} [.276] HE801 / 807: 6 _{MAX} [.236]
D'			4.6 [.181]	4.1 _{MAX} [.161]
E	3.2 _{MAX} [.126]	1.6 to 2.4 [.063 to .094]		
A'	Hex 5 [.197]		M 2.5 [.098]	Hex 4 [.157]
C'		Ø 1.6 [0.63]		

** To order the fitting alone: HE8C + xxx


*To order the same fitting in passivated stainless steel, change the "2" in the HE8 reference to a "4" (2xx => 4xx)

*To order the same fitting in nickel over brass, change the "4" in the HE8 reference to a "2" (4xx => 2xx)

x: unlocked - y: screw out - z: locked


127 / HE8 >>> MALE FITTINGS (3)

END FITTINGS FOR PLUGS**



Non codable & Non lockable fittings

PA




- Daughter board or extension board single or double sided
- Free plug - with plated thru holes
- Compatibility**
 - Female contact: 801 / 804 / 807
 - Male contact: 807
 - Nickel over brass *

HE 801 / 804 / 807

EF 102 | CF 102

PC




- Daughter board or extension board single or double sided
- Free plug - with plated thru holes
- Compatibility**
 - Male contact: 801 / 804
 - Nickel over brass *

- Daughter board or extension board single or double sided
- Free plug - with plated thru holes
- Compatibility**
 - Male contact: 801 / 804
 - Nickel over brass *

HE 801 / 804

EF 102 | CF 102

T



- Chassis or mother board
- Board to board, board to chassis, parallel to one another
- Compatibility**
 - Female contact: 801 / 804 / 807
 - Male contact: 801 / 804 / 807
 - Nickel over brass *

HE 801 / 807


EF 118 | CF 129

HE 804

EF 111 | CF 113

Non codable & lockable fittings

D




- Daughter board single or double sided
- Free plug - with plated thru holes
- Lockable on receptacle side
- Compatibility**
 - Female contact: 801 / 804 / 807
 - Male contact: 807
 - Nickel over brass *

HE 801 / 804 / 807

EF 103 | CF 102

EF



- Chassis or mother board
- Board to board, board to chassis, parallel to one another, board to cable or chassis to cable
- Lockable on receptacle side
- Compatibility**
 - Female contact: 801 / 804 / 807
 - Male contact: 807
 - Nickel over brass *


HE 801 / 807

EF 119 | CF 129

HE 804

EF 112 | CF 113

NF



- SMT daughter board aligned with connector centerline
- Lockable on receptacle side
- Compatibility**
 - Female contact: 801 / 804
 - Male contact: 801 / 804
 - Nickel over brass *


HE 801

EF 116 | CF 114

HE 804

EF 108 | CF 104

	PA / PC	T
A	Hex 4 [.157]	Hex 5 [.197]
C	1.6 to 2.4 [.063 to .094]	M 2.5 [.098]
D	1.3 _{MAX} [.051]	6 _{MAX} [.236]




- Daughter board single or double sided
- Free plug - with plated thru holes
- Lockable on receptacle side
- Compatibility**
 - Male contact: 801 / 804
 - Nickel over brass *

HE 801 / 804

EF 103 | CF 102

RF



- Chassis or mother board
- Free plug - with plated thru holes
- Lockable on receptacle side
- Compatibility**
 - Male contact: 801 / 804
 - Nickel over brass *

HE 801

EF 119 | CF 129

HE 804

EF 112 | CF 113

	D / S	EF	RF	NF
A	Hex 4 [.157]	Hex 5 [.197]		
C	1.6 to 2.4 [.063 to .094]	M 2.5 [.197]		1.6 [.063]
D	1.3 _{MAX} [.051]		6 _{MAX} [.236]	HE801 13.9 _{MAX} [.547] HE804 12.2 _{MAX} [.480]
F			3.2 _{MAX} [.126]	1.1 [.043]
G				3.5 [.138]


127 / HE8 >>> MALE FITTINGS (3)

END FITTINGS FOR PLUGS**



Codable & Non lockable fittings

A




- Daughter board single or double sided
- Free plug - with plated thru holes

Compatibility

- Female contact: 801 / 804 / 807
- Male contact: 807
- Nickel over brass *

	EF	CF
HE 801 / 804 / 807	101	102

J




- Daughter board single or double sided
- Free plug - with plated thru holes

Compatibility

- Male contact: 801 / 804
- Nickel over brass *

	EF	CF
HE 801 / 804	101	102

N




- SMT daughter board aligned with connector centreline
- Free plug - with plated thru holes

Compatibility

- Female contact: 801 / 804
- Male contact: 801 / 804
- Nickel over brass *

	EF	CF
HE 801	115	114
HE 804	106	104

V




- SMT daughter board aligned with connector centreline
- Free plug - with plated thru holes

Compatibility

- Female contact: 801 / 804
- Male contact: 801 / 804
- Nickel over brass *

	EF	CF
HE 801	114	114
HE 804	104	104

E




- Chassis or mother board
- Board to board, board to chassis

Compatibility

- Female contact: 801 / 804 / 807
- Male contact: 807
- Nickel over brass *

	EF	CF
HE 801 / 807	117	129
HE 804	110	113

R




- Chassis or mother board (board to board, board to chassis)

Compatibility

- Male contact: 801 / 804
- Nickel over brass *

	EF	CF
HE 801	117	129
HE 804	110	113

H



- SMT daughter board
- Offset from connector centreline
- Free plug - with plated thru holes

Compatibility

- Female contact: 804
- Nickel over brass *

	EF	CF
HE 804	107	105


	A	J	N	V	E	R	H
A	Hex 4 [.157]				Hex 5 [.197]		
C	1.6 to 2.4 [0.63 to 0.94]		1.6 [0.63]		M 2.5 [.098]	1.6 [0.63]	
D	1.3 _{MAX} [.051]	HE801 13.9 _{MAX} [.547] HE804 12.2 _{MAX} [.480]			6 _{MAX} [.236]	13.05 _{MAX} [.514]	
F			1.1 [.043]		3.2 _{MAX} [.126]	1.1 [.043]	
G				3.5 [.138]			2.7 [.106]

*To order the same fitting in passivated stainless steel, change the "1" in the HE8 reference to a "3" (1xx => 3xx)

** To order the fitting alone: HE8C + xxx


127 / HE8 >>> MALE FITTINGS (3)

END FITTINGS FOR PLUGS**



Codable & lockable fittings

AS




- Daughter board single or double sided
- Free plug - with plated thru holes
- Lockable on receptacle side

Compatibility

- Female contact: 801 / 804 / 807
- Male contact: 807
- Nickel over brass *

	EF	CF
HE 801 / 804 / 807	124	102

JS




- Daughter board single or double sided
- Free plug - with plated thru holes
- Lockable on receptacle side

Compatibility

- Male contact: 801 / 804
- Nickel over brass *

	EF	CF
HE 801 / 804	124	102

ES




- Chassis or mother board
- Board to board, board to chassis, parallel to one another, board to cable or chassis to cable
- Lockable on receptacle side

Compatibility

- Female contact: 801 / 804 / 807
- Male contact: 807
- Nickel over brass *

	EF	CF
HE 801	125	129
HE 804	125	113

RS




- Chassis or mother board
- Board to board, board to chassis, parallel to one another, board to cable or chassis to cable
- Lockable on receptacle side

Compatibility

- Male contact: 801 / 804
- Nickel over brass *

	EF	CF
HE 801	125	129
HE 804	125	113

ET




- Cable to board or cable to chassis
- Quarter turn locking
- Dimensions given in reset position

Compatibility

- Female contact: 801 / 804 / 807
- Male contact: 807
- Passivated stainless steel only

	EF	CF
HE 801/807	327	329
HE 804	327	313

RT




- Cable to board or cable to chassis
- Quarter turn locking
- Dimensions given in reset position

Compatibility

- Male contact: 801 / 804
- Passivated stainless steel only

	EF	CF
HE 801	327	329
HE 804	327	313

NS



- SMT daughter board aligned with fitting centerline
- Lockable on receptacle side

Compatibility


- Female contact: 801 / 804
- Male contact: 801 / 804
- Nickel over brass *

	EF	CF
HE 801	114	114
HE 804	126	104


	AS	JS	ES	RS	ET	RT	NS
A	Hex 4 [.157]		Hex 5 [.197]		$\emptyset 6 [.236]$		
C	1.6 to 2.4 [.063 to .094]		M 2.5 [.098]				1.6 [.063]
D	1.3 _{MAX} [.051]		7 _{MAX} [.276]		16 _{MAX} [.630]		HE801 13.9 _{MAX} [.547] HE804 12.2 _{MAX} [.480]
F			3.2 _{MAX} [.126]				1.1 [.043]
G							3.5 [.138]

127 / HE8 >>> MALE FITTINGS (3)

CENTRAL FITTINGS FOR PLUGS**




114



Compatibility

- Female contact: 801
- Male contact: 801
- N / V / NF / NS
- Nickel over brass *

104



Compatibility


- Female contact: 804
- Male contact: 804
- N / V / NF / NS
- Nickel over brass *

HE 801

114

104

129



Compatibility


- Female contact: 801 / 807
- Male contact: 801 / 807
- E / R / T / EF / RF / ES / RS
- Nickel over brass *

HE 801/807

129

113

113




Compatibility

- Female contact: 804
- Male contact: 804
- E / R / T / EF / RF / ES / RS
- Nickel over brass *

HE 804

113

329



Compatibility


- Female contact: 801 / 807
- Male contact: 801 / 807
- ER / RT
- Passivates stainless steel *

HE 801 / 807

329

313

313




Compatibility

- Female contact: 804
- Male contact: 804
- ER / RT
- Passivated stainless steel *

HE 804

313

102




Compatibility

- Female contact: 801 / 804 / 807
- Male contact: 801 / 804 / 807
- A / J / PA / PC / D / S / AS / JS
- Nickel over brass *

HE 801 / 804 / 807

102

105



Compatibility

- Female contact: 804
- H
- Nickel over brass *

HE 804

105

	114	104	129	113	329	313	102	105
A	1.6 [.063]		$\varnothing 4$ [.157]				Hex 4 [.157]	1.1 [.043]
D	13.9_{MAX} [.547]	12.2_{MAX} [.480]	7_{MAX} [.276]				1.3_{MAX} [.051]	12.2_{MAX} [.480]
F	1.1 [.043]						1.6 to 2.4 [.063 to .094]	1.6 [.063]
G	3.5 [.514]						2.7 [.106]	

** To order the fitting alone: HE8C + xxx

*To order the same fitting in passivated stainless steel, change the "1" in the HE8 reference to a "3" (1xx => 3xx)

*To order the same fitting in nickel over brass, change the "3" in the HE8 reference to a "1" (3xx => 1xx)


127 / HE8 >>> HE 801 & HE 804

TYPICAL ARRANGEMENTS



n indicates the total number of signal contacts


Signal contacts on 2 rows without central fitting*



n = 17, 29, 33, 41, 53 or 65

A	6.3 ^{+0.1}
B	(n-1) X 1.27
C	B - 2.54
D	B + 10.16
E	≈ D + 7


Signal contacts on 2 rows with central fittings *



n = 72, 84, or 96

A	6.3 ^{+0.1}
B	(n-4) X 0.635
D	2 X (B + 10.16)
E	≈ D + 7


Signal contacts on 3 rows without central fittings *



n = 80

A	8.94
C	66.04
D	76.3 _{MAX}
E	83.4 _{MAX}
F	3.1


Signal contacts on 3 rows with central fittings *



n = 144


A	8.55 _{MAX}
B	58.42
D	137.16
E	144.36 _{MAX}
F	3.1

Panel drilling*



- Receptacle with A-AD-AT fittings or plug with R-RF-RS-T fittings with male contact W3-ZC-X
- Receptacle with K-KD-KT-L fittings or plug with E-EF-ES-T fittings with female contact W3-Z

D	See above
L	≈ D - 4.6
h	9.5 _{MIN}
R	Ø 2.85 _{MIN}



- Receptacle with B fitting and male contact W3-ZC-X
- Receptacle with P fitting and female contact W3-Z

D	See above
L	≈ D - 4.6
h	9.5 _{MIN}
R	Ø 5 ± 0.1

* in mm: 1mm = 0.03937 inch

** The standard version presents a stiffening bar with W3-ZC-Z contacts and no stiffening bar with YC-V-Y-YD-X contacts. Put an A in the part number code to have no stiffening bar on the connector with W3-ZC-Z contacts or a B to have a stiffening bar on the connector with YC-U-Y-YD-X contacts.

127 / HE8 >>> HE 801 & HE 804


LAYOUTS

The boards are shown from the connector side.


The drawings show various footprints for connectors with a central attachment on board.

For smaller connectors (17, 29, 33, 41, 53 and 65 contacts), omit the center drilling.

All contacts outputs are equidistant. For daughterboard, the first contact's marking is indicated for reference only.




Daughterboard drilling for YC contact*




- Receptacle with KET-AET fittings or plug with A-D-AS-PA-J-S-JS-PC fittings
- YC (male and female contact)

Daughterboard drilling for U contact*




- Plug with H-N-NF-NS-V fittings
- U (male and female contact)

Daughterboard drilling for YC contact*




- Receptacle with KE-KED-AE-AED fittings
- YC (male and female contact)

Motherboard drilling for Y contact (male and female)*



- Receptacle with A-AD-AT fittings or plug with R-RF-RS-T fittings
- Y (male and female contact)

Motherboard drilling for YD contacts (socket only)*



- Receptacle with K-L-KD-KT fittings or plug with E-EF-ES-T fittings
- YD (female contact only)

	D	d ₁	d ₂	p	p _{/2}	h	h ₁	h ₂	h ₄	R ₀	R ₁	R ₂	R ₄	u
See above	3.81 [.150]	5.08 [.200]	2.54 [.100]	1.27 [.050]	3 _{MAX} [.118]	1.9 [.075]	0.64 [.025]	8 _{MAX} [.315]	Ø 1.8 _{MIN} [.071]	Ø 2.85 _{MIN} [.112]	Ø 0.75 _{MIN} [.030]	Ø 2.4 _{MIN} [.094]	1.6 ± 0.1 [.063 ± .004]	

* in mm: 1mm = 0.03937 inch

All dimensions are given for information only and are in mm [inch], except as otherwise specified

127 / HE8 >>> HE 807


TYPICAL ARRANGEMENTS

n indicates the total number of signal contacts

h indicates the total number of hybrid contacts



n signal contacts + 3 cavities without central fittings*



Note:


- Asymmetrical arrangements with female contacts always have plug marking
- Asymmetrical arrangements with male contacts always have receptacle marking

- n = 5, 17, 29, 41 or 53

- h = 3

B	(n - 1) X 1.27
D	(n + 12) x 1.27 + 8.89
E	D + 7

n signal contacts + 6 cavities without central fittings*




- n = 5, 17, 29 or 41

- h = 6

B	(n - 1) X 1.27
D	(n + 24) x 1.27 + 8.89
E	D + 7

n signal contacts + 3 cavities with central fittings*



Note:


- Asymmetrical arrangements with female contacts always have plug marking
- Asymmetrical arrangements with male contacts always have receptacle marking

- n = 60, 72 or 84

- h = 3

A	6.3 ^{+0.1}
D	(n+8) x 1.27 + 20.32
E	D + 7

n signal contacts + 6 cavities with central fittings*




- n = 48, 60, 72

- h = 6


A	6.3 ^{+0.1}
D	(n+20) x 1.27 + 20.32
E	D + 7

Panel drilling*



- Receptacle with K-KD-KT fittings or plug with E-EF-ES fittings and male contacts W3-ZC-X and special contacts
- Receptacle with K-KD-KT fittings or plug with E-EF-ES fittings and female contacts W3-ZC-X1 and special contacts
- F011 / M011 F021 / M021
F121 / M121 FH1 / MH1

D	See above
L	D - 4.6
h	9.5 MIN
R	Ø 2.85 MIN ⊕ Ø 0.2




- Receptacle with P fitting with male contacts W3-ZC-X and special contacts
- Receptacle with P fitting with female contact W3-ZC-X1 and special contacts
- F011 / M011 F021 / M021
F121 / M121 FH1 / MH1


D	See above
L	D - 4.6
h	9.5 MIN
R	Ø 5 ± 0.1 ⊕ Ø 0.2

127 / HE8 >>> HE 807

LAYOUTS COAXIAL CONTACTS




Daughterboard drilling YC + F032/M032 contacts*




- Receptacle with KET fittings or plug A-D-AS-PA
- YC & coaxial F032/M032 contacts (male & female)

Daughterboard drilling YC + F032/M032 contacts*




- Receptacle KE
- YC & coaxial F032/M032 contacts (male & female)

Daughterboard drilling YC + F032/M032 contacts*




- Receptacle IE
- YC & coaxial F032/M032 contacts (male & female)

Motherboard drilling Y + F041/M041 contacts*




- Receptacle with K-KD-KT fittings and plug E-EF-ES-T fittings.
- Y & coaxial F041 / M041 contacts (male & female contacts)

Contact F041/M041



Contact F032/M032




D	d ₁	d ₂	p	p _{/2}	h ₀	h ₁	h ₂	R ₁	R ₂	h
See above	3.81 [.150]	5.08 [.200]	2.54 [.100]	1.27 [.050]	3 _{MAX} [.118]	1.9 [.075]	0.64 [.025]	Ø 2.85 _{MIN} [.112] + Ø 0.2 [.030]	Ø 0.75 _{MIN} [.030] + Ø 0.2 [.030]	9.35 [.368]

* in mm: 1mm = 0.03937 inch


All dimensions are given for information only and are in mm [inch], except as otherwise specified

127 / HE8 >>> HE 807

LAYOUTS. POWER CONTACTS.




Daughterboard drilling YC + FH3/MH3 & F132/M132




- Receptacle with KET fitting & plug with A-D-AS-PA fittings
- YC & power FH3 / MH3 & F132 / M132 contacts (male & female)

Daughterboard drilling YC + FH3/MH3 & F132/M132




- Receptacle with KE fitting
- YC & power FH3 / MH3 & F132 / M132 contacts (male & female)

Daughterboard drilling YC + FH3/MH3 & F132/M132



- Receptacle with IE fitting
- YC & power FH3 / MH3 & F132 / M132 contacts (male & female)

Daughterboard drilling Y + FH2/MH2 & F141/M141



- Receptacle with K-KD-KT fitting with Y & power FH2 / MH2 & F141 / M141 contacts (male & female)
- Plug with E-EF-ES-T fittings with Y & power FH2 / MH2 & F141 / M141 contacts (male & female)

	D	d₁	d₂	d₃	p	p_{/2}	h₀	h₁	h₂	h₃	R₁	R₂	R₃	h
See above	3.81 [.150]	5.08 [.200]	6.35 [.250]	2.54 [.100]	1.27 [.050]	3 _{MAX} [.118]	1.9 [.075]	0.64 [.025]	7.62 [.300]		Ø 2.85 _{MIN} [.112]	Ø 0.75 _{MIN} [.030]	Ø 1.5 _{MIN} [.059]	9.35 [.368]

127 / HE8 >>> FITTINGS & CONTACT COMPATIBILITIES

HE801

COMPATIBLE FEMALE FITTINGS

Connector with male contacts

FALE FITTING PLUG

COMPATIBLE FEMALE FITTINGS

Connector with female contacts

127 / HE8 >>> FITTINGS & CONTACT COMPATIBILITIES

HE804

COMPATIBLE MALE FITTINGS

Connector with
male contacts

		FEMALE FITTING RECEPTACLE											
		RT						JS					
		X	X	X	X	X X X X							
RT						X	X	X					
JS									X	X	X		
NS													
RS		X	X		X								
S													
NF		X	X	X	X								
RF						X	X	X	X				
J		X	X	X	X	X							
PC							X	X	X	X			
N								X	X	X			
V		X	X	X	X	X							
R													
T		X	X	X	X	X							
FEMALE CONTACTS		YD	X1	Z	W3	Y	U	T	YL	YC			
A							X	X	X				
B								X					
AE									X				
D		X	X	X	X	X							
DC							X						
AD								X					
AED		X	X	X	X	X							
AT			X	X	X								
AET													

COMPATIBLE FEMALE FITTINGS

Connector with
male contacts

FEMALE FITTING RECEPTACLE

		COMPATIBLE MALE FITTINGS											
		Connector with male contacts						Connector with female contacts					
		AET	KET	AT	KT	AED	KED	AD	KD	DC	SC	D	S
AET		X	X										
KET													
AT				X	X	X	X						
KT					X	X	X	X					
AED		X	X										
KED													
AD						X							
KD							X						
DC								X	X	X	X		
SC									X				
D									X	X	X	X	
S										X			
L													
AE		X	X										
KE													
B						X				X	X	X	X
P							X						
A								X	X	X	X		
K									YC	YL	U	Y	W3
YC									X	ZC	X		
YL													
U													
Y													
W3													
ZC													
X													

COMPATIBLE MALE FITTINGS

Connector with
female contacts

		COMPATIBLE FEMALE FITTINGS											
		Connector with male contacts						Connector with female contacts					
		A	PA	PC	H	N	V	E	R	T	D	S	SC
A													
PA													
PC		X	X										
H													
N					X								
V						X							
E							X						
R								X	X	X	X		
T									X	X	X	X	
D													
S		X	X										
SC													
K													
P													
KE													
K													
P													
KE													
KD													
KED													
KT													
KET													

COMPATIBLE FEMALE FITTINGS

Connector with
female contacts

MALE FITTING PLUG

127 / HE8 Series

127 / HE8 >>> FITTINGS & CONTACT COMPATIBILITIES

HE807

COMPATIBLE MALE FITTINGS

Connector with
male contacts

		FEMALE FITTING RECEPTACLE								
		ET				AS				
		X X X X		X X X X		X X X X		X X X X		
ET					X X X					
AS						X X X				
ES							X X X			
D								X X X X		
EF									X X X X	
A						X X X				
PA								X X X X		
E			X X X X X							
T				X X X X X						
FEMALE CONTACTS		YD	X1	Z	W3	Y	U	T	YL	YC
K						X X X				
P							X X X			
KE								X X X X		
K			X X X X X							
P								X X X X X		
KE									X X X X X	
S						X X X				
X			X X X X X							
KD						X X X X X				
KED			X X X X X							
KT			X X X							
KET								X X X		

COMPATIBLE FEMALE FITTINGS

Connector with
male contactsFEMALE FITTING
RECEPTACLE

		COMPATIBLE MALE FITTINGS							
		ET				AS			
		X X		X X		X X		X X	
ET		X	X						
KETX		X	X						
AT									
KT				X	X	X	X		
AED									
KED		X	X						
AD									
KD				X	X	X	X		
DC									
SC									
D									
S				X	X	X	X		
L									
AE									
KE		X	X	X					
B									
P					X	X	X	X	
A									
K				X	X	X	X		
YC		YC	YL	U	Y	W3	ZC	X	MALE CONTACTS
A		X	X						
J									
PA		X	X						
PC									
H									
N									
N									
V					X	X	X	X	
E						X	X	X	X
R									
T					X	X	X	X	
D		X	X						
S				X					
NF									
EF				X	X	X	X		
RF									
AS		X	X						
JS									
NS									
ES					X	X	X	X	
RS									
ET					X	X	X	X	
RT									

COMPATIBLE MALE FITTINGS

Connector with
female contactsMALE FITTING
PLUG

COMPATIBLE FEMALE FITTINGS

Connector with
male contacts

127 / HE8 >>> TOOLING

REMOVAL TOOLS

1272



- Pin: ZC / X / YC / YL
- Rear release

24098



- Pin Y / W3 / U
- Front release

Part number

1272

Part number

24098

1271



- Socket: YC / U / Z / X1 (HE 801 & HE 804)
- Rear release

24099



- Socket: YC / U / Z / X1 (HE 807)
- Rear release

Part number

1271

Part number

24099

20973



- Socket: W3
- Front release

20143



- Socket: Y / YD
- Front release

Part number

20973

Part number

20143

23550



- Socket: particular contacts HE 807
- Rear release

INSERTION TOOL

1275



- Pin: X
- Insertion on the same side as removal
- Eased contact insertion

Part number

23550

Part number

1275

CRIMPING TOOLS

HE 8 20 051



- Pin: X
- AWG 26 to 22
- No additional turret

809801



- Socket: X1
- AWG 26 to 22
- Additional turret: 127.800.030
- Military reference: M22520/2-01

Part number

HE 8 20 051

Part number

809801

NOTES

AMPHENOL AEROSPACE OPERATIONS >>> BOARD LEVEL INTERCONNECTS

BRUSH CONTACT TECHNOLOGY



- Multiple strands of high tensile strength wire bundled together to form brush-like contacts.
- Multiple contact interfaces. By intermeshing two multi-strand wire bundles, an electrical connection is made.
- Provides redundant current paths, 14-70 (points of contact) per mated contact with a gas tight junction
- Very smooth (low friction) interface

HDB³ / HSB³ THE HIGH DENSITY BRUSH SERIES

HDB³ series


This new connector series of brush connectors incorporates an even higher density contact pattern and lower mated height than Amphenol's standard low mating force rectangular connectors. These HDB³ connectors utilize the same durable and reliable B³ brush contact in a tighter .070 inch x .060inch staggered grid pattern.



- Higher density contact pattern
- Uses less board space
- Allows for shorter mated height
- Provides durability and performance of the brush contact
- Low cost
- Available in mother board, daughter board, Input/Output and stacker style

HSB³ series: high-speed series 3.125 GBS

The HSB³ is a further new development of the higher density HDB³ connector series. The HSB³ offers higher speed as well as higher density.



- Allows data rates up to 3.125Gb/s via 100 ohm matched impedance differential pairs
- Uses partially populated standard HDB³ mother board and daughter board inserts

The HDB³ / HSB³ series serve various markets, including:



Commercial Avionics & Airframe



Military Avionics & Airframe




C4ISR



Navy

AMPHENOL AEROSPACE OPERATIONS >>> BOARD LEVEL INTERCONNECTS


LRM LINE REPLACEABLE MODULE



Amphenol LRM surface mount connectors meet the high-density needs of today's integrated electronic modules. With its flexibility in design, Amphenol LRM interconnects are capable of meeting the wide variety of user requirements:

- LRM interconnects can be designed in 1, 2, 3 and more bay configurations
- LRM digital (brush) inserts can be combined with inserts for power, fiber optics, RF, high speed and high amperage RADSOK® contacts

Staggered Grid LRM: high contact density in SEM-E form factors



- Digital insert pattern grid is in 8 rows: 0.100 inch spacing along the row with 0.050 inch between rows, rows offset 0.050 inch.
- Typical standard arrangements: 80, 108, 152 or 180 digital brush contacts
- Various shell designs available to accommodate a wide range of PCB/heat sink
- SMT termination on module connectors, PCB on backplane connectors
- ESD protection
- LVDS differential pair insert available, 100 ohm matched impedance, exceeding 1.2 Gbps available

LRM with Fiber Optics



- High speed fiber optic transmission
- Custom combinations of digital contacts and fiber optic termini
- Insertion losses range from .3dB to <1.5dB
- MIL-T-29504/4, /5, /14 & /15 termini
- MT ferrule arrangements (12 or 24 fiber lines per ferrule)

High-speed LRM: GigaStak, GigaStak-LG, DigiStak & DigiStak-X

These LRM's are designed, or can be configured, to achieve data rates up to 6.25 Gb/s and include all the features of the rugged and reliable staggered grid LRM series.

In addition, the GigaStak and DigiStak series incorporate Amphenol's cStack solderless termination technology.



- Optimized insert through strategic placement of signal and ground contacts
- Perfect balance of impedance control and cross talk mitigation
- 100 ohm matched impedance differential pairs
- GigaStak 6.25 Gb/s
- GigaStak-LG 3.125 Gb/s
- DigiStak & DigiStak-X 3.125 Gb/s
- Standard staggered grid 1.25 Gb/s

The LRM series serve various markets, including:



Military Avionics & Airframe



Commercial Avionics & Airframe



C4ISR



Ground vehicles



Space


AMPHENOL AEROSPACE OPERATIONS >>> BOARD LEVEL INTERCONNECTS

RUGGEDIZED VME64X INTERCONNECTS



In a harsh military environment the COTS VME connector interface can fail, negating the ruggedization of the cards. The Amphenol Ruggedized VME64x interconnect has a more rugged interface than standard connectors for improved vibration durability. It meets the needs for a harsh environment connector requiring Level 2 maintenance. The Amphenol Ruggedized VME64x connector mounts to standard VME64x cards and backplanes, but it does not mate to other types of VME commercial connectors.

Features and benefits include:



- Metal shells - mount directly to the standard VME card mounting holes, providing support and protection to the inserts in the module and additional stiffness to the backplane
- The metal shells create a faraday cage around the contacts, preventing ESD (Electrostatic Discharge) into the contacts (module only)
- Robust contact system
- 3 module inserts in one unified shell; each can have different interconnect combinations.
- Thru-hole solder tail or solderless termination is available on the backplane connector.

The ruggedized VME64x series serves various markets, including:



Commercial Avionics & Airframe



Military Avionics & Airframe



C4ISR



Ground vehicles

AMPHENOL BACKPLANE SYSTEMS >>> BOARD LEVEL INTERCONNECTS

VIPER VITA 46, VITA 48 & VITA 60 FOOTPRINT COMPATIBLE



- High-level vibration and mechanical shock protection
- Condensing moisture resistance
- Ruggedization in packaging
- Scaling from 80 Mbps to over 10 Gb/s while retaining the same VITA 46 platform slot pitch at 20.3mm to 25.4mm.

The VIPER® connector is a shielded, high-density, high speed modular interconnect with press fit terminations. The daughtercard assembly is optimized for differential pair architecture on a 1.8mm x 1.35mm grid. The daughtercard is waferized, and provides single-ended and power wafer options integrated onto a stainless steel stiffener with stainless steel frame and keying elements. The backplane has signal contacts that incorporate highly reliable 4-point-of-contact beam design, and ground contacts which are robust compliant pin & contact fork design.

Key features

MECHANICAL CHARACTERISTICS	
Normal force per contact (g)	85
Mating force per contact (g)	35 < F < 45
Unmating force per contact (g)	25 < F < 30
Durability cycles	500
Random vibrations (90 minutes per X, Y and Z axis)	0.6 g ² / Hz
Shocks 11 ms half sine	50 Grms in Y axis 80 Grms in Y and Z axis
ENVIRONMENTAL CHARACTERISTICS	
Thermal shocks (°C)	-55 / +125
Temperature life (+125°C, in hours)	1 000
ELECTRICAL CHARACTERISTICS	
Data rate (Gbps)	10
Differential impedance (Ω)	100
Differential insertion & return loss	- 5 dB up to 5 GHz (10 Gbps)
Far end & near end crosstalk	- 35 dB & -33 dB up to 8 GHz
Current rating per contacts (A)	1
Current rating per power wafer (A)	12 at 30°C
Insulation resistance (GΩ)	1 _{MIN}
Contact resistance (mΩ)	1 _{MAX}
Dielectric Withstanding Voltage (Vrms)	500

- Fully footprint-compatible with VITA 46 and VITA 48 standards
- Hi-speed: designed for 10+ Gb/s data rate performance
- 100 ohm impedance for differential pair configuration
- ESD protection
- ± 0.520 mm nominal translation in fully mated condition
- Separable interface offering 70 single-ended signals and 63 differential signals

The VIPER series serves various markets, including:



Military Avionics & Airframe



Commercial Avionics & Airframe



C4ISR



Ground vehicles

AMPHENOL TERADYNE CONNECTION SYSTEMS >>> HIGH SPEED INTERCONNECTS

BACKPLANE INTERCONNECTS

XCede® 20+ Gbps		<ul style="list-style-type: none"> Meets the IEEE 802.3ap v3.2 10GBASE-KR standard with margin Up to 82 differential pairs per inch (32 differential pairs per centimeter) Secondary routing channels significantly lower backplane costs 85 and 100 ohm components are readily available in all configurations without the hassle of retooling and requalification
XCede® LC 10 Gbps		<ul style="list-style-type: none"> Mates with standard XCede backplane module Daughtercard wafer designed without resonance damping polymer to optimize cost Fully compatible with the XCede family of components, including power and guidance Available in 85 and 100 ohm impedance
eHSD® 10 Gbps		<ul style="list-style-type: none"> Meets the IEEE 802.3ap v3.2 10GBASE-KR standard Fully backwards compatible with VHDM-HSD, delivering up to 10 dB lower crosstalk Scale existing systems to next generation speeds 25 - 38 real differential pairs per linear inch (10 - 15 real differential pairs per centimeter)
Ventura® 6.25 - 12 Gbps		<ul style="list-style-type: none"> High-density, high-performance single-ended connector 12 Gbps differential, 6.25 Gbps single-ended 102 - 178 real signals per inch (40 - 70 signals per centimeter) Surface mount attach
GbX® 5.0 Gbps		<ul style="list-style-type: none"> 27.5 - 69 differential pairs per inch (11 - 27 differential pairs per centimeter) Ideal for 4 x 3.125 XAUI links Full range of proven components (e.g. power, guidance, polarizing) Robust mechanical design
GbX® U-Series 10+ Gbps		<ul style="list-style-type: none"> Enhanced footprint for improved impedance and crosstalk performance Backplane modules are compatible with all generations of GbX daughtercards Up to 10 dB crosstalk improvement on actual backplanes
GbX® E-Series 6.25 Gbps		<ul style="list-style-type: none"> Enhanced electrical performance Crosstalk as low as 2% Backplane module shares the same footprint as standard GbX
GbX® L-Series < 1 Gbps		<ul style="list-style-type: none"> 1.85mm x 1.85mm open pin field version of GbX Customize signal integrity performance by varying ground-to-signal ratio Ideal for TTL sense and control and other low-speed data lines
AirMax VS® 2.5 - 6.25 Gbps <small>AirMax VS is a registered trademark of FCI</small>		<ul style="list-style-type: none"> Shieldless connector system Cost-effective interconnect for multi-gigabit applications Up to 63 differential pairs/inch 3, 4, and 5-Pair standard and reverse gender available
Aptera™ 3.125 - 6.25 Gbps		<ul style="list-style-type: none"> Low-profile, high-reliability 2-piece edge-card connector 6.25 Gbps performance differential; 3.125 Gbps single-ended Low profile construction reduces minimum slot pitch between daughtercards to 10mm (.39") Right angle and stacker versions available
VHDM-HSD™ 5 Gbps		<ul style="list-style-type: none"> Optimized for high-speed differential backplane applications 25 - 38 differential pairs per inch (10 - 15 differential pairs per centimeter) Modular design enables mix of single-ended and differential signals within the same connector
VHDM® 3.125 Gbps		<ul style="list-style-type: none"> Optimized for single-ended, high-density applications 76 - 101 real signals per inch (30 - 40 real signals per centimeter) Less than 5% crosstalk Stripline shielding allows 100% of the pins to be used for signals
VHDM® H-Series 6.25 Gbps		<ul style="list-style-type: none"> Superior signal integrity Backwards compatible with the full VHDM product family - design into same slot for fast, easy system upgrades 0.018" (0,045mm) PCB hole for improved performance
VHDM® L-Series < 1 Gbps		<ul style="list-style-type: none"> Open pin-field version of VHDM Fully compatible with the full VHDM product family to optimize cost and performance by mixing high- and low-speed signals on the same connector Ideal for TTL sense and control and other low-speed data lines
HDM® HDM® Plus < 1 Gbps		<ul style="list-style-type: none"> Economical 2mm modular design 75 real signals per inch (30 contacts per centimeter) Can operate in applications with rise times as low as 500 pico seconds

AMPHENOL TERADYNE CONNECTION SYSTEMS >>> HIGH SPEED INTERCONNECTS

ORTHOGONAL INTERCONNECTS

Crossbow™ 20+ Gbps		<ul style="list-style-type: none"> • XCede® technology optimized for orthogonal midplane architectures • Meets the IEEE 802.3ap v3.2 10GBASE-KR standard with margin • Demonstrated 100 Ohms ± 5% impedance across an entire link • Less than 1.5 picoseconds in-pair skew • Crosstalk < 1.5% at 50 picoseconds • 4 x 4, 6 x 6, 8 x 8 and 8 x 9 configurations available
------------------------------	---	---

CO-PLANAR INTERCONNECTS

XCede® Co-planar 20+ Gbps		<ul style="list-style-type: none"> • Right angle male enables co-planar board-to-board or board-to-cable high-speed interconnection • Mates with standard right female daughtercards • Available in 85 and 100 ohm impedance
GbX® Right Angle Male (RAM) 5.0 Gbps		<ul style="list-style-type: none"> • Enables co-planar board-to-board or board-to-cable high-speed interconnection • Currently available in 2-pair configuration (27 differential pairs per linear inch) • Available in two different heights - standard RAM and extended RAM • High-speed differential and L-Series versions available
VHDM® Right Angle Male (RAM) 3.125 Gbps		<ul style="list-style-type: none"> • Right angle male enables co-planar board-to-board or board-to-cable high-speed interconnection • 76 - 101 real signals per linear inch (30 - 40 real signals per centimeter) • Grow systems horizontally by creating traditional backplane components in a right angle orientation

MEZZANINE INTERCONNECTS

XCede® Stacker 20+ Gbps		<ul style="list-style-type: none"> • 4-pair size provides density and mechanical robustness to address increasing I/O counts • Modular construction and guidance options allow optimized connector lengths for each application • Heights available from 15mm up to 44mm • Press fit attachment
NeXLev® 12.5 Gbps		<ul style="list-style-type: none"> • Enhanced BGA attachment process to increase SMT process yields • 125 micron co-planarity • 57 real signals per linear centimeter (145 signals per inch) • 20 stacking heights from 10-33mm
VHDM® Stacker 3.125 Gbps		<ul style="list-style-type: none"> • Press fit solution for stacking applications • Route single-ended or differentially • 76 - 101 real signals per inch (30 - 40 real signals per centimeter) • Stacking heights from 18mm and up
Aptera™ Stacker 3.125 - 6.25 Gbps		<ul style="list-style-type: none"> • Mezzanine solution provides the same electrical performance as standard Aptera • Mates with standard backplane modules • Available in 40mm board-to-board stack heights • Uses proven GbX compliant pin technology
HDM® Stacker < 1 Gbps		<ul style="list-style-type: none"> • Available in 72 pin and 144 pin signal modules in solder tail or press fit configurations • 75 real signals per inch (30 contacts per centimeter) • 30 Amp power module, end stackable • Stacking heights from 15 to 32mm

HIGH-SPEED CABLE ASSEMBLIES INTERCONNECTS

XCede® Cable Connectors & Assemblies 20+ Gbps		<ul style="list-style-type: none"> • Ideal for front panel and backplane connections • Provides the same industry leading electrical and mechanical performance as the standard right angle connectors • Available in 2-Pair and 4-Pair configurations • Tightly matched impedance control at cable termination • Wafers are available for 85 and 100 ohm impedance • Supports multiple cable designs ranging from 24 to 30 AWG
---	---	---

AMPHENOL PRINTED CIRCUITS >>> PRINTED CIRCUIT BOARDS CAPABILITIES

RIGID PRINTED CIRCUIT BOARDS



Amphenol Printed Circuits' (APC) capabilities are among the world's broadest and most advanced, delivering consistent quality and reliability for demanding high-bandwidth systems and mission critical applications for more than 25 years. Proven engineering and manufacturing expertise eliminates printed circuit board design obstacles.

APC's North America printed circuit board operation provides tightly controlled processes for prototype through production printed circuit board volumes. The 214,000 square foot New Hampshire facility features state-of-the-art PCB manufacturing equipment and optimized material handling to ensure the highest quality and consistency.

Design formats	Mentor PADS	Cadence Zuken	
Manufacturing formats	ODB++ (Preferred) DXF Gerber 274X	Autoplot Excelon HPGL	
Maximum panel size	24" x 54" (609.1mm x 1370.6mm) 30" x 44" (761.4mm x 1116.7mm) 36" x 42" (913.7mm x 1065.9mm)		
Maximum panel thickness	0.400" (10.15mm)		
Layer count	Up to 64		
Interconnection formation types	Back Drilled Dual Diameter Thru Hole* <i>* Includes conductive and non-conductive fill</i>	Buried Electrically Isolated Blind (Laser & Mechanical)	
Aspect ratio - drilled size	Backplane Daughtercard	17:1 15:1	
Finished hole size	Compliant Pin Via (A/R dependent) Buried Vias Microvias (Up to 3 electrical layers)	0.018" (0.457mm) 0.008" (0.203mm) 0.006" (0.152mm) 0.004" (0.101mm)	
Blind via aspect ratio	1.25:1		
Internal features	Lines Spacing Buried Resistors Buried Capacitance Core Thickness	0.003" (0.076mm) 0.5 oz copper 0.003" (0.076mm) 0.5 oz copper No No 0.001" (0.0254mm) minimum	
External features	Lines Spacing	0.004" (0.101mm) 0.5 oz copper 0.004" (0.101mm) 0.5 oz copper	
Materials	High Tg FR4 (Including phenolic cure) Megtron 6 Isola FR408 Nelco 4000-13 & Nelco 4000-SI Rogers 4350/FR4 BT (Bismaleimide triazine resin)	Taconic Gore Cyanate Ester Polyimide Rogers 4350	
Copper processing	1/4 oz up to 15 oz (U/L 7 oz)		
Impedance single & differential	± 10% ± 7.5% ± 5.0%*	<i>* Consult factory</i>	
Surface finishes	Electrolytic Ni/ Au (Hard & Soft) HASL Immersion Tin Reflowed Tin/Lead	ENIG Immersion Silver OSP-Entek 106	
Certifications	AS9100 Certification IPC-6012 Class I, II and III ITAR Registration MIL-PRF-31032/2a	ISO 9001:2000 ISO 14001:1996 MIL-PRF-31032/1b MIL-P-55110	

AMPHENOL PRINTED CIRCUITS >>> PRINTED CIRCUIT BOARDS CAPABILITIES

RIGID PRINTED CIRCUIT BOARDS



APC is one of the industry's leading manufacturers of flexible and rigid-flex circuit interconnects. For more than 30 years, APC has been providing quick turn prototypes from initial concept through full production with cutting-edge technologies including interconnects with blind and buried vias, microvias, and bookbinder.

Our assembly centers of excellence, located in Nashua, New Hampshire and Nogales, Mexico are fully ITAR qualified, providing competitive value-added services including SMT, wave and manual through-hole assembly.

APC works closely with our customers to understand their true system requirements. This allows us to deliver the most cost-effective interconnect solutions with up-front engineering and consistent manufacturing techniques. From functional testing and turn-key assembly, APC's commitment to our customers success is what sets us apart in the industry.

Design formats	DXF Gerber	IGES PADS
Panel size	12" x 18" (304.5mm x 456.8mm) 18" x 24" (456.8mm x 609.1mm) 24" x 24" (609.1mm x 609.1mm) 24" x 36" (609.1mm x 913.7mm) 24" x 54" (609.1mm x 1370.6mm) <i>Consult Factory</i>	
Panel thickness	0.003" to 0.225" (0.0762mm to 5.71mm)	
Layer count	1-30+	
Interconnection formation types	Thru Hole Buried Blind	SMT Filled Vias Dual Diameter
Finished hole size	Compliant Pin (Rigid zone only) Via (A/R dependent) Buried Vias Microvias (Up to 3 electrical layers)	0.018" (0.457mm) 0.008" (0.203mm) 0.006" (0.152mm) 0.004" (0.101mm)
Blind via aspect ratio	1.25:1	
Internal features (cu weight dependent)	Line Spacing	0.003" (0.076mm) 0.003" (0.076mm)
Materials	Polyimide - FR Polyimide - AP Polyimide - GI Soldermask	Polyimide - Standard Acrylic Silver Epoxy Shielding Copper Epoxy Shielding FR4/ 24/ 26/ 28
Copper processing	1/4 oz up to 15 oz	
Impedance single & differential	± 10% ± 7%*	* <i>Consult factory</i>
Surface finishes	HASL Reflowed Tin/ Lead OSP-Entek 106 ENIG	Immersion Tin Immersion Silver Bright Tin Electrolytic Ni/ Au (Hard & Soft)
Assembly capabilities	Full Turn-Key Thru-Hole (Wave & Manual) SMT (Pick & Place)	Wire-Bond Crimp RoHS Compliance
Assembly finishes	Conformal Coat - UR, Acrylic, Parylene, Flouropel, Glop Top	
Test capabilities	Overmolding Impedance Testing Hi-Pot up to 5,000 VDC 2,000 Points per Circuit Insulation Resistance up to 1,000 VDC Four-Wire Kelvin 0.001 Ω to 1 Ω	Bed of Nails Flying Probe Flex Cycling Environmental Functional Test
Certifications	MIL-P-50884, Types 1-5 IPC-6013 Class I, II and III, Types 1-5 ITAR Registration	ISO 9001:2000 IPC-610 AS9100 Certification

Amphenol in the world



Amphenol Socapex

948, promenade de l'Arve BP29
74311 Thyez Cedex - France
Phone: +33 (0)4 50 89 28 00
contact@amphenol-socapex.fr
www.amphenol-socapex.com



www.twitter.com/AmphenolSocapex



www.linkedin.com/company/amphenol-socapex

Other Amphenol Sales contacts in Europe

Amphenol Air LB
10 rue champ Raymond
08110 Carignan - France
Phone: +33 (0)1 49 05 30 00

Amphenol AIR LB GmbH
Am Kleinbahnhof 4
66740 Saarbrücken - Germany
Phone: +49 6831 981 00

Amphenol TUCHEL ELECTRONICS
August-Haeusser-Str. 10
D-74080 Heilbronn - Germany
Phone: +49 7131 929 00

Amphenol BENELUX
Zadelmaker 121
NL - 2401 PD Alphen aan den Rijn -
The Netherlands
Phone: +31 172 444 903

Amphenol Limited Whitstable, UNITED KINGDOM
Thanet Way, Whitstable
Kent, CT53JF - United Kingdom
Phone: +44 1227 773 200

Amphenol ITALY
Via Barbaiana n.5
20020 Lainate - Milano - Italy
Phone: +39 293 254 214

Amphenol IBERICA
Edificio Burgosol, Oficina nr 55 - Comunidad
de Madrid, 35-bis Las Rozas (Madrid) - Spain
Phone: +34 91 640 73 06

Amphenol NORDIC
Phone: +46 768 418 600

Amphenol POLAND & CENTER EAST
EUROPE - Austria, Poland, Czech Rep.,
Slovakia, Romania
Wiener gasse 68 - 2380 Perchtoldsdorf -
Austria
Phone: +43 699 10396 071

Amphenol SWITZERLAND & SOUTH CENTER
Switzerland, Slovenia, Serbia, Montenegro,
Yugoslavia, Greece, Bulgaria
948, promenade de l'Arve BP29
74311 Thyez Cedex - France
Phone: +33 (0)4 50 89 28 40

Amphenol Sales contacts in Asia

Amphenol Daeshin
558 SongNae-Dong SoSa-Gu, Bucheon-city, Kyunggi-Do
Korea 420-130
Phone: +81-32 610 3830/3845

Amphenol East Asia Ltd.
No.72, Bendemeer Road,
#03-32/33, Luerne
Singapore 339941
Phone: +65 6294 2128

Amphenol Interconnect India Private Limited
105 Bhosari Industrial Area - Pune 411 026 - India
Phone: +91 20 3068 8304

Amphenol PCD CO. LTD
Building 21, 1st Liao Keng Industrial Zone, Shi Yan Street
Bao An District, Shenzhen 518108
China
Phone: +86 755 8173 8000/8286

Amphenol Japan
471-1, Deba, Ritto-City, Shiga 520 3041 - Japan
Phone: +81 77 553 8501

Amphenol Sales contacts in North America

Amphenol PCD
72 Cherry Hill Drive - Beverly, MA. 01915 - USA
Phone: +1 978 624 3400

Amphenol Aerospace Operations
40-60 Delaware street - Sidney, NY 13838-1395 - USA
Phone: +1 607 563 5011

Amphenol Backplane Systems
18 Celina avenue - Nashua, NH 03063 - USA
Phone: +1 603 883 5100

Amphenol Canada Corporation
605 Milner avenue - Toronto, Ontario - Canada - M1B 5X6
Phone: +1 416 291 4401

Amphenol Fiber System Int.
1300 Central Expwy N, Suite 100
Allen, TX 75013 - USA
Phone: +1 214 547 2400

Amphenol Sales contacts in Other Areas

Amphenol Argentina
Av. Callao 930 2do piso Oficina B "Plaza" C1023 - AAP
Buenos Aires - Argentina
Phone: +54 11 4815 6886

Amphenol Australia Pty Limited
2 Fiveways Blvd., Keysborough - Melbourne
Victoria 3173- Australia
Phone: +61 3 8796 8888

Amphenol Do Brazil
Rua Diogo Moreira, 132, 20 andar, rooms 2001-2-3
CEP: 05423-010 Sao Paulo SP - Brazil
Phone: +55 11 3815 1003

Bar-Tec Ltd., ISRAEL
3 Hagavish Street, Kfir-Barkan Bldg. East Industrial
Zone - Kfar-Sava, 44102 - Israel
Phone: +972 9 764 4100

Amphenol Mexico
Prolongacion Reforma 61-6 B2
Col Paseo de las Lomas - C.P. 013130 Mexico
Phone: +52 55 5258 9984

Amphenol Russia
Yaroslavskaja Street 8,
129164 Moscow - Russia
Phone: +7 495 937 6341

Amphenol Interconnect South Africa (Pty) Ltd
58 Malcolm Moodie Crescent, Jet Park
Boksburg, SOUTH AFRICA
Phone: +27 11 397 6069

Amphenol TURKEY
Sun Plaza 15 Kat: 15 Maslak Hah. Bilim
Sok. No.5
Sisli/Istanbul, 34398 - Turkey
Phone: +90 212 367 92 19

Amphenol

The information given in this document are **as a guideline only**.
We reserve the right to **modify our products** in any way we deem necessary.
Any duplication is **prohibited**, unless approved in writing.
October 2013
Gestion & Edition by **AMPHENOL SOCAPEX**

DOC-000090-ANG

Your local Contact:

For more information, please visit our website:
www.pcb-interconnect.com