


SMCD SERIES MINIATURE PUSHWHEEL SWITCHES



FEATURES

- Miniature pushwheel switches with large visible readout characters.
- Models available with ESD protection - consult factory.
- Bi-directional snap action detent pushbutton mechanism.
- Black housing and drum with white printing.
- Gangable front and rear mounting models with spacers and side covers.
- Gold wiping action contacts.
- P.C. board options include solderable lands.

SMCD SPECIFICATIONS

Panel mounting hole:	
Height	.945"(24mm)
Width	.315"(8mm)
Installed depth with p.c. board:	
Short	1.260"(32mm)
Long	1.654"(42mm)
Insertion from front	yes
Insertion from rear	yes

CODES

Code	positions	marking	
111 Decimal	10	0-9	see truth tables
131 BCD	10	0-9	see truth tables
137 BCD comp	10	0-9	see truth tables
301 Hexadecimal	16	0-9, A-F(0-15)	see truth tables
400 change-over	10	+, -, +, -, etc..	see truth tables

ELECTRICAL DATA

Operating voltage:	40 V max.
Contact load, static:	1 A max.
Contact load, dynamic:	100 mA max.
Contact resistance (type AK):	less than 100 mOhm

TECHNICAL DATA

Operating temperature range:	-20°C to 80°C
Electric life, min. switching cycles	1,000,000
Actuation force, approx (oz.):	14
Weight, approx. (grams):	4
Character height:	10 digit .193" (4.9mm)
	16 digit .134" (3.4mm)
Audible click	yes
Vibration DIN IEC 68, parts 2-6	yes
Shock DIN 40046, part 7	yes

MATERIALS

Body:	PPO
PC board:	FR 4 DIN 40802 IEC 249-2, Contact surface gold over nickel on copper
Sliding contact:	Gold over nickel on copper alloy

STANDARD COLORS

Housing, Drum, Printing	
2 = black 3 = white	2,2,3

Other special features are available upon request including:

- Factory or customer set stops (10 digit models)
- L.E.D. illumination (transparent wheel)
- Red digits
- Decimal point
- Special codes or printing
- Gray housing
- See sockets at end of Pushwheel section.


SMCD SERIES MINIATURE PUSHWHEEL SWITCHES

TRUTH TABLES

CODE 131 BCD						CODE 137 BCD COMP.						CODE 400 CHANGE-OVER				CODE 301 HEXADECIMAL						CODE 111 DECIMAL											
	C	1	2	4	8		C	$\bar{1}$	$\bar{2}$	$\bar{4}$	$\bar{8}$		C	A+	A-		1	2	4	8	C		C	0	1	2	3	4	5	6	7	8	9
0	●					0	●	●	●	●	●		+		●		0					●		0	●	●							
1	●	●				1	●				●	●				●	1	●						1	●								
2	●		●			2	●	●			●	●					2		●			●		2	●		●						
3	●	●	●			3	●				●	●				●	3	●	●			●		3	●			●					
4	●			●		4	●	●	●		●	●					4			●		●		4	●			●					
5	●	●			●	5	●		●		●	●				●	5	●		●	●			5	●				●				
6	●		●	●	●	6	●	●			●	●					6	●	●	●		●		6	●				●				
7	●	●	●	●	●	7	●				●	●				●	7	●	●	●		●		7	●					●	●		
8	●				●	8	●	●	●	●			+		●		8				●		8	●							●		
9	●	●			●	9	●		●	●	●		-		●		9	●			●		9	●							●	●	
																	A		●			●											
																	B	●	●			●											
																	C			●	●	●											
																	D	●		●	●	●											
																	E		●	●	●	●											
																	F	●	●	●	●	●											

MECHANICAL OUTLINE WITH PANEL CUT-OUT & MOUNTING

n = number of switches



PIN CONNECTIONS

● The switching mode is shorting - i.e. - even during actuation, at least one output is connected to input C.

● "bl" is used for models ordered with L.E.D. illumination only.

●	131	1		2		4		8		C				
	131bl	+	1	8		4		2	C	-				
	137	$\overline{1}$		$\overline{2}$		$\overline{4}$		$\overline{8}$		C				
	137bl	+	$\overline{1}$	$\overline{2}$		$\overline{4}$		$\overline{8}$	C	-				
	301	1		2		4		8		C				
	301bl	+	1	2		4		8	C	-				
	400	+		A+		C		A-		-				
	111	0	1	2	3	4	C	5	6	7	8	9		
AK	111bl	+	0	1	2	3	4	C	5	6	7	8	9	-
		+											-	
AL	111bl	0	1	2	3	4	C	5	6	7	8	9		

Pitch .079"(2mm)

Pitch .067"(1.7mm)


Pitch .079"(2mm)

●	131	1	2	4	8	C
	301	1	2	4	8	C

SMCD SERIES MINIATURE PUSHWHEEL SWITCHES

PRINTED CIRCUIT OPTIONS

P.C. boards have .039" (1mm) holes and are suitable for soldering or socket connection (with the exception of LED illumination option).



AK short p.c. board

AL long p.c. board

Allows customer to add resistors, diodes, ect.

ALU long p.c. board

LS p.c. board w/solder pins

Ordering information: Below is an order format that enables you to 'build your own switch' and specify the correct switch model number by simply selecting from available options shown and filling in the boxes. Consult factory for fully assembled switches.

'BUILD YOUR OWN SWITCH' ORDER FORMAT


Series model	Code	P.C. board	Terminations	Standard colors
S M C D				
	1 1 1 Decimal 1 3 1 BCD 1 3 7 BCD comp. 3 0 1 Hexadecimal. 4 0 0 Change-over	A K Short A L Long A L U Long (rt. angle)	(NONE) L S with p.c. solder pins	2 Black housing. & drum, white lettering.

Example of complete model no.: **SMCD137ALLS2**
Order SP12 as a separate line item for limit stop pin (for 10 position models only).


ACCESSORIES

Order separately


SMCL2 Dummy switches - These are empty plastic housings with the same dimensions as SMCD model (see outline). Use to fill hole where switch is not needed. **SMCRD2 & SMCRND2** switches for rear mounting available on request.




SMCL2 Dummy housing




SMCPK2 Pair of side covers




SMCA2 Spacer



SMCL2 Dummy housing



SMCPK2 Pair of side covers



SMCA2 Spacer