





5 4 3 2 1


Mating face according to : MIL-C-24308 / DIN 41652 / CECC 75301-802



Printed board layout
component side



A

							Dat.	Name	 All Dim. in mm Orig. Size DIN A 4	D-Sub,male, standard angle 15 poles, with solder pin, screw lock and hole	Maßstab/ Scale 1.5:1
						Detail.	11/dec/00	ALSPACE			
						Insp.					
09 65 222 6803	4-40 UNC	2	29773	18-APR-02	CV	Stand.			 HARTING EURL F-95972 Paris	TB 0965222x80x	Blatt/ Page 3
09 65 222 7803	4-40 UNC	3	29689	02/07/01	AA						
09 65 222 5803	4-40 UNC	0.76 µm Au	27960	11/dec/00	ALSPACE						
Part number	Screw lock thread	Performance level	Mod.	Dat.	Name						

09 65 222 5803
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Stamped solder pins
shell	tinned metal shell with dimples
Number of contacts	15 way
Row pitch	Row separation 2.54 mm
Board fixing	without grounding board locks
flange	with screw lock UNC 4-40
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 65 222 6803
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Stamped solder pins
shell	tinned metal shell with dimples
Number of contacts	15 way
Row pitch	Row separation 2.54 mm
Board fixing	without grounding board locks
flange	with screw lock UNC 4-40
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 65 222 7803
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Stamped solder pins
shell	tinned metal shell with dimples
Number of contacts	15 way
Row pitch	Row separation 2.54 mm
Board fixing	without grounding board locks
flange	with screw lock UNC 4-40
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF