

**WPD 133 1X300/1X300 BN****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

Klippon® Connect power feed-in terminal blocks WPD allow for an easy and safe installation of aluminium and copper conductors on a small footprint. A power supply or monitoring connection can also be used as an option. Customers can use the power feed-in terminal blocks WPD, regardless of the conductor material. They can be mounted either directly or on DIN rail TS35.

**General ordering data**

|            |                                                                                                         |
|------------|---------------------------------------------------------------------------------------------------------|
| Version    | W-Series, Distribution block, Rated cross-section: 300 mm <sup>2</sup> , Terminal rail / mounting plate |
| Order No.  | <a href="#">2502880000</a>                                                                              |
| Type       | WPD 133 1X300/1X300 BN                                                                                  |
| GTIN (EAN) | 4050118516708                                                                                           |
| Qty.       | 1 pc(s).                                                                                                |

## WPD 133 1X300/1X300 BN

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 83.5 mm | Depth (inches)  | 3.287 inch |
| Height     | 118 mm  | Height (inches) | 4.646 inch |
| Width      | 45 mm   | Width (inches)  | 1.772 inch |
| Net weight | 338 g   |                 |            |

## Temperatures

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -50 °C |
| Continuous operating temp., max. | 120 °C         |                                  |        |

## Material data

|                           |       |        |       |
|---------------------------|-------|--------|-------|
| Material                  | Wemid | Colour | brown |
| UL 94 flammability rating | V-0   |        |       |

## Rating data IECEx/ATEX

|                                |                     |                         |                   |
|--------------------------------|---------------------|-------------------------|-------------------|
| Certificate No. (ATEX)         | CNEX18ATEX0016U     | Certificate No. (IECEX) | IECEXCNEX18.0010U |
| Max. voltage (ATEX)            | 1100 V              | Current (ATEX)          | 520 A             |
| Wire cross section max. (ATEX) | 300 mm <sup>2</sup> | Max. voltage (IECEX)    | 1100 V            |
| Current (IECEX)                | 520 A               |                         |                   |

## System specifications

|         |                  |                  |   |
|---------|------------------|------------------|---|
| Version | Screw connection | Number of levels | 1 |
|---------|------------------|------------------|---|

## Additional technical data

|                     |                                |                  |         |
|---------------------|--------------------------------|------------------|---------|
| Installation advice | Terminal rail / mounting plate | Type of mounting | Snap-on |
|---------------------|--------------------------------|------------------|---------|

## General

|                     |                                |                 |   |
|---------------------|--------------------------------|-----------------|---|
| Installation advice | Terminal rail / mounting plate | Number of poles | 1 |
| Standards           | IEC 60947-7-1, UL 1059, CSA    |                 |   |

## Rating data

|                                              |                     |                                 |                             |
|----------------------------------------------|---------------------|---------------------------------|-----------------------------|
| Rated cross-section                          | 300 mm <sup>2</sup> | Rated voltage                   | 1,000 V                     |
| Rated AC voltage                             | 1,000 V             | Rated DC voltage                | 1,000 V DC                  |
| Rated current                                | 520 A               | Standards                       | IEC 60947-7-1, UL 1059, CSA |
| Volume resistance according to IEC 60947-7-x | 0.06 mΩ             | Rated impulse withstand voltage | 8 kV                        |
| Power loss in accordance with IEC 60947-7-x  | 16.64 W             | Pollution severity              | 3                           |
| Surge voltage category                       | III                 |                                 |                             |

## UL rating data

|                         |        |
|-------------------------|--------|
| Certificate No. (cURus) | E60693 |
|-------------------------|--------|

## WPD 133 1X300/1X300 BN

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000897    | ETIM 7.0    | EC000897    |
| ETIM 8.0    | EC000897    | ECLASS 9.0  | 27-14-11-20 |
| ECLASS 9.1  | 27-14-11-20 | ECLASS 10.0 | 27-14-11-20 |
| ECLASS 11.0 | 27-14-11-20 |             |             |

## Important note

Product information You will find additional information in the downloadsection of the onlinecatalogue

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E60693  |

## Downloads


|                                             |                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">UKCA Ex Attestation of Conformity</a><br><a href="#">CB Certificate</a><br><a href="#">FIMKO certificate</a><br><a href="#">EAC EX Certificate</a><br><a href="#">CCC Ex Certificate</a><br><a href="#">ATEX Certificate</a><br><a href="#">IECEX Certificate</a><br><a href="#">DNV Certificate</a><br><a href="#">UKCA Ex Certificate</a><br><a href="#">CE Declaration of Conformity</a> |
| Engineering Data                            | <a href="#">CAD data – STEP</a>                                                                                                                                                                                                                                                                                                                                                                         |
| Engineering Data                            | <a href="#">EPLAN</a>                                                                                                                                                                                                                                                                                                                                                                                   |
| User Documentation                          | <a href="#">DATA SHEET WPD 133</a><br><a href="#">StorageConditionsTerminalBlocks</a><br><a href="#">NTI WPD 133</a>                                                                                                                                                                                                                                                                                    |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>                                                                                                                                                                                                                                                                                                                                                                |

## WPD 133 1X300/1X300 BN

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings



## Power feed-in Screw connection

### W-Series

#### WPD 133 1X300/1X300 GY



#### WPD 133

300 mm<sup>2</sup>

#### WPD 233


300 mm<sup>2</sup>

|                               |                   |
|-------------------------------|-------------------|
| Width / Height / Depth        | mm                |
| max. current / max. conductor | A/mm <sup>2</sup> |
| max. clamping range           | mm <sup>2</sup>   |

45 / 83.5 / 118  
520 / 300  
35...300



82.6 / 83.5 / 118  
520 / 300  
35...300



### Technical data

| Rated data                                           |                                        |                 |
|------------------------------------------------------|----------------------------------------|-----------------|
| Rated voltage                                        |                                        | V               |
| Rated current                                        |                                        | A               |
| for wire cross-section                               | 300 mm <sup>2</sup>                    | mm <sup>2</sup> |
|                                                      | Auxiliary connection 6 mm <sup>2</sup> | mm <sup>2</sup> |
| Rated impulse withstand voltage / Pollution severity |                                        |                 |
| Overvoltage category / UL 94 flammability rating     |                                        |                 |
| Approvals                                            |                                        |                 |
| Clamped conductors (H05V/H07V)                       |                                        |                 |
| Solid / Stranded                                     | 300 mm <sup>2</sup>                    | mm <sup>2</sup> |
|                                                      | Auxiliary connection 6 mm <sup>2</sup> | mm <sup>2</sup> |
| Flexible with ferrule                                | 300 mm <sup>2</sup>                    | mm <sup>2</sup> |
|                                                      | Auxiliary connection 6 mm <sup>2</sup> | mm <sup>2</sup> |
| Stripping length / Blade size                        | 300 mm <sup>2</sup>                    | mm/-            |
|                                                      | Auxiliary connection 6 mm <sup>2</sup> | mm/-            |
| Tightening torque                                    |                                        | Nm              |
| <b>Note</b>                                          |                                        |                 |

### IEC 60947-7-1

| IEC       | UL                | CSA               | EN 60079-7 |
|-----------|-------------------|-------------------|------------|
| 1000      | 1000              | 1000              | 1100       |
| 520       | 420               | 420               | 340        |
| 300       | AWG 2...kcmil 600 | AWG 2...kcmil 600 | 300        |
| 6         | AWG 16...8        | AWG 16...8        | 6          |
| 8 kV / 3  |                   |                   |            |
| III / V-0 |                   |                   |            |

| Rated connection                       |  |
|----------------------------------------|--|
| 150...300 / 150...300                  |  |
| 1.5...10 / 1.5...10                    |  |
| 35...240                               |  |
| 1.5...6                                |  |
| 34 / M24 (SW 12)                       |  |
| 10 / M4 (+/- PZ2)                      |  |
| see appendix at the end of the chapter |  |

### IEC 60947-7-1

| IEC       | UL                | CSA               | EN 60079-7 |
|-----------|-------------------|-------------------|------------|
| 1000      | 1000              | 1000              | 1100       |
| 1040      | 420               | 420               | 340        |
| 300       | AWG 2...kcmil 600 | AWG 2...kcmil 600 | 300        |
| 6         | AWG 16...8        | AWG 16...8        | 6          |
| 8 kV / 3  |                   |                   |            |
| III / V-0 |                   |                   |            |

| Rated connection                       |  |
|----------------------------------------|--|
| 150...300 / 150...300                  |  |
| 1.5...10 / 1.5...10                    |  |
| 35...240                               |  |
| 1.5...6                                |  |
| 34 / M24 (SW 12)                       |  |
| 10 / M4 (+/- PZ2)                      |  |
| see appendix at the end of the chapter |  |

B

### Ordering data

| Version     |            |
|-------------|------------|
|             | light grey |
|             | blue       |
|             | green      |
|             | brown      |
|             | black      |
| <b>Note</b> |            |

| Type                   | Qty. | Order No.  |
|------------------------|------|------------|
| WPD 133 1X300/1X300 GY | 1    | 2502850000 |
| WPD 133 1X300/1X300 BL | 1    | 2502860000 |
| WPD 133 1X300/1X300 GN | 1    | 2502870000 |
| WPD 133 1X300/1X300 BN | 1    | 2502880000 |
| WPD 133 1X300/1X300 BK | 1    | 2502890000 |

| Type                   | Qty. | Order No.  |
|------------------------|------|------------|
| WPD 233 2X300/2X300 GY | 1    | 2502900000 |
| WPD 233 2X300/2X300 BL | 1    | 2502910000 |
| WPD 233 2X300/2X300 GN | 1    | 2502920000 |
| WPD 233 2X300/2X300 BN | 1    | 2502930000 |
| WPD 233 2X300/2X300 BK | 1    | 2502940000 |

### Accessories

| Protective cover       |            |
|------------------------|------------|
|                        | light grey |
| End bracket            |            |
|                        | grey       |
|                        | black      |
| Screwdriver            |            |
|                        | SET        |
| Identification systems |            |

| Type              | Qty. | Order No.  |
|-------------------|------|------------|
| WPDPC X33 GY      | 8    | 2503390000 |
| WEW 35/2 GR 7042  | 100  | 1859200000 |
| AEB 35 SC/1 BK    | 50   | 2475310000 |
| SK WSD-S 1.5-10,0 | 1    | 9008850000 |
| DEK 5/5 MC NE WS  | 1000 | 1609801044 |
| WS 8/5 MM WS      | 800  | 2007150000 |

| Type              | Qty. | Order No.  |
|-------------------|------|------------|
| WPDPC X33 GY      | 8    | 2503390000 |
| WEW 35/2 GR 7042  | 100  | 1859200000 |
| AEB 35 SC/1 BK    | 50   | 2475310000 |
| SK WSD-S 1.5-10,0 | 1    | 9008850000 |
| DEK 5/5 MC NE WS  | 1000 | 1609801044 |
| WS 8/5 MM WS      | 800  | 2007150000 |

# Conductor connection data according to IEC 60947-7-1 (Cu), UL 1059 (AL+Cu)

| Input (x1) / Output (x1)                                | Copper                                                                            |                                                                                   |                                                                                   | Aluminium                                                                         |                                                                                   |
|---------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
|                                                         |  |  |  |  |  |
| 300 mm <sup>2</sup>                                     | 45 Nm                                                                             |                                                                                   |                                                                                   | 65 Nm                                                                             | 65 Nm                                                                             |
| 240 mm <sup>2</sup>                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |
| 185 mm <sup>2</sup>                                     |                                                                                   | 45 Nm                                                                             |                                                                                   |                                                                                   |                                                                                   |
| 150 mm <sup>2</sup>                                     |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |
| 120 mm <sup>2</sup>                                     |                                                                                   |                                                                                   | 65 Nm                                                                             |                                                                                   |                                                                                   |
| 95 mm <sup>2</sup>                                      |                                                                                   |                                                                                   |                                                                                   |                                                                                   | 30 Nm                                                                             |
| 70 mm <sup>2</sup>                                      |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |
| 50 mm <sup>2</sup>                                      |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |
| 35 mm <sup>2</sup>                                      |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                   |
| Flat band 10x20x1 mm                                    |                                                                                   |                                                                                   | 65 Nm                                                                             |                                                                                   |                                                                                   |
| Max. current with 2 x 300 mm <sup>2</sup> (acc. to IEC) | 1040 A                                                                            |                                                                                   |                                                                                   | 340 A                                                                             |                                                                                   |
| Stripping lengths                                       | 34 mm                                                                             |                                                                                   |                                                                                   |                                                                                   |                                                                                   |
| Allen screw                                             | M24 (SW 12 mm)                                                                    |                                                                                   |                                                                                   |                                                                                   |                                                                                   |

| Input (x1) / Output (x1)                 | Copper                                                                              |                                                                                     | Aluminium                                                                           |                                                                                     |
|------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                                          |  |  |  |  |
| 600 kcmil                                | 300Lb In.                                                                           |                                                                                     | 575Lb In.                                                                           | 575Lb In.                                                                           |
| 500 kcmil                                |                                                                                     | 300Lb In.                                                                           |                                                                                     |                                                                                     |
| 350 kcmil                                |                                                                                     |                                                                                     |                                                                                     |                                                                                     |
| 300 kcmil                                |                                                                                     |                                                                                     |                                                                                     |                                                                                     |
| 250 kcmil                                |                                                                                     | 200Lb In.                                                                           |                                                                                     |                                                                                     |
| AWG 3/0                                  |                                                                                     |                                                                                     |                                                                                     |                                                                                     |
| AWG 2/0                                  |                                                                                     |                                                                                     |                                                                                     |                                                                                     |
| AWG 1                                    |                                                                                     |                                                                                     |                                                                                     |                                                                                     |
| AWG 2                                    |                                                                                     |                                                                                     |                                                                                     |                                                                                     |
| Max. current at 1 x 300 mm² (acc. to UL) | 420 A                                                                               |                                                                                     | 340 A                                                                               |                                                                                     |
| Stripping lengths                        | 34 mm                                                                               |                                                                                     |                                                                                     |                                                                                     |
| Allen screw                              | M24 (SW 12 mm)                                                                      |                                                                                     |                                                                                     |                                                                                     |

## Auxiliary connection

| Copper              |                                                                                   |                                                                                   |
|---------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
|                     |  |  |
| 10 mm <sup>2</sup>  | 1,2 Nm                                                                            | 1,2 Nm                                                                            |
| 6 mm <sup>2</sup>   |                                                                                   |                                                                                   |
| 4 mm <sup>2</sup>   |                                                                                   |                                                                                   |
| 2.5 mm <sup>2</sup> |                                                                                   |                                                                                   |
| 1.5 mm <sup>2</sup> |                                                                                   |                                                                                   |
| max. current        | 57 A                                                                              |                                                                                   |
| Stripping lengths   | 10 mm                                                                             |                                                                                   |
| screw               | M4 (+/-PZ2)                                                                       |                                                                                   |

| Copper            |                                                                                                                                                                            |                                                                                     |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                   | <br> |  |
| AWG 8             | 20.3Lb In.                                                                                                                                                                 |                                                                                     |
| AWG 10            |                                                                                                                                                                            | 20.3Lb In.                                                                          |
| AWG 12            |                                                                                                                                                                            |                                                                                     |
| AWG 14            |                                                                                                                                                                            |                                                                                     |
| AWG 16            |                                                                                                                                                                            |                                                                                     |
| max. current      | 57 A                                                                                                                                                                       |                                                                                     |
| Stripping lengths | 10 mm                                                                                                                                                                      |                                                                                     |
| screw             | M4 (+/- PZ2)                                                                                                                                                               |                                                                                     |

 Stranded
  Solid
  Flexible with ferrule
  Sector shaped

 Flat band

## Drawings

