






- Notes
- 1 The recommended clamp torque of ref. No. ⑦: $3 \text{ N} \cdot \text{m}$.
LOCTITE 243, HENKEL JAPAN or equivalent is recommended to prevent ref. No. ⑦ from loosening.
 - 2 The direction of solder cup ref. No. ② is an example.
 - 3 When mounted on chassis, be careful reference No. ⑤ is fitted into the indicates groove any biting.

4	Diallyl phthalate	(Black) UL94V-0						
3	Diallyl phthalate	(Black) UL94V-0		7	Brass	Nickel plating		
2	Brass 	Silver plating 3 μm min.		6	Phosphor bronze	Nickel plating		
1	Zinc alloy	Chrome plating		5	Silicone rubber	(Black)		
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 2 : 1		COUNT 1	DESCRIPTION OF REVISIONS DIS-C-00007456	DESIGNED TY. SUZUKI	CHECKED HY. KOBAYASHI	DATE 20210806
 HIROSE ELECTRIC CO., LTD.		APPROVED	HY. KOBAYASHI		20160122	DRAWING NO. EDC-111084-71-00		
		CHECKED	HY. KOBAYASHI		20160122	PART NO. RM15WTRZA-3P(71)		
		DESIGNED	KN. IKEHARA		20160122	CODE NO. CL0109-1652-2-71		
		DRAWN	KN. IKEHARA		20160122	 1/1		