

DRAWING FOR REFERENCE: This is subject to change without notice
08/11/2012

TO
RF

1			2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		
△					△						
△					△						
△					△						

A

B

C

D

E

F

Technical drawing of a connector assembly showing a cross-section and a top view. The cross-section shows a hexagonal base with a central bore, surrounded by a flange. Dimensions include a total height of 18.85±1, a flange thickness of 7±0.2, and a central bore diameter of 4.62±0.03. The top view shows a hexagonal shape with a diameter of 8±0.15. Callouts 1 through 7 identify different components: 1 (Stainless Steel, Passivate), 2 (PTFE), 3 (Beryllium Copper, Gold Plated), 4 (PTFE), 5 (Stainless Steel, Passivate), 6 (Beryllium Copper, Nickel Plated), and 7 (Brass, Nickel Plated). The drawing also shows a 'POD SIDE' and an 'HRM(SMA) SIDE'.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
4	PTFE		7	BRASS	NICKEL PLATED
3	BERYLLIUM COPPER	GOLD PLATED	6	BERYLLIUM COPPER	NICKEL PLATED
2	PTFE		5	STAINLESS STEEL	PASSIVATE
1	STAINLESS STEEL	PASSIVATE			

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	M. Kaneko	M. Kaneko	M. Yamane	J. Mitani	
RoHS COMPLIANT	07.5.25	07.5.25	07.05.25	07.05.25	

DRAWING NO.	PART NO.
EDC4-008468-40	HRMJ-PODP(40)

UNITS	CODE NO.
mm	CL311-0157-0-40

HRS HIROSE ELECTRIC CO., LTD.

1 2 3 4

FORM NO.228