



09 65 462 6811  
D-Sub - S PCB connector

Other applications

|                    |                                 |
|--------------------|---------------------------------|
| gender             | male connector, right angled    |
| Termination        | Stamped solder pins             |
| shell              | tinned metal shell with dimples |
| Number of contacts | 37 way                          |
| Row pitch          | Row separation 2.54 mm          |
| Board fixing       | with grounding board locks      |
| flange             | M 3                             |
| Performance level  | Performance level 2             |
| Material           | PBTP                            |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 65 462 5811  
D-Sub - S PCB connector

Other applications

|                    |                                 |
|--------------------|---------------------------------|
| gender             | male connector, right angled    |
| Termination        | Stamped solder pins             |
| shell              | tinned metal shell with dimples |
| Number of contacts | 37 way                          |
| Row pitch          | Row separation 2.54 mm          |
| Board fixing       | with grounding board locks      |
| flange             | M 3                             |
| Performance level  | Performance level S4            |
| Material           | PBTP                            |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 65 462 5812  
D-Sub - S PCB connector

Other applications

|                    |                                 |
|--------------------|---------------------------------|
| gender             | male connector, right angled    |
| Termination        | Stamped solder pins             |
| shell              | tinned metal shell with dimples |
| Number of contacts | 37 way                          |
| Row pitch          | Row separation 2.54 mm          |
| Board fixing       | with grounding board locks      |
| flange             | UNC4-40                         |
| Performance level  | Performance level S4            |
| Material           | PBTP                            |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.



Data sheets are available in following formats  
2D files

Typenblatt

Typenblatt

09 65 462 6812  
D-Sub - S PCB connector

Other applications

|                    |                                 |
|--------------------|---------------------------------|
| gender             | male connector, right angled    |
| Termination        | Stamped solder pins             |
| shell              | tinned metal shell with dimples |
| Number of contacts | 37 way                          |
| Row pitch          | Row separation 2.54 mm          |
| Board fixing       | with grounding board locks      |
| flange             | UNC4-40                         |
| Performance level  | Performance level 2             |
| Material           | PBTP                            |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 65 462 7811  
D-Sub - S PCB connector

Other applications

|                    |                                 |
|--------------------|---------------------------------|
| gender             | male connector, right angled    |
| Termination        | Stamped solder pins             |
| shell              | tinned metal shell with dimples |
| Number of contacts | 37 way                          |
| Row pitch          | Row separation 2.54 mm          |
| Board fixing       | with grounding board locks      |
| flange             | M 3                             |
| Performance level  | Performance level 3             |
| Material           | PBTP                            |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 65 462 7812  
D-Sub - S PCB connector

Other applications

|                    |                                 |
|--------------------|---------------------------------|
| gender             | male connector, right angled    |
| Termination        | Stamped solder pins             |
| shell              | tinned metal shell with dimples |
| Number of contacts | 37 way                          |
| Row pitch          | Row separation 2.54 mm          |
| Board fixing       | with grounding board locks      |
| flange             | UNC4-40                         |
| Performance level  | Performance level 3             |
| Material           | PBTP                            |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF