



STRAIGHT JACK RECEPTACLE FOR PCB

SMT TYPE - EDGE CARD.

R124.423.243

Series : SMA-COM



All dimensions are in mm.

COMPONENTS	MATERIALS	PLATINGS (μm)
BODY	BRASS	GOLD 0.2 OVER NICKEL 2
CENTER CONTACT	BERYLLIUM COPPER	GOLD 0.5 OVER NICKEL 2
OUTER CONTACT	-	-
INSULATOR	PTFE	-
GASKET	-	-
OTHERS PARTS	-	-
-	-	-
-	-	-

Issue : 1149 A

In the effort to improve our products, we reserve the right to make changes judged to be necessary.



STRAIGHT JACK RECEPTACLE FOR PCB**SMT TYPE - EDGE CARD.****R124.423.243**

Series : SMA-COM

PACKAGING

Standard	Unit	Other
100	'W' option	Contact us

SPECIFICATION**ELECTRICAL CHARACTERISTICS**

Impedance	50	Ω
Frequency	0-18	GHz
VSWR	1.14 + 0,0000	x F(GHz) Maxi
Insertion loss	0.05	$\sqrt{F}(\text{GHz})$ dB Maxi
RF leakage	- (100)	- F(GHz)) dB Maxi
Voltage rating	500	Veff Maxi
Dielectric withstanding voltage	1000	Veff mini
Insulation resistance	5000	M Ω mini

ENVIRONMENTAL

Operating temperature	-65/+165	$^{\circ}\text{C}$
Hermetic seal	NA	Atm.cm3/s
Panel leakage	NA	

OTHERS CHARACTERISTICSAssembly instruction **NA**Others :
-**MECHANICAL CHARACTERISTICS**

Center contact retention	
Axial force – Mating end	27 N mini
Axial force – Opposite end	27 N mini
Torque	2.8 N.cm mini
Recommended torque	
Mating	NA N.cm
Panel nut	NA N.cm
Mating life	100 Cycles mini
Weight	1,5600 g

Issue : 1149 A

In the effort to improve our products, we reserve the right to make changes judged to be necessary.




STRAIGHT JACK RECEPTACLE FOR PCB**SMT TYPE - EDGE CARD.****R124.423.243**

Series : SMA-COM

SOLDER PROCEDURE

1. Deposition of solder paste 'Sn Ag4 Cu0.5' on mounting zone by screen printing application. We recommend a low residue flux.
We advise a thickness of 150 microns (5.850 microinch). Verify that the edges of the zone are clean.
2. Placement of the receptacle on the mounting zone with an automatic machine of 'pick and place' type.
Video camera is recommended for the positioning of the component. Adhesive agents must not be used on the receptacle.
3. Soldering by infra-red reflow.
Below, please find the typical profile to use.
4. Cleaning of printed circuit boards.
5. Checking of solder joints and position of the component by visual inspection.

TEMPERATURE PROFILE

Parameter	Value	Unit
Temperature rising Area	1 - 4	°C/sec
Max Peak Temperature	260	°C
Max dwell time @260°C	10	sec
Min dwell time @235°C	20	sec
Max dwell time @235°C	60	sec
Temperature drop in cooling Area	-1 to - 4	°C/sec
Max dwell time above 100°C	420	sec

Issue : 1149 A

In the effort to improve our products, we reserve the right to make changes judged to be necessary.




STRAIGHT JACK RECEPTACLE FOR PCB**SMT TYPE - EDGE CARD.****R124.423.243**

Series : SMA-COM


MOUNTING TYPE

This type of connector is adapted to one specific PCB thickness.
It can be used with different ways of transmission.

**1**


COPLANAR LINE

Signal and ground are coplanar.

**2**

MICROSTRIP LINE

Signal and ground are opposite.

**3**

Coplanar and opposite grounds.

Solution ③ features a stronger mechanical retention on the PCB because the 4 leads are soldered.

Issue : 1149 A

In the effort to improve our products, we reserve the right to make changes judged to be necessary.



R124.423.243

Series : **SMA-COM**

Technical drawing of a mechanical part with dimensions and tolerances. The drawing shows a cross-section of a part with a central hole and a rectangular feature. The dimensions are as follows:

- Overall width: 4 ± 0.2
- Overall height: 1.5
- Distance from the left edge to the center of the hole: 3.5
- Distance from the center of the hole to the right edge: 1.9
- Distance from the top edge to the center of the hole: 0.2
- Distance from the bottom edge to the center of the hole: 1.5
- Distance from the left edge to the center of the rectangular feature: 1.5
- Distance from the center of the rectangular feature to the right edge: 1.5
- Distance from the top edge to the center of the rectangular feature: 0.2
- Distance from the bottom edge to the center of the rectangular feature: 1.5
- Distance from the left edge to the center of the hole: 1.5
- Distance from the center of the hole to the right edge: 1.5
- Distance from the top edge to the center of the hole: 0.2
- Distance from the bottom edge to the center of the hole: 1.5
- Distance from the left edge to the center of the rectangular feature: 1.5
- Distance from the center of the rectangular feature to the right edge: 1.5
- Distance from the top edge to the center of the rectangular feature: 0.2
- Distance from the bottom edge to the center of the rectangular feature: 1.5
- Distance from the left edge to the center of the hole: 1.5
- Distance from the center of the hole to the right edge: 1.5
- Distance from the top edge to the center of the hole: 0.2
- Distance from the bottom edge to the center of the hole: 1.5
- Distance from the left edge to the center of the rectangular feature: 1.5
- Distance from the center of the rectangular feature to the right edge: 1.5
- Distance from the top edge to the center of the rectangular feature: 0.2
- Distance from the bottom edge to the center of the rectangular feature: 1.5

COPLANAR LINE
Pattern and signal are on the same side
The material of PCB is the epoxy resin
of glass fabrics bacs. ($\epsilon_r = 4.8$)
The solder resist should be printed
except for the land pattern on the PCB.

 Land for solder paste

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

