

DOF-0-212F(05.08)

8Z89E0P8
(ON 0NIMV80) 品番図

版数 REV.	年月日 DATE	DCN NO.	変更内容 DESCRIPTION	製図 DR.	担当 CHK.	査閲 APPD.	承認 APPD.
6	5.Feb.2007	062203	REDRAWN etc.		H.YOKOO	J. Kudo	K. Throck






TABLE 1

NO. OF CONTACT	A	B	C	D	E
6	7.2	4.0	2.5	8.3	8.7
8	8.2	5.0	3.5	9.3	9.7
10	9.2	6.0	4.5	10.3	10.7
15	11.7	8.5	7.0	12.8	13.2
16	12.2	9.0	7.5	13.3	13.7
18	13.2	10.0	8.5	14.3	14.7
20	14.2	11.0	9.5	15.3	15.7
22	15.2	12.0	10.5	16.3	16.7
24	16.2	13.0	11.5	17.3	17.7
26	17.2	14.0	12.5	18.3	18.7
30	19.2	16.0	14.5	20.3	20.7
36	22.2	19.0	17.5	23.3	23.7
40	24.2	21.0	19.5	25.3	25.7
45	26.7	23.5	22.0	27.8	28.2
50	29.2	26.0	24.5	30.3	30.7

APPLICABLE F.P.C. DIMENSION(REF.)
適合FPC寸法(参考)

TABLE 2


FINISH	CONTACT PART	TERMINAL PART
1	GOLD PLATING	LEAD-FREE TIN ALLOY PLATING





SECT. A-A
(SCALE 10:1)

注1.仕上りは金メッキのこと。

NOTE1. EXPOSURE CONDUCTORS SHOULD BE GIVEN GOLD PLATING.



MATED CONDITION(REF.)
嵌合状態図(参考)



APPLICABLE P.C.B. DIMENSION(REF.)
適合基板寸法(参考)

5	HOLD-DOWN-L	1	COPPER ALLOY	LEAD-FREE TIN ALLOY PLATING	
4	HOLD-DOWN-R	1	COPPER ALLOY	LEAD-FREE TIN ALLOY PLATING	
3	ACTUATOR	1	GLASS FILLED NY		COLOR:WHITE UL94V-0
2	BASE INSULATOR	1	GLASS FILLED LCP		COLOR:BLACK UL94V-0
1	CONTACT	TABLE 1	COPPER ALLOY	TABLE 2	
符号 NO.	名称 DESCRIPTION	個数 QTY.	材料 MATERIAL	仕上り FINISH	備考 REMARKS

仕様書(SPECIFICATION) JACS-1710 JABL-1710		第1版(ORIGINAL DATE) 5.Jul.2002		尺度(SCALE) 2:1	シリーズ(SERIES) FA5	日本航空電子工業株式会社 JAPAN AVIATION ELECTRONICS INDUSTRY, LTD. 図面番号(DRAWING NO.) SJ036878	版数 (REV.) 6
公差(GENERAL TOLERANCE)		製図 DR. K.HIROSE		名称(TITLE) FA5S***HP1			
寸法(DIMENSION)		担当 CHK. T.KUDOU					
角度(ANGLES)		査閲 APPD. M.SUZUKI					
. ±0.8		承認 APPD. T.MORINO		質量(MASS)			
.X ±0.4							
.XX ±0.1							
.XXX ±							

LEAD FREE この製品は鉛フリー品です