


## TrenchT2™ Power MOSFET


**IXTA70N075T2**  
**IXTP70N075T2**

N-Channel Enhancement Mode  
Avalanche Rated




$$\begin{aligned} V_{DSS} &= 75V \\ I_{D25} &= 70A \\ R_{DS(on)} &\leq 12m\Omega \end{aligned}$$

TO-263 (IXTA)



TO-220 (IXTP)



G = Gate      D = Drain  
S = Source    Tab = Drain

| Symbol     | Test Conditions                                                       | Maximum Ratings    |                  |
|------------|-----------------------------------------------------------------------|--------------------|------------------|
| $V_{DSS}$  | $T_J = 25^\circ\text{C}$ to $175^\circ\text{C}$                       | 75                 | V                |
| $V_{DGR}$  | $T_J = 25^\circ\text{C}$ to $175^\circ\text{C}$ , $R_{GS} = 1M\Omega$ | 75                 | V                |
| $V_{GSM}$  | Transient                                                             | $\pm 20$           | V                |
| $I_{D25}$  | $T_C = 25^\circ\text{C}$                                              | 70                 | A                |
| $I_{DM}$   | $T_C = 25^\circ\text{C}$ , Pulse Width Limited by $T_{JM}$            | 180                | A                |
| $I_A$      | $T_C = 25^\circ\text{C}$                                              | 40                 | A                |
| $E_{AS}$   | $T_C = 25^\circ\text{C}$                                              | 300                | mJ               |
| $P_D$      | $T_C = 25^\circ\text{C}$                                              | 150                | W                |
| $T_J$      |                                                                       | -55 ... +175       | $^\circ\text{C}$ |
| $T_{JM}$   |                                                                       | 175                | $^\circ\text{C}$ |
| $T_{stg}$  |                                                                       | -55 ... +175       | $^\circ\text{C}$ |
| $T_L$      | Maximum Lead Temperature for Soldering                                | 300                | $^\circ\text{C}$ |
| $T_{SOLD}$ | 1.6 mm (0.062in.) from Case for 10s                                   | 260                | $^\circ\text{C}$ |
| $F_C$      | Mounting Force (TO-263)                                               | 10..65 / 2.2..14.6 | N/lb             |
| $M_d$      | Mounting Torque (TO-220)                                              | 1.13 / 10          | Nm/lb.in         |
| Weight     | TO-263                                                                | 2.5                | g                |
|            | TO-220                                                                | 3.0                | g                |

| Symbol       | Test Conditions<br>( $T_J = 25^\circ\text{C}$ Unless Otherwise Specified) | Characteristic Values |      |                   |
|--------------|---------------------------------------------------------------------------|-----------------------|------|-------------------|
|              |                                                                           | Min.                  | Typ. | Max.              |
| $BV_{DSS}$   | $V_{GS} = 0V$ , $I_D = 250\mu\text{A}$                                    | 75                    |      | V                 |
| $V_{GS(th)}$ | $V_{DS} = V_{GS}$ , $I_D = 250\mu\text{A}$                                | 2.0                   |      | 4.0 V             |
| $I_{GSS}$    | $V_{GS} = \pm 20V$ , $V_{DS} = 0V$                                        |                       |      | $\pm 200$ nA      |
| $I_{DSS}$    | $V_{DS} = V_{DSS}$ , $V_{GS} = 0V$<br>$T_J = 150^\circ\text{C}$           |                       |      | 2 $\mu\text{A}$   |
|              |                                                                           |                       |      | 200 $\mu\text{A}$ |
| $R_{DS(on)}$ | $V_{GS} = 10V$ , $I_D = 25A$ , Notes 1 & 2                                | 10                    | 12   | m $\Omega$        |

### Features

- International Standard Packages
- Avalanche Rated
- Low Package Inductance
- Fast Intrinsic Rectifier
- 175°C Operating Temperature
- High Current Handling Capability
- ROHS Compliant
- High Performance Trench Technology for extremely low  $R_{DS(on)}$

### Advantages

- High Power Density
- Easy to Mount
- Space Savings

### Applications

- Automotive Engine Control
- Synchronous Buck Converter (for Notebook SystemPower & General Purpose Point & Load)
- DC/DC Converters
- High Current Switching Applications
- Power Train Management
- Distributed Power Architecture


| Symbol       | Test Conditions<br>( $T_J = 25^\circ\text{C}$ Unless Otherwise Specified)                                                                   | Characteristic Values |      |                         |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|------|-------------------------|
|              |                                                                                                                                             | Min.                  | Typ. | Max.                    |
| $g_{fs}$     | $V_{DS} = 10\text{V}$ , $I_D = 0.5 \cdot I_{D25}$ , Note 1                                                                                  | 22                    | 36   | S                       |
| $C_{iss}$    | $V_{GS} = 0\text{V}$ , $V_{DS} = 25\text{V}$ , $f = 1\text{MHz}$                                                                            |                       | 2725 | pF                      |
| $C_{oss}$    |                                                                                                                                             |                       | 334  | pF                      |
| $C_{rss}$    |                                                                                                                                             |                       | 60   | pF                      |
| $t_{d(on)}$  | <b>Resistive Switching Times</b><br>$V_{GS} = 10\text{V}$ , $V_{DS} = 0.5 \cdot V_{DSS}$ , $I_D = 25\text{A}$<br>$R_G = 5\Omega$ (External) |                       | 15   | ns                      |
| $t_r$        |                                                                                                                                             |                       | 28   | ns                      |
| $t_{d(off)}$ |                                                                                                                                             |                       | 31   | ns                      |
| $t_f$        |                                                                                                                                             |                       | 22   | ns                      |
| $Q_{g(on)}$  | $V_{GS} = 10\text{V}$ , $V_{DS} = 0.5 \cdot V_{DSS}$ , $I_D = 25\text{A}$                                                                   |                       | 46   | nC                      |
| $Q_{gs}$     |                                                                                                                                             |                       | 14   | nC                      |
| $Q_{gd}$     |                                                                                                                                             |                       | 7.5  | nC                      |
| $R_{thJC}$   | TO-220                                                                                                                                      |                       |      | 1.00 $^\circ\text{C/W}$ |
| $R_{thCS}$   |                                                                                                                                             | 0.50                  |      | $^\circ\text{C/W}$      |

### Source-Drain Diode

| Symbol   | Test Conditions<br>( $T_J = 25^\circ\text{C}$ Unless Otherwise Specified)                              | Characteristic Values |      |       |
|----------|--------------------------------------------------------------------------------------------------------|-----------------------|------|-------|
|          |                                                                                                        | Min.                  | Typ. | Max.  |
| $I_S$    | $V_{GS} = 0\text{V}$                                                                                   |                       |      | 70 A  |
| $I_{SM}$ | Repetitive, Pulse Width Limited by $T_{JM}$                                                            |                       |      | 280 A |
| $V_{SD}$ | $I_F = 25\text{A}$ , $V_{GS} = 0\text{V}$ , Note 1                                                     | 0.86                  | 1.0  | V     |
| $t_{rr}$ | $I_F = 50\text{A}$ , $V_{GS} = 0\text{V}$ ,<br>$-di/dt = 100\text{A}/\mu\text{s}$ , $V_R = 38\text{V}$ |                       | 48   | ns    |
| $I_{RM}$ |                                                                                                        |                       | 3.7  | A     |
| $Q_{RM}$ |                                                                                                        |                       | 89   | nC    |


- Notes: 1. Pulse test,  $t \leq 300\mu\text{s}$ ; duty cycle,  $d \leq 2\%$ .  
2. On through-hole packages,  $R_{DS(on)}$  Kelvin test contact location must be 5mm or less from the package body.

### TO-263 Outline



| SYM | INCHES   |      | MILLIMETER |       |
|-----|----------|------|------------|-------|
|     | MIN      | MAX  | MIN        | MAX   |
| A   | .170     | .185 | 4.30       | 4.70  |
| A1  | .000     | .008 | 0.00       | 0.20  |
| A2  | .091     | .098 | 2.30       | 2.50  |
| b   | .028     | .035 | 0.70       | 0.90  |
| b2  | .046     | .060 | 1.18       | 1.52  |
| C   | .018     | .024 | 0.45       | 0.60  |
| C2  | .049     | .060 | 1.25       | 1.52  |
| D   | .340     | .370 | 8.63       | 9.40  |
| D1  | .300     | .327 | 7.62       | 8.30  |
| E   | .380     | .410 | 9.65       | 10.41 |
| E1  | .270     | .330 | 6.86       | 8.38  |
| e   | .100 BSC |      | 2.54 BSC   |       |
| H   | .580     | .620 | 14.73      | 15.75 |
| L   | .075     | .105 | 1.91       | 2.67  |
| L1  | .039     | .060 | 1.00       | 1.52  |
| L2  | —        | .070 | —          | 1.77  |
| L3  | .010 BSC |      | 0.254 BSC  |       |

### TO-220 Outline



| SYM  | INCHES   |      | MILLIMETERS |       |
|------|----------|------|-------------|-------|
|      | MIN      | MAX  | MIN         | MAX   |
| A    | .169     | .185 | 4.30        | 4.70  |
| A1   | .047     | .055 | 1.20        | 1.40  |
| A2   | .079     | .106 | 2.00        | 2.70  |
| b    | .024     | .039 | 0.60        | 1.00  |
| b2   | .045     | .057 | 1.15        | 1.45  |
| c    | .014     | .026 | 0.35        | 0.65  |
| D    | .587     | .626 | 14.90       | 15.90 |
| D1   | .335     | .370 | 8.50        | 9.40  |
| (D2) | .500     | .531 | 12.70       | 13.50 |
| E    | .382     | .406 | 9.70        | 10.30 |
| (E1) | .283     | .323 | 7.20        | 8.20  |
| e    | .100 BSC |      | 2.54 BSC    |       |
| e1   | .200 BSC |      | 5.08 BSC    |       |
| H1   | .244     | .268 | 6.20        | 6.80  |
| L    | .492     | .547 | 12.50       | 13.90 |
| L1   | .110     | .154 | 2.80        | 3.90  |
| ØP   | .134     | .150 | 3.40        | 3.80  |
| Q    | .106     | .126 | 2.70        | 3.20  |

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

|                                                                                  |           |           |           |           |             |             |             |             |             |             |
|----------------------------------------------------------------------------------|-----------|-----------|-----------|-----------|-------------|-------------|-------------|-------------|-------------|-------------|
| IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: | 4,835,592 | 4,931,844 | 5,049,961 | 5,237,481 | 6,162,665   | 6,404,065B1 | 6,683,344   | 6,727,585   | 7,005,734B2 | 7,157,338B2 |
|                                                                                  | 4,860,072 | 5,017,508 | 5,063,307 | 5,381,025 | 6,259,123B1 | 6,534,343   | 6,710,405B2 | 6,759,692   | 7,063,975B2 |             |
|                                                                                  | 4,881,106 | 5,034,796 | 5,187,117 | 5,486,715 | 6,306,728B1 | 6,583,505   | 6,710,463   | 6,771,478B2 | 7,071,537   |             |

Fig. 1. Output Characteristics @  $T_J = 25^\circ\text{C}$




Fig. 2. Extended Output Characteristics @  $T_J = 25^\circ\text{C}$




Fig. 3. Output Characteristics @  $T_J = 150^\circ\text{C}$




Fig. 4.  $R_{DS(on)}$  Normalized to  $I_D = 35\text{A}$  Value vs. Junction Temperature




Fig. 5.  $R_{DS(on)}$  Normalized to  $I_D = 35\text{A}$  Value vs. Drain Current







Fig. 6. Drain Current vs. Case Temperature




**Fig. 7. Input Admittance**




**Fig. 8. Transconductance**




**Fig. 9. Forward Voltage Drop of Intrinsic Diode**




**Fig. 10. Gate Charge**




**Fig. 11. Capacitance**




**Fig. 12. Forward-Bias Safe Operating Area**




**Fig. 13. Resistive Turn-on**  
**Rise Time vs. Junction Temperature**




**Fig. 14. Resistive Turn-on**  
**Rise Time vs. Drain Current**




**Fig. 15. Resistive Turn-on**  
**Switching Times vs. Gate Resistance**



**Fig. 16. Resistive Turn-off**  
**Switching Times vs. Junction Temperature**



**Fig. 17. Resistive Turn-off**  
**Switching Times vs. Drain Current**



**Fig. 18. Resistive Turn-off**  
**Switching Times vs. Gate Resistance**





Fig. 19. Maximum Transient Thermal Impedance





---

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).