

|       |               |
|-------|---------------|
| $V_R$ | 1200V         |
| $I_F$ | 5A/10A*       |
| $Q_C$ | 17nC(Per leg) |

(\*Per leg/ Both legs)

### ●Features

- 1) Low forward voltage
- 2) Negligible recovery time/current
- 3) Temperature independent switching behavior

### ●Applications

- Switch Mode Power Supply
- Uninterruptible Power Supply
- Solar Inverter
- Motor Drive
- Air Conditioner
- EV Charger

### ●Absolute maximum ratings ( $T_j = 25^\circ\text{C}$ )


| Parameter                                              |                                           | Symbol              | Value       | Unit             |
|--------------------------------------------------------|-------------------------------------------|---------------------|-------------|------------------|
| Reverse voltage (repetitive peak)                      |                                           | $V_{RM}$            | 1200        | V                |
| Reverse voltage (DC)                                   |                                           | $V_R$               | 1200        | V                |
| Continuous forward current *4 (T <sub>c</sub> = 148°C) |                                           | I <sub>F</sub>      | 5/10        | A                |
| Surge non-repetitive forward current *4                | PW=10ms sinusoidal, T <sub>j</sub> =25°C  | I <sub>FSM</sub>    | 22/45       | A                |
|                                                        | PW=10ms sinusoidal, T <sub>j</sub> =150°C |                     | 17/34       | A                |
|                                                        | PW=10μs square, T <sub>j</sub> =25°C      |                     | 80/160      | A                |
| Repetitive peak forward current*4                      |                                           | I <sub>FRM</sub>    | 26/52*2     | A                |
| i <sup>2</sup> t value*3                               | PW=10ms, T <sub>j</sub> =25°C             | ∫ i <sup>2</sup> dt | 2.5/10      | A <sup>2</sup> s |
|                                                        | PW=10ms, T <sub>j</sub> =150°C            |                     | 1.4/5       | A <sup>2</sup> s |
| Total power dissipation *4                             |                                           | P <sub>D</sub>      | 83/170*3    | W                |
| Junction temperature                                   |                                           | T <sub>j</sub>      | 175         | °C               |
| Range of storage temperature                           |                                           | T <sub>stg</sub>    | −55 to +175 | °C               |

\*1 Tolerances of dimensions and packing specifications slightly differ between TO-247 and TO-247N, which is unlikely to influence compatibility for mounting. Please refer to corresponding specifications of dimensions for more details.


\*2  $T_c=100^\circ\text{C}$ ,  $T_j=150^\circ\text{C}$ , Duty cycle=10% \*3  $T_c=25^\circ\text{C}$  \*4 Per leg/ Both legs

### ●Outline

TO-247  
TO-247N



### ●Inner circuit



### ●Packaging specifications\*1

| Package | TO-247                    | TO-247N   |
|---------|---------------------------|-----------|
| Type    | Packing                   | Tube      |
|         | Reel size (mm)            | -         |
|         | Tape width (mm)           | -         |
|         | Basic ordering unit (pcs) | 30        |
|         | Packing code              | C C11     |
|         | Marking                   | SCS210KE2 |

**●Electrical characteristics ( $T_j = 25^\circ\text{C}$ ) (Per Leg)**


| Parameter               | Symbol   | Conditions                                           | Values |      |      | Unit          |
|-------------------------|----------|------------------------------------------------------|--------|------|------|---------------|
|                         |          |                                                      | Min.   | Typ. | Max. |               |
| DC blocking voltage     | $V_{DC}$ | $I_R = 0.1\text{mA}$                                 | 1200   | -    | -    | V             |
| Forward voltage         | $V_F$    | $I_F = 5\text{A}, T_j = 25^\circ\text{C}$            | -      | 1.4  | 1.6  | V             |
|                         |          | $I_F = 5\text{A}, T_j = 150^\circ\text{C}$           | -      | 1.8  | -    | V             |
|                         |          | $I_F = 5\text{A}, T_j = 175^\circ\text{C}$           | -      | 1.9  | -    | V             |
| Reverse current         | $I_R$    | $V_R = 1200\text{V}, T_j = 25^\circ\text{C}$         | -      | 5    | 100  | $\mu\text{A}$ |
|                         |          | $V_R = 1200\text{V}, T_j = 150^\circ\text{C}$        | -      | 40   | -    | $\mu\text{A}$ |
|                         |          | $V_R = 1200\text{V}, T_j = 175^\circ\text{C}$        | -      | 65   | -    | $\mu\text{A}$ |
| Total capacitance       | $C$      | $V_R = 1\text{V}, f = 1\text{MHz}$                   | -      | 260  | -    | pF            |
|                         |          | $V_R = 800\text{V}, f = 1\text{MHz}$                 | -      | 21   | -    | pF            |
| Total capacitive charge | $Q_C$    | $V_R = 800\text{V}, di/dt = 500\text{A}/\mu\text{s}$ | -      | 17   | -    | nC            |
| Switching time          | $t_C$    | $V_R = 800\text{V}, di/dt = 500\text{A}/\mu\text{s}$ | -      | 15   | -    | ns            |

**●Thermal characteristics**





| Parameter          | Symbol        | Conditions | Values |      |      | Unit                      |
|--------------------|---------------|------------|--------|------|------|---------------------------|
|                    |               |            | Min.   | Typ. | Max. |                           |
| Thermal resistance | $R_{th(j-c)}$ | Per Leg    | -      | 1.5  | 1.8  | $^\circ\text{C}/\text{W}$ |
|                    |               | Both Legs  | -      | 0.75 | 0.90 | $^\circ\text{C}/\text{W}$ |

**●Typical Transient Thermal Characteristics (Per Leg)**

| Symbol    | Value                 | Unit | Symbol    | Value                 | Unit |
|-----------|-----------------------|------|-----------|-----------------------|------|
| $R_{th1}$ | $4.22 \times 10^{-1}$ | K/W  | $C_{th1}$ | $2.40 \times 10^{-3}$ | Ws/K |
| $R_{th2}$ | $9.58 \times 10^{-1}$ |      | $C_{th2}$ | $5.95 \times 10^{-3}$ |      |
| $R_{th3}$ | $1.19 \times 10^{-1}$ |      | $C_{th3}$ | $1.40 \times 10^{-1}$ |      |



# ●Electrical characteristic curves

Fig.1  $V_F - I_F$  Characteristics (Per Leg)Fig.2  $V_F - I_F$  Characteristics (Per Leg)Fig.3  $V_R - I_R$  Characteristics (Per Leg)Fig.4  $V_R - C_t$  Characteristics (Per Leg)

## ●Electrical characteristic curves

Fig.5 Typical Transient Thermal Resistance vs. Pulse Width (Per Leg)




Fig.6 Power Dissipation (Per Leg)






Fig.7\*5 Maximum peak forward current derating curve  $I_P - T_c$  (Per Leg)



Case Temperature :  $T_c$  [°C]  
 \*5 Based on max  $V_f$ , max  $R_{th(j-c)}$   
 Valid for switching of above 10kHz,  
 excluding D.C. curve.

Fig.8\*6 Typical peak forward current derating curve  $I_P - T_c$  (Per Leg, Not guaranteed)



Case Temperature :  $T_c$  [°C]  
 \*6 Based on typ  $V_f$ , typ  $R_{th(j-c)}$   
 Typical value, not guaranteed  
 Valid for switching of above 10kHz,  
 excluding D.C. curve

## ●Electrical characteristic curves

Fig.9 Surge non-repetitive forward current vs. Pulse width (Sinusoidal waveform) (Per Leg)






Fig.10 Typical capacitance store energy (Per Leg)



## ●Simplified forward characteristic model (Per Leg)

Fig.11 Equivalent forward current curve



$$V_F = V_{th} + R_{diff} I_F$$

$$V_{th}(T_j) = a_0 + a_1 T_j$$

$$R_{diff}(T_j) = b_0 + b_1 T_j + b_2 T_j^2$$

| Symbol | Typical Value          | Unit              |
|--------|------------------------|-------------------|
| $a_0$  | $9.93 \times 10^{-1}$  | V                 |
| $a_1$  | $-1.27 \times 10^{-3}$ | V/°C              |
| $b_0$  | $7.30 \times 10^{-2}$  | Ω                 |
| $b_1$  | $4.12 \times 10^{-4}$  | Ω/°C              |
| $b_2$  | $2.66 \times 10^{-6}$  | Ω/°C <sup>2</sup> |

$T_j$  in °C;  $-55^\circ\text{C} < T_j < 175^\circ\text{C}$ ;  $I_F < 10\text{ A}$

## Notes

- 1) The information contained herein is subject to change without notice.
- 2) Before you use our Products, please contact our sales representative and verify the latest specifications :
- 3) Although ROHM is continuously working to improve product reliability and quality, semiconductors can break down and malfunction due to various factors.  
Therefore, in order to prevent personal injury or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. ROHM shall have no responsibility for any damages arising out of the use of our Products beyond the rating specified by ROHM.
- 4) Examples of application circuits, circuit constants and any other information contained herein are provided only to illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.
- 5) The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM or any other parties. ROHM shall have no responsibility whatsoever for any dispute arising out of the use of such technical information.
- 6) The Products specified in this document are not designed to be radiation tolerant.
- 7) For use of our Products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a ROHM representative : transportation equipment (i.e. cars, ships, trains), primary communication equipment, traffic lights, fire/crime prevention, safety equipment, medical systems, and power transmission systems.
- 8) Do not use our Products in applications requiring extremely high reliability, such as aerospace equipment, nuclear power control systems, and submarine repeaters.
- 9) ROHM shall have no responsibility for any damages or injury arising from non-compliance with the recommended usage conditions and specifications contained herein.
- 10) ROHM has used reasonable care to ensure the accuracy of the information contained in this document. However, ROHM does not warrant that such information is error-free, and ROHM shall have no responsibility for any damages arising from any inaccuracy or misprint of such information.
- 11) Please use the Products in accordance with any applicable environmental laws and regulations, such as the RoHS Directive. For more details, including RoHS compatibility, please contact a ROHM sales office. ROHM shall have no responsibility for any damages or losses resulting from non-compliance with any applicable laws or regulations.
- 12) When providing our Products and technologies contained in this document to other countries, you must abide by the procedures and provisions stipulated in all applicable export laws and regulations, including without limitation the US Export Administration Regulations and the Foreign Exchange and Foreign Trade Act.
- 13) This document, in part or in whole, may not be reprinted or reproduced without prior consent of ROHM.



Thank you for your accessing to ROHM product informations.  
More detail product informations and catalogs are available, please contact us.

## ROHM Customer Support System

<http://www.rohm.com/contact/>