



P.C. MOUNTING



CIRCUIT: SPDT



WITHOUT LOCKING RING


WITH STANDARD
LOCKING RING

PANEL MOUNTING




SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
ON	OFF	ON
2-3	OPEN	2-1

NOTE:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
- TERMINAL NUMBERS FOR REF ONLY
- PLATING MATERIAL: SILVER
- RATING: 3 AMPS @ 120VAC OR 28VDC UL, CUL
1 AMPS @ 250VAC UL, CUL
- ELECTRIC LIFE: 30,000 MAKE-AND-BREAK CYCLES AT FULL LOAD.
- INSULATION RESISTANCE: 1,000 MEGA-OHM MIN.
- DIELECTRIC STRENGTH: 1,000 V RMS @SEA LEVEL.
- OPERATING TEMP.: -30°C to 85°C
- 2002/95/EC (ROHS) COMPLIANT
- ▲ DENOTES CRITICAL PARAMETER.
- HARDWARE TO BE SHIPPED IN BULK:
T200000 - LOCK WASHER QTY-1
T200003 - LOCK RING QTY-1
T200001 - HEX NUT QTY-2



KEYWAY

10-48 UNS-2A
THREADSE-LOGO ON
OPPOSITE SIDENO EPOXY ON TERMINALS
BELOW THIS SURFACE

B	21828	Hardware from 1/4 to 10-48 hardware	4/9/15	MW
A	21802	RELEASED FOR PRODUCTION	3/16/15	MW
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY
TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

TITLE 200MSP3T2B3M2QEH

SCALE 2:1

DATE 3/16/2015

DR MW

DWG ST211157

REV B