



- Notes
- 1 The recommended crimp torque of ref.No. ⑤ shall be 0.15 to 0.2N·m.
LOCTITE 263, HENKEL JAPAN or equivalent is recommended to prevent ref. No. ⑤ from loosening.
 - 2 Applicable cable : $\phi 18 \pm 0.3$
 - 3 Assemble with applicable connector : RM31WTP-**(71)
** shows number of contact, and male or female of connector.
 - 4 The cable pull and twisting strength(, waterproof tightness) and other characteristics may differ, depending on the cable structure, please confirm before the use.

3	Brass	Nickel plating			
2	Phosphor bronze	Nickel plating	5	Brass	Nickel plating
1	Brass	Nickel plating	4	Chloroprene rubber	(Black)
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED
					CHECKED
					DATE
APPROVED :HY. KOBAYASHI 16.01.25			DRAWING NO. EDC-110126-71-00		
CHECKED :HY. KOBAYASHI 16.01.25			PART NO. RM31WTP-CP(18)(71)		
DESIGNED :HY. KISHI 16.01.25			CODE NO. CL109-1578-1-71		
DRAWN :HY. KISHI 16.01.25					