

[Skip to content](#)



Our commitment. Your advantage.



## • [Products](#)

- [By Type](#)
  - [Connectors](#)
  - [Electromechanical Components](#)
  - [Electronic Modules](#)
  - [Fiber Optics](#)
  - [Filters](#)
  - [Identification & Labeling](#)
  - [Passive Components](#)
  - [Power Sources](#)
  - [RF & Microwave Products](#)
  - [Tooling Products](#)
  - [Touch Screen Displays](#)
  - [Tubing, Molded and Harnessing Products](#)
  - [Wire, Cable and Cable Assemblies](#)
  - [List all product types...](#)
- [By Industry](#)
  - [Aerospace & Defense Products](#)
  - [Appliance](#)
  - [Automotive](#)
  - [Communications](#)
  - [Computer & Consumer Electronics](#)
  - [Industrial & Commercial](#)
  - [Instrumentation & Medical](#)
- [By Brand](#)
- [A to Z](#)
- [Product News](#)

## • [Documentation](#)

- [Find Documents & Drawings](#)
- [Find CAD Models](#)
- [SPICE/Electrical Models](#)
- [NAFTA Certificate of Origin](#)
- [White Papers](#)

## • [Resources](#)

- [RoHS Compliance & Alternates](#)
- [Cross Reference Products](#)
- [Compare Multiple Products](#)
- [Check Distributor Inventory](#)
- [Find Authorized Distributors](#)

## • [My Account](#)

- [Sign In](#)
- [Register](#)

## • [Customer Support](#)

- [Support](#)
- [RoHS Support Center](#)
- [Glossary of Terms](#)
- [eBulletin Newsletter](#)

# 1755082-1 Product Details



1755082-1



Active

## Rotary Relays

[Not EU RoHS or ELV Compliant](#)

### Product Highlights:

- Contact Arrangement = 4 Form C, 4PDT, 4 C/O
- DC Actuating System
- Input Voltage = 125 VDC
- Coil Current = .082 Amps.
- Coil Resistance = 1520 ?

[View all Features](#) | [Find Similar Products](#)



[Previous](#) [1](#) [2](#) **[3]** [4](#) [5](#) ... [15](#) [Next](#)



### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Compare Products](#)
- [Contact Us About This Product](#)

## Documentation & Additional Information

### Product Drawings:

- None Available

### Catalog Pages/Data Sheets:

- None Available

### Product Specifications:

- None Available

### Application Specifications:

- None Available

### Instruction Sheets:

- None Available

### CAD Files:

- None Available

### Additional Information:

- [Product Line Information](#)

### Additional Product Images:

- [Dimensional Drawing](#)

### Related Products:

- [Tooling](#)

## Product Features (Please use the Product Drawing for all design activity)

### Product Type Features:

- Comment = Small

### Electrical Characteristics:

- Actuating System= DC
- Input Voltage (VDC) = 125
- Coil Current (Amps.) = 0.082
- Coil Resistance (?) = 1520
- Coil Power, Nominal (W) = 10.30
- Breakdown Volts RMS (V) = 1275

### Termination Related Features:

- Base Dimensions (mm[in]) = 66.68 x 66.68 [2.625 x 2.625]
- Height (mm[in]) = 79.50 [3.130]

### Configuration Related Features:

- [Contact Arrangement](#) = 4 Form C, 4PDT, 4 C/O
- Coil Magnetic System= Non-Latching

### Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process

### Conditions for Usage:

- Temperature Range (C) = 0 65

### Other:

- Brand = Potter & Brumfield