


Subminiature, Sensitive SPDT Signal Switching Relay

- High sensitivity: 98-mW (Rated power consumption: 200mW) pickup coil power.
- Impulse withstand voltage of 1,500V (10×160 µs) meets FCC requirements.
- Stick packing employed in consideration of supporting automatic implementation.
- Plastic-sealed model that allows automatic soldering.
- New series of ultrasonically cleanable models is available.
- Standard model conforms to UL/CSA standards.

RoHS Compliant



■ Model Number Legend

G6E-1-234567-8

1. Relay Function
None: Single-side stable
U : Single-winding latching
K : Double-winding latching

**2. Number of poles/
Contact Form**
1: 1-pole/SPDT (1c)

3. Contact Type
3: Bifurcated crossbar Ag
(Au-Alloy) contact

4. Enclosure Rating
4: Fully sealed

5. Terminals Shape
P: PCB terminals

6. Classification
None : Standard
L : Low sensitivity coil
(400 mW)

7. Approved Standards

US: UL, CSA
(UL: FILE No.E41515
CSA: FILE No.LR31928)

8. Special Function

None : Standard
U : For ultrasonically
cleanable

■ Application Examples

- Telecommunication equipment
- Office automation machines
- Industrial equipment
- Security equipment

G
6
E

■ Ordering Information

● Standard Models (UL, CSA certified)

Relay Function			Single-side stable			Single-winding latching			Double-winding latching			Minimum packing unit
Classification			Standard		Low-sensitivity	Standard		Standard		Low-sensitivity		
Contact form	Model	Rated coil voltage	Model	Rated coil voltage		Model	Rated coil voltage	Model	Rated coil voltage			
SPDT (1c)	G6E-134P-US	5 VDC	G6E-134PL-US	5 VDC		G6EU-134P-US	5 VDC	G6EK-134P-US	5 VDC		G6EK-134PL-US	5 VDC
		6 VDC		6 VDC			6 VDC		6 VDC			6 VDC
		9 VDC		9 VDC			9 VDC		9 VDC			—
		12 VDC		12 VDC			12 VDC		12 VDC			12 VDC
		24 VDC		24 VDC			24 VDC		24 VDC			24 VDC
		48 VDC		—			—		—			—
		—		—			—		—			—

● Models for Ultrasonically Cleanable

Relay Function			Single-side stable			Single-winding latching			Double-winding latching			Minimum packing unit
Classification			Standard		Low-sensitivity	Standard			Standard			
Contact form	Model	Rated coil voltage	Model	Rated coil voltage		Model	Rated coil voltage	Model	Rated coil voltage			
SPDT (1c)	G6E-134P-US-U	5 VDC	G6E-134PL-US-U	5 VDC		G6EU-134P-US-U	5 VDC	G6EK-134P-US-U	5 VDC		G6EK-134PL-US-U	5 VDC
		6 VDC		—			—		—			—
		9 VDC		—			—		—			—
		12 VDC		12 VDC			12 VDC		12 VDC			12 VDC
		24 VDC		24 VDC			—		—			24 VDC
		48 VDC		—			—		—			—
		—		—			—		—			—

Note: When ordering, add the rated coil voltage to the model number.

Example: G6E-134P-US DC5

_____ Rated coil voltage

However, the notation of the coil voltage on the product case as well as on the packing will be marked as □□ VDC.

■ Ratings

● Coil: Single-side Stable

Classification	Rated voltage	Rated current (mA)	Coil resistance (Ω)	Must operate voltage (V)	Must release voltage (V)	Max. voltage (V)	Power consumption (mW)
Standard	5 VDC	40.0	125	70% max.	10% min.	190% (at 23°C)	Approx. 200
	6 VDC	33.3	180				
	9 VDC	22.2	405				
	12 VDC	16.7	720			170% (at 23°C)	Approx. 400
	24 VDC	8.3	2,880				
	48 VDC	8.3	5,760				
Low-sensitivity	5 VDC	79.4	63	70% max.	10% min.	170% (at 23°C)	Approx. 400
	6 VDC	66.6	90				
	9 VDC	44.3	203				
	12 VDC	33.3	360				
	24 VDC	16.7	1,440				

● Coil: Single-winding latching

Contact type	Rated voltage	Rated current (mA)	Coil resistance (Ω)	Must set voltage (V)	Must reset voltage (V)	Max. voltage (V)	Power consumption	
							% of rated voltage	
Bifurcated crossbar	5 VDC	40.0	125	70% max.	70% max.	190% (at 23°C)	Approx. 200	Approx. 200
	6 VDC	33.3	180					
	9 VDC	22.2	405					
	12 VDC	16.7	720					
	24 VDC	8.3	2,880					

● Coil: Double-winding latching

Classification	Rated voltage	Rated current (mA)		Coil resistance (Ω)		Must set voltage (V)	Must reset voltage (V)	Max. voltage (V)	Power consumption	
		Set coil	Reset coil	Set coil	Reset coil				% of rated voltage	
Standard	5 VDC	40.0	40.0	125	125	70% max.	70% max.	190% (at 23°C)	Approx. 200	Approx. 200
	6 VDC	33.3	33.3	180	180					
	9 VDC	22.2	22.2	405	405					
	12 VDC	16.7	16.7	720	720					
	24 VDC	8.3	8.3	2,880	2,880					
Low-sensitivity	5 VDC	79.4	79.4	63	63	70% max.	70% max.	170% (at 23°C)	Approx. 400	Approx. 400
	6 VDC	66.6	66.6	90	90					
	9 VDC	44.3	44.3	203	203					
	12 VDC	33.3	33.3	360	360					
	24 VDC	16.7	16.7	1,440	1,440					

Note 1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of ±10%.

2. Operating characteristics are measured at a coil temperature of 23°C.

3. The maximum voltage is the highest voltage that can be imposed on the relay coil.

4. Refer to the engineering data for relations between the ambient temperature and maximum coil voltage.

● Contacts

Item	Load	Resistive load	Inductive load (cosφ = 0.4; L/R = 7 ms)
Contact type	Bifurcated crossbar		
Contact material	Ag (Au-Alloy)		
Rated load	0.4 A at 125 VAC; 2 A at 30 VDC	0.2 A at 125 VAC; 1 A at 30 VDC	
Rated carry current	3 A		
Max. switching voltage	250 VAC, 220 VDC		
Max. switching current	3 A		

■ Characteristics (Including Models for Ultrasonically Cleanable)

Item	Relay Function	Single-side Stable	Single-winding Latching	Double-winding Latching
Contact resistance *1			50 mΩ max.	
Operate (set) time			5 ms max.	
Release (reset) time			5 ms max.	
Min. set pulse width		—		15 ms
Min. reset pulse width		—		15 ms
Insulation resistance *2			1,000 MΩ min. (at 500 VDC)	
Impulse withstand voltage	Between coil and contacts		2,500 V (10×160 μs) (conforms to FCC part 68)	
	Between contacts of same polarity		1,500 V (10×160 μs) (conforms to FCC part 68)	
Dielectric strength	Between coil and contacts		1,500 VAC, 50/60 Hz for 1 min	
	Between contacts of same polarity		1,000 VAC, 50/60 Hz for 1 min	
Vibration resistance	Destruction		10 to 55 to 10 Hz, 2.5 mm single amplitude (5 mm double amplitude)	
	Malfunction		10 to 55 to 10 Hz, 1.65 mm single amplitude (3.3 mm double amplitude)	
Shock resistance	Destruction		1,000 m/s ²	
	Malfunction		300 m/s ²	
Durability	Mechanical		100,000,000 operations min. (at 36,000 operations/hr)	
	Electrical		100,000 operations min. (0.4 A at 125 VAC resistive load; 0.2 A at 125 VAC inductive load) (at 1,800 operations/hr)	
			500,000 operations min. (2 A at 30 VDC resistive load; 1 A at 30 VDC inductive load) (at 1,800 operations/hr)	
			200,000 operations min. (3 A at 30 VDC resistive load) (at 1,800 operations/hr)	
Failure rate (P level) (reference value) *3			10 μA at 10 mVDC	
Ambient operating temperature			-40°C to 70°C (with no icing or condensation)	
Ambient operating humidity			5% to 85%	
Weight			Approx. 2.7 g	

Note: The values here are initial values.

*1. The contact resistance was measured with 1 A at 5 VDC using a voltage-drop method.

*2. The insulation resistance was measured with a 500 VDC Megger Tester applied to the same parts as those used for checking the dielectric strength.


*3. This value was measured at a switching frequency of 120 operations/min and the criterion of contact resistance is 50 Ω.

This value may vary depending on the switching frequency and operating environment. Always double-check relay suitability under actual operating conditions.


G
6
E

■ Engineering Data


● Maximum Switching Power



● Durability




● Ambient Temperature vs. Maximum Coil Voltage




Note: The maximum coil voltage refers to the maximum value in a varying range of operating power voltage, not a continuous voltage.


● Ambient Temperature vs. Must Operate or Must Release Voltage



● Shock Malfunction G6E-134P-US




G6EK-134P-US




Test Conditions: Shock is applied in ±X, ±Y, and ±Z directions three times each with and without energizing the Relays to check the number of contact malfunction.


● Contact Reliability Test *1, *2
G6E-134P-US




● High-frequency Characteristics (Isolation) *1, *3
G6E-134P-US




● Must Operate and Must Release Time Distribution *1
G6E-134P-US




● Distribution of Bounce Time *1
G6E-134P-US




● Contact Reliability Test (70°C) *1, *2
G6E-134P-US




● High-frequency Characteristics (Insertion Loss) *1, *3
G6E-134P-US




● Mutual Magnetic Interference
G6E-134P-US




G6E-134PL-US



G6E-134PL-US





G6E-134P-US 48 VDC




- *1. The tests were conducted at an ambient temperature of 23°C.
- *2. The contact resistance data are periodically measured reference values and are not values from each monitoring operation. Contact resistance values will vary according to the switching frequency and operating environment, so be sure to check operation under the actual operating conditions before use.
- *3. High-frequency characteristics depend on the PCB to which the Relay is mounted. Always check these characteristics, including durability, in the actual machine before use.

Dimensions


Single-side stable
G6E-134P-US
G6E-134PL-US
G6E-134P-US-U
G6E-134PL-US-U



PCB Mounting Holes
(Bottom View)
Tolerance: ± 0.1





Terminal Arrangement/
Internal Connections
(Bottom View)




Note: Be sure to confirm coil polarity.

Note: Orientation marks are indicated as follows:


Single-winding latching
G6EU-134P-US
G6EU-134P-US-U



PCB Mounting Holes
(Bottom View)
Tolerance: ± 0.1




Terminal Arrangement/
Internal Connections
(Bottom View)




Note: Be sure to confirm coil polarity.

Note: Orientation marks are indicated as follows:


Double-winding latching
G6EK-134P-US
G6EK-134PL-US
G6EK-134P-US-U



PCB Mounting Holes
(Bottom View)
Tolerance: ± 0.1



Terminal Arrangement/
Internal Connections
(Bottom View)



Note: Be sure to confirm coil polarity. The model G6EK-134P-1-US has positive (+) terminal #3 and negative (-) terminals #1 and #6.

Note: Orientation marks are indicated as follows:

■ Approved Standards

- The approval rating values for overseas standards are different from the performance values determined individually. Confirm the values before use.

UL recognized:  (File No. E41515)

CSA certified:  (File No. LR31928)

Model	Contact form	Coil ratings	Contact ratings	Number of test operations
G6E()-134P()US	SPDT (1c)	5 to 48 VDC	0.2 A, 250 VAC	6,000
			0.6 A, 125 VAC	
			2 A, 30 VDC	
			0.6 A, 125 VDC	

■ Precautions

- Please refer to "PCB Relays Common Precautions" for correct use.


Correct Use

● Long-term Continuously ON Contacts

- Using the Relay in a circuit where the Relay will be ON continuously for long periods (without switching) can lead to unstable contacts because the heat generated by the coil itself will affect the insulation, causing a film to develop on the contact surfaces. We recommend using a latching relay (magnetic-holding relay) in this kind of circuit. If a single-side stable model must be used in this kind of circuit, we recommend using a fail-safe circuit design that provides protection against contact failure or coil burnout.


● Mounting

- Do not reverse the polarity of the coil (+, -).
- Provide sufficient space between Relays when mounting two or more on the same PCB, as shown in the following diagram.



● Wiring

- Refer to the following diagram when wiring to switch a DC load. The difference in polarity applied to the contacts will affect the endurance of the Relay due to the amount of contact movement. To extend the endurance characteristics beyond the performance ratings, wire the common (pin 7) terminal to the positive (+) side.



● Relay Handling

- When washing the product after soldering the Relay to a PCB, use a water-based solvent or alcohol-based solvent, and keep the solvent temperature to less than 40°C. Do not put the Relay in a cold cleaning bath immediately after soldering.

● Ultrasonic Cleaning

- Do not use ultrasonic cleaning on standard relay models. Doing so may result in resonance, coil burnout, and contact adhesion within the Relay. Use a model designed for ultrasonic cleaning if ultrasonic cleaning is required.

- Application examples provided in this document are for reference only. In actual applications, confirm equipment functions and safety before using the product.
- Consult your OMRON representative before using the product under conditions which are not described in the manual or applying the product to nuclear control systems, railroad systems, aviation systems, vehicles, combustion systems, medical equipment, amusement machines, safety equipment, and other systems or equipment that may have a serious influence on lives and property if used improperly. Make sure that the ratings and performance characteristics of the product provide a margin of safety for the system or equipment, and be sure to provide the system or equipment with double safety mechanisms.

Note: Do not use this document to operate the Unit.

OMRON Corporation

Electronic and Mechanical Components Company

Contact: www.omron.com/ecb

Cat. No. K024-E1-11
0617(0207)(O)