

1

2

品赞电子（东莞）有限公司

4

5





A

B

G-Switch Technology (Dongguan) Co., Ltd

D

E






1

2

品赞电子（东莞）有限公司

4




5



G-Switch USB-C Specification:

- 1.Current rated: 5A on vbus/1.25A on vconn/0.25A on other
- 2.Withstanding voltage: 100V AC/minute
- 3.Contact resistance: 40mΩ Max
- 4.Insulation resistance: 100MΩ Min
- 5.Operating temperature: -40°C ~ +85°C
- 6.Mating force: 5N~20N
- 7.Unmating force: 8N~20N
- 8.Durability cycle:10,000 cycles
- 9.Data transmission rate up to 10Gbp/s min
- 10.Compliant with: IEC62680-1-3

USB IF TID:13209



A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND	TX1+	TX1-	VBUS	CC1	D+	D-	SBU1	VBUS	RX2-	RX2+	GND
First	Second	Second	First	Second	Second	Second	Second	First	Second	Second	First
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
GND	RX1+	RX1-	VBUS	SBU2	D-	D+	CC2	VBUS	TX2-	TX2+	GND
First	Second	Second	First	Second	Second	Second	Second	First	Second	Second	First

NO.	PARTS	MATERIAL	REMARKS
1	SHELL	STAINLESS STEEL304	Ni30u"MIN PLATED
2	GND PLATE	STAINLESS STEEL301	Ni30u"MIN PLATED
3	MID PLATE	STAINLESS STEEL301	--
4	HOUSING	HIGH TEMPERATURE PLASTIC	LCP BLACK UL 94V-0
5	TERMINALS	COPPER ALLOY C7025	Au1u"MIN PLATING ON CONTACT AREA G/F MIN PLATING ON CONTACT AREA

RECOMMENDED PCB LAYOUT
TOLERANCE:±0.05



RoHS
Compliant
EU RoHS Standards



SCALE: 1:1 UNIT: mm
SIZE: A4

Unless otherwise
General Tolerance:
X..x ±0.30
X..xx ±0.20
X..xxx ±0.10
X..x" ±3°
X..xx" ±2°

Title: Horizontal Type-c 24P Female SMT
Mid-Mount0.8 CH=0.78 L=7.9mm

Molde Code: GT-USB-9007A

DRAWN	CHECKED	APPROVED	DATE
Xia	Chen	Chen	2023.02.01



REV: A0 SHEET: 1/1

A

B

G-Switch Technology (Dongguan) Co., Ltd

D

E



中国认可
国际互认
检测
TESTING
CNAS L13628

EN/SASO IEC 62680-1-3 Test Report

25T04N000387-001-COM

For

Type-C Receptacle Connector

Company Name: G-Switch Technology (Dongguan) Co., Ltd.

Product Name: Horizontal Type-c 24P Female SMT Mid-Mount
0.8/1.0/1.6 L=7.9mm

Model Name: GT-USB-9007

Hardware Version: A0

Issued Date: 2025-04-14

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SAICT.

Test Laboratory:

SAICT, Shenzhen Academy of Information and Communications Technology
Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen,
Guangdong, P. R. China 518000.

Tel: +86(0)755-33322000, Fax: +86(0)755-33322001

Email: yewu@saict.ac.cn, www.saict.ac.cn



NO.25T04N000387-001-COM

REPORT HISTORY

Report Number	Revision	Description	Issue Date
25T04N000387-001-COM	V1	First release	2025-04-14

Note: the latest revision of the test report supersedes all previous versions.



CONTENTS

1. Test Laboratory	1
1.1. Testing Location	1
1.2. Testing Environment	1
1.3. Project Data	1
1.4. Signature	1
2. Client Information	1
2.1. Applicant Information	1
2.2. Manufacturer Information	1
3. Unit Under Test (UUT) Information	2
3.1. About UUT	2
3.2. Sample Coding	2
4. Reference Documents	3
5. USB Type-C Compliance Requirements	3
5.1. DC Electrical	3
5.2. Mechanical	4
5.3. Environmental	5
6. Test Procedure	6
7. Test Result Summary	9
8. Test Detail	10
8.1. Clause 3.2.1 (6) Construction	10
8.2. Clause 3.2.1 (8) Critical Dimensions	12
8.3. Clause 3.7.8.1 Low level contact resistance	13
8.4. Clause 3.7.8.2 Dielectric withstanding voltage	30
8.5. Clause 3.7.8.3 Insulation Resistance	31
8.6. Clause 3.7.8.4 Contact Current Rating	32
8.7. Clause 3.8.1.1 Insertion force	33
8.8. Clause 3.8.1.2 Extraction force	33
8.9. Clause 3.8.1.3 Durability	38
8.10. Clause 3.8.1.3 Reseating	40
8.11. Clause 3.8.1.6 4-Axis Continuity	40



8.12. Clause 3.8.2 Temperature life	45
8.13. Clause 3.8.2 Thermal shock	45
8.14. Clause 3.8.2 Cyclic temperature and humidity	46
8.15. Clause 3.8.2 Vibration	46
8.16. Clause 3.8.2 Mixed flowing gas	48
8.17. Clause 3.8.2 Thermal disturbance	48
9. Test Equipments Utilized	49
ANNEX A: UUT photograph	51
ANNEX B: Drawing	52
ANNEX C: Insertion Force & Extraction Force Test Layout	53
ANNEX D: Durability Test Layout	54
ANNEX E: Dielectric withstanding voltage Test Layout	55
ANNEX F: Vibration Test Layout	56
ANNEX G: Contact Current Rating Test Layout	57



1. Test Laboratory

1.1. Testing Location

Location: SAICT

Address: Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518000

1.2. Testing Environment

Normal Temperature: 15-35℃

Relative Humidity: 25-85%RH

Atmospheric pressure 86-106kPa

1.3. Project Data

Testing Start Date: 2025-03-07

Testing End Date: 2025-04-08

1.4. Signature

Su Kun

Prepared this test report

Wang Yang

Reviewed this test report

Wei Ming

Approved this test report

2. Client Information

2.1. Applicant Information

Company Name: G-Switch Technology (Dongguan) Co., Ltd.
Address: Room 701, Workshop 2, Optical Technology Innovation Center, Xinhong, Marina Bay New District, Dongguan City
City: Dongguan
Country: China
Email: feng@g-switch.cn
Telephone: 0769-82388879

2.2. Manufacturer Information

Company Name: G-Switch Technology (Dongguan) Co., Ltd.
Address: Room 701, Workshop 2, Optical Technology Innovation Center, Xinhong, Marina Bay New District, Dongguan City
City: Dongguan
Country: China
Email: feng@g-switch.cn
Telephone: 0769-82388879



3. Unit Under Test (UUT) Information

3.1. About UUT

Description:	USB 3.2 Type-C Receptacle Connector
Brand Name:	G-Switch Technology (Dongguan) Co., Ltd.
Marking Name:	Horizontal Type-c 24P Female SMT Mid-Mount 0.8/1.0/1.6 L=7.9mm
Material Code:	GT-USB-9007
Hardware Version:	A0

3.2. Sample Coding

Test Group	Number of Plug/Receptacle	Qty of Specimen
Group A-1	UT01aa to UT05aa	5 pcs
Group A-2	UT06aa to UT10aa	5 pcs
Group A-3	UT11aa to UT15aa	5 pcs
Group A-4	UT16aa to UT25aa	10 pcs
Group A-7	UT26aa to UT30aa	5 pcs
Group B-1	UT31aa to UT38aa	8 pcs
Group B-5	UT39aa to UT41aa	3 pcs
Group B-6	UT42aa to UT44aa	3 pcs

4. Reference Documents

1. EN IEC 62680-1-3:2022, Universal serial bus interfaces for data and power_Part 1-3Common components-USB Type-C(r) cable and connector specification
2. SASO IEC 62680-1-3:2023, Universal serial bus interfaces for data and power-Part 1-3: Universal Serial Bus interfaces-Common components- USB Type-CTM cable and connector specification


Note:The requirements of the standards SASO IEC 62680-1-3 is the same as EN IEC 62680-1-3.

5. USB Type-C Compliance Requirements

5.1. DC Electrical

Clause	Test Item	Test Procedure	Requirement
3.7.8.1	Low Level Contact Resistance (LLCR)	EIA 364-23 The low level contact resistance (LLCR) measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle. The test boards shall be provided with the connectors to be tested. • Measure at 20 mV (max) open, circuit at 100 mA.	The following requirements apply to the power and signal contacts: • 40 mΩ (max) initial for VBUS, GND and all other contacts. • 50 mΩ maximum after initial measurement.
3.7.8.2	Dielectric Withstanding Voltage	EIA 364-20 Applicable to both receptacle and plug. • Measurement per Method B.	The dielectric shall withstand 100 VAC (RMS) for one minute at sea level after the environmental stress defined in Table 4-8, Test Group A-7.
3.7.8.3	Insulation Resistance	EIA 364-21 Applicable to both receptacle and plug. See Table 4-8 Test Group A-7.	A minimum of 100 MΩ insulation resistance is required between adjacent contacts of unmated and mated connectors.
3.7.8.4	Contact Current Rating	A current of 5 A shall be applied collectively to VBUS pins (i.e., pins A4, A9, B4, and B9) and 1.25 A shall be applied to the VCONN pin (i.e., B5) as applicable, terminated through the corresponding GND pins (i.e., pins A1, A12, B1, and B12). A minimum current of 0.25 A shall also be applied individually to all the other contacts, as applicable.	The temperature rise of the outside shell surface of the mated pair above the VBUS and GND contacts shall not exceed 30°C above the ambient temperature.

5.2. Mechanical

Clause	Test Item	Test Procedure	Requirement																																								
3.2.1	Critical Dimensions	8.5 USB Type-C Receptacle  Table B-5 Receptacle Critical Dimensions for Receptacles Using SECTION A-A in Figure B-5 <table border="1"> <thead> <tr> <th>Description</th><th>Dimension</th><th>+ Tol.</th><th>- Tol.</th></tr> </thead> <tbody> <tr> <td>1. Receptacle inside opening</td><td>8.50</td><td>0.05</td><td>0.02</td></tr> <tr> <td>2. Receptacle inside opening position tolerance</td><td>0.04 with datum A/B/C</td><td>n/a</td><td>n/a</td></tr> <tr> <td>3. Receptacle signal pin length</td><td>3.50</td><td>0.15</td><td>0.15</td></tr> <tr> <td>4. Pin length datum</td><td>0.50</td><td>0.20</td><td>0.20</td></tr> <tr> <td>5. Tongue width</td><td>0.600</td><td>0.045</td><td>0.035</td></tr> <tr> <td>6. Contact width</td><td>0.25</td><td>0.04</td><td>0.04</td></tr> <tr> <td>7. Contact width position tolerance</td><td>0.08 with datum A/B/C</td><td>n/a</td><td>n/a</td></tr> <tr> <td>8. Tongue thickness</td><td>0.70</td><td>0.05</td><td>0.05</td></tr> <tr> <td>9. Receptacle inside thickness</td><td>2.50</td><td>0.05</td><td>0.05</td></tr> </tbody> </table> Notes: 1. All values are in millimeters.	Description	Dimension	+ Tol.	- Tol.	1. Receptacle inside opening	8.50	0.05	0.02	2. Receptacle inside opening position tolerance	0.04 with datum A/B/C	n/a	n/a	3. Receptacle signal pin length	3.50	0.15	0.15	4. Pin length datum	0.50	0.20	0.20	5. Tongue width	0.600	0.045	0.035	6. Contact width	0.25	0.04	0.04	7. Contact width position tolerance	0.08 with datum A/B/C	n/a	n/a	8. Tongue thickness	0.70	0.05	0.05	9. Receptacle inside thickness	2.50	0.05	0.05	
Description	Dimension	+ Tol.	- Tol.																																								
1. Receptacle inside opening	8.50	0.05	0.02																																								
2. Receptacle inside opening position tolerance	0.04 with datum A/B/C	n/a	n/a																																								
3. Receptacle signal pin length	3.50	0.15	0.15																																								
4. Pin length datum	0.50	0.20	0.20																																								
5. Tongue width	0.600	0.045	0.035																																								
6. Contact width	0.25	0.04	0.04																																								
7. Contact width position tolerance	0.08 with datum A/B/C	n/a	n/a																																								
8. Tongue thickness	0.70	0.05	0.05																																								
9. Receptacle inside thickness	2.50	0.05	0.05																																								
3.8.1.1	Insertion force	EIA 364-13 The insertion force test shall be done at a maximum speed of 12.5 mm (0.492") per minute.	Within the range from 5 N to 20 N. This requirement does not apply to the plugs that are used for direct docking without a cable.																																								
3.8.1.2	Extraction force	EIA 364-13 The extraction force test shall be done at a maximum speed of 12.5 mm (0.492") per minute.	Within the range of 8 N to 20 N, measured after a preconditioning of five insertion/extraction cycles (i.e., the sixth extraction). After an additional twenty-five insertion/extraction cycles, the extraction force shall be measured again (i.e., the 32nd extraction) and the extraction force shall be within: a) 33 % of the initial reading, and b) within the range of 8 N to 20 N. The extraction force shall be within the range of 6 N to 20 N after 10,000 insertion/extraction cycles. This requirement does not apply to the plugs that are used for direct docking without a cable.																																								
3.8.1.3	Durability	EIA 364-09	10,000 cycles minimum. Low level contact resistance and dielectric withstanding voltage shall be checked to be within spec after the 10,000 durability cycles according to Table 4-8, Test Group A-7.																																								
3.8.1.6	4-Axis Continuity	See Appendix D for detailed test fixtures and procedures. Plug and Receptacle: Subject the mating interface to the moments defined in appendix D for at least 10 seconds.	No discontinuities greater than 1 microsecond duration in any of the four orientations tested.																																								

5.3. Environmental

Clause	Test Item	Test Procedure	Requirement
3.8.2	Temperature life	EIA 364-17, Method A. 105° C without applied voltage for 120 hours. 105° C without applied voltage for 72 hours when used as preconditioning.	Low level contact resistance meets spec before and after the Temperature Life test.
3.8.2	Vibration	EIA 364-28 Test Condition VII, Test Letter D	No evidence of physical damages and no discontinuity longer than 1 microsecond. Low level contact resistance meets spec before and after the Vibration test.
3.8.2	Cyclic temperature and humidity	EIA 364-31	Low level contact resistance meets spec before and after the Cyclic Temperature and Humidity test.
3.8.2	Thermal shock	EIA 364-32, Test Condition I 10 Cycles –55°C and +85°C.	No evidence of any physical damage. Low level contact resistance meets spec before and after the Thermal Shock test.
3.8.2	Mixed flowing gas	EIA 364-65, Class II A Samples should be placed in an environmentally controlled 'test chamber' that is monitored by a gas analyzing system for controlled concentrations of the specified gas mixture. Test coupons shall also be used and the weight gain reported. Test duration is 7 days.	Low level contact resistance meets spec before and after the Mixed Flowing Gas test.
3.8.2	Thermal disturbance	Cycle the connector or socket between 15 °C ±3 °C and 85 °C ± 3 °C, as measured on the part. Ramps should be a minimum of 2 °C per minute, and dwell times should insure that the contacts reach the temperature extremes (a minimum of 5 minutes). Humidity is not controlled. Perform 10 such cycles.	Low level contact resistance meets spec before and after the Thermal disturbance test.

6. Test Procedure

For the DC electrical, Mechanical and Environmental compliance requirements of Type-C connector, refer to the grouping and test methods in the EIA364.1000.01 standard to implement the test.

Group A-1	
No.	Test Item
A-1-1	Low level contact resistance
A-1-2	Durability (preconditioning)
A-1-3	Temperature life
A-1-4	Low level contact resistance
A-1-5	Re-seating
A-1-6	Low level contact resistance
Group A-2	
No.	Test Item
A-2-1	Low level contact resistance
A-2-2	Durability (preconditioning)
A-2-3	Thermal shock
A-2-4	Low level contact resistance
A-2-5	Cyclic temperature and humidity
A-2-6	Low level contact resistance
A-2-7	Re-seating
A-2-8	Low level contact resistance
Group A-3	
No.	Test Item
A-3-1	Low level contact resistance

A-3-2	Durability (preconditioning)
A-3-3	Temperature life (preconditioning)
A-3-4	Low level contact resistance
A-3-5	Vibration
A-3-6	Low level contact resistance
Group A-4	
No.	Test Item
A-4-1	Low level contact resistance
A-4-2	Durability (preconditioning)
A-4-3	Temperature life (preconditioning)
A-4-4	Low level contact resistance
A-4-5	Mixed flowing gas
A-4-6	Low level contact resistance
A-4-7	Thermal disturbance
A-4-8	Low level contact resistance
A-4-9	Re-seating
A-4-10	Low level contact resistance
Group A-7	
No.	Test Item
A-7-1	Dielectric withstanding voltage
A-7-2	Low level contact resistance
A-7-3	Durability (preconditioning)
A-7-4	Insertion force
A-7-5	Extraction force

A-7-6	Durability
A-7-7	Extraction force
A-7-8	Durability
A-7-9	Extraction force
A-7-10	Low level contact resistance
A-7-11	Dielectric withstanding voltage
A-7-12	Insulation Resistance
Group B-1	
No.	Test Item
B-1-4	4-Axis Continuity
Group B-5	
No.	Test Item
B-5-1	Critical Dimensions
Group B-6	
No.	Test Item
B-6-1	Contact Current Rating

7. Test Result Summary

Test Item	Clause	Result
Construction	3.2.1 (6)	Pass
Critical Dimensions	3.2.1 (8)	Pass
Low level contact resistance	3.7.8.1	Pass
Dielectric withstanding voltage	3.7.8.2	Pass
Insulation Resistance	3.7.8.3	Pass
Contact Current Rating	3.7.8.4	Pass
Insertion force	3.8.1.1	Pass
Extraction force	3.8.1.2	Pass
Durability	3.8.1.3	Pass
Reseating	3.8.1.3	Pass
4-Axis Continuity	3.8.1.6	Pass
Temperature life	3.8.2	Pass
Thermal shock	3.8.2	Pass
Cyclic temperature and humidity	3.8.2	Pass
Vibration	3.8.2	Pass
Mixed flowing gas	3.8.2	Pass
Thermal disturbance	3.8.2	Pass

8. Test Detail


8.1. Clause 3.2.1 (6) Construction

Construction				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/07	Temperature(°C)	22.0	Huang Siwei	Pass
	Humidity (RH)	52.7 %		

EMC ground return path			
Description	Sample Coding		
	UT39aa	UT40aa	UT41aa
1.EMC spring	N	N	N
2.EMC pad	Y	Y	Y
3.Solid bumps	N	N	N
4.Distance between the bumps	N/A	N/A	N/A
Result	Pass	Pass	Pass
Note: Receptacle configurations with a conductive shell. The requirements apply to the receptacle contact dimensions shown in ALTERNATE SECTION A-A Figure B-5. Receptacle configuration with respect to mounting surface: Right angle			

Number of pins: 24

<u>A1</u>	<u>A2</u>	<u>A3</u>	<u>A4</u>	<u>A5</u>	<u>A6</u>	<u>A7</u>	<u>A8</u>	<u>A9</u>	<u>A10</u>	<u>A11</u>	<u>A12</u>
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
<u>B12</u>	<u>B11</u>	<u>B10</u>	<u>B9</u>	<u>B8</u>	<u>B7</u>	<u>B6</u>	<u>B5</u>	<u>B4</u>	<u>B3</u>	<u>B2</u>	<u>B1</u>
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

EMC Springs/bumps/EMC Pad photograph

8.2. Clause 3.2.1 (8) Critical Dimensions

B-5-1 Critical Dimensions				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/07	Temperature(°C)	22.0	Huang Siwei	Pass
	Humidity (RH)	52.7 %		

Test data: (Unit:mm)			
B-5-1 Critical Dimensions – Receptacle			
Description	Sample Coding		
	UT39aa	UT40aa	UT41aa
1.Receptacle inside opening (8.32~8.40)	8.3554	8.3493	8.3478
2.Receptacle insider opening position tolerance (0.04 with datum A/B/C)	0.0313	0.0342	0.0027
3.Receptacle signal pin length (3.35~3.65)	3.4120	3.3935	3.4346
4.Pin length delta (0.30~0.70)	0.5284	0.5267	0.5593
5.Tongue width (6.635~6.735)	6.6372	6.6362	6.6407
6.Contact width (0.21~0.29)	0.2389	0.2372	0.2325
7.Contact width position tolerance (0.08 with datum A/B/C)	0.0282	0.0273	0.0329
8.Tongue thickness (0.65~0.75)	0.7427	0.7345	0.7367
9.Receptacle inside thickness (2.52~2.60)	2.5886	2.5856	2.5938
Decision result	Pass	Pass	Pass

8.3. Clause 3.7.8.1 Low level contact resistance

A-1-1 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/24	Temperature(℃)	22.6	Huang Siwei	Pass
	Humidity (RH)	56.2 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤40 mΩ（Initial）			

A-1-1 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT01aa	14.8	15.9	16.1	15.2	15.9	15.1	15.4	15.8	14.1	15.0	15.9	14.5
UT02aa	16.5	15.9	15.6	15.0	14.7	16.5	13.9	17.5	13.5	15.1	14.5	13.2
UT03aa	13.9	15.0	16.8	15.3	16.2	15.8	15.9	16.3	12.9	14.7	15.5	13.4
UT04aa	14.2	15.3	15.4	14.4	14.7	14.5	15.3	14.6	13.3	14.3	15.0	13.4
UT05aa	14.6	15.8	16.1	15.0	15.8	15.5	14.3	15.7	13.6	14.5	15.6	13.9
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT01aa	15.5	15.8	16.2	14.8	14.8	15.3	14.7	15.1	14.7	15.2	15.2	13.8
UT02aa	14.6	15.9	15.2	14.3	13.8	13.7	13.7	13.7	13.5	14.7	14.7	13.3
UT03aa	14.1	15.5	14.7	14.2	14.3	13.2	13.6	13.9	13.4	14.7	14.4	13.3
UT04aa	14.6	15.8	15.1	14.0	13.8	13.8	14.0	13.7	13.6	14.4	14.7	13.2
UT05aa	15.0	15.3	14.9	14.0	13.7	13.5	13.2	13.9	13.6	14.4	14.5	13.2

A-1-4 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/31	Temperature(℃)	22.6	Huang Siwei	Pass
	Humidity (RH)	56.1 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤50 mΩ			

A-1-4 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT01aa	14.8	15.8	16.0	15.2	15.3	15.1	15.1	15.4	13.7	14.9	15.6	14.2
UT02aa	15.7	18.5	16.9	15.7	16.6	21.5	14.9	19.3	13.5	15.3	15.2	13.9
UT03aa	14.3	16.0	16.9	15.1	17.4	15.6	15.1	15.9	13.4	15.5	17.5	14.2
UT04aa	14.3	15.4	15.7	15.4	16.8	15.6	16.2	15.8	13.5	15.1	15.6	14.2
UT05aa	14.4	15.7	16.4	15.6	18.5	16.4	15.9	19.1	14.3	15.2	18.6	14.6
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT01aa	15.7	16.2	16.2	15.0	15.3	15.0	15.9	15.2	14.5	15.8	15.2	13.9
UT02aa	15.2	16.1	15.9	14.5	15.2	14.8	14.7	15.6	14.1	15.3	15.0	13.6
UT03aa	14.9	16.6	16.0	15.0	17.0	14.4	14.4	16.6	14.6	15.6	15.0	15.5
UT04aa	15.2	16.3	15.8	14.8	15.1	14.9	15.2	15.3	14.4	15.2	15.1	13.6
UT05aa	18.4	17.1	15.9	14.9	15.1	14.6	14.4	15.3	14.5	15.4	14.9	13.8

A-1-6 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/31	Temperature(℃)	22.6	Huang Siwei	Pass
	Humidity (RH)	56.1 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤50 mΩ			

A-1-6 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT01aa	14.7	17.0	16.3	15.5	16.1	16.4	15.7	15.1	13.9	14.4	15.4	13.8
UT02aa	14.3	16.5	16.7	15.2	17.8	16.7	15.8	15.7	14.3	15.7	15.9	13.5
UT03aa	14.6	16.9	16.4	15.2	17.0	16.0	16.6	15.9	13.2	14.9	16.1	14.1
UT04aa	14.5	16.6	16.9	15.1	17.3	16.4	16.7	15.6	14.5	15.8	16.2	14.8
UT05aa	14.9	15.8	16.9	15.5	18.0	15.2	15.0	16.2	14.4	14.9	16.2	13.9
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT01aa	15.9	17.0	16.4	15.6	15.9	15.0	15.6	16.3	14.7	15.3	15.4	13.3
UT02aa	14.9	17.1	16.7	15.7	16.5	14.2	14.5	15.5	14.5	16.0	15.3	14.5
UT03aa	14.4	16.5	15.2	14.1	16.1	14.1	14.5	16.8	14.7	15.4	16.0	14.7
UT04aa	14.9	17.3	15.4	14.7	16.9	14.2	15.1	15.6	15.0	15.9	15.2	14.5
UT05aa	15.6	16.1	15.7	15.2	16.3	14.3	14.8	15.4	14.6	15.5	15.9	13.8



A-2-1 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/24	Temperature(℃)	22.9	Huang Siwei	Pass
	Humidity (RH)	56.5 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤40 mΩ （Initial）			

A-2-1 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT06aa	14.3	15.8	16.0	15.4	14.9	15.7	15.2	15.1	13.0	14.3	13.8	12.9
UT07aa	14.9	15.6	16.0	15.1	14.7	14.9	14.7	14.8	13.6	14.4	14.1	12.9
UT08aa	14.9	16.0	15.7	14.4	14.8	14.7	16.0	14.6	12.8	13.6	14.3	13.0
UT09aa	14.8	15.6	15.2	14.2	13.8	14.2	14.0	14.3	14.8	15.4	15.6	14.0
UT10aa	15.2	15.9	16.7	14.8	14.8	14.4	14.4	15.0	13.9	14.5	15.2	13.8
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT06aa	15.2	16.2	15.5	14.9	13.2	12.8	13.0	13.1	13.1	14.1	13.9	13.6
UT07aa	15.2	16.3	15.6	14.9	13.2	13.3	13.2	13.4	12.9	14.1	14.3	13.4
UT08aa	14.8	15.9	15.4	14.3	12.9	12.9	13.4	13.1	12.7	13.9	13.9	13.0
UT09aa	13.8	15.6	15.0	14.4	13.9	14.4	14.6	13.8	14.3	15.0	14.8	14.2
UT10aa	13.9	15.7	15.2	14.3	14.5	14.1	14.2	14.1	14.6	15.0	14.8	13.4

A-2-4 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/25	Temperature(℃)	22.1	Huang Siwei	Pass
	Humidity (RH)	56.4 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤50 mΩ			

A-2-4 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT06aa	14.3	16.1	16.0	15.9	15.4	15.7	16.3	16.1	13.2	14.0	14.7	13.5
UT07aa	15.4	15.8	15.9	16.5	15.8	15.6	15.1	15.3	13.5	14.3	14.2	14.0
UT08aa	14.8	15.6	15.8	15.4	14.9	14.9	36.1	15.4	13.0	13.9	14.9	13.6
UT09aa	14.8	15.8	16.6	15.4	15.5	14.9	15.5	16.2	14.0	14.9	15.1	14.5
UT10aa	14.7	15.7	16.5	15.3	15.3	14.9	15.4	16.0	13.9	14.9	15.0	14.4
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT06aa	15.3	16.6	15.7	15.0	13.8	14.0	13.7	14.3	13.3	14.4	14.4	13.9
UT07aa	14.9	16.4	15.7	14.7	14.0	14.1	13.8	13.6	13.1	14.2	13.9	13.3
UT08aa	15.1	16.5	15.9	14.6	13.8	14.1	14.5	13.6	13.3	14.6	13.7	13.1
UT09aa	14.8	16.8	16.8	15.3	16.0	15.0	15.6	15.8	15.6	15.7	15.7	14.1
UT10aa	14.7	16.7	16.7	15.3	15.8	14.9	15.4	15.7	15.5	15.6	15.6	14.1



A-2-6 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/28	Temperature(℃)	22.1	Huang Siwei	Pass
	Humidity (RH)	56.0 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤50 mΩ			

A-2-6 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT06aa	14.5	16.0	15.7	18.9	16.1	16.0	15.5	15.7	13.2	13.9	15.5	13.8
UT07aa	15.0	16.0	16.1	15.8	15.7	15.5	14.8	15.4	13.3	14.5	14.6	13.3
UT08aa	15.1	16.8	16.9	15.2	17.1	16.3	20.7	15.6	12.9	14.1	15.7	14.1
UT09aa	14.2	15.1	15.0	14.1	14.0	14.8	14.3	14.7	13.4	14.1	14.2	13.4
UT10aa	14.3	15.6	15.6	15.1	14.9	14.5	15.1	15.0	13.5	14.8	15.3	14.1
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT06aa	15.1	16.4	15.8	14.6	16.1	13.9	13.8	15.0	13.7	14.6	14.3	13.6
UT07aa	15.0	17.0	15.9	14.7	15.4	13.6	13.9	14.3	13.2	14.6	14.0	13.4
UT08aa	16.6	17.2	16.1	14.6	14.0	14.2	14.8	13.9	13.2	14.6	14.0	13.7
UT09aa	13.9	15.6	15.1	14.2	14.2	14.4	14.8	14.2	14.2	15.2	14.5	13.3
UT10aa	14.4	16.2	15.8	14.5	15.0	14.5	15.2	15.1	14.9	15.0	15.5	13.8

A-2-8 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/28	Temperature(℃)	22.1	Huang Siwei	Pass
	Humidity (RH)	56.0 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤50 mΩ			

A-2-8 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT06aa	14.3	15.5	15.5	14.4	15.7	16.7	14.0	15.2	13.0	14.8	14.4	14.3
UT07aa	15.5	15.7	15.1	14.9	16.8	16.0	15.1	15.3	13.3	13.6	14.4	13.7
UT08aa	14.3	16.2	15.5	14.8	15.3	15.2	15.6	15.7	13.5	13.3	15.5	13.1
UT09aa	15.3	16.8	15.9	15.1	15.6	16.1	14.1	14.4	13.5	13.9	14.3	13.5
UT10aa	15.7	16.1	15.7	14.1	16.8	14.5	15.1	15.9	13.7	13.5	15.4	14.9
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT06aa	14.8	16.3	15.1	14.8	15.3	14.5	14.1	16.4	14.2	15.6	14.7	14.0
UT07aa	14.6	16.6	15.3	14.6	14.6	14.9	15.9	16.1	14.8	14.5	15.8	13.7
UT08aa	15.1	16.4	16.0	14.4	14.2	14.7	15.4	15.6	13.0	15.8	14.5	14.0
UT09aa	15.1	15.2	16.6	14.4	14.3	14.7	15.3	16.0	14.2	14.3	15.0	13.2
UT10aa	15.2	15.7	16.7	14.7	15.7	14.9	15.2	15.8	13.5	15.6	14.2	13.9

A-3-1 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/19	Temperature(℃)	22.7	Su Kun	Pass
	Humidity (RH)	36.8 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤40 mΩ （Initial）			

A-3-1 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT11aa	14.5	15.4	15.5	14.3	14.1	14.4	14.0	14.6	13.4	14.5	15.0	13.3
UT12aa	14.3	15.6	16.4	14.5	14.3	15.8	13.8	14.8	13.4	14.4	14.5	13.2
UT13aa	15.1	15.8	16.0	15.9	14.9	14.6	14.7	15.8	13.5	14.2	14.7	13.3
UT14aa	14.2	15.6	16.2	15.4	15.5	15.0	14.7	17.1	12.9	14.2	14.5	13.6
UT15aa	14.4	15.3	15.5	15.1	14.8	14.7	15.5	14.9	13.0	13.8	13.8	13.2
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT11aa	13.8	15.3	15.1	14.1	14.0	13.6	14.1	14.2	13.8	14.8	14.7	13.6
UT12aa	14.7	15.6	15.2	14.3	13.4	14.1	14.1	13.9	14.0	14.6	14.5	13.5
UT13aa	14.6	15.7	15.5	14.7	14.8	14.0	14.1	14.0	13.6	14.6	14.5	13.3
UT14aa	16.6	17.8	16.0	15.1	13.7	13.3	13.3	14.1	13.2	14.6	14.2	13.5
UT15aa	15.1	16.2	15.9	14.8	13.8	13.9	14.1	13.9	13.6	14.5	13.7	13.4

A-3-4 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/25	Temperature(℃)	23.4	Su Kun	Pass
	Humidity (RH)	53.6 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤50 mΩ			

A-3-4 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT11aa	15.4	15.6	15.9	15.4	14.8	15.3	16.2	16.6	14.1	15.3	16.5	14.6
UT12aa	14.6	15.6	16.0	15.0	14.9	16.8	16.4	15.5	14.2	15.3	14.7	13.4
UT13aa	14.7	16.4	16.5	16.4	17.7	16.6	18.8	16.7	15.1	14.9	15.8	14.9
UT14aa	13.9	16.1	16.9	17.7	18.2	17.6	16.0	16.5	13.6	14.5	14.6	14.2
UT15aa	14.8	16.0	16.1	15.2	16.0	16.5	16.2	16.2	13.7	14.8	15.0	13.8
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT11aa	15.3	16.0	15.6	14.6	16.6	15.5	15.1	15.9	15.5	15.8	15.2	13.8
UT12aa	15.1	15.8	15.8	14.2	14.9	15.6	14.1	14.8	14.4	15.1	14.8	13.5
UT13aa	15.3	16.6	16.4	15.3	15.4	16.7	15.8	16.1	16.4	15.3	15.9	14.0
UT14aa	18.6	17.3	16.0	14.6	14.1	15.3	14.4	16.0	13.9	15.4	14.1	13.6
UT15aa	16.4	16.8	16.6	14.8	14.9	14.9	15.4	16.2	14.2	15.2	13.7	13.4

A-3-6 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/25	Temperature(℃)	23.8	Su Kun	Pass
	Humidity (RH)	47.3 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤50 mΩ			

A-3-6 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT11aa	14.4	15.3	15.7	15.6	15.2	15.3	15.1	15.6	13.3	14.6	15.9	14.0
UT12aa	14.6	15.8	15.7	14.9	15.1	16.6	15.6	15.4	13.6	14.6	15.2	13.7
UT13aa	14.3	15.2	15.2	14.6	14.7	15.5	16.8	15.4	13.2	14.0	14.2	13.0
UT14aa	14.0	15.5	16.3	14.4	14.7	14.5	15.1	15.9	12.4	13.7	13.9	13.1
UT15aa	14.9	15.8	15.1	14.4	15.5	14.8	15.4	14.9	13.3	13.7	13.8	13.0
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT11aa	15.0	16.1	15.6	14.5	16.0	15.1	15.1	16.2	15.0	15.6	15.2	13.6
UT12aa	14.9	16.0	15.8	14.2	14.5	14.4	15.8	15.3	14.9	15.1	15.1	13.7
UT13aa	14.7	15.7	15.5	14.4	13.8	15.4	15.9	15.5	14.9	14.2	14.5	13.7
UT14aa	14.6	15.3	15.4	14.4	13.5	14.5	13.7	13.7	13.2	14.1	13.5	13.2
UT15aa	14.5	15.7	15.3	14.0	15.3	14.1	15.4	13.8	13.0	13.7	13.5	12.9

A-4-1 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/26	Temperature(℃)	23.3	Huang Siwei	Pass
	Humidity (RH)	55.2 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤40 mΩ（Initial）			

A-4-1 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT16aa	14.9	15.5	15.8	19.4	14.3	14.7	15.4	15.0	13.6	14.0	13.9	13.1
UT17aa	14.7	15.8	16.1	14.9	14.3	15.3	15.1	14.8	13.1	13.6	14.3	13.9
UT18aa	14.8	16.2	17.0	15.2	16.4	15.2	16.1	15.7	13.0	14.2	14.2	13.5
UT19aa	14.4	15.4	15.6	14.3	14.4	14.6	15.1	14.4	12.8	13.7	14.4	13.1
UT20aa	14.8	16.6	16.7	15.2	16.9	16.7	15.9	15.1	13.1	14.1	14.3	13.4
UT21aa	16.6	18.3	16.4	15.3	20.6	15.8	14.6	17.2	20.9	17.9	15.8	20.9
UT22aa	14.8	15.8	17.8	16.8	15.2	17.8	14.6	18.2	12.9	13.9	14.3	13.8
UT23aa	14.6	16.2	16.4	14.7	14.8	14.6	14.9	15.8	15.0	15.1	15.8	14.9
UT24aa	15.5	17.3	18.1	16.0	16.6	15.8	15.5	16.6	13.4	15.1	15.6	15.3
UT25aa	14.3	16.1	15.9	14.8	15.1	14.6	14.8	14.7	14.0	15.2	16.1	14.8
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT16aa	14.7	16.3	15.7	14.8	13.3	13.2	13.2	13.5	13.0	14.2	14.1	13.3
UT17aa	16.0	17.2	17.0	14.8	14.1	14.4	13.8	14.2	13.9	15.0	16.3	15.4
UT18aa	15.5	18.1	17.2	15.0	13.7	13.3	14.2	15.3	13.2	14.7	14.2	13.5
UT19aa	14.9	15.4	15.2	14.1	13.5	12.9	13.6	13.2	12.8	14.5	14.0	13.4
UT20aa	16.1	16.5	15.9	15.3	13.2	13.4	13.4	13.2	13.8	14.6	14.8	14.0
UT21aa	14.6	17.1	17.3	15.7	14.5	13.4	15.2	15.0	15.6	15.8	16.1	14.1
UT22aa	16.8	17.4	16.5	15.5	14.3	13.2	13.4	13.8	13.8	15.0	14.7	13.6
UT23aa	15.3	16.9	15.3	15.0	15.6	16.4	15.4	16.2	15.2	16.0	15.3	13.6
UT24aa	15.2	17.3	15.8	14.8	15.2	14.8	14.3	15.3	14.4	14.9	15.0	14.1
UT25aa	14.6	15.3	16.1	14.7	16.0	13.9	14.2	14.7	13.7	15.0	14.8	13.4

A-4-4 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/29	Temperature(℃)	22.7	Huang Siwei	Pass
	Humidity (RH)	56.7 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤50 mΩ			

A-4-4 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT16aa	14.5	15.4	15.8	23.1	14.8	15.2	25.6	15.3	12.6	14.1	14.1	13.4
UT17aa	15.1	16.2	16.4	14.4	14.4	15.0	15.6	15.4	13.6	14.9	15.3	14.2
UT18aa	14.5	15.7	15.7	14.9	16.1	15.2	15.2	16.4	12.6	13.8	14.1	13.2
UT19aa	14.4	16.4	16.9	15.8	16.0	16.0	16.3	15.0	14.0	13.8	15.2	14.2
UT20aa	14.7	16.4	18.4	15.6	15.2	16.3	15.4	14.4	12.9	14.1	14.6	13.8
UT21aa	14.6	15.6	15.7	15.2	20.6	16.6	15.3	19.5	13.8	14.6	15.1	13.9
UT22aa	14.1	15.2	15.6	14.4	15.8	14.8	14.0	15.5	12.7	13.7	13.8	13.4
UT23aa	14.2	15.0	15.3	14.1	15.1	14.6	14.9	15.0	13.4	14.7	14.6	13.7
UT24aa	14.6	16.2	17.1	15.5	16.2	15.3	15.3	15.3	13.9	15.0	15.7	14.6
UT25aa	14.0	15.5	15.6	14.6	14.8	14.6	14.6	14.9	13.5	14.6	23.8	14.9
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT16aa	14.8	16.2	16.7	14.5	18.9	13.7	13.8	13.4	13.3	14.0	14.1	13.4
UT17aa	16.2	17.0	17.3	14.4	16.0	15.3	15.2	15.9	13.9	14.7	14.9	13.6
UT18aa	15.4	19.1	16.5	14.6	13.8	13.3	13.8	20.3	13.0	14.7	13.7	13.1
UT19aa	14.9	15.7	15.6	13.9	15.0	13.9	14.1	13.9	13.3	16.2	14.2	13.4
UT20aa	15.3	15.8	15.6	14.8	13.5	13.6	13.2	13.8	13.1	14.2	13.6	13.3
UT21aa	14.8	17.0	17.1	16.7	14.7	13.6	14.0	14.2	13.5	14.7	14.8	13.4
UT22aa	14.9	16.4	15.6	14.1	13.9	13.2	13.2	13.8	12.8	14.8	13.7	12.9
UT23aa	14.8	15.7	15.3	14.1	14.3	14.9	14.2	14.8	14.3	15.2	14.8	13.4
UT24aa	15.3	16.9	16.2	15.0	15.3	14.7	14.3	16.4	14.4	15.1	14.8	14.2
UT25aa	14.8	15.6	15.6	14.7	15.7	14.3	15.3	15.1	14.1	14.8	15.0	13.6

A-4-6 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/04/07	Temperature(℃)	22.2	Huang Siwei	Pass
	Humidity (RH)	55.4 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤50 mΩ			

A-4-6 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT16aa	14.2	15.8	16.9	15.6	17.5	15.0	16.8	15.5	14.3	14.2	15.7	14.8
UT17aa	14.5	16.1	16.7	15.5	16.2	16.2	15.1	15.8	13.3	14.4	15.3	14.7
UT18aa	14.7	16.4	16.7	15.1	17.6	16.6	15.6	16.6	14.9	15.1	15.4	13.6
UT19aa	14.2	15.4	16.5	15.2	16.4	16.4	16.5	16.6	13.5	15.7	15.0	13.6
UT20aa	14.3	16.0	16.7	15.7	16.9	16.0	17.0	15.1	14.4	15.8	15.3	13.6
UT21aa	14.2	15.2	16.0	15.9	16.1	16.6	15.3	16.9	13.7	15.4	15.4	14.6
UT22aa	14.6	16.7	16.1	15.4	16.7	15.1	16.2	16.5	13.8	15.0	15.8	14.8
UT23aa	14.3	16.6	16.7	15.2	16.1	15.1	15.5	15.5	14.6	14.8	16.9	13.9
UT24aa	14.6	16.4	16.9	15.6	17.6	16.4	16.6	15.3	14.3	14.0	16.3	14.4
UT25aa	14.4	16.5	16.4	15.9	17.6	16.8	15.9	15.3	13.3	15.4	16.1	13.2
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT16aa	15.5	16.4	15.4	15.9	16.6	14.2	14.2	15.7	14.5	15.6	15.4	14.6
UT17aa	15.6	17.2	15.5	15.7	15.1	14.4	14.5	15.3	14.5	15.5	15.9	14.2
UT18aa	15.2	17.0	15.6	14.3	16.4	14.0	15.2	16.2	14.4	15.3	15.0	13.1
UT19aa	15.2	17.0	15.5	15.8	16.4	14.8	14.3	16.9	14.4	15.9	15.4	14.8
UT20aa	15.5	16.2	16.5	15.7	15.1	14.6	15.7	16.4	14.5	15.3	15.5	14.2
UT21aa	14.5	16.5	16.9	15.1	16.8	14.2	14.2	15.4	14.1	15.7	15.7	13.1
UT22aa	14.2	16.2	15.9	15.7	15.1	14.3	15.4	15.3	14.1	15.7	15.2	13.3
UT23aa	15.1	16.8	16.7	14.9	16.2	14.6	14.6	16.1	14.0	15.9	15.6	15.0
UT24aa	15.3	16.3	15.3	14.4	16.1	14.7	15.7	15.5	14.6	15.4	15.1	15.0
UT25aa	15.4	17.2	17.0	14.1	16.7	14.1	14.7	15.9	14.2	15.6	15.4	14.3

A-4-8 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/04/08	Temperature(℃)	22.8	Huang Siwei	Pass
	Humidity (RH)	55.7 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤50 mΩ			

A-4-8 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT16aa	14.9	16.8	16.7	15.1	16.1	16.6	16.1	15.5	13.4	14.8	16.5	14.8
UT17aa	14.8	15.9	16.2	15.4	17.7	15.1	16.2	16.4	13.3	15.2	16.7	14.7
UT18aa	14.2	16.1	16.0	15.8	16.1	16.6	15.7	16.4	13.1	15.4	16.6	13.8
UT19aa	14.6	16.6	16.7	15.7	17.0	16.3	16.5	16.5	14.7	15.9	16.0	13.3
UT20aa	14.6	15.1	16.3	15.5	17.7	15.5	15.1	16.9	14.3	15.5	16.3	13.7
UT21aa	14.9	16.7	16.7	15.0	16.8	16.0	16.9	16.4	14.6	15.7	15.1	14.0
UT22aa	14.1	16.1	16.4	15.4	16.2	15.6	15.4	16.7	13.3	14.4	16.2	14.8
UT23aa	14.4	15.3	16.1	15.2	17.7	16.4	16.7	15.9	13.0	15.5	16.5	14.6
UT24aa	14.4	15.9	16.6	15.8	17.4	16.1	15.2	16.4	13.3	14.2	15.7	14.3
UT25aa	14.0	15.6	16.5	15.8	17.1	16.1	16.2	16.0	13.9	15.4	16.1	14.5
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT16aa	15.8	17.3	16.7	14.8	16.5	14.2	14.7	15.3	14.5	15.1	15.6	13.2
UT17aa	14.4	16.7	15.6	15.5	16.2	14.9	14.3	15.4	14.5	15.2	15.9	14.7
UT18aa	15.6	16.4	15.8	14.8	15.4	14.9	15.7	16.2	14.0	15.5	15.8	14.9
UT19aa	15.1	17.4	16.4	14.1	16.6	14.9	15.7	16.0	14.1	15.9	15.1	13.7
UT20aa	14.3	16.6	15.8	15.8	15.3	14.9	15.3	16.9	14.3	15.6	15.0	13.1
UT21aa	15.1	16.7	15.8	14.3	15.4	14.5	14.7	16.4	14.2	15.3	15.4	14.0
UT22aa	14.5	16.9	16.1	14.4	16.8	14.9	15.0	15.6	14.2	15.4	15.1	14.9
UT23aa	15.5	16.3	15.9	14.2	16.1	14.6	15.5	15.8	14.8	15.5	15.4	13.8
UT24aa	14.4	16.4	15.8	14.5	16.6	14.8	16.0	15.8	14.7	15.1	15.9	13.8
UT25aa	15.1	16.9	16.6	15.6	16.4	14.9	15.7	15.3	14.4	15.5	15.4	13.7

A-4-10 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/04/08	Temperature(℃)	22.8	Huang Siwei	Pass
	Humidity (RH)	55.7 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤50 mΩ			

A-4-10 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT16aa	14.4	17.0	16.1	15.7	16.3	16.4	16.1	16.0	14.3	15.7	15.7	14.9
UT17aa	14.5	15.6	16.5	15.0	17.1	16.7	16.8	16.8	13.1	14.3	15.1	14.6
UT18aa	14.7	15.5	17.0	15.1	17.0	15.1	15.6	16.1	14.0	14.9	16.7	13.8
UT19aa	14.0	16.2	16.6	15.9	17.6	16.2	16.2	16.4	13.5	14.4	16.4	13.0
UT20aa	14.8	15.4	16.9	15.8	16.6	15.2	16.8	15.5	13.7	15.7	16.3	14.1
UT21aa	14.6	16.7	16.0	15.6	16.3	15.8	15.2	16.7	13.6	14.6	16.3	14.9
UT22aa	14.0	16.1	16.6	15.8	17.5	15.8	15.9	16.9	14.4	15.0	15.4	14.3
UT23aa	14.5	15.6	16.3	15.2	17.8	16.3	17.0	16.4	14.0	15.6	16.4	13.7
UT24aa	14.9	16.6	16.8	15.0	16.4	16.8	15.7	15.4	13.6	14.3	15.1	13.6
UT25aa	14.0	16.9	16.4	15.9	16.4	15.9	15.4	15.9	14.9	15.4	15.7	14.6
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT16aa	15.0	16.4	15.8	15.5	15.7	14.5	14.9	15.7	14.7	15.7	15.0	13.0
UT17aa	14.8	16.2	15.7	14.6	15.9	15.0	14.1	17.0	14.0	15.3	15.7	14.1
UT18aa	14.0	16.9	16.9	15.2	16.4	14.4	15.0	15.3	14.3	15.2	15.1	14.4
UT19aa	15.1	17.1	16.6	15.2	16.5	14.6	15.6	15.6	15.0	15.5	15.2	14.2
UT20aa	14.3	16.6	16.8	15.3	16.2	14.6	15.7	16.7	14.7	15.3	15.1	14.6
UT21aa	14.6	16.1	16.1	15.6	16.4	14.7	16.0	16.0	14.7	15.7	15.7	13.4
UT22aa	15.2	16.7	16.1	15.2	15.4	14.8	14.0	16.5	14.9	15.9	15.6	13.7
UT23aa	14.1	17.4	16.7	14.4	16.4	14.2	15.3	16.8	14.8	15.2	15.3	13.6
UT24aa	14.2	16.2	15.9	15.5	15.2	14.1	15.0	16.8	14.8	15.7	15.3	14.1
UT25aa	15.9	16.0	15.6	14.9	17.0	14.1	14.7	16.2	14.5	15.1	15.1	14.1

A-7-2 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/25	Temperature(℃)	23.9	Su Kun	Pass
	Humidity (RH)	49.5 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤40 mΩ （Initial）			

Test data:												
A-7-2 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT26aa	14.8	15.6	15.7	14.7	15.4	14.4	14.5	15.2	13.3	14.4	14.6	13.8
UT27aa	15.2	17.5	16.9	16.5	18.3	18.4	16.5	16.7	13.2	14.6	14.8	13.8
UT28aa	14.2	15.3	15.2	14.8	14.0	13.9	14.2	14.2	13.4	14.1	14.4	13.5
UT29aa	14.4	15.5	15.8	14.7	14.2	14.2	15.8	14.7	13.8	14.7	14.8	13.6
UT30aa	14.4	15.7	16.1	15.7	15.5	14.6	16.4	15.2	13.0	14.1	14.8	13.6
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT26aa	15.1	16.2	16.6	14.8	13.5	14.1	13.7	14.3	13.3	14.5	14.5	13.3
UT27aa	16.3	17.2	16.6	15.3	14.4	14.7	14.7	14.8	14.2	15.3	14.8	13.9
UT28aa	13.6	14.8	14.8	14.3	14.2	13.7	14.7	14.3	13.9	15.0	14.7	13.5
UT29aa	14.6	15.2	15.2	14.4	15.8	13.9	14.7	14.3	13.5	17.0	14.3	13.6
UT30aa	15.0	16.9	16.4	15.5	13.7	14.0	13.6	14.1	13.4	15.3	15.2	14.0

A-7-10 Low level contact resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/28	Temperature(℃)	24.3	Su Kun	Pass
	Humidity (RH)	70.0 %		
Test condition	Mated; Maximum open circuit voltage 20 mV; Test current 100 mA.			
Criteria	≤50 mΩ			

A-7-10 Low Level Contact Resistance (mΩ)												
Sample Coding	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
UT26aa	15.0	16.6	17.4	16.6	17.3	15.3	16.4	16.5	13.5	14.7	14.7	13.7
UT27aa	14.6	17.1	16.5	15.5	16.8	16.0	15.3	16.5	13.8	14.2	14.4	14.6
UT28aa	14.6	15.3	15.8	15.1	14.5	14.1	14.9	15.7	13.6	14.6	15.8	13.8
UT29aa	14.6	15.5	15.7	15.0	14.3	14.4	14.3	14.5	13.4	14.3	15.2	13.7
UT30aa	14.2	16.0	15.9	15.9	17.0	15.1	15.8	17.4	13.3	15.6	14.9	14.4
Sample Coding	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
UT26aa	20.4	17.6	17.2	16.2	14.4	14.0	15.7	16.8	13.9	14.8	15.2	13.9
UT27aa	16.4	16.6	16.1	14.6	14.3	15.0	14.7	14.7	15.4	15.4	15.0	13.6
UT28aa	14.7	15.5	15.5	14.7	14.6	15.1	14.2	15.7	14.8	15.3	15.0	13.6
UT29aa	15.3	15.8	15.3	14.6	14.2	14.2	14.0	14.6	13.8	14.7	14.5	13.6
UT30aa	16.0	19.0	15.9	14.9	15.3	14.3	14.9	15.3	16.7	16.3	14.6	13.7

8.4. Clause 3.7.8.2 Dielectric withstanding voltage

A-7-1 Dielectric withstanding voltage				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/25	Temperature(℃)	23.6	Su Kun	Pass
	Humidity (RH)	48.5 %		
Test condition	Mated; 100 VAC (RMS), 1 min. The test voltage shall be applied between adjacent contacts.			
Criteria	A failure is the occurrence of a disruptive discharge as evidenced by flashover (surface discharge), sparkover (air discharge), breakdown (puncture discharge) or leakage in excess of 5 mA			

A-7-11 Dielectric withstanding voltage				
Testing Period	Measure environment		Test Engineer	Test Result
2025/04/02	Temperature(°C)	22.5	Su Kun	Pass
	Humidity (RH)	53.0 %		
Test condition	Mated; 100 VAC (RMS), 1 min. The test voltage shall be applied between adjacent contacts.			
Criteria	A failure is the occurrence of a disruptive discharge as evidenced by flashover (surface discharge), sparkover (air discharge), breakdown (puncture discharge) or leakage in excess of 5 mA			

8.5. Clause 3.7.8.3 Insulation Resistance

A-7-12 Insulation Resistance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/04/02	Temperature(℃)	22.5	Su Kun	Pass
	Humidity (RH)	53.0 %		
Test condition	Mated and Unmated, 500 Vdc, 2min. The test voltage shall be applied between adjacent contacts.			
Criteria	≥100MΩ			


A-7-12 Insulation Resistance Mated					
Sample Coding	UT26aa	UT27aa	UT28aa	UT29aa	UT30aa
Test contacts					
A4 to A5	> 100MΩ	> 100MΩ	> 100MΩ	> 100MΩ	> 100MΩ
A5 to A6	> 100MΩ	> 100MΩ	> 100MΩ	> 100MΩ	> 100MΩ
A6 to A7	> 100MΩ	> 100MΩ	> 100MΩ	> 100MΩ	> 100MΩ
B4 to B5	> 100MΩ	> 100MΩ	> 100MΩ	> 100MΩ	> 100MΩ
B5 to B6	> 100MΩ	> 100MΩ	> 100MΩ	> 100MΩ	> 100MΩ
Note: Followed by the specific resistance value.					

8.6. Clause 3.7.8.4 Contact Current Rating

B-6-1 Contact Current Rating				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/26	Temperature(℃)	25.4	Su Kun	Pass
	Humidity (RH)	64.1 %		
Test condition	1、 5A applied collectively to VBUS pins（i.e.,pins A4,A9,B4,and B9）. 2、 0.5 A applied to the VCONN pin（i.e.,B5）,terminated. 3、 0.25 A applied individually to all the other contacts.			
Criteria	The temperature rise shall not exceed 30℃ at the outside surface of the shell.			

Test data:			
B-6-1 Contact Current Rating			
Sample Coding	Ambient temperature (°C)	Thermocouple temperature (°C)	Temperature rise (°C)
UT42aa	25.4	46.1	20.7
UT43aa	25.3	45.7	20.4
UT44aa	25.4	46.7	21.3
Note: Temperature rise of sample = Thermocouple temperature - Ambient temperature.			

B-6 Temperature Rise Curve



8.7. Clause 3.8.1.1 Insertion force

A-7-4 Insertion Force				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/25	Temperature(℃)	23.5	Su Kun	Pass
	Humidity (RH)	44.5 %		
Test condition	Speed: 12.5mm/min; Insertion depth: 4.7mm.			
Criteria	Insertion force:5N～20N			

Test data:					
A-7-4 Insertion Force					
Sample Coding	UT26aa	UT27aa	UT28aa	UT29aa	UT30aa
Insertion force (N)	14.8	14.8	15.2	15.7	15.7

8.8. Clause 3.8.1.2 Extraction force

A-7-5 Extraction Force				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/25	Temperature(℃)	23.5	Su Kun	Pass
	Humidity (RH)	44.5 %		
Test condition	Speed: 12.5mm/min; Extraction depth: 4.7mm.			
Criteria	Extraction force: 8N~20N(Initial reading)			

A-7-7 Extraction Force				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/25	Temperature(℃)	23.5	Su Kun	Pass
	Humidity (RH)	44.5 %		
Test condition	Speed: 12.5mm/min; Extraction depth: 4.7mm.			
Criteria	Extraction force: 8N~20N; 33% of the initial reading.			

A-7-9 Extraction Force				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/28	Temperature(℃)	23.8	Su Kun	Pass
	Humidity (RH)	72.0 %		
Test condition	Speed: 12.5mm/min; Extraction depth: 4.7mm.			
Criteria	Extraction force: 6N～20N.			

Test data:					
A-7-5 Extraction Force					
Sample Coding	UT26aa	UT27aa	UT28aa	UT29aa	UT30aa
Extraction force (N)	17.9	17.9	18.2	18.3	18.6
A-7-7 Extraction Force					
Sample Coding	UT26aa	UT27aa	UT28aa	UT29aa	UT30aa
Extraction force (N)	13.3	12.8	18.5	15.8	18.8
$\frac{ (A-7-7)-(A-7-5) }{(A-7-5)} * 100\%$	25.70%	28.49%	1.65%	13.66%	1.08%
A-7-9 Extraction Force					
Sample Coding	UT26aa	UT27aa	UT28aa	UT29aa	UT30aa
Extraction force (N)	8.0	8.1	8.2	7.5	8.4

A-7 Mechanical Curve

Sample UT26aa




Fig.4 Insertion Force




Fig.5 Initial Extraction Force




Fig.6 32nd Extraction Force




Fig.7 Final Extraction Force

Sample UT27aa




Fig.8 Insertion Force




Fig.9 Initial Extraction Force




Fig.10 32nd Extraction Force










Fig.11 Final Extraction Force

Sample UT28aa



Sample UT29aa



Sample UT30aa




Fig.20 Insertion Force




Fig.21 Initial Extraction Force




Fig.22 32nd Extraction Force




Fig.23 Final Extraction Force

8.9. Clause 3.8.1.3 Durability

A-1-2 Durability				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/24	Temperature(℃)	22.6	Huang Siwei	Pass
	Humidity (RH)	56.2 %		
Test condition	Auto cycle; cycle rate: 500±50/h; Number of cycles: 50.			
Criteria	No evidence of physical damages.			

A-2-2 Durability				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/24	Temperature(℃)	22.9	Huang Siwei	Pass
	Humidity (RH)	56.5 %		
Test condition	Auto cycle; cycle rate: 500±50/h; Number of cycles: 50.			
Criteria	No evidence of physical damages.			

A-3-2 Durability				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/19	Temperature(℃)	22.7	Su Kun	Pass
	Humidity (RH)	36.8 %		
Test condition	Auto cycle; cycle rate: 500±50/h; Number of cycles: 50.			
Criteria	No evidence of physical damages.			

A-4-2 Durability				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/26	Temperature(℃)	23.3	Huang Siwei	Pass
	Humidity (RH)	55.2 %		
Test condition	Auto cycle; cycle rate: 500±50/h; Number of cycles: 50.			
Criteria	No evidence of physical damages.			

A-7-3 Durability				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/25	Temperature(℃)	23.5	Su Kun	Pass
	Humidity (RH)	44.5 %		
Test condition	Manual mating/unmating 4 cycles.			
Criteria	No evidence of physical damages.			

A-7-6 Durability				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/25	Temperature(℃)	23.5	Su Kun	Pass
	Humidity (RH)	44.5 %		
Test condition	Manual mating/unmating 25 cycles.			
Criteria	No evidence of physical damages.			

A-7-8 Durability				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/26-2025/03/27	Temperature(℃)	21.5 - 22.6	Su Kun	Pass
	Humidity (RH)	60.0 - 65.0 %		
Test condition	Auto cycle; cycle rate: 500±50/h; Number of cycles: 10000. 2468 cycles (normal) + 2500 cycles (Rotate the receptacle 180°) + 2500 cycles (normal) + 2500 cycles (Rotate the receptacle 180°)			
Criteria	No evidence of physical damages.			

8.10. Clause 3.8.1.3 Reseating

A-1-5 Re-seating				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/31	Temperature(℃)	22.6	Huang Siwei	Pass
	Humidity (RH)	56.1 %		
Test condition	Manual mating/unmating 3 cycles.			
Criteria	No evidence of physical damages.			

A-2-7 Re-seating				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/28	Temperature(℃)	22.1	Huang Siwei	Pass
	Humidity (RH)	56.0 %		
Test condition	Manual mating/unmating 3 cycles.			
Criteria	No evidence of physical damages.			

A-4-9 Re-seating				
Testing Period	Measure environment		Test Engineer	Test Result
2025/04/08	Temperature(℃)	22.8	Huang Siwei	Pass
	Humidity (RH)	55.7 %		
Test condition	Manual mating/unmating 3 cycles.			
Criteria	No evidence of physical damages.			

8.11. Clause 3.8.1.6 4-Axis Continuity

B-1-4 4-Axis Continuity				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/24	Temperature(°C)	22.9	Su Kun	Pass
	Humidity (RH)	57.5 %		
Test condition	Mated, 20N Force at 15 mm from receptacle shell mating edge. Duration: 10 seconds; Direction: 0, 90, 180, 270.			
Criteria	No discontinuities greater than 1.0 microsecond during 10 seconds at each axis.			

B-1-4 Mechanical Curve

Sample UT31aa




Fig.24 0 degree




Fig.25 180 degree




Fig.26 90 degree




Fig.27 270 degree

Sample UT32aa




Fig.28 0 degree




Fig.29 180 degree




Fig.30 90 degree






Fig.31 270 degree

Sample UT33aa



Sample UT34aa



Sample UT35aa




Fig.40 0 degree




Fig.41 180 degree




Fig.42 90 degree




Fig.43 270 degree

Sample UT36aa




Fig.44 0 degree




Fig.45 180 degree




Fig.46 90 degree




Fig.47 270 degree

Sample UT37aa




Fig.48 0 degree




Fig.49 180 degree




Fig.50 90 degree




Fig.51 270 degree

Sample UT38aa




Fig.52 0 degree




Fig.53 180 degree




Fig.54 90 degree




Fig.55 270 degree

8.12. Clause 3.8.2 Temperature life

A-1-3 Temperature Life				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/24-2025/03/29	Temperature(℃)	22.7 - 24.1	Huang Siwei	Pass
	Humidity (RH)	55.2 - 59.4 %		
Test condition	Mated; Temperature: 105±2℃; Duration: 120h.			
Criteria	No evidence of physical damages.			

A-3-3 Temperature Life				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/19-2025/03/22	Temperature(℃)	22.3 - 24.8	Su Kun	Pass
	Humidity (RH)	30.2 - 35.9 %		
Test condition	Mated; Temperature: 105±2℃; Duration: 72h.			
Criteria	No evidence of physical damages.			

A-4-3 Temperature Life				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/26-2025/03/29	Temperature(℃)	23.3 - 24.2	Huang Siwei	Pass
	Humidity (RH)	54.8 -57.2 %		
Test condition	Mated; Temperature: 105±2℃; Duration: 72h.			
Criteria	No evidence of physical damages.			

8.13. Clause 3.8.2 Thermal shock

A-2-3 Thermal Shock				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/24-2025/03/25	Temperature(°C)	22.7 - 23.5	Huang Siwei	Pass
	Humidity (RH)	56.2 - 57.3 %		
Test condition	Mated; -55⁰₋₅ °C			

8.14. Clause 3.8.2 Cyclic temperature and humidity

A-2-5 Cyclic temperature and humidity				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/25-2025/03/28	Temperature(℃)	21.8 - 23.1	Huang Siwei	Pass
	Humidity (RH)	56.5 - 58.6 %		
Test condition	Mated;			
	Temperature of 25℃±3℃ relative humidity of 80% ±3% to Temperature of 65℃±3℃ relative humidity of 50% ±3% , Thermal ramp time 0.5 hour , maintain 1 hour, 24 cycles. Temperature Humidity 80 %R.H. 50 %R.H. 65 °C 25 °C 1.0 h 0.5 h 1.0 h 0.5 h Time ← As one cycle, total 24 cycles →			
Criteria	No evidence of physical damages.			

8.15. Clause 3.8.2 Vibration

A-3-5 Vibration				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/25	Temperature(℃)	27.0	Su Kun	Pass
	Humidity (RH)	42.7 %		
Test condition	Mated; random vibration; Frequency:20-500Hz; 15min./axis for 3 axis (X,Y,Z); Power spectral density:0.02g ² /Hz, Acceleration:3.1grms.			
Criteria	No evidence of physical damages. No discontinuities of 1us or greater duration happened			

A-3-5 Vibration Curve

Sample UT11aa to UT15aa




Fig.56 X-axis Under Testing

Fig.57 X-axis After Testing




Fig.58 Y-axis Under Testing

Fig.59 Y-axis After Testing




Fig.60 Z-axis Under Testing

Fig.61 Z-axis After Testing

8.16. Clause 3.8.2 Mixed flowing gas

A-4-5 Mixed flowing gas				
Testing Period	Measure environment		Test Engineer	Test Result
2025/03/31-2025/04/07	Temperature(°C)	22.7 - 23.7	Huang Siwei	Pass
	Humidity (RH)	57.5 - 58.1 %		
Test condition	CL2:(10±3) ppb; No2:(200±50) ppb; H2S:(10±5) ppb SO2:(100±20) ppb; Temperature:(30±1)℃; Humidity:(70±2)%RH 1/3 days and then unmated for 2/3 days. The others are exposed mated for full 7 days test period.			
Criteria	No evidence of physical damages.			

8.17. Clause 3.8.2 Thermal disturbance

A-4-7 Thermal disturbance				
Testing Period	Measure environment		Test Engineer	Test Result
2025/04/07-2025/04/08	Temperature(°C)	23.1 - 24.2	Huang Siwei	Pass
	Humidity (RH)	56.2 - 57.3 %		
Test condition	Mated Cycle the connector or socket between 15 °C ± 3 °C and 85 °C ± 3 °C, as measured on the part. Ramps should be a minimum of 2 °C per minute, and dwell times should insure that the contacts reach the temperature extremes (a minimum of 5 minutes). Humidity is not controlled. Perform 10 such cycles.			
Criteria	No evidence of physical damages.			


9. Test Equipments Utilized

Name	Model	Serial number	Calibration Date	Expire Date
Oven Machine (ESPEC)	LC-213	1010170239	2024.11.22	2025.11.21
Oven Machine (ESPEC)	LC-213	1010170285	2024.11.22	2025.11.21
Thermal Shock Chamber(ESPEC)	TSE-12-A	161003228	2024.11.22	2025.11.21
Temperature & Humidity Chamber	GPL-2	0010-003613	2024.11.22	2025.11.21
Mixed Flow Gas Chamber(Yamasaki)	GH-180/VL	705	2024.11.22	2025.11.21
Vibration machine	V455-PAL1000 L	1020385-1	2024.11.22	2025.11.21
Durability Tester	YH-8816USDT	17068816076	2024.11.22	2025.11.21
Durability Tester	YH-8816USDT	17068816077	2024.11.22	2025.11.21
Durability Tester	YH-8816USDT	17068816078	2024.11.22	2025.11.21
Durability Tester	YH-8816USDT	17068816079	2024.11.22	2025.11.21
4-axis Tester	YH-8812WEXT	17068812429	2024.11.22	2025.11.21
4-axis Tester	YH-8812WEXT	17068812430	2024.11.22	2025.11.21
Microscope	MM-400/L	3413948	2024.11.22	2025.11.21
Micro-ohmmeter	RM3545	170938239	2024.11.22	2025.11.21
Electronic load meter	63610-80-20	636001001093	2024.11.22	2025.11.21
Electronic load meter	63610-80-20	636001001094	2024.11.22	2025.11.21
DC power supply	9202B	652E22230	2024.11.22	2025.11.21




Temperature rise test system	GP10	S5T909482	2024.11.22	2025.11.21
Moment disconnection tester	NM11B	20010112	2024.11.25	2025.11.24
Electrical Safety Analyzer	TOS9201	XK002479	2024.11.22	2025.11.21
AVO meter	87VC	37980325WS	2024.11.22	2025.11.21


ANNEX A: UUT photograph




Top



Bottom




Top



Bottom




Receptacle




Receptacle

ANNEX B: Drawing



ANNEX C: Insertion Force & Extraction Force Test Layout



ANNEX D: Durability Test Layout




ANNEX E: Dielectric withstanding voltage Test Layout



ANNEX F: Vibration Test Layout



ANNEX G: Contact Current Rating Test Layout



END OF REPORT