

C. Webster 52692

SAFETY ORGANIZATION(S):

THIS FILTER HAS BEEN FORMALLY RECOGNIZED, CERTIFIED OR APPROVED BY THE LISTED AGENCY. THEREFORE, ALL TEST/REQUIREMENTS SPECIFIED IN THE LATEST REVISION OF THE FOLLOWING AGENCY STANDARDS HAVE BEEN MET:

- UL 1283
- CSA 22.2, NO. 0.0.4.8
- VDE 565-3

OPERATING SPECIFICATIONS:

- LINE VOLTAGE/CURRENT:
- LINE FREQUENCY:

- MAX. LEAKAGE CURRENT, EACH LINE TO GROUND
- OPERATING AMBIENT TEMP. RANGE:

IN AN AMBIENT, T_a , HIGHER THAN 40°C, THE MAXIMUM OPERATING CURRENT, I_o , IS AS FOLLOWS:

$$I_o = I_r \sqrt{\frac{85 - T_a}{45}}$$

RELIABILITY SPECIFICATIONS:

- STORAGE TEMPERATURE:
- HUMIDITY:
- CURRENT OVERLOAD TEST:

TEST SPECIFICATIONS:



- INDUCTANCE:
- CAPACITANCE, (MEASURED @ 1 KHz, 0.25 VAC MAX., 25°C ±1°C)
- LINE TO GROUND:
- LINE TO LINE:
- DISCHARGE RESISTOR
- LINE/GROUND AND LINE/LINE INSULATION RESISTANCE

RECOMMENDED RECEIVING INSPECTION HIPOT:

- LINE TO GROUND:
- LINE TO LINE:

FILTER APPROVAL:

THE BEST WAY TO SELECT AND QUALIFY A FILTER IS FOR YOUR ENGINEERING TO TEST THE UNIT IN YOUR EQUIPMENT.



50a - 50a (MINIMUM) INSERTION LOSS												
FREQUENCY MHz	.15	.5	1	2	5	10	20	30				
COMMON dB	17	31	39	44	47	50	52	52				
DIFF. dB	30	55	65	65	65	62	62	62				

This document is proprietary to CORCOM INC. and is not to be reproduced nor used for manufacturing purposes except on CORCOM's order or prior written consent.

TOLERANCE EXCEPT AS NOTED		DECIMAL: .XXX .XX .X ANGLES ± 1°	
ENGLISH: ±.025		METRIC: ±	
MATERIAL: AS SUPPLIED		FINISH: AS SUPPLIED	
DATE: 11-5-90	SCALE: NTS	REV. NO. 3EDK1.01	REV. 1
APP. BY: CFW	ORIGINATOR: CFW		



POWER LINE FILTER

LIBERTYVILLE, IL 60048