




DUAL-IN-LINE SOCKETS

SERIES 115...001 • VERY LOW PROFILE • OPEN FRAME



- Low profile DIP socket, sits only .122" above the PCB
- Hi-Rel, 4-finger BeCu #30 contact is rated at 3 amps. See page 253 for details
- Series 115 uses MM #0501 pins. See page 162 for details
- Insulators are high temperature thermoplastic, suitable for all soldering operations
- For Electrical, Mechanical and Environmental Data, see page 264 for details



Total number of pins				Quantity per tube	ORDERING INFORMATION				
	A	B	C						
10	0.5	0.2	0.3	41	115-XX-210-41-001000				
4	0.2	0.3	0.4	102	115-XX-304-41-001000				
6	0.3	0.3	0.4	67	115-XX-306-41-001000				
8	0.4	0.3	0.4	50	115-XX-308-41-001000				
10	0.5	0.3	0.4	40	115-XX-310-41-001000				
14	0.7	0.3	0.4	28	115-XX-314-41-001000				
16	0.8	0.3	0.4	25	115-XX-316-41-001000				
18	0.9	0.3	0.4	22	115-XX-318-41-001000				
20	1.0	0.3	0.4	20	115-XX-320-41-001000				
22	1.1	0.3	0.4	18	115-XX-322-41-001000				
24	1.2	0.3	0.4	16	115-XX-324-41-001000				
28	1.4	0.3	0.4	14	115-XX-328-41-001000				
20	1.0	0.4	0.5	20	115-XX-420-41-001000				
22	1.1	0.4	0.5	18	115-XX-422-41-001000				
24	1.2	0.4	0.5	16	115-XX-424-41-001000				
28	1.4	0.4	0.5	14	115-XX-428-41-001000				
32	1.6	0.4	0.5	12	115-XX-432-41-001000				
24	1.2	0.6	0.7	16	115-XX-624-41-001000				
28	1.4	0.6	0.7	14	115-XX-628-41-001000				
32	1.6	0.6	0.7	12	115-XX-632-41-001000				
36	1.8	0.6	0.7	11	115-XX-636-41-001000				
40	2.0	0.6	0.7	10	115-XX-640-41-001000				
42	2.1	0.6	0.7	9	115-XX-642-41-001000				
48	2.4	0.6	0.7	8	115-XX-648-41-001000				
50	2.5	0.6	0.7	8	115-XX-650-41-001000				
52	2.6	0.6	0.7	7	115-XX-652-41-001000				
50	2.5	0.9	1.0	8	115-XX-950-41-001000				
52	2.6	0.9	1.0	7	115-XX-952-41-001000				
64	3.2	0.9	1.0	6	115-XX-964-41-001000				
XX=Plating Code See Below					RoHS-2 2011/65/EU				
SPECIFY PLATING CODE XX =					91	93	41	43	47
Sleeve (Pin) 					200 μ" Sn/Pb	200 μ" Sn/Pb	200 μ" Sn	200 μ" Sn	200 μ" Sn
Contact (Clip) 					10 μ" Au	30 μ" Au	10 μ" Au	30 μ" Au	Au Flash

XX=Plating Code
See Below

RoHS-2
2011/65/EU



Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com