





**Fast Recovery Bridge Rectifiers**  
**Reverse Voltage-1000v**  
**Forward current-4A**

## Features

Glass passivated chip  
High surge current capability  
Ideal for surface mounted applications  
Low power loss, high efficiency  
Plastic Case Material has UL Flammability

## Mechanical Data

Package:HBS  
Terminals:Tin Plated leads, solderable per  
Mil-STD-750 Method 2026  
Polarity: As marked  
Molding compound meets UL 94 V-0 flammability rating,  
ROHS-compliant



## Maximum Ratings (Ta=25°C Unless otherwise specified)

Type Number	SYMBOL	RHBS410	Unit
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	1000	V
Maximum RMS Voltage	$V_{RMS}$	700	V
Maximum DC Blocking Voltage	$V_{DC}$	1000	V
Maximum Average Forward Rectified Current	$I_{O(AV)}$	4.0	A
Peak Forward Surge Current 8.3ms Single half-sine-wave superimposed on rated load(JEDEC Method) on rated	IFSM	100.0	A
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25°C		200.0	A
Current squared time @1ms≤t≤8.3ms Tj=25°C, Rating of per diode	$I^2t$	41.5	A <sup>2</sup> S
Maximum Forward Voltage at 4.0A DC	$V_{FM}$	1.3	V
Maximum Reverse Current TA = 25°C	IR	5	uA
at Rated DC Blocking Voltage TA = 125°C		100	
Maximum reverse recovery time (IF=0.5A,IR=1.0A, Irr=0.25A)	Trr	500	ns
Typical Thermal Resistance	$R_{QJa}$	55.0	°C/W
Operating Junction Temperature Range	Tj	—55to+150	°C
Storage Temperature Range	TSTG	—55to+150	°C



FIG. 1 MAXIMUM AVERAGE FORWARD CURRENT DERATING




FIG. 2 TYPICAL FORWARD CHARACTERISTICS




FIG. 3 MAXIMUM NON-REPEITIVE SURGE CURRENT






FIG. 4 TYPICAL REVERSE CHARACTERISTICS (per element)





## MARKING INFORMATION



= Logo

\*\*\*\*


= Date Code Marking

RHBS610 = Marking Code


Print according to customer request

## PACKING REQUIRMENTS

### • Carrier tape packing




Specificati ons	Carrier tape type	Ao	A1	BO	B1	KO	K1	Po	W	t	Explain
HBS	DIM	10.6	8.3	10.9	7.6	1.9	2.4	4.0	16.0	0.3	
	TOLE	±0.2	±0.2	±0.2	±0.2	±0.1	±0.1	±0.1	±0.2	±0.05	



DEVICE TYPE	Units/Reel	Tubes/ Inner Box	Units/ Inner Box	Inner Box/ Carton Box	Units/ Carton Box
HBS	1500	1	1500	10	15000



## Outline Dimensions



HBS				
DIM	INC HES		MM	
	MIN	MAX	MIN	MAX
A	0.39	0.41	10.0	10.4
B	0.28	0.29	7.0	7.4
C	0.06	0.07	1.4	1.7
D	0.38	0.40	9.7	10.2
E	0.21	0.22	5.3	5.7
F	0.07	0.08	1.7	2.0



## **Important Statements and disclaimers.**

Do not copy or modify file information without permission.

Xumao Micro reserves the right to modify this document and its products.

Specifications are available without prior notice. Customer shall obtain and confirm the latest product information and specifications prior to final design, purchase or use.

Xumao Micro does not assume any implied warranties, including warranties of fitness for special purposes, non-infringement and merchantability.

The products shown here are not designed and licensed for demanding equipment at a level of reliability or for human life and any life-saving related applications or life-sustaining, such as medical devices, transportation equipment, aerospace machinery, and so on. Customers who use or sell these products for such applications do so at their own risk.

As Xumao Micro uses batch number as tracking benchmark, please provide batch number for tracking in case of exception.