



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Name: SAW Filter 1500 MHz SMD 3.0x3.0 mm

TST Parts No.:TA0583A

Customer Parts No.:_____

Company:_____

Division:_____

Approved by :_____

Date:_____

Checked by:_____ David Chang *David*

Approval by:_____ Andy Yu *Andy Yu*

Date:_____ 2018/8/21

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 1500MHz

MODEL NO.:TA0583A

REV. NO.:2

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage : 3V
3. Operating Temperature: -55°C to +85°C
4. Storage Temperature: -55°C to +95°C
5. . Moisture Sensitivity Level: Level 1


RoHS Compliant
Lead free
Lead-free soldering

B. ELECTRICAL CHARACTERISTICS:


Item	Unit	Min.	Type.	Max.	Note
Center Frequency Fc	MHz	-	1500	-	-
Insertion Loss (1480 ~ 1520 MHz) IL	dB	-	3.2	5	-
Relative Attenuation (relative to 0 dB)					
1400 MHz	dB	45	59	-	-
1600 MHz	dB	40	47	-	-

C. MEASUREMENT CIRCUIT:

HP Network analyzer



D.OUTLINE DRAWING:




△ : Year Code (2011->1, ..., 2020->0)



□ : Date Code (W01->A,...,W26->Z,W27->a,...,W52->z)

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z

E. PCB Footprint:




F. Frequency Characteristics :



7 Sep 2006 17:15:08
 [CH1] S11 1 U FS 2:43.168 α -25.465 α 4.1118 pF 1 520.000 000 MHz
 α_p

Cor

+



CENTER 1 500.000 000 MHz

SPAN 100.000 000 MHz


CH1 Markers

1: 40.762 α
 -5.0098 α
 1.48000 GHz

7 Sep 2006 17:15:14
 [CH1] S33 1 U FS 2:45.975 α -26.838 α 3.9015 pF 1 520.000 000 MHz
 α_p

Cor

+



CENTER 1 500.000 000 MHz

SPAN 100.000 000 MHz


CH1 Markers

1: 43.121 α
 -5.1367 α
 1.48000 GHz


G. PACKING:

1. REEL DIMENSION

(Reel Count : 7''=1000 ; 13''=3000)



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE :

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 245~260°C peak (min. 10sec).
4. Time: 2 times.

