



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 413 MHz SMD 3.0x3.0 mm (BW=2 MHz)

TST Part No.: TA1663A

Customer Part No.: _____

Customer signature required
Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ David Chang 張閔智

Approved by: _____ Bob Chau 陳伯

Date: _____ 2013/08/15

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 413 MHz

MODEL NO.:TA1663A

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 15 dBm
2. DC Voltage : 3 V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -40°C to +85°C

RoHS Compliant
Lead free
Lead-free soldering


Electrostatic Sensitive Device (ESD)

B. ELECTRICAL CHARACTERISTICS:


Item	Unit	Min.	Type.	Max.
Center frequency Fc	MHz	-	413	-
Insertion Loss (412~414 MHz) IL	dB	-	1.5	3.0
Amplitude Ripple (412~414 MHz)	dB	-	0.2	1.5
VSWR (412~414 MHz)	-	-	1.3	2.2
Attenuation (Reference level from 0 dB)				
10 ~ 400 MHz	dB	50	56	-
400 ~ 405 MHz	dB	10	47	-
425 ~ 430 MHz	dB	20	37	-
430 ~ 440 MHz	dB	30	40	-
440 ~ 800 MHz	dB	50	59	-
800 ~ 1000 MHz	dB	45	56	-
Temperature coefficient of frequency	ppm/	-	-36	-

C. MEASUREMENT CIRCUIT:

HP Network analyzer



D. OUTLINE DRAWING:




- B: Input
- E: Output
- A, C, D, F: Ground
- Unit: mm
- : Year Code (2011->1, 2012->2, ..., 2019->9, 2020->0)
- : Date Code



Date Code Table:

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z

E. PCB Footprint:




F. Frequency Characteristics:




Reflection Functions:

S11



S22



1. REEL DIMENSION

[illegible]

H. RECOMMENDED REFLOW PROFILE:

